

INTERNATIONAL STANDARD

**Cable networks for television signals, sound signals and interactive services
Part 3: Active wideband equipment for cable networks**

IEC 60728-3:2017
<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IEC 60728-3:2017
INTERNATIONAL STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/57775-01-4/iec-60728-3-2017>
7d932b76b820/iec-60728-3-2017

INTERNATIONAL STANDARD

**Cable networks for television signals, sound signals and interactive services
Part 3: Active wideband equipment for cable networks**

<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060.40; 33.170

ISBN 978-2-8322-4934-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions, symbols and abbreviated terms.....	9
3.1 Terms and definitions.....	9
3.2 Symbols.....	12
3.3 Abbreviated terms.....	14
4 Methods of measurement	14
4.1 General.....	14
4.2 Linear distortion	15
4.2.1 Return loss	15
4.2.2 Group delay variation	15
4.3 Non-linear distortion.....	16
4.3.1 General	16
4.3.2 Types of measurements.....	16
4.3.3 Intermodulation.....	17
4.3.4 Composite triple beat.....	19
4.3.5 Composite second order beat.....	22
4.3.6 Method of measurement of non-linearity for pure digital channel load	22
4.3.7 Hum modulation of carrier.....	30
4.4 Noise figure.....	33
4.4.1 General	33
4.4.2 Equipment required	33
4.4.3 Connection of equipment.....	33
4.4.4 Measurement procedure	34
4.5 Crosstalk attenuation	34
4.5.1 Crosstalk attenuation for loop-through ports	34
4.5.2 Crosstalk attenuation for output ports	34
4.6 Measurement of noise power ratio (NPR).....	36
4.6.1 General	36
4.6.2 Equipment required	37
4.6.3 Connection of equipment.....	37
4.6.4 Measurement procedure	38
4.6.5 Presentation of the results	38
4.7 Immunity to surge voltages	39
4.7.1 General	39
4.7.2 Equipment required	39
4.7.3 Connection of equipment.....	39
4.7.4 Measurement procedure	40
5 Equipment requirements	40
5.1 General requirements	40
5.2 Safety	40
5.3 Electromagnetic compatibility (EMC).....	40
5.4 Frequency range.....	40
5.5 Impedance and return loss.....	40

5.6	Gain.....	41
5.6.1	Minimum and maximum gain.....	41
5.6.2	Gain control.....	41
5.6.3	Slope and slope control	41
5.7	Flatness.....	41
5.8	Test points.....	41
5.9	Noise figure	41
5.10	Non-linear distortion.....	42
5.10.1	General	42
5.10.2	Second-order distortion	42
5.10.3	Third order distortion	42
5.10.4	Composite triple beat.....	42
5.10.5	Composite second order	42
5.10.6	Maximum operating level for pure digital channel load	42
5.11	Hum modulation.....	43
5.12	Power supply	43
5.13	Environmental.....	43
5.13.1	General	43
5.13.2	Transportation	43
5.13.3	Installation or maintenance.....	43
5.13.4	Operation	43
5.13.5	Energy efficiency of equipment.....	44
5.14	Marking.....	44
5.14.1	Marking of equipment	44
5.14.2	Marking of ports	44
5.15	Requirements for multi-switches.....	44
5.15.1	Control signals for multi-switches	44
5.15.2	Amplitude frequency response flatness.....	44
5.15.3	Return loss	44
5.15.4	Through loss.....	44
5.15.5	Isolation.....	44
5.15.6	Crosstalk attenuation	44
5.15.7	Satellite IF to terrestrial signal isolation	45
5.16	Immunity to surge voltages	45
5.16.1	Degrees of testing levels	45
5.16.2	Recommendation of testing level degree	45
Annex A (normative)	Test carriers, levels and intermodulation products.....	46
A.1	Two signal tests for second- and third-order products	46
A.1.1	Intermodulation products with test signals at frequencies f_a and f_b , see Table A.1	46
A.1.2	Signal levels	46
A.2	Three signal tests for third order products – Intermodulation products with test signals at frequencies f_a , f_b and f_c , see Table A.2 and Figure A.3	47
Annex B (informative)	Test frequency plan for composite triple beat (CTB), composite second order (CSO).....	48
Annex C (informative)	Measurement errors that occur due to mismatched equipment	50
Annex D (informative)	Examples of measurement channels	51
D.1	Operating frequency range 110 MHz to 1 006 MHz	51
D.2	Operating frequency range 110 MHz to 862 MHz	51

D.3 Operating frequency range 258 MHz to 1 218 MHz	51
Bibliography.....	52

Figure 1 – Basic arrangement of test equipment for evaluation of the ratio of signal to intermodulation product	18
Figure 2 – Connection of test equipment for the measurement of non-linear distortion by composite beat.....	21
Figure 3 – BER measurement test configuration	24
Figure 4 – CINR measurement test setup.....	28
Figure 5 – Plot of CINR in dB curve (forward path) versus EUT channel output signal level in dBµV	29
Figure 6 – Carrier/hum ratio	30
Figure 7 – Test set-up for local-powered objects	31
Figure 8 – Test set-up for remote-powered objects	31
Figure 9 – Oscilloscope display	32
Figure 10 – Measurement of noise figure	33
Figure 11 – Measurement of crosstalk attenuation for loop through ports of multi-switches.....	36
Figure 12 – Characteristic of the noise filter	37
Figure 13 – Test setup for the non-linearity measurement.....	37
Figure 14 – Presentation of the result of NPR.....	39
Figure 15 – Measurement set-up for surge immunity test	40
Figure A.1 – An example showing products formed when $2f_a > f_b$	46
Figure A.2 – An example showing products formed when $2f_a < f_b$	47
Figure A.3 – Products of the form $f_a \pm f_b \pm f_c$	47
Figure C.1 – Error concerning return loss measurement	50
Figure C.2 – Maximum ripple	50
Table 1 – Measurement parameters for full channel load	26
Table 2 – Notch filter frequencies	37
Table 3 – Example of return loss requirements	41
Table 4 – Parameters of surge voltages for different degrees of testing levels	45
Table 5 – Recommendations for degree of testing levels	45
Table A.1 – Intermodulation products with two signals	46
Table A.2 – Intermodulation products with three signals.....	47
Table B.1 – Frequency allocation plan	48

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CABLE NETWORKS FOR TELEVISION SIGNALS,
SOUND SIGNALS AND INTERACTIVE SERVICES –****Part 3: Active wideband equipment for cable networks****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-a992b69927c4/iec-60728-3-2017>
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-3 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This fifth edition cancels and replaces the fourth edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) extension of upper frequency range limit for cable network equipment in the forward path from 1 000 MHz to 1 218 MHz (optional up to 1 794 MHz);
- b) extension of upper frequency range limit for cable network equipment in the return path from 85 MHz to 204 MHz;
- c) integration and update of IEC 60728-3-1 content;

- d) integration and update of the Technical Specification CLC/TS 50083-3-3 content;
- e) deletion of specifications and test methods for obsolete analogue parameters;
- f) additional normative references;
- g) additional terms and definitions and abbreviations.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
100/2975/FDIS	100/2990/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60728 series, under the general title *Cable networks for television signals, sound signals and interactive services*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
 - withdrawn,
 - replaced by a revised edition, or
 - amended.
- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Standards and other deliverables of the IEC 60728 series deal with cable networks, including equipment and associated methods of measurement for headend reception, processing and distribution of television and sound signals and for processing, interfacing and transmitting all kinds of data signals for interactive services using all applicable transmission media. These signals are typically transmitted in networks by frequency-multiplexing techniques.

This includes for instance:

- regional and local broadband cable networks,
- extended satellite and terrestrial television distribution systems,
- individual satellite and terrestrial television receiving systems,

and all kinds of equipment, systems and installations used in such cable networks, distribution and receiving systems.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input of the customer premises equipment.

The standardization work will consider coexistence with users of the RF spectrum in wired and wireless transmission systems.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

[IEC 60728-3:2017](https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017)

<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 3: Active wideband equipment for cable networks

1 Scope

This part of IEC 60728 specifies the measuring methods, performance requirements and data publication requirements for active wideband equipment of cable networks for television signals, sound signals and interactive services.

This document

- applies to all amplifiers used in cable networks;
- covers the frequency range 5 MHz to 3 000 MHz;

NOTE The upper limit of 3 000 MHz is an example, but not a strict value.

- applies to one-way and two-way equipment;
- specifies the basic methods of measurement of the operational characteristics of the active equipment in order to assess the performance of this equipment;
- identifies the performance specifications to be published by the manufacturers;
- states the minimum performance requirements of certain parameters.

2 Normative references

[IEC 60728-3:2017](https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017)

<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-1, *Environmental testing – Part 2-1: Tests – Tests A: Cold*

IEC 60068-2-2, *Environmental testing – Part 2-2: Tests – Tests B: Dry heat*

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-27, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-30, *Environmental testing – Part 2-30: Tests – Test dB: Damp heat, cyclic (12 h + 12 h cycle)*

IEC 60068-2-31, *Environmental testing – Part 2-31: Tests – Test Ec: Rough handling shocks, primarily for equipment-type specimens*

IEC 60068-2-40, *Basic environmental testing procedures – Part 2-40: Tests – Test Z/AM: Combined cold/low air pressure tests*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60728-2, *Cable networks for television signals, sound signals and interactive services – Part 2: Electromagnetic compatibility for equipment*

IEC 60728-4, *Cable networks for television signals, sound signals and interactive services – Part 4: Passive wideband equipment for coaxial cable networks*

IEC 60728-5, *Cable networks for television signals, sound signals and interactive services – Part 5: Headend equipment*

IEC 60728-11, *Cable networks for television signals, sound signals and interactive services – Part 11: Safety*

IEC 61000-4-5, *Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test*

IEC 61319-1, *Interconnections of satellite receiving equipment – Part 1: Europe*

IEC 61319-2, *Interconnections of satellite receiving equipment – Part 2: Japan*

IEC 62368-1, *Audio/video, information and communication technology equipment – Part 1: Safety requirements*

iTeh STANDARD PREVIEW

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the following terms, definitions, symbols and abbreviated terms apply.

<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Terms and definitions

3.1.1

amplitude frequency response

gain or loss of an equipment or system plotted against frequency

3.1.2

attenuation

ratio of the input power to the output power of an equipment or system, usually expressed in decibels

3.1.3

carrier-to-noise ratio

difference in decibels between the vision or sound carrier level at a given point in an equipment or system and the noise level at that point (measured within a bandwidth appropriate to the television or radio system in use)

3.1.4

composite intermodulation noise

CIN

sum of noise and intermodulation products from digital modulated signals

3.1.5

CINR

composite intermodulation noise ratio

ratio of the signal level and the CIN level

3.1.6

crosstalk attenuation

ratio of the wanted signal power to the unwanted signal power, which is caused by electromagnetic coupling between two leads, while equal signal powers are applied to the leads

Note 1 to entry: Crosstalk attenuation is usually expressed in decibels.

3.1.7

decibel ratio

ten times the logarithm of the ratio of two quantities of power P_1 and P_2 , i.e.

$$10 \lg \frac{P_1}{P_2} \text{ in dB}$$

3.1.8

equaliser

device designed to compensate over a certain frequency range for the amplitude/frequency distortion or phase/frequency distortion introduced by feeders or equipment

Note 1 to entry: This device is for the compensation of linear distortions only.

3.1.9

feeder

transmission path forming part of a cable network

IEC 60728-3:2017

<https://standards.iteh.ai/catalog/standards/sist/550778cf-9bbb-4c65-85d9-7d932b76b820/iec-60728-3-2017>

Note 1 to entry: Such a path may consist of a metallic cable, optical fibre, waveguide or any combination of them. By extension, the term is also applied to paths containing one or more radio links.

3.1.10

gain

ratio of the output power to the input power, usually expressed in decibels

3.1.11

ideal thermal noise

noise generated in a resistive component due to the thermal agitation of electrons

Note 1 to entry: The thermal power generated is given by

$$P = 4 \cdot B \cdot k \cdot T$$

where

P is the noise power, in watts;

B is the bandwidth, in hertz;

k is the Boltzmann's constant = $1,38 \times 10^{-23}$ J/K;

T is the absolute temperature, in kelvins.

It follows that

$$\frac{U^2}{R} = 4 \cdot B \cdot k \cdot T$$

and

$$U = \sqrt{4 \cdot R \cdot B \cdot k \cdot T}$$

where

U is the noise voltage (e.m.f.);

R is the resistance, in ohms.

In practice, it is normal for the source to be terminated with a load equal to the internal resistance value, the noise voltage at the input is then $U/2$.

3.1.12

level

decibel ratio of any power P_1 to the standard reference power P_0 , i.e.

$$10 \lg \frac{P_1}{P_0}$$

decibel ratio of any voltage U_1 to the standard reference voltage U_0 , i.e.

$$20 \lg \frac{U_1}{U_0}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Note 1 to entry: The power level may be expressed in decibels relative to $P_0 = (U_0^2/R) = (1/75)$ pW, i.e. in dB(P_0), taking into account that the level of P_0 corresponds to 0 dB(P_0) or, as more usually, in dB(pW), taking into account that the level of P_0 corresponds to -18,75 dB(pW). The voltage level is expressed in decibels relative to 1 µV (across 75 Ω), i.e. in dB(µV).

3.1.13

modulation error ratio

MER

sum of the squares of the magnitudes of the ideal symbol vectors is divided by the sum of the squares of the magnitudes of the symbol error vectors of a sequence of symbols, the result being expressed as a power ratio in dB

$$MER = 10 \lg \left\{ \frac{\sum_{j=1}^N (I_j^2 + Q_j^2)}{\sum_{j=1}^N (\delta I_j^2 + \delta Q_j^2)} \right\} \text{ in dB}$$

3.1.14

multi-switch

equipment used in distribution systems for signals that are received from satellites and converted to a suitable IF

Note 1 to entry: The IF signals that are received from different polarisations, frequency bands and orbital positions are input signals to the multi-switch. Subscriber feeders are connected to the multi-switch output ports. Each output port is switched to one of the input ports, depending on control signals that are transmitted from the subscriber equipment to the multi-switch. Besides a splitter for each input port and a switch for each output port, a multi-switch can contain amplifiers to compensate for distribution or cable losses.

3.1.15

multi-switch loop through port

one or more ports to loop through the input signals through a multi-switch

Note 1 to entry: This enables larger networks with multiple multi-switches, each one installed close to a group of subscribers. The multi-switches are connected in a loop through manner. The IF signals that are received by an outdoor unit from different polarisations, frequency bands and orbital positions are input signals to a first multi-switch. Cables connect the loop through ports of this multi-switch to the input ports of a second multi-switch and so on.

3.1.16

noise factor

noise figure

figure of merit describing the internally generated noise of an active device

Note 1 to entry: The noise factor, F , is the ratio of the carrier-to-noise ratio at the input, to the carrier-to-noise ratio at the output of an active device.

$$F = \frac{C_1/N_1}{C_2/N_2}$$

where

C_1 is the signal power at the input;

C_2 is the signal power at the output;

N_1 is the noise power at the input (ideal thermal noise);

N_2 is the noise power at the output.

In other words, the noise factor is the ratio of noise power at the output of an active device to the noise power at the same point if the device had been ideal and added no noise.

iTeh STANDARD PREVIEW

(standards.tch.ai)

IEC 60728-3:2017

The noise factor is dimensionless and is often expressed as noise figure, NF , in dB

$$NF = 10 \lg F \quad \text{in dB}$$

3.1.17

slope

difference in gain or attenuation at two specified frequencies between any two points in an equipment or system

Note 1 to entry: The slope sign is considered

- negative when the attenuation increases with frequency (cables) or the gain (amplifiers) decreases with frequency,
- positive when the gain (amplifiers) increases with frequency (compensating slope).





























3.1.18

surge voltage

surge which is produced by a direct or indirect lightning stroke

3.2 Symbols

The following graphical symbols are used in the figures of this standard. These symbols are either listed in IEC 60617 or based on symbols defined in IEC 60617.

Symbols	Terms	Symbols	Terms
	Ammeter based on [IEC 60617-S00910 (2001-07)]		Voltmeter based on [IEC 60617-S00910 (2001-07)]
	Selective voltmeter		Power meter based on [IEC 60617-S00910 (2001-07)]
	Equipment under test based on [IEC 60617-S00059 (2001-07)]		Signal generator based on [IEC 60617-S00899, IEC 60617-S01403 (2001-07)]
	Noise generator [IEC 60617-S01230 (2001-07)]		Variable signal generator based on [IEC 60617-S00081, IEC 60617-S00899, IEC 60617-S01403 (2001-09)]
	Surge generator [IEC 60617-S01228 (2001-07)]		High-pass filter [IEC 60617-S01247 (2001-07)]
	Low-pass filter [IEC 60617-S01248 (2001-07)]		Band-stop filter [IEC 60617-S01250 (2001-07)]
	Band-pass filter [IEC 60617-S01249 (2001-07)]		Oscilloscope based on [IEC 60617-S00059, and IEC 60617-S00922 (2001-07)]
	Spectrum analyser (electrical) based on [IEC 60617-S00910 (2001-07)]		Attenuator based on [IEC 60617-S01244 (2001-07)]
	Variable attenuator [IEC 60617-S01245 (2001-07)]		Amplifier [IEC 60617-S01239 (2001-07)]
	RF modulator based on [IEC 60617-S01278 (2001-07)]		RF demodulator based on [IEC 60617-S01278 (2001-07)]
	Combiner based on [IEC 60617-S00059 (2001-07)]		Detector with LF-amplifier
	Functional equipotential bonding [IEC 60617-S01410 (2001-11)]		Adjustable AC voltage source
	Resistor [IEC 60617-S00555 (2001-07)]		Variable resistor [IEC 60617-S00557 (2001-07)]
	Capacitor [IEC 60617-S00567 (2001-07)]		RF choke [IEC 60617-S00583 (2001-07)]