



Edition 7.0 2017-12 REDLINE VERSION

INTERNATIONAL STANDARD



Explosive atmospheres – Teh Standards
Part 0: Equipment – General requirements

(https://standards.iteh.ai)

Document Preview

IEC 60079-0:2017

0179-1-17/https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Tel.: +41 22 919 02 11

info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore. iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC 60079-0:2017

https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-60079-0-2017





Edition 7.0 2017-12 REDLINE VERSION

INTERNATIONAL STANDARD



Explosive atmospheres – i Teh Standards
Part 0: Equipment – General requirements

Document Preview

IEC 60079-0:2017

https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-60079-0-2017

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.260.20 ISBN 978-2-8322-5204-8

Warning! Make sure that you obtained this publication from an authorized distributor.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

IEC 60079-0 Edition 7.0 2017-12

EXPLOSIVE ATMOSPHERES –

Part 0: Equipment - General requirements

INTERPRETATION SHEET 1

This interpretation sheet has been prepared by IEC technical committee 31: Equipment for explosive atmospheres.

The text of this interpretation sheet is based on the following documents:

h	ttng DISH	Report on voting
	31/1455/DISH	31/1464/RVDISH

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

<u> 1100 000 7 0 201 7</u>

/https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-60079-0-201

Interpretation sheet of Subclause 16.6 of IEC 60079-0:2017

The TC31/CAG requested (Resolution 2 of 2018-04-19) that WG22 prepare an interpretation sheet based on IECEx Decision Sheet DS2018/002 addressing the assignment of entry point and branching point temperatures of electrical rotating machines.

Details of interpretation:

IEC 60079-0:2017 (Ed. 7), Explosive atmospheres – Part 0: Equipment – General requirements

Interpretation of Subclause 16.6: Temperature at branching point and entry point:

Question: Subclause 16.6 of IEC 60079-0:2017 states "When the temperature under rated conditions is higher than 70 °C at the entry point or 80 °C at the branching point of the conductors, information shall be marked on the equipment exterior to provide guidance to the user on the proper selection of cable and cable gland or conductors in conduit."

It is not normal practice for electrical rotating machines to be tested with the cable entry devices and cables that might be used in an actual installation, but with the cables available at the manufacturer's test area. In many cases, there will be no formal entry device as the cables will enter via the space reserved for fixing of a gland plate.

How shall the relevant entry point and branching point temperatures be determined?

Interpretation: The use of the maximum internal air space temperature to represent the maximum service temperature of terminal box gaskets and seals, the cable branching point temperature, and the entry point temperature reflects the normal practice of testing electrical rotating machines without prior knowledge of the actual glands and cables to be used for installation. The production of heat from the electrical rotating machine connections is generally insignificant with respect to the production of heat from the machine windings and core.

Further amplification:

- The entry point of the cable where the temperature is measured should be sealed so far as possible to ensure that there is minimum air-circulation which can reduce the measured temperature.
- 2) This is not intended to apply to any gasket between the terminal box and the frame of the electrical rotating machine, where higher temperatures may be recorded, but only to the gasket between the terminal box and its lid.

Although written in the context of electrical rotating machines, there may be other types of equipment where an equivalent approach is applicable

https://standards.iteh.ai)
Document Preview

IEC 60079-0:2017

https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ffld2dd17/iec-60079-0-2017

INTERNATIONAL ELECTROTECHNICAL COMMISSION

IEC 60079-0 Edition 7.0 2017-12

EXPLOSIVE ATMOSPHERES –

Part 0: Equipment - General requirements

INTERPRETATION SHEET 2

This interpretation sheet has been prepared by IEC technical committee 31: Equipment for explosive atmospheres.

The text of this interpretation sheet is based on the following documents:

DISH	Report on voting
31/1469/DISH	31/1486/RVDISH

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-60079-0-2017

Question:

How shall marking be shown for equipment covered by both the electrical and non-electrical standards (IEC 60079 and ISO 80079 series)?

Answer:

Equipment which includes both an electrical part and a non-electrical part shall have combined marking. For example:

Ex db h IIA T4 Gb Ex h tb IIIC T135 °C Db It will be clearer for the user that the combined risk of the electrical part and the non-electrical part, covered by a single certificate, has been assessed for the complete equipment, stating one EPL, one equipment Group and one temperature class for Gas and the same for Dust (but showing a maximum surface temperature instead of a temperature class). It is also noted that Ex Components are not marked with either a temperature class (Group II) or a maximum surface temperature (Group III).

For equipment where separate certificates have been prepared, with one for the electrical parts, and one for the non-electrical parts, it is appropriate to have separate electrical and non-electrical marking strings, each with its own associated certificate number.

NOTE Additional guidance on the marking of assemblies is given in IEC TS 60079-46.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60079-0:2017

https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-60079-0-2017

CONTENTS

	FC	REWO	RD	9
	1	Scop	e	16
	2	Norm	ative references	18
	3	Term	s and definitions	21
	4	Eauir	oment grouping	21
l		4.1	General	
l		4.2	Group I	
		4.3	Group II	
		4.4	Group III	
		4.5	Equipment for a particular explosive gas atmosphere	
ı	5		peratures	
		5.1	Environmental influences	
		5.1.1		
		5.1.2	•	
		5.2	Service temperature	
		5.3	Maximum surface temperature	
		5.3.1	Determination of maximum surface temperature	42
		5.3.2		
		5.3.3	Small component temperature for Group I or Group II electrical equipment	42
		5.3.4		
	6	Regu	irements for all-electrical equipment	
	Ū	6.1	General	
		6.2	Mechanical strength of equipment	
		6.3	Opening times	45
l		6.4	Circulating currents in enclosures (e.g. of large electrical machines)	
l		6.5	Gasket retention	
		6.6	Electromagnetic and ultrasonic energy radiating equipment	
		6.6.1		
1		6.6.2	Radio frequency sources	46
		6.6.3		47
		6.6.4	Lasers, luminaires, and other non-divergent continuous wave optical	
	_		sources	
	7		metallic enclosures and non-metallic parts of enclosures	
		7.1	General	
		7.1.1		
		7.1.2	•	
		7.2	Thermal endurance	
		7.2.1	Tests for thermal endurance	
		7.2.2		
ı		7.2.3	1	
		7.3	Resistance to ultraviolet light	
		7.4	Electrostatic charges on external non-metallic materials	
		7.4.1	Applicability	51

	7.4.	Avoidance of a build-up of electrostatic charge -on for Group I or Group II -electrical equipment	51
	7.4.3	·	01
		III	
	7.5	Accessible metal Attached external conductive parts	55
8	Meta	allic enclosures and metallic parts of enclosures	55
	8.1	Material composition	55
	8.2	Group I	
	8.3	Group II	
	8.4	Group III	
	8.5	Copper Alloys	
9		eners	
	9.1	General	
	9.2	Special fasteners	
	9.3	Holes for special fasteners	
	9.3.	5 5	
	9.3.		
	9.4	Hexagon socket set screws	
		locking devices	
1		nings	
1		erials used for cementing (Reserved for future use)	
1	3 Ex (Components	
	13.1	General Genera	
	13.2	Mounting	60
	13.3	Internal mounting	60
	13.4	External mounting	
	13.5	Ex Component certificateIEC 60079-0:2017	
https	4 Con	nection facilities and termination compartments 48-5936-824ff d2dd17/sc-600	61
	14.1	General	61
	14.2	Termination compartment	
	14.2	Type of protection	
	14.3	Creepage and clearance	61
1	5 Con	nection facilities for earthing or bonding conductors	61
	15.1	Equipment requiring earthing or bonding	61
	15.1	.1 Internal earthing	61
	15.1	.2 External bonding	61
	15.2	Equipment not requiring earthing	
	15.3	Size of protective earthing conductor connection	
	15.4	Size of equipotential bonding conductor connection	
	15.5	Protection against corrosion	
	15.6	Secureness of electrical connections	
	15.7	Internal earth continuity plate	
1	6 Entr	ies into enclosures	
	16.1	General	
	16.2	Identification of entries	
	16.3	Cable glands	
	16.4	Blanking elements	
	16.5	Thread adapters	64

	16.6	Temperature at branching point and entry point	64
	16.7	Electrostatic charges of cable sheaths	64
17	Supp	olementary requirements for -rotating electric machines	65
	17.1	General	65
'	17.2	Ventilation	65
	17.2.	.1 Ventilation openings	65
	17.2.	2 Materials for external fans	66
	17.2.	.3 Cooling fans of rotating electric machines	66
	17.2.	.4 Auxiliary motor cooling fans	66
	17.2.	.5 Room ventilating fans	67
	17.3	Bearings	67
18	Supp	olementary requirements for switchgear	68
	18.1	Flammable dielectric	68
	18.2	Disconnectors	68
	18.3	Group I – Provisions for locking	69
	18.4	Doors and covers	69
19	Supp	plementary requirements for fuses Reserved for future use	69
20	Supp	plementary requirements for external plugs, socket outlets and connectors for	
		wiring connection	69
1	20.1	General	69
	20.2	Explosive gas atmospheres	70
	20.3	Explosive dust atmospheres	70
	20.4	Energized plugs	70
21	Supp	plementary requirements for luminaires	
	21.1	General	
	21.2	Covers for luminaires of EPL Mb, EPL Gb, or EPL Db	
	21.3	Covers for luminaires of EPL Gc or EPL Dc	
	21.4	Sodium lamps standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-6007	
22	Supp	olementary requirements for caplights and handlights	
	22.1	Group I caplights	
	22.2	Group II and Group III caplights and handlights	
23		pment incorporating cells and batteries	
	23.1	General	
ī	23.1	Interconnection of cells to form batteries	
	23.2		
	23.4	Cell types Cells in a battery	
	23.5	Ratings of batteries	
	23.6	Interchangeability	
	23.7	Charging of primary batteries	
	23.8	Leakage	
	23.9	Connections	
	23.10	Orientation	
	23.10	Replacement of cells or batteries	
	23.11	·	
24			
		ımentation	
25		pliance of prototype or sample with documents	
26	Туре	tests	77
	26.1	General	77

26.2		t configuration	
26.3	Tes	ts in explosive test mixtures	77
26.4	Tes	ts of enclosures	77
26.4	.1	Order of tests	77
26.4	.2	Resistance to impact	79
26.4	.3	Drop test	81
26.4	.4	Acceptance criteria	82
26.4	.5	Degree of protection (IP) by enclosures	82
26.5	The	rmal tests	83
26.5	5.1	Temperature measurement	83
26.5	5.2	Thermal shock test	85
26.5	5.3	Small component ignition test (Group I and Group II)	85
26.6	Tor	que test for bushings	86
26.6	5.1	Test procedure	86
26.6	.2	Acceptance criteria	87
26.7	Nor	n-metallic enclosures or non-metallic parts of enclosures	87
26.7	'.1	General	87
26.7	.2	Test temperatures	87
26.8	The	rmal endurance to heat	87
26.9		rmal endurance to cold	
26.10	Res	sistance to UV light	89
26.1	0.1	Test procedure General	89
26.1	0.2	Light exposure	89
26.1	0.3	Acceptance criteria	
26.11	Res	istance to chemical agents for Group I -electrical equipment	
		th continuity	
26.13		face resistance test of parts of enclosures of non-metallic materials	
/ 26.14		asurement of capacitance 5.7.45.225.5564.4648.45036.92459.42441.7566.60	
26.1		General	
26.1	4.2	Test procedure	92
26.15	Ver	ification of ratings of ventilating fans	
		ernative qualification of elastomeric sealing O-rings	
		nsferred charge test	
26.1		Test equipment	
26.1		Test sample	
26.1	7.3	Test procedure	
27 Rou	tine t	ests	
		urer's responsibility	
28.1		nformity with the documentation	
28.2		tificate	
28.3		ponsibility for marking	
	•		
29.1		olicability	
29.2		ation	
29.3		neral	
29.4		marking for explosive gas atmospheres	
29.5		marking for explosive dust atmospheres	
29.6	Cor	nbined types (or levels) of protection	103

	29.7	Multiple types of protection	103
	29.8	Ga equipment using two independent Gb types (or levels) of protection	103
	29.9	Boundary wall	103
•	29.10	Ex Components	104
	29.11	Small Ex Equipment and small Ex Components	104
	29.12	Extremely small Ex Equipment and extremely small Ex Components	104
	29.13	Alternate marking of equipment protection levels (EPLs)	
		29.13.1 Alternate marking of type of protection for explosive gas	
		atmospheres	
		29.13.2 Alternate marking of type of protection for explosive dust atmospheres	
	29.13	Warning markings	105
	29.14	Cells and batteries	106
	29.15	Converter-fed Electrical machines operated with a converter	106
ı	29.16	Examples of marking	107
		uctions	
	30.1	General	111
	30.2	Cells and batteries	
١	30.3	Electrical machines	
١	30.4	Ventilating fans	
١	30.5	Cable glands	114
١		(normative) Supplementary requirements for cable glands	
	A.1	GeneralSS.I.2.II.0.2.K.O.SI.2.1	
	A.1 A.2		
	A.2.1	Constructional requirements	115
	A.2.2	•	
	A.2.3	5 1	
	A.2.4	<u>110 00079 0.2017</u>	
	ps://sta ^./2 .5 A.2.5		
	A.2.6	•	
	A.2.7	•	
	A.2.7	Type tests	
	A.3 A.3.1		
	A.3.1	1 5	
	A.3.3	. •	
	A.3.4	•	
	A.3	Marking	
	A.4.1	· · ·	
ı	A.4.2	· ·	
	A.5	Instructions	
١		(normative) Requirements for Ex Components	
		(informative) Example of rig for resistance to impact test	
ı		(informative) Motors supplied by Electric machines connected to converters	
		(informative) Temperature <u>rise testing</u> evaluation of electric machines	
		· · · · · · · · · · · · · · · · · · ·	130
		(informative) Guideline Guidance flowchart for tests of non-metallic es or non-metallic parts of enclosures (26.4)	133
١		(informative) Guidance flowchart for tests of cable glands	
		(informative) Shaft voltages resulting in motor bearing or shaft brush	104
		(Informative) Shaft voltages resulting in motor bearing or shaft brush Discharge energy calculation	135

H.1	General	135
H.2	Assessment of the risk of ignition using ignition energy calculation	135
H.3	Shaft voltage determination for a rotating machine	
H.4	Capacitance "C" calculation for a rotating machine	
H.5	Energy "E" calculation for a rotating machine	
H.6	Assessment using reference curves	
Bibliograp	bhy	141
Figure 1 -	- Typical battery examples	23
Figure 2 -	- Typical battery compartment	25
Figure 3 -	- Typical replaceable battery pack	25
Figure 4 -	- Tolerances and clearance for threaded fasteners	58
Figure 5 -	- Contact surface under head of fastener with a reduced shank	59
Figure 6 -	- Cable gland	65
Figure 7 -	- Illustration of entry points and branching points Conduit entry	65
Figure 8 -	- Assembly of test sample for earth-continuity test	91
_	- Test piece with painted electrodes	
_	- Compression set of an O-ring	
•	1 – Illustration of the terms used for cable glands	
_	2 – Rounded edge of the point of entry of the flexible cable	
_	3 – Example of rig for resistance to impact test	
	1 – Example of rig for resistance to impact test	
	I – Non-metallic enclosures or non-metallic parts of enclosures	
•	1 – Capacitance stored in bearing clearance of sleeve bearing Between	.00
	d outer bearing housing	138
Figure H.2	2 – Air-gap between stator and rotor?h5fi.d4648h936824ff1.42.dd17.fcc60079	138
Figure H.3	3 – Typical surfaces that form capacitors from the motor shaft to ground	139
Figure H.4	4 – Capacitive ignition curves	140
Table 1 –	Ambient temperatures in service and additional marking	41
Table 2 –	Classification of maximum surface temperatures for Group II electrical	
equipmen	t	42
	Assessment of temperature classification according to component size at 40	4.4
	nt temperature	
	Assessment of temperature classification Component surface area ≥ 20 mm ²	
	Radio frequency power thresholds Threshold power	
	Radio frequency energy thresholds Threshold energy	
	Limitation of surface areas	
Table 8 –	Maximum diameter or width	53
Table 9 –	Limitation of thickness of non-metallic layer	53
Table 10 -	- Maximum acceptable transferred charge	54
Table 11 -	– Maximum capacitance of unearthed -metal conductive parts	55
Table 12 -	– Minimum cross-sectional area of PE conductors	62
Table 13 -	– Primary cells	73
Table 14 -	– Secondary cells	74

Table 15 – Tests for resistance to impact	81
Table 16 – Torque to be applied to the stem of bushing used for connection facilities	87
Table 17 – Thermal endurance test	88
Table 18 – Text of warning markings	105
Table 19 – Example of type-test converter parameters	113
Table B.1 – Applicability of clauses with which to Ex Components shall comply	125
Table H.1 – Maximum permitted energy	136

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60079-0:2017

https://standards.iteh.ai/catalog/standards/iec/2574b22b-5fcd-4648-b936-824ff1d2dd17/iec-60079-0-2017