

# INTERNATIONAL STANDARD

Information technology – Small computer system interface (SCSI) –  
Part 326: Reduced block commands (RBC)

[standards.iteh.ai](http://standards.iteh.ai)

[ISO/IEC 14776-326:2015](https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-b58cb63f9775/iso-iec-14776-326-2015)

<https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-b58cb63f9775/iso-iec-14776-326-2015>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2015 ISO/IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

**IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)**

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

**IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)**

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

INTERNATIONAL STANDARD PREVIEW  
(standards) (ch) (ie)

ISO/IEC 14776-3:2015  
a.1  
b58cb63f9775/iso-iec-14776-3-2015



ISO/IEC 14776-326

Edition 2.0 2015-09

# INTERNATIONAL STANDARD

---

Information technology – Small computer system interface (SCSI) –  
Part 326: Reduced block commands (RBC)

<https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-b58cb63f9775/iso-iec-14776-326-2015>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 35.200

ISBN 978-2-8322-2861-6


**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms, definitions, abbreviations, keywords, and conventions .....	7
3.1 Terms and definitions .....	7
3.2 Abbreviations .....	8
3.3 Keywords .....	8
3.4 Conventions .....	9
3.4.1 Non-numeric values .....	9
3.4.2 Numeric values .....	10
4 RBC device model .....	10
4.1 General .....	10
4.2 Removable medium device .....	10
4.3 Command usage .....	11
4.3.1 General .....	11
4.3.2 Using the INQUIRY command .....	11
4.3.3 Using the REQUEST SENSE command .....	11
4.3.4 FORMAT UNIT command progress determination .....	11
4.4 Using the PREVENT ALLOW MEDIUM REMOVAL command .....	12
4.4.1 General .....	12
4.4.2 START STOP UNIT command state restrictions .....	12
4.5 Logical Blocks .....	12
4.6 Reservations .....	13
5 Reduced Block Commands .....	14
5.1 General .....	14
5.2 FORMAT UNIT command .....	16
5.3 READ(10) Command .....	17
5.4 READ CAPACITY command .....	17
5.5 START STOP UNIT command .....	18
5.5.1 General .....	18
5.5.2 Power conditions .....	19
5.5.3 Enable/Disable bits .....	20
5.6 SYNCHRONIZE CACHE command .....	21
5.7 VERIFY command .....	21
5.8 WRITE(10) command .....	22
5.9 Mode parameters .....	23
5.9.1 General .....	23
5.9.2 Mode parameter list .....	23
5.9.3 Mode Parameter header .....	23
5.9.4 RBC Device Parameter's page .....	23
6 SPC-2 implementation requirements for RBC devices .....	25
6.1 General .....	25
6.2 INQUIRY command .....	25
6.2.1 Standard INQUIRY data .....	25
6.2.2 INQUIRY vital product data pages .....	26
6.3 MODE SELECT(6) command .....	27

6.4	MODE SENSE(6) command .....	27
6.5	PREVENT ALLOW MEDIUM REMOVAL .....	28
6.6	REQUEST SENSE command .....	28
6.7	TEST UNIT READY command .....	28
6.8	WRITE BUFFER Command .....	29
6.8.1	General .....	29
6.8.2	Download microcode and save mode (101b) .....	30
6.8.3	Download microcode with offsets and save mode (111b) .....	30
7	Asynchronous event notification for RBC devices .....	30
7.1	General .....	30
7.2	Unit attention .....	31
7.2.1	General .....	31
7.2.2	Power condition change notification .....	31
7.3	Deferred errors .....	31
7.4	Information exception condition notification .....	31
7.5	Event status notification .....	31
7.5.1	General .....	31
7.5.2	Event Status sense information .....	32
7.5.3	Power Management CLASS event INFORMATION field .....	32
7.5.4	MEDIA CLASS EVENT INFORMATION field .....	33
7.5.5	DEVICE BUSY CLASS EVENT INFORMATION field .....	34
7.5.6	Event status retention .....	35
7.5.7	Removable medium device initial response .....	35
Annex A (normative)	RBC device implementation requirements for SBP-2 .....	36
A.1	SBP-2 terms and definitions .....	36
A.1.1	Terms and definitions .....	36
A.1.2	Abbreviations .....	38
A.2	SBP-2 storage model .....	38
A.2.1	General .....	38
A.2.2	Model configuration .....	38
A.2.3	Reconnect/Power reset support .....	40
A.3	Configuration ROM support .....	40
A.3.1	General .....	40
A.3.2	Unit Directory – Command_Set_Spec_ID .....	40
A.3.3	Unit Directory – Command_Set .....	41
A.3.4	Unit Directory – Logical_Unit_Number .....	41
A.4	Security support .....	41
A.5	Status block support .....	41
A.6	Unsolicited Status support .....	42
A.6.1	General .....	42
A.6.2	Unit attention condition .....	42
A.6.3	Event Status retention .....	42
Figure A.1	– Mass storage interface block diagram .....	39
Figure A.2	– Status block for RBC .....	42
Table 1	– RBC direct access commands that are allowed in the presence of various reservations .....	14

Table 2 – Reduced Block Command set.....	15
Table 3 – FORMAT UNIT command .....	16
Table 4 – READ (10) Command Descriptor Block.....	17
Table 5 – READ CAPACITY Command Descriptor Block.....	18
Table 6 – READ CAPACITY data .....	18
Table 7 – START STOP UNIT Command Descriptor Block.....	19
Table 8 – POWER CONDITIONS .....	19
Table 9 – START STOP control bit definitions.....	21
Table 10 – SYNCHRONIZE CACHE Command Descriptor Block.....	21
Table 11 – VERIFY Command Descriptor Block .....	22
Table 12 – WRITE(10) Command Descriptor Block .....	22
Table 13 – Mode parameter list.....	23
Table 14 – RBC Device Parameters page format .....	24
Table 15 – Required SPC-2 commands.....	25
Table 16 – Standard Inquiry data format .....	26
Table 17 – MODE SELECT(6) Command Descriptor Block.....	27
Table 18 – MODE SENSE(6) Command Descriptor Block .....	28
Table 19 – FAILURE PREDICTION ASCQ.XY definitions.....	29
Table 20 – WRITE BUFFER Command Descriptor Block.....	29
Table 21 – Asynchronous Event conditions.....	30
Table 22 – Power condition sense code and qualifier values.....	31
Table 23 – Event status ASCQ values.....	32
Table 24 – Event Status INFORMATION field format.....	32
Table 25 – POWER MANAGEMENT CLASS EVENT INFORMATION field format .....	32
Table 26 – POWER MANAGEMENT CLASS EVENT EVENT field .....	33
Table 27 – POWER MANAGEMENT CLASS EVENT STATUS field.....	33
Table 28 – MEDIA CLASS EVENT INFORMATION field format .....	33
Table 29 – MEDIA CLASS EVENT EVENT field .....	34
Table 30 – DEVICE BUSY CLASS EVENT information field format .....	34
Table 31 – DEVICE BUSY CLASS EVENT EVENT field .....	34
Table 32 – DEVICE BUSY CLASS STATUS field .....	35


  
 (standards.itech.ai)
   
<https://standards.itech.ai/catalog/standards/sist/b9485e92-c66d-4e09-9327-63061e15120a/iso-iec-14776-326-2015>

## INFORMATION TECHNOLOGY – SMALL COMPUTER SYSTEM INTERFACE (SCSI) –

### Part 326: Reduced block commands (RBC)

#### FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.
- 3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14776-326 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This second edition cancels and replaces the first edition published in 2002 and constitutes a minor revision.

This second edition provides additional explanations and corrects mistakes with respect to the first edition.

A list of all parts in the ISO/IEC 14776 series, published under the general title *Information technology – Small computer system interface (SCSI)*, can be found on the IEC website.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

## INFORMATION TECHNOLOGY – SMALL COMPUTER SYSTEM INTERFACE –

### Part 326: Reduced block commands (RBC)

#### 1 Scope

This part of ISO/IEC 14776 defines a Reduced Block Command set for logical block devices. The Reduced Block Commands along with the required SPC-2 commands and their restrictions described in this standard, fully specify the complete command set for RBC logical block devices.

The purpose of this part of ISO/IEC 14776 is to provide a command set of reduced requirements and options from SCSI Block Commands (SBC) (ISO/IEC 14776-321) for block devices. The reduced command set is intended to more closely match the functionality required for simple block logical units. The specified commands place no restrictions on device performance. The initial focus of this command set was to enable rigid disks and removable media devices attached to Serial Bus and utilizing SBP-2 (ISO/IEC 14776-232) for command and control.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 13213:1994, *Information technology – Microprocessor systems – Control and Status Registers (CSR) Architecture for microcomputer buses*

ISO/IEC 14776-232:2001, *Information technology – Small computer system interface (SCSI) – Part 232: Serial Bus Protocol 2 (SBP-2)*

ISO/IEC 14776-321:2001, *Information technology – Small Computer System Interface (SCSI-3) – Part 321: Block commands (SBC)*

ISO/IEC 14776-362:2006, *Information technology – Small computer system interface (SCSI) – Part 362: Multimedia commands-2 (MMC-2)*

ISO/IEC 14776-412, *Information technology – Small computer system interface (SCSI) – Part 412: SCSI, Architecture model-2 (SAM-2)*

ISO/IEC 14776-452:2005, *Information technology – Small computer system interface (SCSI) – Part 452: Primary commands-2 (SPC-2)*

IEEE Standard 1394-1995, *High Performance Serial Bus*

IEEE Standard 1394A-2000, *High Performance Serial Bus Amendment 1*

### 3 Terms, definitions, abbreviations, keywords, and conventions

#### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

##### 3.1.1

**additional sense code**

**ASC**

field in the sense data

Note 1 to entry: See 7.20.2 in ISO/IEC 14776-452:2005.

[SOURCE: ISO/IEC 14776-452:2005, 3.1.2, modified – Reference to SPC-2 added.]

##### 3.1.2

**additional sense code qualifier**

**ASCQ**

field in the sense data

Note 1 to entry: See 7.20.2 in ISO/IEC 14776-452:2005.

##### 3.1.3

**byte**

**B**

eight bit of data

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SOURCE: ISO/IEC 14776-452:2005, 3.1.9, modified – Definition simplified.]

[ISO/IEC 14776-326:2015](https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-b58cb63f9775/iso-iec-14776-326-2015)

##### 3.1.4

**command descriptor block**

**CDB**

structure of up to 16 B in length used to communicate a command from an initiator to a device

<https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-b58cb63f9775/iso-iec-14776-326-2015>

[SOURCE: ISO/IEC 14776-452:2005, 3.1.11, modified – Definition changed.]

##### 3.1.5

**EVENT field**

byte 0 of the sense data INFORMATION field

Note 1 to entry: See Table 24 for the Event Status INFORMATION field format when the sense code indicates EVENT STATUS NOTIFICATION (38h).

##### 3.1.6

**logical unit**

part of the device that is an instance of a device model

Note 1 to entry: For example mass storage, CD-ROM or a printer are device models.

Note 2 to entry: In devices that implement one or more logical units, the device type of the logical units may differ.

[SOURCE: ISO/IEC 14776-452:2005, 3.1.30, modified – Definition and explanatory information changed.]

##### 3.1.7

**sense data**

data describing an error or exceptional device condition that a device delivers to an initiator

[SOURCE: ISO/IEC 14776-452:2005, 3.1.47, modified – Definition simplified and explanatory information deleted.]

### 3.1.8

#### **sense key**

field in the sense data

Note 1 to entry: See 7.20.3 in ISO/IEC 14776-452.

[SOURCE: ISO/IEC 14776-452:2005, 3.1.48, modified – Definition changed.]

### 3.1.9

#### **status**

response information sent from a device to an initiator upon completion of each command

[SOURCE: ISO/IEC 14776-452:2005, 3.1.52, modified – Definition simplified and explanatory information deleted.]

### 3.1.10

#### **unit attention condition**

condition that a logical unit maintains while it has asynchronous status information to report to one or more initiators

[SOURCE: ISO/IEC 14776-452:2005, 3.1.58, modified – "State" has been replaced by "condition" and reference information has been deleted.]

### 3.1.11

#### **vendor specific**

bit, field, code value, etc., not defined in this standard, that may be vendor defined

[SOURCE: ISO/IEC 14776-452:2005, 3.1.59, modified – Minor editorial change of the definition.]

## 3.2 Abbreviations

The following abbreviations are used in this standard:

ASC	Additional Sense Code
ASCQ	Additional Sense Code Qualifier
CDB	Command Descriptor Block
MMC-2	Multi-Medial Commands 2
RBC	Reduced Block Commands (this standard)
SAM-2	SCSI Architecture Model 2
SBC	SCSI Block Commands
SBP-2	Serial Bus Protocol 2
SPC-2	SCSI Primary Commands 2

## 3.3 Keywords

Several keywords are used to differentiate levels of requirements and options, as follows.

### 3.3.1

#### **expected**

keyword used to describe the behavior of the hardware or software in the design models assumed by this standard. Other hardware and software design models may also be implemented.

### 3.3.2

#### **ignored**

keyword that describes bits, bytes, quadlets, or fields whose values are not checked by the recipient

### 3.3.3

#### **mandatory**

keyword that indicates items required to be implemented as defined by this standard

### 3.3.4

#### **may**

keyword that indicates flexibility of choice with no implied preference

### 3.3.5

#### **optional**

keyword that describes features which are not required to be implemented by this standard. However, if any optional feature defined by the standard is implemented, it shall be implemented as defined by the standard.

### 3.3.6

#### **reserved**

keyword used to describe objects (eg., bits, bytes, and field) or the code values assigned to these objects in cases where either the object or the code value is set aside for future standardization. Usage and interpretation may be specified by future extensions to this or other standards. A reserved object shall be zeroed or, upon development of a future standard, set to a value specified by such a standard. The recipient of a reserved object shall not check its value. The recipient of a defined object shall check its value and reject reserved code values.

<https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-b58cb63f9775/iso-iec-14776-326-2015>

### 3.3.7

#### **shall**

keyword that indicates a mandatory requirement. Designers are required to implement all such mandatory requirements to assure interoperability with other products conforming to this standard.

## 3.4 Conventions

The following conventions shall be understood by the reader in order to comprehend this standard.

### 3.4.1 Non-numeric values

Lowercase is used for words having the normal English meaning. Certain words and terms used in this standard have a specific meaning beyond the normal English meaning. These words and terms are defined either in Clause 3 or in the text where they first appear.

The names of abbreviations, commands, and acronyms are in all uppercase (e.g., TEST UNIT READY command).

Fields are shown in small caps (e.g., LOGICAL BLOCK ADDRESS).

Fields containing only one bit are usually referred to as the NAME bit instead of the NAME field.

Formal lists connoted by letters (e.g., a) red; b) blue; c) green) are in an arbitrary order. Formal lists connoted by numbers (e.g., 1) red; 2) blue; 3) green) are in a required sequential order.

If a conflict arises between text, tables, or figures, the order of precedence to resolve conflicts is text; then tables; and finally figures. Not all tables or figures are fully described in text. Tables show data format and values. Notes do not constitute any requirements for implementations.

### 3.4.2 Numeric values

The ISO convention of numbering is used (i.e., the thousands and higher multiples are separated by a space and a comma is used as the decimal point as in 65 536 or 0,5).

Decimal numbers are represented by Arabic numerals without subscripts or by their English names (e.g., 42, or twelve).

Hexadecimal numbers are represented by digits from the character set 0 to 9 and A to F followed by the lower-case h (e.g., 2Ah).

Binary numbers are represented by digits from the character set 0 and 1 followed by the lower-case b (e.g., 0010 1010b).

The most significant bit of a binary quantity is shown on the left side and represents the highest algebraic value position in the quantity.

For the sake of legibility, binary and hexadecimal numbers are separated into groups of four digits separated by spaces.

## 4 RBC device model

[standards.iteh.ai](https://standards.iteh.ai/)

### 4.1 General

[ISO/IEC 14776-326:2015](https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-bb6c47718122/iso-iec-14776-326-2015)

<https://standards.iteh.ai/catalog/standards/sist/b9485e92-e66d-4e09-9327-bb6c47718122/iso-iec-14776-326-2015>

RBC logical units store blocks of data for later retrieval. Each block of data is stored at a unique location. Initiators send WRITE commands to store the blocks of data (i.e., write operations) and READ commands to retrieve the blocks of data (i.e., read operations). Other commands sent by the initiator may cause write and read operations to occur.

A write operation causes one or more blocks of data to be written on the medium. A read operation causes one or more blocks of data to be read from the medium. A verify operation confirms that one or more blocks of data were correctly written and may be read without error from the medium.

Blocks of data are stored by a process that causes localized changes or transitions within the medium. The changes made to the medium to store the blocks of data may be volatile (i.e., not retained through off/on power cycles) or non-volatile (retained through off/on power cycles). The medium may be divided in parts that are used for data blocks, parts that are reserved for defect management, and parts that are reserved for use by the target for the management of the logical unit.

### 4.2 Removable medium device

The medium in a RBC device may be removable (e.g., used in a floppy disk drive) or non-removable (e.g. used in a fixed disk drive). Typically, removable medium is contained within a cartridge (or jacket) to prevent damage to the recording surfaces.

A removable medium has an attribute of being mounted or de-mounted on a suitable transport mechanism. A removable medium is mounted when the device/media combination is capable of performing write or read operations and the initiator is informed of this status. A removable medium is de-mounted at any other time (e.g., during loading, unloading, or storage).

Initiators may determine whether a RBC removable medium device is capable of performing read or write operations by one of three methods:

- a) enabling Asynchronous Event Reporting (see SPC-2) in the device and examining the event information transmitted from the device;
- b) issuing a TEST UNIT READY command and examining the returned status information; or
- c) issuing a MODE SENSE command for Mode Page 06h (see 5.9.4) and examining the state of the READD bit or WRITED bit. If the READD bit is set to one, then the media is not readable. If the WRITED bit is set to one, then the media is not writable.

Until the RBC removable medium device and media are ready to be accessed, a READ(10) command shall cause the device to return status of CHECK CONDITION (02h), sense key of NOT READY (02h), and an ASC of LOGICAL UNIT NOT READY (04h). The ASCQ shall reflect the current state of the device/media.

When the device becomes ready, a unit attention condition shall be established. The sense key value shall be set to UNIT ATTENTION (06h), and the ASC/ASCQ to event STATUS NOTIFICATION/MEDIA CLASS EVENT (38h/04h). The EVENT field contained within the sense data INFORMATION field shall be set to NEW MEDIA READY FOR ACCESS (02h). When the unit attention condition is delivered to the initiator, the status shall be set to CHECK CONDITION (02h).

### 4.3 Command usage

#### 4.3.1 General

RBC devices are not required to support the REQUEST SENSE command or the SEND DIAGNOSTIC command. Devices that do not provide the Auto Sense function, Asynchronous Event Reporting, or the GET EVENT/STATUS NOTIFICATION command (see MMC-2) shall implement the REQUEST SENSE command.

All sense key, ASC, and ASCQ names and values contained in this standard are defined in SPC-2. No additional or alternative meaning is intended by the use of such names and values in this standard.

#### 4.3.2 Using the INQUIRY command

The INQUIRY command (see SPC-2 and 6.2) may be used by an initiator to determine the configuration of a logical unit. RBC devices return information that includes type and standard version. The device may also return the vendor identification number, model number, and other vendor specific information. It is recommended that devices provide the capability to return this information upon completing power-on initialization. A device may take more time to return certain portions of this information, especially if the information shall be retrieved from the medium.

#### 4.3.3 Using the REQUEST SENSE command

Whenever a command completes with CHECK CONDITION status and Auto Sense data is not provided, the initiator that received the error status should send a REQUEST SENSE command to acquire the sense data describing the cause of the condition. If the initiator sends a command other than REQUEST SENSE, the sense data is lost.

Devices may be required to support the REQUEST SENSE command if they are unable to provide command progress information by any other method.

#### 4.3.4 FORMAT UNIT command progress determination

The FORMAT UNIT command (see 5.2) requires IMMED bit support because it may consume significantly more time to complete than normal read or write commands. If the IMMED bit is set to one, the device is required to return status as soon as the command descriptor block is