

INTERNATIONAL STANDARD



Power transformers – iTeh Standards
Part 7: Loading guide for mineral-oil-immersed power transformers

(<https://standards.iteh.ai>)
Document Preview

[IEC 60076-7:2018](https://standards.iteh.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018)

<https://standards.iteh.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

[IEC 60076-7:2018](https://standards.iteh.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018)

<https://standards.iteh.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018>



IEC 60076-7

Edition 2.0 2018-01
REDLINE VERSION

INTERNATIONAL STANDARD



Power transformers – iTeh Standards
Part 7: Loading guide for mineral-oil-immersed power transformers
(<https://standards.itih.ai>)

Document Preview

[IEC 60076-7:2018](#)

<https://standards.itih.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.180

ISBN 978-2-8322-5279-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	10
2 Normative references	10
3 Terms and definitions	10
4 Symbols and abbreviations.....	13
5 Effect of loading beyond nameplate rating	14
5.1 Introduction General	14
5.2 General consequences	14
5.3 Effects and hazards of short-time emergency loading	15
5.4 Effects of long-time emergency loading.....	16
5.5 Transformer size.....	16
Non-thermally and thermally upgraded insulation paper	18
6 Relative ageing rate and transformer insulation life	18
6.1 General.....	18
6.2 Insulation life	19
6.3 Relative ageing rate.....	23
6.4 Loss-of-life calculation	24
7 Limitations.....	25
7.1 Current and Temperature limitations	25
7.2 Current limitations.....	26
7.3 Specific limitations for distribution small transformers	27
7.3.1 Current and temperature limitations	27
7.3.2 Accessory and other considerations	27
7.3.3 Indoor transformers	27
7.3.4 Outdoor ambient conditions	27
7.4 Specific limitations for medium power transformers.....	27
7.4.1 Current and temperature limitations	27
7.4.2 Accessory, associated equipment and other considerations.....	27
7.4.3 Short-circuit withstand requirements	28
7.4.4 Voltage limitations	28
7.5 Specific limitations for large power transformers	28
7.5.1 General	28
7.5.2 Current and temperature limitations	28
7.5.3 Accessory, equipment and other considerations	28
7.5.4 Short-circuit withstand requirements	29
7.5.5 Voltage limitations	29
8 Determination of temperatures.....	29
8.1 Hot-spot temperature rise in steady state.....	29
8.1.1 General	29
8.1.2 Calculation of hot-spot temperature rise from normal heat-run test data	29
8.1.3 Direct measurement of hot-spot temperature rise	30
8.1.4 Hot-spot factor.....	35
8.2 Top-oil and hot-spot temperatures at varying ambient temperature and load conditions	37

8.2.1	General	37
8.2.2	Exponential equations solution	39
8.2.3	Differential Difference equations solution	44
8.3	Ambient temperature	46
8.3.1	Outdoor air-cooled transformers	46
8.3.2	Correction of ambient temperature for transformer enclosure	47
8.3.3	Water-cooled transformers	48
9	Influence of tap-changers	48
9.1	General	48
9.2	Short-circuit losses Load loss	48
9.3	Ratio of losses	48
9.4	Load factor	49
Annex A (informative) Insulation life expectancy and relative ageing rate considering oxygen and water effect		50
A.1	Insulation life expectancy	50
A.2	Relative ageing rate considering oxygen and water effect	52
Annex B (informative) Core temperature		55
B.1	General	55
B.2	Core hot-spot locations	55
Annex C (informative) Specification of loading beyond rated power		56
Annex D (informative) Description of Q , S and H factors		58
Annex E (informative) Calculation of winding and oil time constant		61
Annex F (informative) Thermal model parameters		63
F.1	General	63
F.2	Thermal constant estimation: experimental approach	63
F.3	Dynamic thermal modelling: further development	65
Annex G (informative) Oil and winding exponents		66
G.1	General	66
G.2	Historical background	66
G.3	Theoretical approach	68
G.4	Extended temperature rise test approach	70
Annex H (informative) Practical example of the exponential equations method		72
H.1	Introduction General	72
H.2	Time period 0 min to 190 min	73
H.3	Time period 190 min to 365 min	74
H.4	Time period 365 min to 500 min	74
H.5	Time period 500 min to 710 705 min	75
H.6	Time period 710 705 min to 735 730 min	76
H.7	Time period 735 730 min to 750 745 min	77
H.8	Comparison with measured values	77
Annex I (informative) Illustration Application of the differential difference equation solution method		79
I.1	General	82
I.2	Example	82
I.3	Use of measured top-oil temperature	87
Annex J (informative) Flowchart, based on the example in Annex H		88
Annex K (informative) Example of calculating and presenting overload data		90

Annex L (informative) Geomagnetic induced currents	94
L.1 Background.....	94
L.2 GIC capability of power transformers [54], [55].....	94
Annex M (informative) Alternative oils	96
Bibliography.....	97
Figure — Sealed tube accelerated ageing in mineral oil at 150 °C	94
Figure — Local temperature rises above air temperature in a 120 kV winding at a load factor of 1,6	94
Figure — Local temperature rises above air temperature in a 410 kV winding at a load factor of 1,6	94
Figure — Two fibre optic sensors installed in a spacer before the spacer was installed in the 120 kV winding.....	96
Figure 1 – Structural formula of cellulose	18
Figure 2 – Correlation between tensile strength and DP value	20
Figure 3 – Accelerated ageing in mineral oil at 140 °C, oxygen and moisture contents maintained at < 6 000 ppm and 0,5 %, respectively	21
Figure 4 – Expected life for non-thermally upgraded paper and its dependence upon moisture, oxygen and temperature	22
Figure 5 – Expected life for thermally upgraded paper and its dependence upon moisture, oxygen and temperature	23
Figure 6 – Thermal diagram	30
Figure 7 – Temperature rises above top-oil temperature (in tank) 65,8 °C of the zig-zag cooled HV-winding of a 400 MVA ONAF cooled 3-phase transformer, load current 1,0 p.u., tap position (-)	33
Figure 8 – Coil edges, where the sensors should be located in the edge with the higher calculated temperature rise.....	34
Figure 9 – Temperature rises above top-oil temperature at the end of an 8 h thermal no-load test at 110 % supply voltage.....	35
Figure 10 – Zigzag-cooled winding where the distance between all sections is the same and the flow-directing washer is installed in the space between sections	36
Figure 11 – Top view section of a rectangular winding with “collapsed cooling duct arrangement” under the yokes	37
Figure 12 – Block diagram representation of the differential equations.....	38
Figure 13 – Temperature responses to step changes in the load current.....	40
Figure 14 – The function $f_2(t), f_2(t) \Delta\theta_h(t)/\Delta\theta_{hr}$ generated by the values given in Table 4.....	44
Figure 15 – Principle of losses as a function of the tap position	48
Figure A.1 – Arrhenius plot for an ageing process	51
Figure F.1 – Hot-spot and top-oil overall model.....	65
Figure G.1 – Extended temperature rise test.....	70
Figure G.2 – Transformer exponent estimation plots	71
Figure H.1 – Hot-spot temperature response to step changes in the load current.....	77
Figure H.2 – Top-oil temperature response to step changes in the load current	78
Figure I.1 – Plotted input data for the example	84
Figure I.2 – Plotted output data for the example.....	87
Figure K.1 – OF large power transformers: permissible duties for normal loss of life.....	93
Figure L.1 – GIC flow into a power transformer	94

Table — Life of paper under various conditions
Table — Normal insulation life of a well-dried, oxygen-free thermally upgraded insulation system at the reference temperature of 110 °C
Table — Current and temperature limits applicable to loading beyond nameplate rating
Table 1 – Relative ageing rates due to hot-spot temperature	24
Table 2 – Maximum permissible temperature limits applicable to loading beyond nameplate rating	26
Table 3 – Recommended current limits applicable to loading beyond nameplate rating	27
Table 4 – Recommended thermal characteristics for exponential equations	43
Table 5 – Correction for increase in ambient temperature due to enclosure	47
Table A.1 – Activation energy (E_A) and environment factor (A) for oxidation, hydrolysis	51
Table A.2 – Expected life of paper under various conditions	52
Table A.3 – Relative ageing rates due to hot-spot temperature, oxygen and moisture for non-upgraded paper insulation	53
Table A.4 – Relative ageing rates due to hot-spot temperature, oxygen and moisture for upgraded paper insulation	54
Table H.1 – Load steps of the 250 MVA transformer	72
Table H.2 – Temperatures at the end of each load step	78
Table I.1 – Input data for example	83
Table I.2 – Output data for the example	86
Table K.1 – Example characteristics related to the loadability of transformers	90
Table K.2 – An example table with the permissible duties and corresponding daily loss of life (in “normal” days), and maximum hot-spot temperature rise during the load cycle	92

IEC 60076-7:2018

<https://standards.iteh.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

POWER TRANSFORMERS –

**Part 7: Loading guide for mineral-oil-immersed
power transformers**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60076-7 has been prepared by IEC technical committee 14: Power transformers.

This second edition cancels and replaces the first edition published in 2005. It constitutes a technical revision. This edition includes the following significant technical changes with respect to the previous edition:

- a) title has been updated from "oil-immersed power transformers" to "mineral-oil-immersed power transformers";
- b) insulation life is updated by considering latest research findings;
- c) temperature limits have been reviewed and maximum core temperature is recommended;
- d) number of fibre optic sensors is recommended for temperature rise test;
- e) Q, S and H factors are considered;
- f) thermal models are revised and rewritten in generally applicable mathematical form;
- g) geomagnetic induced currents are briefly discussed and corresponding temperature limits are suggested;
- h) extensive literature review has been performed and a number of references added to bibliography.

The text of this standard is based on the following documents:

FDIS	Report on voting
14/933/FDIS	14/942/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60076 series, under the general title *Power transformers*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 60076 provides guidance for the specification and loading of power transformers from the point of view of operating temperatures and thermal ageing. It provides recommendations for loading above the nameplate rating and guidance for the planner to choose appropriate rated quantities and loading conditions for new installations.

IEC 60076-2 is the basis for contractual agreements and it contains the requirements and tests relating to temperature-rise figures for oil-immersed transformers during continuous rated loading. ~~It should be noted that IEC 60076-2 refers to the average winding temperature rise while this part of IEC 60076 refers mainly to the hot-spot temperature and the stated values are provided only for guidance.~~

This part of IEC 60076 gives mathematical models for judging the consequence of different loadings, with different temperatures of the cooling medium, and with transient or cyclical variation with time. The models provide for the calculation of operating temperatures in the transformer, particularly the temperature of the hottest part of the winding. This hot-spot temperature is, in turn, used for evaluation of a relative value for the rate of thermal ageing and the percentage of life consumed in a particular time period. The modelling refers to small transformers, here called distribution transformers, and to power transformers.

~~A major change from IEC 60354:1991 is the increased use of fibre optic temperature sensors in transformers. This has radically increased the possibilities of obtaining a proper thermal modelling of power transformers, especially at step changes in the load current. These possibilities have also yielded some differences between the "oil exponent x " and the "winding exponent y " used in this part of IEC 60076 and in IEC 60076-2:1993, for power transformers:~~

- ~~• $x = 0,9$ in IEC 60076-2, and $x = 0,8$ in this part of IEC 60076 at ON cooling.~~
- ~~• $y = 1,6$ in IEC 60076-2, and $y = 1,3$ in this part of IEC 60076 at ON and OF cooling.~~

~~For distribution transformers, the same x and y values are used in this part of IEC 60076 as in IEC 60076-2.~~

A major change from the previous edition is the extensive work on the paper degradation that has been carried out indicating that the ageing may be described by combination of the oxidation, hydrolysis and pyrolysis. Also, providing possibility to estimate the expected insulation life considering different ageing factors, i.e. moisture, oxygen and temperature, and more realistic service scenarios. The title has been updated from "oil-immersed power transformers" to "mineral-oil-immersed power transformers". The temperature and current limits are reviewed and the maximum core temperature is recommended. The use of fibre optic temperature sensors has become a standard practice, however, the number of installed sensors per transformer highly varies. This issue and the description of Q, S and H factors are now considered as well. The thermal models are revised and rewritten in generally applicable mathematical form. The geomagnetic induced currents are briefly discussed and corresponding temperature limits are suggested.

This part of IEC 60076 further presents recommendations for limitations of permissible loading according to the results of temperature calculations or measurements. These recommendations refer to different types of loading duty – continuous loading, normal cyclic undisturbed loading or temporary emergency loading. The recommendations refer to distribution transformers, to medium power transformers and to large power transformers. Clauses 1 to 7 contain definitions, common background information and specific limitations for the operation of different categories of transformers.

Clause 8 contains the determination of temperatures, presents the mathematical models used to estimate the hot-spot temperature in steady state and transient conditions.

Clause 9 contains a short description of the influence of the tap position.

Application examples are given in Annexes **A, B, C, D, E, F, G, H, I** and **K**.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 60076-7:2018](#)

<https://standards.iteh.ai/catalog/standards/iec/0e204cc0-4cfd-4090-84c6-6dbb71e398a1/iec-60076-7-2018>

POWER TRANSFORMERS –

Part 7: Loading guide for mineral-oil-immersed power transformers

1 Scope

This part of IEC 60076 is applicable to mineral-oil-immersed transformers. It describes the effect of operation under various ambient temperatures and load conditions on transformer life.

NOTE For furnace transformers, the manufacturer ~~should be~~ is consulted in view of the peculiar loading profile.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~IEC 60076-2:1993, Power transformers – Part 2: Temperature rise for liquid-immersed transformers~~

~~IEC 60076-4:2002, Power transformers – Part 4: Guide to the lightning impulse and switching impulse testing – Power transformers and reactors~~

~~IEC 60076-5:2000, power transformers – Part 5: Ability to withstand short circuit~~

IEC 60076-14, Power transformers – Part 14: Liquid-immersed power transformers using high-temperature insulation materials

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

distribution transformer

~~power transformer with a maximum rating of 2 500 kVA three-phase or 833 kVA single-phase~~

3.1

small power transformer

power transformer without attached radiators, coolers or tubes including corrugated tank irrespective of rating

3.2

medium power transformer

power transformer with a maximum rating of 100 MVA three-phase or 33,3 MVA single-phase

3.3

large power transformer

power transformer ~~exceeding the limits specified in 3.2~~ with a maximum rating of greater than 100 MVA three-phase or greater than 33,3 MVA single-phase

3.4 cyclic loading

loading with cyclic variations (the duration of the cycle usually being 24 h) which is regarded in terms of the accumulated amount of ageing that occurs during the cycle

Note 1 to entry: The cyclic loading may either be a normal loading or a long-time emergency loading.

3.5 normal cyclic loading

loading in which a higher ambient temperature or a higher-than-rated load current is applied during part of the cycle, but which, from the point of view of relative thermal ageing rate (according to the mathematical model), is equivalent to the rated load at normal ambient temperature

Note 1 to entry: This is achieved by taking advantage of low ambient temperatures or low load currents during the rest of the load cycle. For planning purposes, this principle can be extended to provide for long periods of time whereby cycles with relative thermal ageing rates greater than unity are compensated for by cycles with thermal ageing rates less than unity.

3.6 long-time emergency loading

loading resulting from the prolonged outage of some system elements that will not be reconnected before the transformer reaches a new and higher steady-state temperature

3.7 short-time emergency loading

unusually heavy loading of a transient nature (less than 30 min) due to the occurrence of one or more unlikely events which seriously disturb normal system loading

3.8 hot-spot

if not specially defined, hottest spot of the windings

3.9 relative thermal ageing rate

for a given hot-spot temperature, rate at which transformer insulation ageing is reduced or accelerated compared with the ageing rate at a reference hot-spot temperature

3.10 transformer insulation life

total time between the initial state for which the insulation is considered new and the final state ~~when~~ for which the insulation is considered deteriorated due to thermal ageing, dielectric stress, short-circuit stress, or mechanical movement (which could occur in normal service), and ~~result in~~ at which a high risk of electrical failure exists

3.11 per cent loss of life

equivalent ageing in hours over a time period (usually 24 h) times 100 divided by the expected transformer insulation life

Note 1 to entry: The equivalent ageing in hours is obtained by multiplying the relative ageing rate with the number of hours.

3.12 non-thermally upgraded paper

kraft paper produced from unbleached softwood pulp under the sulphate process without addition of stabilizers

3.13**thermally upgraded paper**

cellulose-based paper which has been chemically modified to reduce the rate at which the paper decomposes

Note 1 to entry: Ageing effects are reduced either by partial elimination of water forming agents (as in cyanoethylation) or by inhibiting the formation of water through the use of stabilizing agents (as in amine addition, dicyandiamide). A paper is considered as thermally upgraded if it meets the life criteria defined in ANSI/IEEE C57.100 [1]¹; 50 % retention in tensile strength after 65 000 h in a sealed tube at 110 °C or any other time/temperature combination given by the equation:

$$\text{Time (h)} = e^{\left(\frac{15\,000}{(\theta_h + 273)} - 28,082\right)} \approx 65\,000 \times e^{\left(\frac{15\,000}{(\theta_h + 273)} - \frac{15\,000}{(110 + 273)}\right)} \quad (1)$$

Because the thermal upgrading chemicals used today contain nitrogen, which is not present in kraft pulp, the degree of chemical modification is determined by testing for the amount of nitrogen present in the treated paper. Typical values for nitrogen content of thermally upgraded papers are between 1 % and 4 % when measured in accordance with ASTM D-982 [2], but after the sealed tube test.

~~NOTE This definition was approved by the IEEE Transformers Committee Task Force for the Definition of Thermally Upgraded Paper on 7 October 2003.~~

3.14**non-directed oil flow****OF**

flow indicating that the pumped oil from heat exchangers or radiators flows freely inside the tank, and is not forced to flow through the windings

Note 1 to entry: The oil flow inside the windings can be either axial in vertical cooling ducts or radial in horizontal cooling ducts with or without zigzag flow.

3.15**non-directed oil flow****ON**

flow indicating that the oil from the heat exchangers or radiators flows freely inside the tank and is not forced to flow through the windings

Note 1 to entry: The oil flow inside the windings can be either axial in vertical cooling ducts or radial in horizontal cooling ducts with or without zigzag flow.

3.16**directed oil flow****OD**

flow indicating that the principal part of the pumped oil from heat exchangers or radiators is forced to flow through the windings

Note 1 to entry: The oil flow inside the windings can be either axial in vertical cooling ducts or zigzag in horizontal cooling ducts.

3.17**design ambient temperature**

temperature at which the permissible average winding and top-oil and hot-spot temperature over ambient temperature are defined

¹ Numbers in square brackets refer to the bibliography.