



SLOVENSKI STANDARD SIST EN 50131-2-7-2:2012

01-november-2012

Nadomešča:

SIST-TS CLC/TS 50131-2-7-2:2009

Alarmni sistemi - Sistemi za javljanje vloma in ropa - 2-7-2. del: Zahteve za javljalnike vloma - Javljalniki loma stekla (pasivni)

Alarm systems - Intrusion and hold-up systems - Part 2-7-2: Intrusion detectors - Glass break detectors (passive)

Alarmanlagen - Einbruch- und Überfallmeldeanlagen - Teil 2-7-2: Einbruchmelder - Glasbruchmelder (Passiv)

Systemes d'alarme - Systemes d'alarme contre l'intrusion et les hold-up - Partie 2-7-2: Détecteurs d'intrusion - Détecteurs bris de glace (passifs)

Ta slovenski standard je istoveten z: EN 50131-2-7-2:2012

ICS:

| | | |
|--------|-------------------------------|---------------------------|
| 13.310 | Varstvo pred kriminalom | Protection against crime |
| 13.320 | Alarmni in opozorilni sistemi | Alarm and warning systems |

SIST EN 50131-2-7-2:2012

en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 50131-2-7-2:2012

<https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-80378cfl9052/sist-en-50131-2-7-2-2012>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 50131-2-7-2

September 2012

ICS 13.320

Supersedes CLC/TS 50131-2-7-2:2009

English version

**Alarm systems -
Intrusion and hold-up systems -
Part 2-7-2: Intrusion detectors -
Glass break detectors (passive)**

Systemes d'alarme -
Systemes d'alarme contre l'intrusion et les
hold-up -
Partie 2-7-2: Détecteurs d'intrusion -
Détecteurs bris de glace (passifs)

Alarmanlagen -
Einbruch- und Überfallmeldeanlagen -
Teil 2-7-2: Einbruchmelder -
Glasbruchmelder (Passiv)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50131-2-7-2:2012](https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-8094ac117423/sist-en-50131-2-7-2-2012)

<https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-8094ac117423/sist-en-50131-2-7-2-2012>
This European Standard was approved by CENELEC on 2012-08-13. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents

| | |
|---|----------|
| Foreword | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms, definitions and abbreviations | 6 |
| 3.1 Terms and definitions | 6 |
| 3.2 Abbreviations | 7 |
| 4 Functional Requirements | 7 |
| 4.1 Event Processing | 7 |
| 4.2 Operational requirements | 9 |
| 4.2.1 Time interval between intrusion signals or messages | 9 |
| 4.2.2 Switch on delay | 9 |
| 4.2.3 Self tests | 9 |
| 4.3 Detection | 9 |
| 4.3.1 Detection performance | 9 |
| 4.3.2 Indication of detection | 10 |
| 4.4 Immunity to false alarm sources | 10 |
| 4.4.1 General | 10 |
| 4.4.2 Immunity to Small objects hitting the glass | 10 |
| 4.4.3 Immunity to Soft objects hitting the glass | 10 |
| 4.4.4 Immunity to Hard objects hitting the glass | 10 |
| 4.4.5 Immunity to Static pressure | 10 |
| 4.4.6 Immunity to Dynamic pressure | 11 |
| 4.4.7 Immunity to wide band noise | 11 |
| 4.5 Tamper security | 11 |
| 4.5.1 Resistance to and detection of unauthorised access to the inside of the detector through covers and existing holes | 11 |
| 4.5.2 Detection of removal from the mounting surface | 11 |
| 4.5.3 Detection of masking | 11 |
| 4.5.4 Immunity to magnetic field interference | 12 |
| 4.6 Electrical requirements | 12 |

| | | |
|----------|---|-----------|
| 4.6.1 | Detector current consumption | 12 |
| 4.6.2 | Slow input voltage rise and voltage range limits | 12 |
| 4.6.3 | Input voltage ripple | 12 |
| 4.6.4 | Input voltage step change | 12 |
| 4.7 | Environmental classification and conditions | 12 |
| 4.7.1 | Environmental classification | 12 |
| 4.7.2 | Immunity to environmental conditions | 13 |
| 5 | Marking, identification and documentation..... | 13 |
| 5.1 | Marking and/or identification..... | 13 |
| 5.2 | Documentation..... | 13 |
| 6 | Testing..... | 13 |
| 6.1 | General | 13 |
| 6.2 | General test conditions | 14 |
| 6.2.1 | Standard laboratory conditions for testing | 14 |
| 6.2.2 | General detection testing environment and procedures..... | 14 |
| 6.3 | Basic Detection Test..... | 14 |
| 6.3.1 | General | 14 |
| 6.3.2 | Basic Test Source..... | 14 |
| 6.3.3 | Basic Detection Test Method..... | 15 |
| 6.4 | Performance tests..... | 15 |
| 6.4.1 | General | 15 |
| 6.4.2 | Verification of detection performance | 15 |
| 6.4.3 | Hole drilling with a diamond hole saw | 16 |
| 6.4.4 | Glass cutting | 16 |
| 6.5 | Switch-on delay, time interval between signals, and indication of detection | 17 |
| 6.6 | Fault condition signals or messages: self tests | 17 |
| 6.7 | Tests of immunity to false alarm sources | 18 |
| 6.7.1 | General | 18 |
| 6.7.2 | Immunity to Small objects hitting the glass..... | 18 |
| 6.7.3 | Immunity to Soft objects hitting the glass | 18 |
| 6.7.4 | Immunity to Hard objects hitting the glass..... | 19 |
| 6.7.5 | Immunity to Static pressure | 19 |
| 6.7.6 | Immunity to Dynamic pressure | 20 |
| 6.7.7 | Immunity to wide band noise based using IC's | 20 |
| 6.8 | Tamper security | 21 |

| | | |
|----------------|---|-----------|
| 6.8.1 | Prevention of unauthorised access to the inside of the detector through covers and existing holes | 21 |
| 6.8.2 | Detection of removal from the mounting surface..... | 21 |
| 6.8.3 | Resistance to magnetic field interference..... | 21 |
| 6.8.4 | Detection of masking | 21 |
| 6.9 | Electrical tests | 22 |
| 6.9.1 | General | 22 |
| 6.9.2 | Detector current consumption | 22 |
| 6.9.3 | Slow input voltage change and input voltage range limits..... | 22 |
| 6.9.4 | Input voltage ripple | 23 |
| 6.9.5 | Input voltage step change | 23 |
| 6.9.6 | Total loss of power supply | 23 |
| 6.10 | Environmental classification and conditions | 23 |
| 6.11 | Marking, identification and documentation | 24 |
| 6.11.1 | Marking and/or identification..... | 24 |
| 6.11.2 | Documentation | 25 |
| Annex A | (normative) Catalogue of standard glass types..... | 26 |
| Annex B | (informative) List of small tools suitable for testing immunity of casing to attack..... | 27 |
| Annex C | (normative) Dimensions & Requirements of a standard test magnet | 28 |
| Annex D | (normative) Immunity test: Small objects hit sensitivity | 31 |
| Annex E | (normative) Immunity test: Soft objects hit sensitivity | 32 |
| Annex F | (normative) Immunity test: Hard objects hit sensitivity | 33 |
| Annex G | (normative) Immunity test: Static pressure sensitivity..... | 34 |
| Annex H | (normative) Immunity test: Dynamic pressure sensitivity..... | 35 |
| Annex I | (normative) General testing matrix | 36 |
| Annex J | (normative) Performance test setup and alternative performance test setup | 38 |
| J.1 | Performance test setup..... | 38 |
| J.2 | Alternative performance test setup..... | 39 |
| Annex K | (normative) Performance sensitivity test | 41 |

Foreword

This document (EN 50131-2-7-2:2012) has been prepared by CLC/TC 79 "Alarm systems".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-08-13
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2015-08-13

This document supersedes CLC/TS 50131-2-7-2:2009.

This European Standard provides for security Grades 1 to 4 (see EN 50131-1) glass break (passive) detectors installed in buildings, and uses environmental classes I to IV (see EN 50130-5).

The purpose of a detector is to detect the energy exclusively emitted by the physical destruction of a glass pane, which allows intrusion to the monitored area for example in doors, windows or enclosures and to provide the necessary range of signals or messages to be used by the rest of the intruder alarm system.

Functions additional to the mandatory functions specified in this standard may be included in the detector, providing they do not adversely influence the correct operation of the mandatory functions.

The number and scope of these signals or messages may be more comprehensive for systems that are specified at the higher Grades.

[SIST EN 50131-2-7-2:2012](https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-8016c1e05125/sist-en-50131-2-7-2-2012)

[https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-](https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-8016c1e05125/sist-en-50131-2-7-2-2012)

This standard is only concerned with the requirements and tests for the detector. Other types of detectors are covered by other documents identified as TS / EN 50131-2-x.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

1 Scope

This European Standard is for passive surface mounted glass break detectors installed in buildings and provides for security Grades 1 to 4 (see EN 50131-1), specific or non-specific wired or wire-free detectors, and uses environmental classes I to IV (see EN 50130-5). This European Standard does not include requirements for passive surface mounted glass break detectors intended for use outdoors.

A detector shall fulfil all the requirements of the specified Grade.

Functions additional to the mandatory functions specified in this standard may be included in the detector, providing they do not adversely influence the correct operation of the mandatory functions.

This European Standard does not apply to system interconnections.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

| | |
|-----------------|---|
| EN 50130-4 | <i>Alarm systems — Part 4: Electromagnetic compatibility — Product family standard: Immunity requirements for components of fire, intruder and social alarm systems</i> |
| EN 50130-5 | <i>Alarm systems — Part 5: Environmental test methods</i> |
| EN 50131-1:2006 | <i>Alarm systems — Intrusion and hold-up systems — Part 1: System requirements</i> |
| EN 50131-6 | <i>Alarm systems — Intrusion systems — Part 6: Power supplies</i> |
| EN 60068-1:1994 | <i>Environmental testing — Part 1: General and guidance (IEC 60068-1:1988 + A1:1992 + corrigendum Oct. 1988)</i> |
| EN 60529 | <i>Degrees of protection provided by enclosures (IP code) (IEC 60529)</i> |

3 Terms, definitions and abbreviations

For the purposes of this document, the terms, definitions and abbreviations given in EN 50131-1:2006 and the following apply.

3.1 Terms and definitions

3.1.1

glass breakage

physical destruction of a glass pane, which allows intrusion to the monitored area, for example in doors, windows or enclosures

3.1.2

passive surface mounted glass break detector

detector that is mounted on a glass pane, which detects the energy emitted by a glass breakage of the pane the detector is mounted on

3.1.3

Basic Test Source

signal simulator designed to verify the basic function of the detector

3.1.4**incorrect operation**

physical condition that causes an inappropriate signal or message from a detector

3.1.5**Basic Detection Test**

test whose purpose is to verify the operation of a detector after conditioning

3.1.6**masking**

interference with the detector input capability such as an introduction of a physical barrier (e.g. metal, plastic, paper or sprayed paints or lacquers in close proximity to the detector) or changing the characteristics of the monitored area (e.g. placing wet newspapers on the outside of the monitored glass pane)

3.1.7**standard immunity glass pane**

glass pane to be used for all immunity tests, where a glass pane is needed, according to Annex A.

3.1.8**simultaneous Installation**

installation of more than one detector or sensor pair of one detector type (e.g. sender and receiver) for one or more detector's processing units

3.2 Abbreviations

BTS – Basic Test Source.

EMC – Electromagnetic Compatibility

[SIST EN 50131-2-7-2:2012
https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-80578cf19052/sist-en-50131-2-7-2-2012](https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-80578cf19052/sist-en-50131-2-7-2-2012)

(standards.iteh.ai)

4 Functional Requirements**4.1 Event Processing**

Detectors shall process the events shown in Table 1. Detectors shall generate signals or messages as shown in Table 2.

Table 1 — Events to be processed by Grade

| Event | Grade | | | |
|--|-------|----|----|---|
| | 1 | 2 | 3 | 4 |
| Intrusion | M | M | M | M |
| No Stimulus ^a | M | M | M | M |
| Masking | Op | Op | M | M |
| Tamper | Op | M | M | M |
| Low Supply Voltage | Op | Op | M | M |
| Total loss of power supply | Op | M | M | M |
| Local Self Test | Op | Op | M | M |
| Remote Self Test | Op | Op | Op | M |
| M = Mandatory Op = Optional ^a 'No Stimulus' is considered to be the quiet condition, while no alarm generating stimulus for a detector at that time applies to the detector input capabilities. | | | | |

Table 2 — Generation of Indication Signals or Messages

| Event | Signals or Messages | | |
|--|---------------------|--------|-------|
| | Intrusion | Tamper | Fault |
| Intrusion | M | NP | NP |
| No Stimulus | NP | NP | NP |
| Masking ^a | M | Op | M |
| Tamper | NP | M | NP |
| Low Supply Voltage | Op | Op | M |
| Total loss of power supply ^b | M | Op | Op |
| Local Self Test Pass | NP | NP | NP |
| Local Self Test Fail | NP | NP | M |
| Remote Self Test Pass | M | NP | NP |
| Remote Self Test Fail | NP | NP | M |
| M = mandatory NP = Not permitted Op = Optional | | | |
| ^a An independent masking signal or message may be provided instead ^b Alternatively Total loss of Power Supply shall be determined by loss of communication with the detector. | | | |
| This permits two methods of signalling a masking event: either by the intrusion signal and fault signal, or by a dedicated output. Use of the intrusion signal and fault signal is preferable, as this requires fewer connections between CIE and detector. If multiple events overlap there will be some signal combinations that may be ambiguous. To overcome this ambiguity it is suggested that detectors should not signal 'intrusion' and 'fault' at the same time except to indicate masking. This implies that the detector should prioritise signals, e.g. 1. Intrusion, 2 Fault, 3 Masking. | | | |
| When, in Table 1, an event may optionally generate signals or messages, they shall be as shown in this table. | | | |

4.2 Operational requirements

4.2.1 Time interval between intrusion signals or messages

Wired detectors shall be able to provide an intrusion signal or message not more than 15 s after the end of the preceding intrusion signal or message.

Wire free detectors shall be able to provide an intrusion signal or message after the end of the preceding intrusion signal or message within the following times:

| | |
|---------|-------|
| Grade 1 | 300 s |
| Grade 2 | 180 s |
| Grade 3 | 30 s |
| Grade 4 | 15 s |

4.2.2 Switch on delay

The detector shall meet all functional requirements within 180 s of the power supply reaching its nominal voltage as specified by the manufacturer.

4.2.3 Self tests

4.2.3.1 Local self test

The detector shall automatically test itself at least once every 24 h according to the requirements of Tables 1 and 2. If normal operation of the detector is inhibited during a local self-test, the detector inhibition time shall be limited to a maximum of 30 s in any period of 2 h.

4.2.3.2 Remote self test

A detector shall process remote self tests and generate signals or messages in accordance with Tables 1 and 2 within 10 s of the remote self test signal being received, and shall return to normal operation within 30 s of the remote test signal being received.

4.3 Detection

4.3.1 Detection performance

The detector shall generate an intrusion signal or message when a simulated or real glass breakage according to the corresponding requirements of Table 3 is performed.

Table 3 — Performance test requirements

| Requirement | Grade 1 | Grade 2 | Grade 3 | Grade 4 |
|---|---------|---------|---------|---------|
| Verification of detection performance | M | M | M | M |
| Performance test: hole drilling with diamond hole saw | Op | Op | Op | M |
| Performance test: Glass cutting | Op | Op | Op | M |
| M = Mandatory Op = Optional | | | | |

4.3.1.1 Verification of detection performance

This test will verify the detection performance for sensitivity and a break through the glass according to the supported conditions claimed by the manufacturer. It will verify the maximum covering range (sensitivity performance test) and the break through detection (breakage performance test), according

to Annex A for different glass types and sizes claimed to be supported (types and dimensions) by the manufacturer. A number of standard glass types and sizes need to be passed by this test according to the corresponding test section.

4.3.1.2 Performance test for hole drilling with a diamond hole saw

This test will verify the detection performance by drilling a hole using a diamond hole saw on different glass types and dimensions according to the supported conditions claimed by the manufacturer and Annex A. It will verify if the detector is able to identify and signal the change of the integrity of the monitored side of the glass pane.

4.3.1.3 Performance test for Glass cutting

This test will verify the detection performance by cutting the glass using a standard glass cutter on different glass types and dimensions according to the supported conditions claimed by the manufacturer and Annex A. It will verify if the detector is able to identify and signal the change of the integrity of the monitored side of the glass pane.

4.3.2 Indication of detection

Powered detectors at Grades 3 and 4 that include processing capabilities shall provide an indicator at the detector to indicate when an intrusion signal or message has been generated. Self-powered detectors (e.g. detectors which rely on the energy resulting from the glass breakage) do not require such an indicator.

At Grades 3 and 4 this indicator shall be capable of being enabled and disabled remotely at Access Level 2.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.4 Immunity to false alarm sources

[SIST EN 50131-2-7-2:2012](https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-80378cfl9052/sist-en-50131-2-7-2-2012)

4.4.1 General

<https://standards.iteh.ai/catalog/standards/sist/c331a216-b95f-4f5a-88d4-80378cfl9052/sist-en-50131-2-7-2-2012>

The detector shall have sufficient immunity to false alarm sources if the following requirements have been met. No intrusion signal or message shall be generated as a result of the false alarm sources according to each individual test clause.

The tests for this clause will be performed on the standard immunity test glass pane as defined in 3.1.7, wherever a glass pane is required.

4.4.2 Immunity to Small objects hitting the glass

The detector shall not generate an intrusion signal or message when small objects such as hail, sand, gravel etc. hit the outside of the monitored glass. The tests are described in 6.7.2.

4.4.3 Immunity to Soft objects hitting the glass

The detector shall not generate an intrusion signal or message when soft objects (e.g. a human fist) hit the outside of the monitored glass. The tests are described in 6.7.3.

4.4.4 Immunity to Hard objects hitting the glass

The detector shall not generate an intrusion signal or message when hard objects (e.g. handlebars of a bicycle) hit the outside of the monitored glass. The tests are described in 6.7.4.

4.4.5 Immunity to Static pressure

The detector shall not generate an intrusion signal or message when permanent pressure changes applied to the monitored glass. The tests are described in 6.7.5.

4.4.6 Immunity to Dynamic pressure

The detector shall not generate an intrusion signal or message when dynamic pressure changes (due to wind, etc.) applied to the monitored glass. The tests are described in 6.7.6.

4.4.7 Immunity to wide band noise

The detector shall not generate an intrusion signal or message when a wide band of frequencies at the same time, which are close to the frequency of a glass breakage (e.g. branches of a tree moving against the window) are applied to the detector. The tests are described in 6.7.7.

4.5 Tamper security

NOTE Tamper security requirements for each Grade of a detector are shown in Table 4.

Table 4 - Tamper security requirements

| Requirement | Grade 1 | Grade 2 | Grade 3 | Grade 4 |
|---|---------|----------------|---------|---------|
| Resistance to access to the inside of the detector | M | M | M | M |
| Detection of access to the inside of the detector ^a | Op | M | M | M |
| Removal from the mounting surface ^b | Op | M ^c | M | M |
| Detection of masking | Op | Op | M | M |
| Magnetic field Immunity | Op | M | M | M |
| Magnet type defined in Annex C | | Type 1 | Type 2 | Type 2 |
| M= Mandatory Op = Optional | | | | |
| ^a Not required for wired detectors which are fully potted and where it is not possible to get access to any adjustments or components ^b At grade 2 and grade 3 not required if the detector is mounted properly according to the manufacturers instructions with a two - component / epoxy glue (adhesive & activator), which supports the requested environmental conditions when mounted and fixed. ^c At grade 2 required for wire free detectors only, if the wire free detectors do not use a two - component / epoxy glue (adhesive & activator) for fixing | | | | |

4.5.1 Resistance to and detection of unauthorised access to the inside of the detector through covers and existing holes

All components and means of adjustment which, when interfered with, could adversely affect the operation of the detector, shall be located within the detector housing. Such access shall require the use of an appropriate tool and depending on the Grade as specified in Table 4 shall generate a tamper signal or message before access can be gained.

It shall not be possible to gain access without generating a tamper signal or message or causing visible damage.

4.5.2 Detection of removal from the mounting surface

A tamper signal or message shall be generated if the detector is removed from its mounting surface, in accordance with Table 4.

4.5.3 Detection of masking

Means shall be provided to detect inhibition of the operation of the detector by masking according to the requirements of Table 4. Alternatively, the detector shall continue to operate normally.

NOTE 1 In an I&HAS any masked detectors prevent the setting of the system.