

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Packaging of components for automatic handling –
Part 1: Tape packaging of components with axial leads on continuous tapes**

**Emballage des composants pour opérations automatisées –
Partie 1: Mise en bande des composants à sorties axiales en bandes continues**

ITU STANDARD PREVIEW
(standards.iteh.ai)

IEC 60286-1:2017
<https://standards.iteh.ai/catalog/standards/sist/d2a181ec-c626-4c7a-bbcb-064cea3afb53/iec-60286-1-2017>





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22.000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67.000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22.000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67.000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Packaging of components for automatic handling –
Part 1: Tape packaging of components with axial leads on continuous tapes**

**Emballage des composants pour opérations automatisées –
Partie 1: Mise en bande des composants à sorties axiales en bandes continues**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.020 31.240

ISBN 978-2-8322-7259-6

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

CONTENTS	2
FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Dimensions	5
4.1 Dimensions common to tapes and taped components with axial leads	5
4.1.1 General	5
4.1.2 Body location (permissible lateral deviation)	7
4.1.3 Tape spacing	7
4.2 Taping	7
4.2.1 General	7
4.2.2 Orientation of polarized components	8
4.2.3 Position, kinks and bends of the leads	8
4.2.4 The ends of the leads	8
4.2.5 Holding in the tape	8
4.2.6 Requirements of tape material, storage, and handling	8
4.2.7 Splices of tape	8
4.2.8 Leader tape	8
5 Packing	8
5.1 General	8
5.2 Dimensions of the reel	9
5.3 Distances W_1 and W_2	9
5.4 Recycling	9
5.5 Protection of components	9
5.6 Reel filling	9
5.7 Dimensions of the fan-fold container	10
5.8 Missing components	10
6 Marking	10
Annex A (informative) Cross-reference for references to the previous edition of this document	11
Bibliography	12
Figure 1 – Dimensions for tape packaging of components with axial leads	6
Figure 2 – Reel dimensions	9
Figure 3 – Outer dimensions of the fan-fold arrangement	10
Table 1 – Tape widths and permissible variation	6
Table 2 – Component spacing and permissible deviation	7
Table 3 – Tape spacing	7
Table A.1 – Cross-reference to clauses	11

ITC STANDARD PREVIEW
 (standards.iteh.ai)

IEC 60286-1:2017

<https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-064cea3afb53/iec-60286-1-2017>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING –**Part 1: Tape packaging of components
with axial leads on continuous tapes**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
<https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-211111111111>
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60286-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This bilingual version (2019-08) corresponds to the monolingual English version, published in 2017-07.

This third edition cancels and replaces the second edition published in 1997. This edition constitutes a technical revision.

This edition includes the following significant changes with respect to the previous edition:

- a) a complete revision of the structure (detailed in Annex A) and reworked layout.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
40/2538/FDIS	40/2552/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60286 series, under the general title *Packaging of components for automatic handling*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60286-1:2017](https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-064cea3afb53/iec-60286-1-2017)

<https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-064cea3afb53/iec-60286-1-2017>

PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING –

Part 1: Tape packaging of components with axial leads on continuous tapes

1 Scope

This part of IEC 60286 applies to the tape packaging of components with axial leads for use in electronic equipment. In general, the tape is applied to the component leads.

It covers requirements for taping techniques used with equipment for the preforming of leads, automatic handling, insertion and other operations, and includes only those dimensions which are essential to the taping of components intended for the above-mentioned purposes.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60294, *Measurement of the dimensions of a cylindrical component with axial terminations*

ISO 11469, *Plastics – Generic identification and marking of plastic products*

<https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-064cea3afb53/iec-60286-1-2017>

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:


- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Dimensions

4.1 Dimensions common to tapes and taped components with axial leads

4.1.1 General

The general configuration is shown in Figure 1, Table 1 and Table 2.



STANDARD PREVIEW (standards.iteh.ai)

Key

- A* is the distance between adjacent components in tape.
- B* Is the Inner distance between two tapes. IEC 60286-1:2017
- K* is the allowed displacement distance of component in tape. <https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-064cea3afb53/iec-60286-1-2017>
- L₁* is lead length between component body and inner side of tape on left side.
- L₂* is lead length between component body and inner side of tape on right side.
- L₃* is the part of lead protruded outside the tape.
- L_{max}* is the body length of the component.
- M* is the max allowed distance of displacement.
- T* is the width of the tape.
- W* is the maximum allowed total distance of the component after protrusion of leads outside of the tape.

Figure 1 – Dimensions for tape packaging of components with axial leads

Table 1 – Tape widths and permissible variation

Nominal widths of tape <i>T</i> mm	Permissible variation in width mm
6	±1
9	±1

Table 2 – Component spacing and permissible deviation

Standard spacing between components <i>A</i> mm	Permissible cumulative deviation over ten spacing <i>P</i> mm
5 ± 0,5	±2
10 ± 0,5	±2
15 ± 0,5	±2
20 ± 0,5	±2

4.1.2 Body location (permissible lateral deviation)

Dimension K , being the width of the window in which the component body shall be located, shall be 1,0 mm (for $B = 26$ mm) or 1,4 mm (for $B > 26$ mm) wider than the maximum length L_{\max} of the component body. The latter is the body length measured in accordance with IEC 60294.

Unless otherwise specified, the window shall be centrally located between the tapes.

When a gauge measurement to determine dimension K is impractical, it is possible to measure the distances L_1 and L_2 of the leads. The difference between L_1 and L_2 shall not exceed 1,0 mm (for $B = 26$ mm) or 1,4 mm (for $B > 26$ mm).

4.1.3 Tape spacing

The maximum overall width W , including any lead protrusion L_3 , shall not exceed 140 mm. Its value shall be chosen in relation to the component dimensions.

The tape spacing given in Table 3 is recommended.

Table 3 – Tape spacing

Inside tape spacing <i>B</i> mm
26 $\begin{smallmatrix} +1,5 \\ 0 \end{smallmatrix}$
52 $\begin{smallmatrix} +2 \\ -1 \end{smallmatrix}$
63 ± 2
73 ± 2
83 ± 2
93 ± 2
Inside tape spacing B above 93 mm to be in 10 mm increments with a tolerance ±2 mm as long as the maximum overall width W of 140 mm is not exceeded.

4.2 Taping

4.2.1 General

The following requirements for axial components shall be met as appropriate (see Figure 1).

4.2.2 Orientation of polarized components

All polarized components shall be oriented in one direction; the polarized components shall be clearly identified by use of different colours or marked tapes, the anode being of a white or neutral colour.

4.2.3 Position, kinks and bends of the leads

The position, kinks and bends of the leads are as follows.

- a) The leads shall be free from kinks and bends.
- b) The method used to position the component leads on the tape shall be such that the leads are not nicked or otherwise damaged.
- c) Leads shall not be bent beyond 1,0 mm (for $B = 26$ mm) or 1,2 mm (for $B > 26$ mm) from their nominal position when measured from the leading edge of the component lead at the inside tape edge and at the lead egress from the component (see dimension M in Figure 1).

4.2.4 The ends of the leads

The ends of the leads shall not protrude beyond the tapes.

4.2.5 Holding in the tape

The components shall be held sufficiently in the tape(s) so that they cannot come free during normal handling.

4.2.6 Requirements of tape material, storage, and handling

The tapes shall be suitable to withstand storage of the taped components. The tape material shall not migrate along the leads or give off vapours that can affect solderability or deteriorate the component properties or leads by chemical action (e.g. corrosion).

In addition, the tapes shall not become detached, thereby causing the components to lose their relative position after storage, and the tape shall not age to such an extent that its strength is reduced, causing it to break either when the components are unreeled manually or by an assembly machine.

Tapes in adjacent layers shall not stick together in the packing, because of the exposed adhesive for instance.

4.2.7 Splices of tape

Splices shall be at least as strong as the original tape and shall not be thicker than four times the thickness of a single layer of the original tape. Splices shall not be misaligned by more than 0,8 mm. When splicing is applied, component spacing A shall remain within the tolerances as specified in Table 2.

4.2.8 Leader tape

A twin leader tape, free of components, having a minimum length of 200 mm shall be provided at the beginning and at the end of the tape.


5 Packing

5.1 General

The tapes of components may either be wound on reels or fan-folded.

5.2 Dimensions of the reel

The preferred reel dimensions are shown in Figure 2.



Key

- 1 is the optional shape: circular or square.
- 2 is the optional shape: circular or polygonal. IEC 60286-1:2017
- A is the reel diameter: maximum 400 mm. <https://standards.iteh.ai/catalog/standards/sist/d2a181ec-cb2b-4e7a-bbeb-064cea3afb53/iec-60286-1-2017>
- C is the arbor hole diameter: 14 mm to 38 mm.
- N is the hub diameter: 34,9 mm to 102 mm.

Figure 2 – Reel dimensions

5.3 Distances W_1 and W_2

The distances W_1 and W_2 shall be governed by the overall width of the taped components W (see Figure 1) and shall allow proper reeling and unreeling.

5.4 Recycling

Reels as defined in Figure 2 should be made of recyclable material. When such material is used, the reel shall be permanently marked with the recycling symbol.

ISO 11469 should be used for making the material.

5.5 Protection of components

In order to prevent component damage and lead distortion, protection between layers of components and over the last layer may be necessary. In this case, protection materials shall not cause deterioration of the component or of lead solderability.

5.6 Reel filling

The total number of components on the reel shall be such that the components and the final cover shall not extend beyond the smallest dimension of the flange in the radial direction.