

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Varistors for use in electronic equipment –
Part 1: Generic specification**

ITIH STANDARD PREVIEW
(standards.iteh.ai)

**Varistances utilisées dans les équipements électroniques –
Partie 1: Spécification générique**

IEC 61051-1:2018
<https://standards.iteh.ai/catalog/standards/sist/3904b12d-80d4-4183-ad15-073445edccf5/iec-61051-1-2018>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 21 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 21 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.



IEC 61051-1

Edition 3.0 2018-10

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Varistors for use in electronic equipment –
Part 1: Generic specification**

**Varistances utilisées dans les équipements électroniques –
Partie 1: Spécification générique**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 31.040.99

ISBN 978-2-8322-6089-0

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	7
1 Scope.....	9
2 Normative references	9
3 Terms and definitions	10
4 Technical data	15
4.1 Units, symbols and terminology	15
4.2 Preferred values and characteristics	15
4.3 Marking.....	15
4.3.1 General	15
4.3.2 Coding.....	16
5 Quality assessment procedures	16
5.1 General.....	16
5.1.1 Overview	16
5.1.2 Applicability of qualification approval	16
5.1.3 Applicability of capability approval	16
5.1.4 Applicability of technology approval	17
5.2 Primary stage of manufacture	17
5.3 Subcontracting	17
5.4 Structurally similar components	17
5.5 Qualification approval procedures	18
5.5.1 Eligibility for qualification approval	18
5.5.2 Application for qualification approval	18
5.5.3 Test procedure for qualification approval	18
5.5.4 Granting of qualification approval	18
5.5.5 Maintenance of qualification approval	18
5.5.6 Quality conformance inspection.....	18
5.6 Capability approval procedures	19
5.6.1 General	19
5.6.2 Eligibility for capability approval.....	19
5.6.3 Application for capability approval	19
5.6.4 Description of capability	19
5.6.5 Demonstration and verification of capability	20
5.6.6 Programme for capability approval	21
5.6.7 Capability approval test report.....	21
5.6.8 Abstract of description of capability	21
5.6.9 Modifications likely to affect the capability approval	21
5.6.10 Initial capability approval	21
5.6.11 Granting of capability approval	22
5.6.12 Maintenance of capability approval.....	23
5.6.13 Extension of capability approval	23
5.6.14 Quality conformance inspection.....	23
5.7 Rework and repair.....	23
5.7.1 Rework	23
5.7.2 Repair	24
5.8 Release for delivery	24
5.8.1 General	24

5.8.2	Certified records of released lots.....	24
5.8.3	Delayed delivery	24
5.8.4	Release for delivery before the completion of Group B tests	24
5.9	Alternative test methods.....	24
5.10	Unchecked parameters.....	25
5.11	Characteristics and parameters for application reference	25
5.12	Technology approval procedures	25
5.12.1	General	25
5.12.2	Eligibility for technology approval	25
5.12.3	Application of technology approval	25
5.12.4	Description of technology	25
5.12.5	Demonstration and verification of the technology	25
5.12.6	Granting of technology approval	26
5.12.7	Maintenance of technology approval.....	26
5.12.8	Quality conformance inspection.....	26
5.12.9	Failure rate level determination	26
5.12.10	Outgoing quality level.....	26
6	Test and measurement procedures	26
6.1	General.....	26
6.2	Standard atmospheric conditions	26
6.2.1	Standard atmospheric conditions for testing.....	26
6.2.2	Recovery conditions	27
6.2.3	Referee conditions	27
6.2.4	Reference conditions	27
6.3	Drying and recovery	27
6.3.1	General	27
6.3.2	Procedure I.....	27
6.3.3	Procedure II.....	27
6.4	Visual examination and check of dimensions	28
6.4.1	Visual examination.....	28
6.4.2	Marking	28
6.4.3	Dimensions (gauging)	28
6.4.4	Dimensions (detail)	28
6.5	General requirements for electrical tests.....	28
6.6	Varistor voltage.....	29
6.7	Leakage current	29
6.8	Capacitance.....	30
6.9	Voltage proof (for insulated varistors only).....	30
6.9.1	General	30
6.9.2	V-block method.....	30
6.9.3	Metal ball method	30
6.9.4	Foil method.....	30
6.10	Insulation resistance (for insulated varistors only).....	31
6.10.1	Test procedure.....	31
6.10.2	Measurement and requirements.....	31
6.11	Clamping voltage	31
6.12	ESD clamping voltage (for surface mount electrostatic protective varistors only)	32
6.13	Maximum peak current	32

6.13.1	Initial measurement.....	32
6.13.2	Test procedure.....	32
6.13.3	Final inspection, measurement and requirements.....	32
6.14	Rated average dissipation power.....	32
6.14.1	General	32
6.14.2	Initial measurement.....	33
6.14.3	Test procedure.....	33
6.14.4	Final inspection, measurement and requirements.....	33
6.15	Rated energy	33
6.15.1	General	33
6.15.2	Initial measurement.....	33
6.15.3	Test procedure.....	34
6.15.4	Final inspection, measurement and requirements.....	34
6.16	Electrostatic discharge (ESD) (for surface mount electrostatic protective varistors only)	35
6.16.1	Initial measurement.....	35
6.16.2	Test procedure.....	35
6.16.3	Final inspection, measurement and requirements.....	35
6.17	Robustness of terminations	35
6.17.1	General	35
6.17.2	Test Ua1 – Tensile.....	35
6.17.3	Test Ub – Bending (half of the number of terminations)	35
6.17.4	Test Uc – Torsion (the other half of the number of terminations)	35
6.17.5	Test Ud – Torque (for terminations with threaded studs or screws and for integral mounting devices).....	36
6.17.6	Visual examination.....	36
6.17.7	Final measurement.....	36
6.17.8	Robustness of terminations of surface mount varistors.....	36
6.18	Resistance to soldering heat	37
6.18.1	Preconditioning	37
6.18.2	Test procedure.....	37
6.18.3	Recovery	38
6.18.4	Final inspection, measurement and requirements.....	38
6.19	Solderability.....	38
6.19.1	General	38
6.19.2	Test procedure.....	38
6.19.3	Final inspection, measurements and requirements.....	39
6.20	Rapid change of temperature	39
6.20.1	Initial measurement.....	39
6.20.2	Test procedure.....	39
6.20.3	Final inspection, measurement and requirements.....	39
6.21	Shock	39
6.21.1	Initial measurement.....	39
6.21.2	Test procedure.....	39
6.21.3	Final inspection, measurement and requirements.....	39
6.22	Vibration	40
6.22.1	Initial measurement.....	40
6.22.2	Test procedure.....	40
6.22.3	Final inspection, measurement and requirements.....	40

6.23	Climatic sequence	40
6.23.1	General	40
6.23.2	Initial measurement	40
6.23.3	Dry heat	40
6.23.4	Damp heat, cyclic, Test Db, first cycle	40
6.23.5	Cold	40
6.23.6	Low air pressure	40
6.23.7	Damp heat, cyclic, Test Db, remaining cycles	41
6.23.8	Final inspection, measurement and requirements	41
6.24	Damp heat, steady state	41
6.24.1	Initial measurement	41
6.24.2	Test procedure	41
6.24.3	Final inspection, measurement and requirements	41
6.25	Fire hazard	42
6.26	Endurance at upper category temperature	42
6.26.1	Test system	42
6.26.2	Initial measurement	42
6.26.3	Mounting of the samples	42
6.26.4	Test procedure, measurement and requirements	43
6.27	Solvent resistance of marking	43
6.27.1	Test procedure	43
6.27.2	Requirements	43
6.28	Component solvent resistance	43
6.28.1	Initial measurements	43
6.28.2	Test procedure	43
6.28.3	Measurement and requirements	44
6.29	Mounting (for surface mount varistors only)	44
Annex A (informative)	Rules for the preparation of detail specifications for capacitors and resistors for electronic equipment	46
Annex B (normative)	Test pulses used in this specification	47
B.1	Types of test pulses	47
B.1.1	General	47
B.1.2	Pulse type 1	47
B.1.3	Pulse type 2 (rectangular pulse)	47
B.1.4	Pulse type 3 (ESD discharge pulse)	47
B.2	Pulse parameters	48
B.2.1	Value of the pulse current/voltage	48
B.2.2	Virtual front time T_1	48
B.2.3	Virtual origin O_1	49
B.2.4	Virtual time to half-value T_2	49
B.2.5	Virtual duration of peak of a rectangular pulse current T_D	49
B.2.6	Virtual total duration T_T of a pulse current	49
B.3	Tolerances for the pulses	50
Annex C (informative)	Recommended measurement/test methods for characteristics and parameters for application reference	51
C.1	Voltage vs. current characteristic	51
C.2	Maximum peak current derating characteristic	52
C.2.1	Rationale related to this test	52
C.2.2	Failure criteria	52

C.2.3	Pulse life test	52
C.2.4	Graphing of the maximum peak current derating curves	54
C.3	Thermal resistance (for leaded varistors only)	54
C.3.1	Test system	54
C.3.2	Mounting of the sample	55
C.3.3	Test procedure	55
C.4	Abnormal overvoltage withstanding duration	55
C.4.1	Test system	55
C.4.2	Test procedure	56
C.4.3	Requirements	56
Figure 1	General scheme for capability approval	19
Figure 2	Mounting method for measurement of surface mount varistors	44
Figure B.1	Shape of pulse current type 1	47
Figure B.2	Shape of pulse voltage type 1	48
Figure B.3	Shape of pulse type 2	48
Figure B.4	Shape of pulse type 3	49
Figure C.1	Maximum peak current derating characteristic	54
Table 1	Standard atmospheric conditions	27
Table 2	Force for wire terminations	36
Table 3	Torque	36
Table 4	Number of cycles	41
Table B.1	Accepted differences between specified and recorded pulse values	50
Table B.2	Tolerances for pulse type 3	50

STANDARD PREVIEW

(standards.itech.ai)

IEC 61051-1:2018

<https://standards.itech.ai/catalog/standards/sist/3904b12d-80d4-4183-ad15-075443edcc15/iec-61051-1-2018>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

VARISTORS FOR USE IN ELECTRONIC EQUIPMENT –**Part 1: Generic specification****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61051-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This third edition cancels and replaces the second edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) 10 new terms and definitions – leaded varistors, surface mount varistors (SMV), electrostatic discharge (ESD), ESD clamping voltage, equivalent rectangular pulse duration, maximum peak current derating characteristic, rated average dissipation power, rated energy, abnormal overvoltage withstanding duration and temperature derating curve – have been added (see 3.6, 3.7, 3.14, 3.15, 3.19, 3.20, 3.23, 3.24, 3.25 and 3.29);
- b) General requirements for electrical tests and 7 new test items – clamping voltage, ESD clamping voltage, maximum peak current, rated average dissipation power, rated energy, electrostatic discharge (ESD), robustness of terminations of surface mount varistors – have been added (see 6.5, 6.11, 6.12, 6.13, 6.14, 6.15, 6.16 and 6.17.8);
- c) In 6.6, 6.7, 6.8, 6.9.3, 6.23.2, 6.23.4 and 6.26, following test items have been revised:

- Varistor voltage, leakage current and capacitance: more detailed requirements and information have been added;
 - Voltage proof – foil method: the space between the edge of the foil and each termination has been changed from 1 mm ~ 1,5 mm to 3 mm ~ 3.5 mm for testing varistors not having axial terminations and the minimum space between the foil and the termination has been changed from 1 mm to 3 mm for testing varistors having axial terminations;
 - Climatic sequence – dry heat: the method has been changed from Ba to Bb;
 - Climatic sequence – cold: the method has been changed from Aa to Ab;
 - Endurance at upper category temperature: the method of "applying test voltages in cycles of 1,5 h on and 0,5 h off" has been changed to the method of applying test voltages continuously throughout the test lasting for 1 000 h;
- d) The test items of pulse current, voltage under pulse condition and bump have been deleted from the section of test and measurement procedures;
- e) Annex A and the contents referring to the test fixture specified in Annex A have been deleted;
- f) All contents related to silicon carbide varistors have been deleted;
- g) A new normative annex entitled "Test pulses used in this specification" (Annex B) has been added;
- h) A new informative annex entitled "Recommended measurement/test methods for characteristics and parameters for application reference" (Annex C) has been added, in which guidelines of measuring/testing characteristics and parameters for application reference including voltage vs. current characteristic, maximum peak current derating characteristic, thermal resistance and abnormal overvoltage withstanding duration have been given.

The text of this International Standard is based on the following documents:

<https://standards.iteh.ai/catalog/standards/sist/3904b12d-80d4-4183-ad15-073445edccf5/iec-61051-1-2018>

FDIS	Report on voting
40/2621/FDIS	40/2625/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61051 series, published under the general title *Varistors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

VARISTORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 1: Generic specification

1 Scope

This part of IEC 61051 is a generic specification and is applicable to varistors with symmetrical voltage-current characteristics for use in electronic equipment.

It establishes standard terms, inspection procedures and methods of test for use in sectional and detail specifications for quality assessment or any other purpose.

NOTE Detail specifications can be specifications within the IEC system, another specification system linked to IEC, or specified by the manufacturer or user. The drafting of a complete detail specification by IEC technical committee 40, if required, follows the rules described in Annex A.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027 (all parts), *Letter symbols to be used in electrical technology*

<http://standards.iteh.ai/iec-61051-1-2018>

IEC 60050 (all parts), *International Electrotechnical Vocabulary (IEV)*

IEC 60062, *Marking codes for resistors and capacitors*

IEC 60068-1:2013, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-1:2007, *Environmental testing – Part 2-1: Tests – Test A: Cold*

IEC 60068-2-2:2007, *Environmental testing – Part 2-2: Tests – Tests B: Dry heat*

IEC 60068-2-6:2007, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (Sinusoidal)*

IEC 60068-2-13:1983, *Environmental testing – Part 2-13: Tests – Test M: Low air pressure*

IEC 60068-2-14:2009, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-20:2008, *Environmental testing – Part 2-20: Tests – Test T: Test methods for solderability and resistance to soldering heat of devices with leads*

IEC 60068-2-21:2006, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-21:2006/COR1:2012

IEC 60068-2-27:2008, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-30:2005, *Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 h + 12-hour cycle)*

IEC 60068-2-45:1980, *Environmental testing – Part 2-45: Tests – Test XA – Immersion in cleaning solvents*

IEC 60068-2-45:1980/AMD1:1993

IEC 60068-2-58:2015, *Environmental testing – Part 2-58: Tests – Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*

IEC 60068-2-69:2017, *Environmental testing – Part 2-69: Tests – Test Te/Tc: Solderability testing of electronic components and printed boards by the wetting balance (force measurement) method*

IEC 60068-2-78:2012, *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60294, *Measurement of the dimensions of a cylindrical component having two axial terminations*

IEC 60617, *Graphical symbols for diagrams*
(available at <http://std.iec.ch/iec60617>)

IEC 60695-11-5:2016, *Fire hazard testing – Part 11-5: Test flames – Needle-flame test method – Apparatus, confirmatory test arrangement and guidance*

IEC 60717:2012, *Method for the determination of the space required by capacitors and resistors with unidirectional terminations*

IEC 61000-4-2:2008, *Electromagnetic Compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test*

IEC 61193-2, *Quality assessment systems – Part 2: Selection and use of sampling plans for inspection of electronic components and packages*

IEC 61249-2-7:2002, *Materials for printed boards and other interconnecting structures – Part 2-7: Reinforced base materials clad and unclad – Epoxide woven E-glass laminated sheet of defined flammability (vertical burning test), copper-clad*

ISO 80000-1:2009, *Quantities and units – Part 1: General*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1**type**

group of components having similar design features and the similarity of whose manufacturing techniques enables them to be grouped together either for qualification approval or for quality conformance inspection

Note 1 to entry: They are generally covered by a single detail specification.

Note 2 to entry: Components described in several detail specifications may, in some cases, be considered as belonging to the same type and can therefore be grouped together for approval and quality conformance inspection.

[SOURCE: IEC 60115-1: 2008, 2.2.25, modified – The remark on "single detail specification" has been deleted from the definition and Note 1 to entry and Note 2 to entry have been added.]

3.2**style**

subdivision of a type, generally based on dimensional factors that can include several variants, generally of a mechanical order

[SOURCE: IEC 60115-1:2008, 2.2.20]

3.3**varistor****voltage dependent resistor****VDR**

component, whose conductance, at a given temperature range, increases rapidly with voltage within a given current range

Note 1 to entry: This note applies to the French language only.

Note 2 to entry: Varistor is graphically symbolized as **Z**.
<https://standards.iteh.ai/catalog/standards/sist/3904b12d-80d4-4183-ad15-073445edc0f5/iec-61051-1-2018>

Note 3 to entry: This property is expressed by either of the following formulae:

$$U = CI^\beta \quad (1)$$

or

$$I = AU^\gamma \quad (2)$$

where

I is the current flowing through the varistor;

U is the voltage applied across the varistor;

β is the non-linearity current index (see 3.4);

γ is the non-linearity voltage index (see 3.5);

A and C are constants.

3.4 **β** **non-linearity current index**

starting from Formula (1) of 3.3, it is defined by the formula

$$\beta = \frac{I}{U} \times \frac{dU}{dI} \quad (3)$$

Note 1 to entry: For the convenience of calculation, the following formula may be used:

$$\beta = \frac{\log_{10}(U_1/U_2)}{\log_{10}(I_1/I_2)} \quad (4)$$

β is always less than 1.

3.5

γ

non-linearity voltage index

reciprocal of non-linearity current index β

Note 1 to entry: γ is always greater than 1.

Note 2 to entry: In varistor industry and literature, the non-linearity voltage index is usually denoted by α rather than γ .

3.6

leaded varistors

varistors connected to electric circuits via lead wire, or conductive plate, or screw terminations

3.7

surface mount varistors

SMV

leadless varistors mounted on electric circuits by use of surface mount technology

3.8

U_{RMS}

maximum continuous AC voltage

maximum AC RMS voltage of a substantially sinusoidal waveform (less than 5 % total harmonic distortion) which can be applied to the component under continuous operating conditions at 25 °C

Note 1 to entry: Full information on derating requirements above 25 °C shall be given in the detail specification.

Note 2 to entry: Normally this voltage value shall be 1,1 times the supply voltage.

Note 3 to entry: Normally the peak value of this voltage shall be equal to or less than the lower limit of varistor voltage tolerance.

3.9

U_{DCM}

maximum continuous DC voltage

maximum DC voltage (with less than 5 % ripple) that can be applied to the component under continuous operating conditions at an ambient temperature of 25 °C

Note 1 to entry: Full information on derating requirements above 25 °C shall be given in the detail specification.

Note 2 to entry: The power loss of varistor at maximum continuous DC voltage shall be approximately the same as that at maximum continuous AC voltage, hence the value of maximum continuous DC voltage is about 1,3 times the maximum continuous AC voltage.

3.10

U_{s}

supply voltage

voltage by which the system is designated and to which certain operating characteristics of the system are referred

3.11

U_{V}

varistor voltage

voltage, at specified DC current (also named as DC reference current), used as a reference point in the component characteristic

Note 1 to entry: Unless otherwise specified, the DC reference current is DC 1 mA.

3.12**limiting voltage**

peak value of the voltage, which appears at the terminations of the varistor, when a specified current pulse is applied to it

Note 1 to entry: Unless otherwise specified, the voltage peak at the initial instant of the pulse current shall be excluded from the limiting voltage. That voltage peak results from time lag of the resistive current of the varistor due to the charging of the varistor's capacitance.

3.13 **U_{CLP}** **clamping voltage**

limiting voltage under standard atmospheric conditions, when passing an 8/20 class current pulse

SEE: Annex B.

3.14**electrostatic discharge****ESD**

<for surface mount electrostatic protective varistors> transfer of electric charge between bodies of different electrostatic potential in proximity or through direct contact

Note 1 to entry: There are two test methods for electrostatic discharge test:

- Contact discharge method: a method of testing in which the electrode of the ESD pulse generator is held in contact with the SMV, and the discharge is actuated by the discharge switch within the generator.
- Air discharge method: a method of testing in which the electrode of the ESD pulse generator is brought close to the SMV, and the discharge is actuated by a spark to the SMV.

[SOURCE: IEC 60050-161, 161-01-22, modified – Note 1 to entry has been added.]

3.15**ESD clamping voltage**

<for surface mount electrostatic varistors> peak voltage developed across the varistor terminations measured at 30 ns after initiation of pulse of 30 A/8 kV defined in Table 3 and Figure 2 of IEC 61000-4-2:2008

SEE: Annex B

3.16 **U_{ISO}** **isolation voltage**

<insulated varistors> maximum peak voltage that can be applied under continuous operating conditions between the varistor terminations and any conducting mounting surface

3.17 **I_L** **leakage current**

current passing through the varistor at the maximum DC voltage and at a temperature of 25 °C or at any other specified temperature

3.18 **I_{Pm}** **maximum peak current**

maximum current per pulse that can be passed by a varistor at an ambient temperature of 25 °C, for a given number of pulses