

INTERNATIONAL STANDARD



Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners

WITHDRAWN

IEC 61162-1:2016

<https://standards.iteh.ai/standards/iec/6550d25a-b550-48d3-a680-a7f7ea3c1022/iec-61162-1-2016>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

INTERNATIONAL STANDARD



**Maritime navigation and radiocommunication equipment and systems – Digital
interfaces –
Part 1: Single talker and multiple listeners**

<https://standards.iteh.ai/standards/iec/61162-1-2016>
<https://standards.iteh.ai/standards/iec/61162-1-2016>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 47.020.70

ISBN 978-2-8322-3605-5

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references.....	11
3 Terms and definitions.....	13
3.1 General.....	13
3.2 Terms and definitions.....	13
4 Manufacturer's documentation.....	13
5 Hardware specification.....	13
5.1 General.....	13
5.2 Interconnecting wire.....	13
5.3 Conductor definitions.....	13
5.4 Electrical connections/shield requirements.....	14
5.5 Connector.....	14
5.6 Electrical signal characteristics.....	14
5.6.1 General.....	14
5.6.2 Signal state definitions.....	14
5.6.3 Talker drive circuits.....	14
5.6.4 Listener receive circuits.....	14
5.6.5 Electrical isolation.....	15
5.6.6 Maximum voltage on bus.....	15
6 Data transmission.....	15
7 Data format protocol.....	16
7.1 Characters.....	16
7.1.1 General.....	16
7.1.2 Reserved characters.....	16
7.1.3 Valid characters.....	16
7.1.4 Undefined characters.....	16
7.1.5 Character symbols.....	16
7.2 Fields.....	16
7.2.1 String.....	16
7.2.2 Address field.....	16
7.2.3 Data fields.....	17
7.2.4 Checksum field.....	18
7.2.5 Sequential message identifier field.....	18
7.3 Sentences.....	19
7.3.1 General structure.....	19
7.3.2 Description of approved sentences.....	19
7.3.3 Parametric sentences.....	20
7.3.4 Encapsulation sentences.....	21
7.3.5 Query sentences.....	23
7.3.6 Proprietary sentences.....	23
7.3.7 Command sentences.....	24
7.3.8 Valid sentences.....	25
7.3.9 Multi-sentence messages.....	25

7.3.10	Sentence transmission timing.....	25
7.3.11	Additions to approved sentences.....	25
7.4	Error detection and handling.....	26
7.5	Handling of deprecated sentences.....	26
8	Data content.....	26
8.1	Character definitions.....	26
8.2	Field definitions.....	28
8.3	Approved sentences.....	32
8.3.1	General format.....	32
8.3.2	AAM – Waypoint arrival alarm.....	32
8.3.3	ABK – AIS addressed and binary broadcast acknowledgement.....	32
8.3.4	ABM – AIS addressed binary and safety related message.....	33
8.3.5	ACA – AIS channel assignment message.....	34
8.3.6	ACK – Acknowledge alarm.....	36
8.3.7	ACN – Alert command.....	36
8.3.8	ACS – AIS channel management information source.....	37
8.3.9	AIR – AIS interrogation request.....	37
8.3.10	AKD – Acknowledge detail alarm condition.....	38
8.3.11	ALA – Report detailed alarm condition.....	39
8.3.12	ALC – Cyclic alert list.....	40
8.3.13	ALF – Alert sentence.....	41
8.3.14	ALR – Set alarm state.....	43
8.3.15	APB – Heading/track controller (autopilot) sentence B.....	43
8.3.16	ARC – Alert command refused.....	44
8.3.17	BBM – AIS broadcast binary message.....	45
8.3.18	BEC – Bearing and distance to waypoint – Dead reckoning.....	46
8.3.19	CBR – Configure broadcast rates for AIS AtoN station message command.....	46
8.3.19	BOD – Bearing origin to destination.....	46
8.3.20	BWC – Bearing and distance to waypoint – Great circle.....	46
8.3.21	BWR – Bearing and distance to waypoint – Rhumb line.....	47
8.3.22	BWW – Bearing waypoint to waypoint.....	47
8.3.23	CUR – Water current layer – Multi-layer water current data.....	49
8.3.24	DBT – Depth below transducer.....	49
8.3.25	DDC – Display dimming control.....	49
8.3.26	DOR – Door status detection.....	50
8.3.27	DPT – Depth.....	51
8.3.28	DSC – Digital selective calling information.....	51
8.3.29	DSE – Expanded digital selective calling.....	52
8.3.30	DTM – Datum reference.....	53
8.3.31	EPV – Command or report equipment property value.....	54
8.3.32	ETL – Engine telegraph operation status.....	55
8.3.33	EVE – General event message.....	56
8.3.34	FIR – Fire detection.....	56
8.3.35	FSI – Frequency set information.....	57
8.3.36	GBS – GNSS satellite fault detection.....	58
8.3.37	GEN – Generic binary information.....	60
8.3.38	GFA – GNSS fix accuracy and integrity.....	61
8.3.39	GGA – Global positioning system (GPS) fix data.....	62

8.3.40	GLL – Geographic position – Latitude/longitude.....	62
8.3.41	GNS – GNSS fix data.....	63
8.3.42	GRS – GNSS range residuals	65
8.3.43	GSA – GNSS DOP and active satellites.....	67
8.3.44	GST – GNSS pseudorange noise statistics.....	69
8.3.45	GSV – GNSS satellites in view	70
8.3.46	HBT – Heartbeat supervision sentence.....	71
8.3.47	HCR – Heading correction report.....	72
8.3.48	HDG – Heading, deviation and variation	72
8.3.49	HDT – Heading true	73
8.3.50	HMR – Heading monitor receive	73
8.3.51	HMS – Heading monitor set.....	74
8.3.52	HRM – heel angle, roll period and roll amplitude measurement device.....	74
8.3.53	HSC – Heading steering command.....	75
8.3.54	HSS – Hull stress surveillance systems	75
8.3.55	MEB – Message input for broadcast command.....	75
8.3.55	HTC – Heading/track control command; HTD – Heading /track control data.....	75
8.3.56	LR1 – AIS long-range reply sentence 1.....	77
8.3.57	LR2 – AIS long-range reply sentence 2.....	77
8.3.58	LR3 – AIS long-range reply sentence 3.....	78
8.3.59	LRF – AIS long-range function	78
8.3.60	LRI – AIS long-range interrogation.....	79
8.3.61	MOB – Man over board notification.....	82
8.3.62	MSK – MSK receiver interface.....	83
8.3.63	MSS – MSK receiver signal status.....	83
8.3.64	MTW – Water temperature.....	84
8.3.65	MWD – Wind direction and speed.....	84
8.3.66	MWV – Wind speed and angle	84
8.3.67	NAK – Negative acknowledgement.....	84
8.3.68	NRM – NAVTEX receiver mask	85
8.3.69	NRX – NAVTEX received message	86
8.3.70	NSR – Navigation status report.....	88
8.3.71	OSD – Own ship data.....	89
8.3.72	POS – Device position and ship dimensions report or configuration command.....	90
8.3.73	PRC – Propulsion remote control status	91
8.3.74	RLM – Return link message	92
8.3.75	RMA – Recommended minimum specific LORAN-C data.....	93
8.3.76	RMB – Recommended minimum navigation information.....	93
8.3.77	RMC – Recommended minimum specific GNSS data	94
8.3.78	ROR – Rudder order status.....	95
8.3.79	ROT – Rate of turn.....	96
8.3.80	RRT – Report route transfer.....	96
8.3.81	RPM – Revolutions	97
8.3.82	RSA – Rudder sensor angle	97
8.3.83	RSD – Radar system data.....	97
8.3.84	RTE – Routes	98
8.3.85	SFI – Scanning frequency information	99

8.3.86	SMI – SafetyNET Message, All Ships/NavArea	99
8.3.87	SM2 – SafetyNET Message, Coastal Warning Area	101
8.3.88	SM3 – SafetyNET Message, Circular Area address	103
8.3.89	SM4 – SafetyNET Message, Rectangular Area Address	105
8.3.90	SMB – IMO SafetyNET Message Body	107
8.3.91	SPW – Security password sentence	109
8.3.92	SSD – AIS ship static data	110
8.3.93	STN – Multiple data ID	110
8.3.94	THS – True heading and status	111
8.3.95	TLB – Target label	111
8.3.96	TLL – Target latitude and longitude	111
8.3.97	TRC – Thruster control data	112
8.3.98	TRL – AIS transmitter-non-functioning log	113
8.3.99	TRD – Thruster response data	114
8.3.100	TTD – Tracked target data	114
8.3.101	TTM – Tracked target message	116
8.3.102	TUT – Transmission of multi-language text	117
8.3.103	TXT – Text transmission	118
8.3.104	UID – User identification code transmission	119
8.3.105	VBW – Dual ground/water speed	119
8.3.106	VDM – AIS VHF data-link message	120
8.3.107	VDO – AIS VHF data-link own-vessel report	121
8.3.108	VDR – Set and drift	121
8.3.109	VER – Version	122
8.3.110	VHW – Water speed and heading	122
8.3.111	VLW – Dual ground/water distance	123
8.3.112	VPW – Speed measured parallel to wind	123
8.3.113	VSD – AIS voyage static data	123
8.3.114	VTG – Course over ground and ground speed	124
8.3.115	WAT – Water level detection	124
8.3.116	WCV – Waypoint closure velocity	125
8.3.117	WNC – Distance waypoint to waypoint	126
8.3.118	WPL – Waypoint location	126
8.3.119	XDR – Transducer measurements	126
8.3.120	XTE – Cross-track error, measured	127
8.3.121	XTR – Cross-track error, dead reckoning	128
8.3.122	ZDA – Time and date	128
8.3.123	ZDL – Time and distance to variable point	128
8.3.124	ZFO – UTC and time from origin waypoint	128
8.3.125	ZTG – UTC and time to destination waypoint	129
9	Applications	129
9.1	Example parametric sentences	129
9.1.1	General	129
9.1.2	Example 1 – LORAN-C latitude/longitude	129
9.1.3	Example 2 – LORAN-C arrival alarm	129
9.1.4	Example 3 – Proprietary sentence	130
9.1.5	Example 4 – RMA examples	130
9.1.6	Example 5 – FSI examples	131
9.1.7	Example 6 – MSK/MSS examples	131

9.1.8	Example 7 – DSC and DSE sentences	131
9.1.9	Example 8 – FIR, DOR and WAT sentences.....	132
9.2	Example encapsulation sentences.....	132
9.3	Examples of receiver diagrams.....	133
Annex A (informative) Glossary		134
Annex B (normative) Guidelines for methods of testing and required test results.....		141
B.1	General.....	141
B.2	Definition of environmental conditions for the tests	141
B.3	Examination of the manufacturer's documentation	141
B.4	Test of hardware	142
B.4.1	Interface units.....	142
B.4.2	Ability of the input circuits to work with limited current	142
B.4.2	Input circuit test	142
B.4.3	Check of electrical isolation.....	142
B.4.4	Ability of input circuits to withstand maximum voltage on the bus Maximum input voltage test.....	142
B.4.5	Test arrangement for performance tests according to IEC 60945.....	142
B.4.6	Test under maximum interface workload	143
B.4.7	Test against corrupted data at an interface	143
B.4.7	Test for correct parsing of sentences	143
B.4.8	Test under long term conditions	144
B.4.9	Protocol test of the interface of the EUT.....	144
B.4.10	Test for correct use of special characters starting a sentence	144
B.4.11	Test for correct parsing of received sentences	144
B.4.12	Test for future extension of received sentences	144
Annex C (normative) Six-bit binary field conversion		153
Annex D (normative) Alarm system fields		156
Annex E (informative) Example of use of FIR, DOR and WAT sentences.....		165
E.1	Example of the use of system status messages.....	165
E.2	Use of system division codes.....	165
E.3	Send complete status.....	166
E.4	Change measurement point status	167
E.5	Point status change during a status update.....	167
E.6	Failure in a sub-system	167
E.7	Status updates when a sub-system is in fault.....	168
E.8	Signal a correction of a sub-system fault	168
Annex F (informative) Example encapsulation sentence.....		169
F.1	Example encapsulation sentence.....	169
F.2	AIS VHF data-link message VDM sentence encapsulation example	169
F.3	Background discussion – Encapsulation coding	169
F.4	Decoding the encapsulated string.....	171
F.5	Conversion from symbols to binary bits.....	171
F.6	Organising the binary message data.....	172
F.7	Interpreting the decoded binary strings	172
Bibliography		176
Figure 1 – Listener receive circuit.....		15
Figure 2 – Data transmission format.....		15

Figure 3 – Example 1, J-FET, N channel, opto-isolator based listener circuit.....	133
Figure 4 – Example 2, NPN opto-isolator based listener circuit	133
Figure C.1 – 6-bit binary code converted to valid IEC 61162-1 character	154
Figure C.2 – Valid IEC 61162-1 character converted to 6-bit binary code	155
Figure E.1 – Example system diagram.....	166
Figure F.1 – Message data format	170
Figure F.2 – Work sheet for decoding and interpreting encapsulated string	175
Table 1 – Reserved characters.....	26
Table 2 – Valid characters.....	27
Table 3 – Character symbol.....	28
Table 4 – Talker identifier mnemonics	29
Table 5 – Field type summary.....	31
Table B.1 – Example – Special characters.....	143
Table B.2 – Example – Parsing	144
Table B.3 – Example – Data string GGA received by the EUT	144
Table B.3 – Example – Future extensions.....	144
Table B.4 – Example – Data string GGA sent by the EUT to the test receiver (listener)	146
Table B.5 – Example – Checksum data sent.....	147
Table B.6 – Example – Data string GNS received by the EUT	149
Table B.7 – Example – Checksum data received.....	151
Table B.8 – Example – Break of data line	151
Table B.9 – Example – Receiving interval.....	151
Table B.10 – Example – Talker ID.....	152
Table C.1 – Six-bit binary field conversion table.....	153
Table D.1 – System alarm fields	156
Table F.1 – Example message from ITU-R M.1371	173

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –****Part 1: Single talker and multiple listeners**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 61162-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This fifth edition cancels and replaces the fourth edition published in 2010, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- new identifiers have been added to Table 4;
- the sentences CBR and MEB have been removed as they are now solely used by AIS shore based equipment;
- new sentences ACN, ALC, ALF, ARC, EPV, HCR, HRM, MOB, NSR, RLM, RRT, SM1, SM2, SM3, SM4, SMB, SPW and TRL have been added;
- revisions have been made to ABK, ABM, GNS, NAK, NRM, RMC, ROR and TTD;
- the methods of testing in Annex B have been revised.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/799/FDIS	80/806/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 61162 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Digital interface*, can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 61162 Maritime navigation and radiocommunication equipment and systems – Digital interfaces consists of ~~4~~ 5 parts which specify digital interfaces for application in marine navigation, radiocommunication and system integration, as follows:

Part 1: *Single talker and multiple listeners;*

Part 2: *Single talker and multiple listeners, high speed transmission;*

Part 3: *Multiple talkers and multiple listeners – Serial data instrument network;*

Part 450: *Multiple talkers and multiple listeners – ~~Ship systems~~ Ethernet interconnection;*

Part 460: *Multiple talkers and multiple listeners – Ethernet interconnection – Safety and security*

IEC technical committee 80 interface standards are developed with input from manufacturers, private and government organisations and equipment operators. The information is intended to meet the needs of users at the time of publication, but users should recognise that as applications and technology change, interface standards should change as well. Users of this standard are advised to immediately inform the IEC of any perceived inadequacies therein.

The first edition of IEC 61162-1 was published in 1995. The second edition published in 2000 removed some sentences which were no longer in use, added some new sentences and included details of the ship equipment defined in IMO resolutions together with appropriate sentences for communication between them. This information was subsequently removed from the third edition when it became the practice to specify the sentence formatters in the individual standards for equipment.

The third edition published in 2007 introduced a re-arrangement of the text and new sentences particularly to support the Automatic Identification System and the Voyage Data Recorder. The third edition also introduced a further type of start of sentence delimiter. The conventional delimiter "\$" was retained for the conventional sentences which are now called parametric sentences. The new delimiter "!" identifies sentences that conform to special purpose encapsulation.

The fourth edition ~~removes~~ removed some sentences which ~~are~~ were not in use, ~~adds~~ added some new sentences for new applications and ~~makes~~ made some corrections and additions. In particular the sentences of relevance to satellite navigation receivers ~~have been~~ were expanded to facilitate the description of new satellite systems.

This fifth edition also removes some sentences which are no longer in use, adds some new sentences for new applications and makes some corrections and additions.

Liaison has been maintained with NMEA and this edition has been aligned where appropriate with NMEA 0183 version ~~4.00~~ 4.10.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

Part 1: Single talker and multiple listeners

1 Scope

This part of IEC 61162 contains the requirements for data communication between maritime electronic instruments, navigation and radiocommunication equipment when interconnected via an appropriate system.

This part of IEC 61162 is intended to support one-way serial data transmission from a single talker to one or more listeners. These data are in printable ASCII form and may include information such as position, speed, depth, frequency allocation, etc. Typical messages may be from about 11 to a maximum of 79 characters in length and generally require transmission no more rapidly than one message per second.

The electrical definitions in this standard are not intended to accommodate high-bandwidth applications such as radar or video imagery, or intensive database or file transfer applications. Since there is no provision for guaranteed delivery of messages and only limited error checking capability, this standard should be used with caution in all safety applications.

For applications where a faster transmission rate is necessary, reference should be made to IEC 61162-2.

For applications to shore based equipment of the automatic identification system (AIS) reference should be made to the IEC 62320 series.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61097-6, *Global maritime distress and safety system (GMDSS) – Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX)*

IEC 61108 (all parts), *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interface*

IEC 61162-2:1998, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 61174, *Maritime navigation and radiocommunication equipment and systems – Electronic chart display and information system (ECDIS) – Operational and performance requirements, methods of testing and required test results*

IEC 61924-2:2012, *Maritime navigation and radiocommunication equipment and systems – Integrated navigation systems – Part 2: Modular structure for INS – Operational and performance requirements, methods of testing and required test results*

IEC 61996 (all parts), *Maritime navigation and radiocommunication equipment and systems – Shipborne voyage data recorder (VDR)*

ISO/IEC 8859 (all parts), *Information technology – 8-bit single-byte coded graphic character sets*

ISO/IEC 8859-1:1998, *Information technology – 8-bit single-byte coded graphic character sets – Part 1: Latin alphabet No.1*

ISO/IEC 10646, *Information technology – Universal Coded Character Set (UCS)*

ITU-R Recommendation M.493, *Digital selective-calling system for use in the maritime mobile service*

ITU-R M.625, *Direct printing telegraph equipment employing automatic identification in the maritime mobile service*

ITU-R Recommendation M.821, *Optional expansion of the digital selective-calling system for use in the maritime mobile service*

ITU-R Recommendation M.1084, *Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service*

ITU-R Recommendation M.1371, *Technical characteristics for an automatic identification system using time division multiple access in the VHF maritime mobile band*

ITU-T Recommendation X.27/V.11:1996, *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s*

IMO GMDSS.1/Circ.18, *Master plan of shore-based facilities for the global maritime distress and safety system (GMDSS master plan)*

IMO, *International Convention on Load Lines*

IMO, *International SafetyNET Manual*

IMO MSC.252(83), *Performance standards for integrated navigation systems (INS)*

IMO MSC.302(87), *Performance standards for Bridge Alert Management (BAM)*

IMO Publication 951E, *NAVTEX Manual*