



SLOVENSKI STANDARD
SIST ISO 10770-2:2000
01-september-2000

:`i]XbUfM b]_U!`<]XfUj`_U!`9`Y`f] bc`j`_fa]`^b]` \]XfUj`] b]`_fa]b]`j` Yb]`j]`!`&"
XY.`DfYg_i gbY`a YfcXY`nUf]dcfbY`_fa]bY`j` Yb]`Y

Hydraulic fluid power -- Electrically modulated hydraulic control valves -- Part 2: Test methods for three-way directional flow control valves

iTeh STANDARD PREVIEW

Transmissions hydrauliques -- Distributeurs hydrauliques à modulation électrique --
Partie 2: Méthodes d'essai pour distributeurs à trois voies

[SIST ISO 10770-2:2000](https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0idcedc3/sist-iso-10770-2-2000)

Ta slovenski standard je istoveten z: **ISO 10770-2:1998**

ICS:

23.100.50 Krmilni sestavni deli Control components

SIST ISO 10770-2:2000 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 10770-2:2000

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>

INTERNATIONAL
STANDARD

ISO
10770-2

First edition
1998-05-15

**Hydraulic fluid power — Electrically
modulated hydraulic control valves —**

Part 2:

Test methods for three-way directional flow
control valves

iTeh STANDARD PREVIEW

*Transmissions hydrauliques — Distributeurs hydrauliques à modulation
électrique*

Partie 2: Méthodes d'essai pour distributeurs à trois voies

[SIST ISO 10770-2:2000](https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000)

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>



Reference number
ISO 10770-2:1998(E)

ISO 10770-2:1998(E)

Contents	Page
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Symbols and units	2
5 Standard test conditions	3
6 Test installation	3
7 Electrical tests	4
8 Performance tests	6
9 Endurance test	20
10 Pressure impulse test	21
11 Environmental tests	21
12 Presentation of results	22
13 Identification statement	25

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Tables

1 Symbols and units	2
2 Standard test conditions	3
3 Sinusoidal signal function	19
4 Input step functions	20
A.1 Permissible systematic errors of measuring instruments as determined during calibration	35

Figures

1 Typical steady-state test circuit	26
2 Typical dynamic test circuit	27
3 Valve coil inductance	28
a) Inductance test	28
b) Voltage vector diagram	28

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Internet central@iso.ch

X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

4	Valve coil step response	29
5	Internal leakage versus input signal	29
6	Output flow versus input signal at constant valve pressure drop	30
7	Threshold characteristics	30
8	Output flow versus valve pressure drop (without integral pressure compensation)	31
9	Output flow versus valve pressure drop (with integral pressure compensation)	31
10	Limiting power curve	32
11	Output flow versus fluid temperature	32
12	Blocked port load versus input signal	33
13	Frequency response	33
14	Step response	34
	a) Transient response to step input signal	34
	b) Transient response to load pressure step with flow compensation	34

Annexes

A	(normative) Errors and classes of measurement	35
B	(informative) Guidance on conducting the tests	36
C	(informative) Bibliography	37

[SIST ISO 10770-2:2000](https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000)

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>

Foreword

ISO (the International Organisation for Standardisation) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organisations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardisation.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 10770-2 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 8, *Product testing*.

This first edition of ISO 10770-2 together with ISO 10770-1 cancel and replace ISO 6404:1985, of which they constitute a technical revision. In particular, ISO 10770 is wider-ranging and more comprehensive, covering both servovalves and proportional valves.

ISO 10770 consists of the following parts, under the general title *Hydraulic fluid power — Electrically modulated hydraulic control valves*:

- *Part 1: Test methods for four-way directional flow control valves*
- *Part 2: Test methods for three-way directional flow control valves*
- *Part 3: Test methods for pressure control valves*

Annex A forms an integral part of this part of ISO 10770. Annexes B and C are for information only.

Introduction

In hydraulic fluid power systems, power is transmitted by a fluid under pressure from a hydraulic power source to one or several loads through electrically modulated hydraulic control valves.

These control valves are components which receive control signals in the form of an electrical signal, receive hydraulic power from a power source, and then, control the direction and amount of hydraulic flow to the load, depending upon the electrical input signal. There are a number of performance characteristics that must be known in order to successfully apply electrically modulated hydraulic control valves.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 10770-2:2000](https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000)

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 10770-2:2000

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>

Hydraulic fluid power — Electrically modulated hydraulic control valves —

Part 2:

Test methods for three-way directional flow control valves

1 Scope

This part of ISO 10770 describes methods for production acceptance and type (or qualification) testing of electrically modulated hydraulic three-way directional flow control valves.

2 Normative references

The following standards contain provisions, which, through reference in this text, constitute provisions of this part of ISO 10770. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 10770 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>

ISO 1219-1:1991, *Fluid power systems and components — Graphic symbols and circuit diagrams — Part 1: Graphic symbols.*

ISO 3448:1992, *Industrial liquid lubricants — ISO viscosity classification.*

ISO 4406:1987, *Hydraulic fluid power — Fluids — Method for coding level of contamination by solid particles.*

ISO 5598:1985, *Fluid power systems and components — Vocabulary.*

ISO 6743-4:1982, *Lubricants, industrial oils and related products (class L) — Classification — Part 4: Family H (Hydraulic systems).*

IEC 617, *Graphical symbols and diagrams.*

3 Definitions

For the purposes of this part of ISO 10770, the definitions given in ISO 5598 and the following definition apply.

3.1 electrically modulated hydraulic flow control valve: Valve that provides a degree of proportional flow control in response to a continuously variable electrical input signal.

4 Symbols and units

The symbols and units for the parameters referred to in this part of ISO 10770 are listed in table 1.

Table 1 — Symbols and units

Parameter	Symbol	Unit
Coil impedance	Z	Ω
Coil inductance	L	H
Coil resistance	R	Ω
Insulation resistance	R_i	Ω
Dither amplitude	—	% of max. input signal
Dither frequency	f_d	Hz
Input signal	I or U	A or V
Rated signal	I_N or U_N	A or V
Output flow	q	l/min
Rated flow	q_N	l/min
Flow gain	$K_V = (\delta q / \delta I \text{ or } \delta q / \delta U)$	l/min/input signal unit
Hysteresis	—	% of max. input signal
Internal leakage	q_i	l/min
Supply pressure	p_P	MPa (bar)
Return pressure	p_T	MPa (bar)
Load pressure	p_A	MPa (bar)
Valve pressure drop	$p_V = p_P - p_A \text{ or } p_A - p_T$	MPa (bar)
Rated valve pressure drop	p_N	MPa (bar)
Pressure gain	$S_V = (\delta p_A / \delta I \text{ or } \delta p_A / \delta U)$	MPa (bar)/input signal unit
Threshold	—	% of max. input signal
Amplitude	—	dB
Phase lag	—	degree
Temperature	—	°C
Frequency	f	Hz
Time	t	s

NOTE — 1 bar = 10^5 N/m² = 0,1 MPa

5 Standard test conditions

Unless otherwise specified, the standard test conditions given in table 2 shall apply to all tests described in this part of ISO 10770.

Table 2 — Standard test conditions

Ambient temperature	(20 ± 5) °C
Filtration	Solid contaminant code number to be stated in accordance with ISO 4406
Fluid type	Commercially available mineral based hydraulic fluid, i.e. L-HL in accordance with ISO 6743-4 or other fluid with which the valve is capable of operating
Fluid temperature	(40 ± 6) °C at valve inlet
Viscosity grade	Grade VG 32 in accordance with ISO 3448
Supply pressure	In accordance with relevant test requirement ± 2,5 %
Return pressure	In accordance with manufacturer's recommendations
NOTE — Where an alternative hydraulic fluid is used, the fluid type and viscosity grade shall be specified.	

6 Test installation

6.1 General

A test installation shall be provided which complies with 6.2 and 6.3 and which is capable of meeting the permissible limits of error stated in annex A. General guidance on conducting the tests is given in annex B.

NOTES

- Figures 1, 2 and 3 are typical circuits that do not incorporate all the safety devices necessary to protect against damage in the event of component failure. Other circuits which achieve the same purpose may be used. It is important that those responsible for conducting the tests give consideration to safeguarding personnel and equipment.
- The graphical symbols used in figures 1, 2 and 3 are in accordance with ISO 1219-1 and IEC 617.

6.2 Steady state tests

A typical test circuit is shown in figure 1. This installation allows either point-to-point or continuous plotting methods for

- a) recording flow as a function of input signal;
- b) recording pressure as a function of input signal;
- c) recording flow as a function of valve pressure drop;
- d) recording flow as a function of load pressure;
- e) recording flow as a function of temperature.

6.3 Dynamic tests

A typical test circuit is shown in figure 2. This installation utilizes much of the circuit shown in figure 1. This installation allows

- a) frequency response tests;
- b) step response tests.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 10770-2:2000](https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000)

<https://standards.iteh.ai/catalog/standards/sist/f38c6e4f-f65e-499c-ba26-261c0fdeedc3/sist-iso-10770-2-2000>

7 Electrical tests

7.1 General

The tests described in 7.2 to 7.4, as appropriate, shall be carried out on all valves without integrated electronics before proceeding to subsequent tests.

7.2 Coil resistance

The test shall be performed with the coil at the specified ambient temperature. Using an electrical test instrument with an accuracy better than $\pm 2\%$ of the measured value, measure the resistance between the two leads of each coil in the valve.

NOTE — The valve under test need not be supplied with pressurized fluid during the measurement of coil resistance.

7.3 Coil inductance

7.3.1 Measure the total coil inductance (corresponding to the series coil connection for a four-lead, two-coil configuration) with the valve operating under the standard test conditions laid down in clause 5.

NOTE — This test measures the apparent inductance, which varies with signal frequency and amplitude due to the back emf (electro-motive force) generated by the moving armature. The result may be used to select the appropriate design of drive amplifier.

7.3.1.1 Connect a suitable oscillator to drive the total valve coil which is in series with a precision non-inductive resistor, as shown in figure 3 a).

7.3.1.2 Set the oscillator frequency, f , at either 50 Hz or 60 Hz, so that it is different from the frequency of the electrical power supply to the test equipment.

7.3.1.3 Adjust the valve input current to a peak amplitude equal to the valve rated current.

7.3.1.4 Use an oscillator which is capable of supplying undistorted current to the valve.

7.3.1.5 Using an oscilloscope, monitor the voltage waveform across the resistor R to check that the waveform is sinusoidal.

iTeh STANDARD PREVIEW

7.3.1.6 Measure the peak a.c. voltages U_R , U_T and U_V .

7.3.1.7 Construct the diagram shown in figure 3 b) to show the vectorial relationship of the voltages.

7.3.1.8 Determine the coil impedance characteristics from the following expressions:

— coil impedance, expressed in ohms

$$Z = R \frac{U_V}{U_R} \quad \dots (1)$$

— apparent inductance, expressed in henry

$$L = \frac{R}{2\pi f} \times \frac{U_L}{U_R} \quad \dots (2)$$

7.3.2 Alternative test method: use step response to full current to give time constant t_c of coil and calculate inductance using:

$$L = R_c \times t_c \quad (\text{as indicated at figure 4}) \quad \dots (3)$$