



SLOVENSKI STANDARD
kSIST FprEN 61643-312:2010
01-marec-2010

**Sestavni deli za nizkonapetostne naprave za zaščito pred prenapetostnimi udari -
312. del: Želene vrednosti in karakteristike za plinske odvodnike**

Components for low-voltage surge protective devices -- Part 312: Preferred values and characteristics for gas discharge tubes

iTeh STANDARD PREVIEW

Composants pour parafoudres (standards.iTeh.ai) -- Partie 312: Valeurs préférentielles et caractéristiques relatives aux tubes à décharge

[kSIST FprEN 61643-312:2010](https://standards.iTeh.ai/catalog/standards/sist/e6fe3805-a5d8-4ca0-99ee-97acd6512268/ksist-fpr-en-61643-312-2010)

Ta slovenski standard je istoveten z: FprEN 61643-312:2010

ICS:

29.120.50	Varovalke in druga medtokovna zaščita	Fuses and other overcurrent protection devices
29.240.10	Transformatorske postaje. Prenapetostni odvodniki	Substations. Surge arresters

kSIST FprEN 61643-312:2010

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[kSIST FprEN 61643-312:2010](https://standards.iteh.ai/catalog/standards/sist/e6fe3805-a5d8-4ca0-99ee-97acd6512268/ksist-fpren-61643-312-2010)

<https://standards.iteh.ai/catalog/standards/sist/e6fe3805-a5d8-4ca0-99ee-97acd6512268/ksist-fpren-61643-312-2010>



37B/99/CDV

COMMITTEE DRAFT FOR VOTE (CDV) PROJET DE COMITÉ POUR VOTE (CDV)

		Project number Numéro de projet	IEC 61643-312 Ed. 1.0		
		IEC/TC or SC: SC 37B CEI/CE ou SC:	Secretariat / Secrétariat USA		
<input checked="" type="checkbox"/>	Submitted for parallel voting in CENELEC Soumis au vote parallèle au CENELEC	Date of circulation Date de diffusion 2010-01-15	Closing date for voting (Voting mandatory for P-members) Date de clôture du vote (Vote obligatoire pour les membres (P)) 2010-06-18		
Also of interest to the following committees Intéresse également les comités suivants TC37, SC37A, TC81			Supersedes document Remplace le document 37B/93/CD and 37B/96A/CC		
Proposed horizontal standard Norme horizontale suggérée <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the TC/SC secretary Les autres CE/SC sont requis d'indiquer leur intérêt, si nécessaire, dans ce CDV à l'intention du secrétaire du CE/SC					
Functions concerned Fonctions concernées <input type="checkbox"/> Safety Sécurité					
		<input type="checkbox"/> EMC CEM	<input type="checkbox"/> Environment Environnement	<input type="checkbox"/> Quality assurance Assurance qualité	

CE DOCUMENT EST TOUJOURS À L'ÉTUDE ET SUSCEPTIBLE DE MODIFICATION. IL NE PEUT SERVIR DE RÉFÉRENCE.

LES RÉCIPIENDAIRES DU PRÉSENT DOCUMENT SONT INVITÉS À PRÉSENTER, AVEC LEURS OBSERVATIONS, LA NOTIFICATION DES DROITS DE PROPRIÉTÉ DONT ILS AURAIENT ÉVENTUELLEMENT CONNAISSANCE ET À FOURNIR UNE DOCUMENTATION EXPLICATIVE.

THIS DOCUMENT IS STILL UNDER STUDY AND SUBJECT TO CHANGE. IT SHOULD NOT BE USED FOR REFERENCE PURPOSES.

RECIPIENTS OF THIS DOCUMENT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

Titre : CEI 61643-312 Ed. 1.0: Composants pour parafoudres basse tension - Partie 312: Valeurs préférentielles et caractéristiques relatives aux tubes à décharge
Title : IEC 61643-312 Ed. 1.0: Components for low-voltage surge protective devices – Part 312: Preferred values and characteristics for gas discharge tubes

Introductory note

The existing IEC 61643-311 standard was published in 2001. The document has a title "Specification for gas discharge tubes (GDT)" which can be interpreted as a specification for testing, of performance values or both. The contents of the published IEC 61643-311 standard has elements of test specification, performance specification and applications principles.

IEC 37/262/INF introduced a more logical numbering scheme for all IEC-Standards developed within IEC-SC 37B. Each of the component technologies had three associated documents; a test specification, a performance specification and a selection and applications principles guide.

For this reason, IEC 37/262/INF defines IEC 61643-311 as "Test circuits and methods for gas discharge tubes", IEC 61643-312 as "Preferred values and characteristics for gas discharge tubes", and IEC 61643-313 is defined as "Selection and applications principles for gas discharge tubes".

ATTENTION VOTE PARALLÈLE CEI – CENELEC

L'attention des Comités nationaux de la CEI, membres du CENELEC, est attirée sur le fait que ce projet de comité pour vote (CDV) de Norme internationale est soumis au vote parallèle.

Les membres du CENELEC sont invités à voter via le système de vote en ligne du CENELEC.

ATTENTION IEC – CENELEC PARALLEL VOTING

The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) for an International Standard is submitted for parallel voting.

The CENELEC members are invited to vote through the CENELEC online voting system.

Copyright © 2010 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Technical data	6
3.1 Symbols.....	6
3.2 Definitions.....	6
4 Service Conditions.....	7
4.1 Low temperature.....	7
4.2 Air pressure and Altitude.....	7
4.3 Ambient Temperature	7
4.4 Relative Humidity.....	7
5 Mechanical requirements and materials	8
5.1 Robustness of terminations	8
5.2 Solderability	8
5.3 Radiation	8
5.4 Marking.....	8
6 General.....	8
6.1 Failure rates.....	8
6.2 Standard atmospheric conditions.....	8
7 Electrical requirements.....	8
7.1 Initial values.....	8
7.2 Requirements after application of load.....	11
Bibliography.....	13

iTeh STANDARD PREVIEW
 (standards.iteh.ai)

KSIST FprEN 61643-312:2010

<https://standards.iteh.ai/catalog/standards/sist/61643-312-2010>

<https://standards.iteh.ai/catalog/standards/sist/61643-312-2010>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMPONENTS FOR LOW-VOLTAGE SURGE PROTECTIVE DEVICES –**Part 312: Preferred values and characteristics for gas discharge tubes**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
<http://www.inteltek.com/standards/standards.iteh.ai/>
kSIST FprEN 61643-312:2010
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61643-312 has been prepared by subcommittee 37B: Specific components for surge arresters and surge protective devices, of IEC technical committee 37: Surge arresters.

The text of this standard is based on the following documents:

FDIS	Report on voting
XX/XX/FDIS	XX/XX/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date¹⁾ indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[kSIST FprEN 61643-312:2010](https://standards.iteh.ai/catalog/standards/sist/e6fe3805-a5d8-4ca0-99ee-97acd6512268/ksist-fpren-61643-312-2010)

<https://standards.iteh.ai/catalog/standards/sist/e6fe3805-a5d8-4ca0-99ee-97acd6512268/ksist-fpren-61643-312-2010>

¹⁾ The National Committees are requested to note that for this publication the maintenance result date is 2015

COMPONENTS FOR LOW-VOLTAGE SURGE PROTECTIVE DEVICES – Part 312: Preferred values and characteristics for gas discharge tubes

1 Scope

This international standard is applicable to gas discharge tubes (GDT) used for overvoltage protection in telecommunications, signalling and low-voltage power distribution networks with nominal system voltages up to 1 000 V (r.m.s.) a.c. and 1 500 V d.c.. They are defined as a gap, or series of gaps, in an enclosed discharge medium other than air. They are designed to protect apparatus or personnel, or both, from high transient voltages. This standard contains a series of test criteria, test methods and test circuits for determining the electrical characteristics of GDTs having two or three electrodes. This standard does not specify requirements applicable to complete surge protective devices, nor does it specify total requirements for GDTs employed within electronic devices, where precise coordination between GDT performance and surge protective device withstand capability is highly critical.

This part of IEC 61643

- does not deal with mountings and their effect on GDT characteristics. Characteristics given apply solely to GDTs mounted in the ways described for the tests;
- does not deal with mechanical dimensions;
- does not deal with quality assurance requirements;
- may not be sufficient for GDTs used on high-frequency (>30 MHz);
- does not deal with electrostatic voltages;
- does not deal with GDTs connected in series with voltage-dependent resistors in order to limit follow-on currents in electrical power systems;
- does not deal with hybrid or composite GDT devices.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61643. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 61643 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60068-2-1: 2007, *Environmental testing – Part 2: Tests. Tests A: Cold*

IEC 60068-2-20: 1979, *Environmental testing – Part 2: Tests. Test T: Soldering*

IEC 60068-2-21: 2006, *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60364-5-51: 2005, *Electrical installations of buildings – Part 5-51: Selection and erection of electrical equipment - Common rules*

IEC 61000-4-5: 2005, *Electromagnetic compatibility (EMC) – Part 4: Testing and measurement techniques – Section 5: Surge immunity test*

IEC 61643-311: 2008, *Components for low voltage surge protective devices – Part 311: Test circuits and methods for gas discharge tubes*

3 Technical data

3.1 Symbols




Figure 1 – Symbol for a two-electrode GDT




Figure 2 – Symbol for a three-electrode GDT

3.2 Definitions

For the purpose of this standard of IEC 61643-312 the following definitions apply.

3.2.1

current turn-off time

time required for the GDT to restore itself to a non-conducting state following a period of conduction.

NOTE This applies only to a condition where the GDT is exposed to a continuous d.c. potential (see d.c. holdover).

3.2.2

d.c. sparkover voltage (d.c. breakdown voltage)

voltage at which the GDT transitions from a high-impedance off to a conduction state when a slowly rising d.c. voltage up to 2 kV/s is applied

NOTE The rate of rise for d.c. sparkover voltage measurements is usually equal or less 2000 V/s.

3.2.3

d.c. holdover

state in which a GDT continues to conduct after it is subjected to an impulse sufficient to cause breakdown.

NOTE In applications where a d.c. voltage exists on a line. Factors that affect the time required to recover from the conducting state (current turn-off time) include the d.c. voltage and the d.c. current

3.2.4

discharge current

current that flows through a GDT after sparkover occurs

NOTE In the event that the current passing through the GDT is alternating current, it will be r.m.s. value. In instances where the current passing through the GDT is an impulse current, the value will be the peak value.

3.2.5

discharge voltage

peak value of voltage that appears across the terminals of a GDT during the passage of GDT discharge current

3.2.6

fail-short (failsafe)

thermally-activated external shorting mechanism

3.2.7**follow (on) current**

current that the GDT conducts from a connected power source after sparkover

NOTE The GDT is expected to extinguish after sparkover to avoid overheating

3.2.8**gas discharge tube (GDT)**

gap, or gaps, in an enclosed discharge medium, other than air at atmospheric pressure, designed to protect apparatus or personnel, or both, from high transient voltages

3.2.9**impulse sparkover voltage**

highest value of voltage attained by an impulse of a designated voltage rate-of-rise and polarity applied across the terminals of a GDT prior to the flow of the discharge current

3.2.10**nominal d.c. sparkover voltage**

voltage specified by the manufacturer to indicate the target value of sparkover voltages of a particular type of GDT products

NOTE 1 The nominal value is generally a rounded number such as: 75 V, 90 V, 150 V, 200 V, 230 V, 250 V, 300 V, 350 V, 420 V, 500 V, 600 V, 800 V, 1000 V, 1200 V, 1400 V, 1800 V, 2100 V, 2700 V, 3000 V, 3600 V, 4000 V and 4500 V

NOTE 2 Values in between shall be agreed jointly between the manufacturer and the user.

3.2.11**sparkover (breakdown)**

abrupt transition of the gap resistance from practically infinite value to a relatively low value

3.2.12**transverse voltage**

the difference in the discharge voltages between terminal A and B (see figure 1) of the gaps assigned to the two conductors of the circuit during the passage of discharge current

NOTE Only for three electrode GDT conducting a longitudinal surge

4 Service Conditions**4.1 Low temperature**

GDT shall be capable of withstanding IEC 60068-2-1, test Aa $-40\text{ }^{\circ}\text{C}$, duration 2 h, without damage. While at $-40\text{ }^{\circ}\text{C}$, the GDT shall meet the d.c. and impulse sparkover requirements of table 1.

4.2 Air pressure and Altitude

Air pressure is 80 kPa to 106 kPa.

These values represent an altitude of +2,000 m to -500 m respectively.

4.3 Ambient Temperature

operating range (GDTs without failsafe): $-40\text{ }^{\circ}\text{C}$ to $+90\text{ }^{\circ}\text{C}$

operating range (GDTs with failsafe): $-40\text{ }^{\circ}\text{C}$ to $+70\text{ }^{\circ}\text{C}$

NOTE This corresponds to class 3K7 in IEC 60721

storage range (GDTs without failsafe): $-40\text{ }^{\circ}\text{C}$ to $+90\text{ }^{\circ}\text{C}$

storage range (GDTs with failsafe): $-40\text{ }^{\circ}\text{C}$ to $+40\text{ }^{\circ}\text{C}$

4.4 Relative Humidity

normal range: 5 % to 95 %

NOTE This corresponds to code AB4 in IEC 60364-5-51