



Edition 1.0 2017-08

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – safety – Part 2-17: Particular requirements for hand-held routers

Outils électroportatifs à moteur, outils portables et machines pour jardins et pelouses – sécurité – 8eblabel6cde/iec-62841-2-17-2017 Partie 2-17: Exigences particulières pour les défonceuses portatives





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on TEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technica) committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms, containing 20,000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

2657000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.





Edition 1.0 2017-08

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery – safety standards.iteh.ai) Part 2-17: Particular requirements for hand-held routers

IEC 62841-2-17:2017Outils électroportatifs à moteur, outils portables et machines pour jardins etpelouses – sécurité –8eblabel6cde/iec-62841-2-17-2017Partie 2-17: Exigences particulières pour les défonceuses portatives

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 25.140.20

ISBN 9978-2-8322-4704-4

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOR	REWORD	4
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	General requirements	7
5	General conditions for the tests	7
6	Radiation, toxicity and similar hazards	7
7	Classification	7
8	Marking and instructions	7
9	Protection against access to live parts	8
10	Starting	8
11	Input and current	8
12	Heating	8
13	Resistance to heat and fire	8
14	Moisture resistance	8
15	Resistance to rusting	8
16	Overload protection of transformers and associated circuits	9
17		
18	Abnormal operation	9
19	Mechanical hazards	9
20	Mechanical strengthstandards.iteh.ai/catalog/standards/sist/a6f860f4-2158-42df-890f	
21	Construction	. 11
22	Internal wiring	. 12
23	Components	. 12
24	Supply connection and external flexible cords	. 12
25	Terminals for external conductors	. 12
26	Provision for earthing	. 12
27	Screws and connections	. 12
28	Creepage distances, clearances and distances through insulation	.12
Ann	exes	es 6 ns 6 ns 7 for the tests 7 and similar hazards 7 attions 7 access to live parts 8 and fire 10 standards.ich.aich.aich.aich.aich.aich.aich.aich.
Ann	ex I (informative) Measurement of noise and vibration emissions	.16
Ann	ex K (normative) Battery tools and battery packs	. 19
	ex L (normative) Battery tools and battery packs provided with mains connection on-isolated sources	.20
Bibli	iography	.21
Figu	re 101 – Measurement of distance between handle and rotary cutting bit	.13
Figu	re 102 – Various designs with barrier	. 14
Figu	re 103 – Design with minimum distance from grasping surface	. 15
Figu	re I.101 – Positions of transducers for type 2 routers	. 17

Table 4 – Required performance levels	9
Table I.101 – Test conditions for type 2 routers	16

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 62841-2-17:2017</u> https://standards.iteh.ai/catalog/standards/sist/a6f860f4-2158-42df-890f-8eb1abe16cde/iec-62841-2-17-2017 - 4 -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS, TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY – SAFETY –

Part 2-17: Particular requirements for hand-held routers

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter. https://standards.iteh.ai/catalog/standards/sist/a6f860f4-2158-42df-890f-
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62841-2-17 has been prepared by IEC technical committee 116: Safety of motor-operated electric tools.

The text of this standard is based on the following documents:

FDIS	Report on voting
116/335/FDIS	116/342/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

This Part 2-17 is to be used in conjunction with the first edition of IEC 62841-1 (2014).

IEC 62841-2-17:2017 © IEC 2017 - 5 -

This Part 2-17 supplements or modifies the corresponding clauses in IEC 62841-1, so as to convert it into the IEC standard: Particular requirements for hand-held routers.

Where a particular subclause of Part 1 is not mentioned in this Part 2-17, that subclause applies as far as relevant. Where this standard states "addition", "modification" or "replacement", the relevant text in Part 1 is to be adapted accordingly.

The following print types are used:

- requirements: in roman type;
- test specifications: in italic type;
- notes: in small roman type.

The terms defined in Clause 3 are printed in **bold typeface**.

Subclauses, notes and figures which are additional to those in Part 1 are numbered starting from 101.

A list of all parts of the IEC 62841 series, under the general title: *Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery* – *Safety*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

reconfirmed,

(standards.iteh.ai)

withdrawn,

- IEC 62841-2-17:2017
- replaced by a revised edition, or alcatalog/standards/sist/a6f860f4-2158-42df-890f-
- 8eb1abe16cde/iec-62841-2-17-2017
- amended.

The National Committees are requested to note that for this document the stability date is 2019.

THIS TEXT IS INCLUDED FOR THE INFORMATION OF THE NATIONAL COMMITTEES AND WILL BE DELETED AT THE PUBLICATION STAGE.

NOTE The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 36 months from the date of publication.

ELECTRIC MOTOR-OPERATED HAND-HELD TOOLS, TRANSPORTABLE TOOLS AND LAWN AND GARDEN MACHINERY – SAFETY –

Part 2-17: Particular requirements for hand-held routers

1 Scope

This clause of Part 1 is applicable, except as follows:

Addition:

This part of IEC 62841 applies to hand-held **routers** intended for cutting slots into or shaping the edge of wood and analogous materials, plastics and non-ferrous metals except magnesium.

NOTE 101 Routers that are primarily used for trimming the edge of materials are also known as trimmers.

NOTE 102 **Routers** that are used to cut various materials through the rotary action are also known as rotary cutters.

This part of IEC 62841 does not apply to jointers D PREVIEW

NOTE 103 Jointers are covered by IE **62841-209** ards.iteh.ai)

 This part of IEC 62841 does not apply to small rotary tools.

 IEC 62841-2-17:2017

 NOTE 104
 Small rotary tools are covered by etc 62841/22/23/sist/a6f860f4-2158-42df-890f

8eb1abe16cde/iec-62841-2-17-2017

2 Normative references

This clause of Part 1 is applicable.

3 Terms and definitions

This clause of Part 1 is applicable, except as follows:

Additional definitions:

3.101 base part supporting the **router** on the workpiece

3.102 rotary cutting bit

rotating cutting **accessory** with a shank for mounting it into a collet having its main feed direction perpendicular to its axis of rotation

Note 1 to entry: There are **rotary cutting bits** that allow an additional plunging operation parallel to its axis of rotation.

3.103 router tool with a **base** and a collet, designed to be fitted with a **rotary cutting bit**

3.104

trimmer

type 1 router designed to be fitted with a rotary cutter and a base that allows for control of trimming the edge of laminate sheet or similar materials

- 7 -

3.105 type 1 router

router that has the following criteria:

- a) a mass, excluding a detachable **base**, a **separable battery pack** or a **detachable battery pack**, not exceeding 2 kg; and
- b) a collet capacity not exceeding 8 mm

3.106

type 2 router

router that has the following criteria:

- a) a mass, excluding a detachable **base**, a **separable battery pack** or a **detachable battery pack**, exceeding 2 kg; or
- b) a collet capacity exceeding 8 mm

4 General requirements

This clause of Part 1 is applicable **CANDARD PREVIEW**

5 General conditions for thetestslards.iteh.ai)

This clause of Part 1 is applicable, except as follows:017

https://standards.iteh.ai/catalog/standards/sist/a6f860f4-2158-42df-890f-5.17 Addition: 8eb1abe16cde/iec-62841-2-17-2017

The mass of the tool includes all handles and the dust extraction adapter, if any.

6 Radiation, toxicity and similar hazards

This clause of Part 1 is applicable.

7 Classification

This clause of Part 1 is applicable.

8 Marking and instructions

This clause of Part 1 is applicable, except as follows:

8.1 Addition:

rated no-load speed.

8.14.1 Addition:

The additional safety instructions as specified in 8.14.1.101 shall be given. This part may be printed separately from the "General Power Tool Safety Warnings".

8.14.1.101 Safety instructions for routers

a) Hold the power tool by insulated gripping surfaces only, because the cutter may contact its own cord. Cutting a "live" wire may make exposed metal parts of the power tool "live" and could give the operator an electric shock.

- 8 -

b) Use clamps or another practical way to secure and support the workpiece to a stable platform. Holding the work by your hand or against the body leaves it unstable and may lead to loss of control.

8.14.2 a) Additional items:

- 101) Information about the types of rotary cutting bits for which the tool is designed;
- 102) Information concerning the diameter of shank for which the collet(s) is intended;
- 103) Instruction to use only **rotary cutting bits** of the correct shank diameter for the collet mounted;
- 104) Instruction to use only rotary cutting bits suitable for the speed of the tool;
- 105) Instruction on how to change the collet or the collet cone (e.g. for setting up different shank diameters), if applicable.

8.14.2 b) Additional items:

101) Instruction on the correct use of the dust collection system, if applicable.

9 Protection against access to live parts 11 en STANDARD PREVIEW

This clause of Part 1 is applicable standards.iteh.ai)

10 Starting

<u>IEC 62841-2-17:2017</u>

https://standards.iteh.ai/catalog/standards/sist/a6f860f4-2158-42df-890f-This clause of Part 1 is applicableeblabel6cde/iec-62841-2-17-2017

11 Input and current

This clause of Part 1 is applicable.

12 Heating

This clause of Part 1 is applicable.

13 Resistance to heat and fire

This clause of Part 1 is applicable.

14 Moisture resistance

This clause of Part 1 is applicable.

15 Resistance to rusting

This clause of Part 1 is applicable.

16 Overload protection of transformers and associated circuits

This clause of Part 1 is applicable.

17 Endurance

This clause of Part 1 is applicable.

18 Abnormal operation

This clause of Part 1 is applicable, except as follows:

18.8 Replacement of Table 4 by the following:

Table 4 – Required performance levels

Type and purpose of SCF	Minimum performance level (PL)
Power switch – prevent unwanted switch-on for type 1 routers	b
Power switch – prevent unwanted switch-on for type 2 routers	С
Power switch – provide desired switch-off	b
Any electronic control to pass the test of 18.3 DARD PREVIEW	а
Overspeed prevention to prevent output speed above 130 % of rated no-load speed	b
Provide desired direction of rotation	а
Prevent exceeding thermal limits as in Clause 18C 62841-2-17:2017	а
Prevent self-resetting as required in 23.3 for type 1 routers/sist/a6186014-2158-42df-89	0 <u>f-</u> a
Prevent self-resetting as required in 23.3 for type 2 routers	b
Prevent unwanted lock-on of the power switch function	b
Lock-off function as required by 21.18.1.2 for type 1 routers	а
Lock-off function as required by 21.18.1.2 for type 2 routers	b
NOTE In Europe (EN 62841-2-17), the following additional requirement applies:	b
Restart prevention as required by 21.18.1.1	

19 Mechanical hazards

This clause of Part 1 is applicable, except as follows:

19.1 *Replacement of the first paragraph:*

Moving and dangerous parts other than the **rotary cutting bit** and the collet shall be so positioned or enclosed to provide adequate protection against personal injury. The protection of the user against accidental contact with the **rotary cutting bit** and the collet is provided by the requirements of 19.4.101.

19.4 *Replacement:*

Type 1 routers shall have at least one handle or grasping surface. The motor housing and/or parts of the **base** that assist in guiding the **router** in use may be considered as a grasping surface, if identified as such in accordance with 8.14.2 b) 6).

Type 2 routers shall have at least one handle and an additional handle or grasping surface to allow the operation of the tool with two hands. The motor housing and/or parts of the base that assist in guiding the router in use may be considered as a grasping surface, if identified as such in accordance with 8.14.2 b) 6).

Compliance is checked by inspection.

19.4.101 Prevention of inadvertent contact

The handles shall be so shaped or located as to minimise the risk of inadvertent contact of the user's hand with the rotary cutting bit and the collet.

For type 1 routers, a removable cover for the purpose of changing the accessory which is provided to meet the requirements of 19.4.101 may be removable without the aid of a tool.

For handle(s), inadvertent contact of the user's hand is considered to be prevented if there is sufficient distance between a defined measuring point on the handle surface and the rotary cutting bit and the collet.

Compliance is checked as follows:

A test pin with a diameter of the largest collet size is mounted to the tool. A mark is applied around the test pin (10 ± 1) mm from the collet. The distance between the defined measuring point and the mark on the test pin shall be at least 120 mm. The measurement shall be carried out as a chain distance. See Figure 101.

With the **base** set to maximum depth of cut, to establish the measuring point on the handle(s), follow the outlined procedure below. IEC 62841-2-17:2017

- a) Establish the closest (A) and the most distant (B) points from the plane of the base on the handle. Equidistant between⁸ points (A) and (B); 2draw the horizontal intersecting line on the plane parallel with the **base** and the surface of the handle.
- b) The point on the intersecting line of the handle surface with the largest radial distance from the centreline of the spindle is the defined measuring point.

For a motor housing and/or parts of the **base** used as a grasping surface, inadvertent contact of the user's hand is considered to be prevented by a barrier located between the grasping surface and the rotary cutting bit, see Figure 102. The barrier shall have a height x of at least 6 mm. A dust collecting system may be part of this barrier.

Alternatively to a barrier, for a motor housing and/or parts of the **base** used as a grasping surface in a type 1 router with an open portion(s) above the base, inadvertent contact of the user's hand is also considered to be prevented if either

the rotary cutting bit and the collet are not accessible above the base by means of the test probe B of IEC 61032:1997 with a force not exceeding 5 N;

or

- there is a minimum distance of 60 mm between
 - a point located 40 mm above the lower edge of the grasping surface area in accordance with 8.14.2 b) 6) along its centreline; and
 - any point on the edge of any open portion (see Figure 103). •

Compliance is checked by manual test using test probe B of IEC 61032:1997 and by measurement. No covers are removed for the manual test. The 60 mm measurement is carried out as a chain distance.

IEC 62841-2-17:2017 © IEC 2017 - 11 -

Adjustment elements capable of being readjusted while the tool is operating, e.g. "revolving depth gauge", shall be located so that touching of rotating parts is avoided.

Compliance is checked by inspection.

19.101 Type 2 routers shall be provided with a base which is capable of being adjusted to surround the rotary cutting bit so as to provide sufficient stability during normal operation.

Compliance is checked by inspection and by the following test.

For the test, the tool is prepared as follows:

- the motor is switched off;
- no rotary cutting bit is installed;
- the tool is adjusted such that the collet is at the highest position;
- tools provided with an appliance inlet are fitted with an appropriate connector and flexible cable or cord.

The tool is placed in its most unfavourable position with its **base** resting on a plane that is inclined at an angle of 10° to the horizontal. The cable or cord, if any, shall rest on the inclined plane in the most unfavourable position. For the test, the tool is prevented from sliding.

The tool shall not tip over the STANDARD PREVIEW

19.102 Type 1 routers shall be provided with a base so as to provide guidance during operation.

LEC 62841-2-17:2017 Compliance is checked by inspection Septabe16cde/iec-62841-2-17-2017

20 Mechanical strength

This clause of Part 1 is applicable.

21 Construction

This clause of Part 1 is applicable, except as follows:

21.18.1.1 Addition:

For routers, power switches other than momentary power switches are permitted.

NOTE In Europe (EN 62841-2-17), the following additional requirement applies:

For **routers**, either

the power switch shall be a momentary power switch without having a locking arrangement in the "on" position

or

 the tool shall not restart after an interruption of the mains supply without releasing and re-actuating the **power** switch.

21.18.1.2 Addition:

Routers are regarded as tools having a risk associated with inadvertent starting.