

SLOVENSKI STANDARD SIST EN 62037-1:2012

01-oktober-2012

Nadomešča: SIST EN 62037:2001

Pasivne radiofrekvenčne (rf) in mikrovalovne naprave, meritve intermodulacijskega nivoja - 1. del: Splošne zahteve in merilne metode (IEC 62037-1:2012)

Passive r.f. and microwave devices, intermodulation level measurement - Part 1: General requirements and measuring methods (IEC 62037-1:2012)

Passive HF- und Mikrowellenbauteile, Messung des Intermodulationspegels - Teil 1: Allgemeine Anforderungen und Messverfahren (IEC 62037-1:2012)

Dispositifs RF et à micro-ondes passifs, mesure du niveau d'intermodulation - Partie 1: Exigences générales et méthodes de mesure (CEI 62037-1:2012)

Ta slovenski standard je istoveten z: EN 62037-1:2012

ICS:

33.120.30

Radiofrekvenčni konektorji R.F. connectors (RF)

SIST EN 62037-1:2012

en

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 62037-1

August 2012

ICS 33.040.20

Supersedes EN 62037:1999 (partially)

English version

Passive RF and microwave devices, intermodulation level measurement -Part 1: General requirements and measuring methods (IEC 62037-1:2012)

Dispositifs RF et à micro-ondes passifs, mesure du niveau d'intermodulation -Partie 1: Exigences générales et méthodes de mesure (CEI 62037-1:2012) Passive HF- und Mikrowellenbauteile, Messung des Intermodulationspegels -Teil 1: Allgemeine Anforderungen und Messverfahren (IEC 62037-1:2012)

This European Standard was approved by CENELEC on 2012-07-03. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

© 2012 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Foreword

The text of document 46/402/FDIS, future edition 1 of IEC 62037-1, prepared by IEC TC 46 "Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62037-1:2012.

The following dates are fixed:

•	latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2013-04-03
•	latest date by which the national standards conflicting with the document have to be withdrawn	(dow)	2015-07-03

This document supersedes EN 62037:1999 (PART).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62037-1:2012 was approved by CENELEC as a European Standard without any modification.





Edition 1.0 2012-05

INTERNATIONAL STANDARD



Passive RF and microwave devices, intermodulation level measurement – Part 1: General requirements and measuring methods

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 33.040.20

ISBN 978-2-83220-110-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOI	REWO	RD		3		
1	Scope					
2	Normative references					
3	Abbreviations5					
4	Characteristics of intermodulation products					
5	Principle of test procedure			6		
6	Test set-up			6		
	6.1 General		6			
	6.2	Test equipment		6		
		6.2.1 General		6		
		6.2.2 Set-up 1		7		
		6.2.3 Set-up 2		8		
7	Prep	aration of DUT and	test equipment	8		
	7.1	General		8		
_	7.2	Guidelines for min	imizing generation of passive intermodulation	8		
8	Test	procedure		10		
9	Reporting			10		
	9.1	Results		10		
	9.2	Example of results	5	10		
10	10 Measurement error					
Annex A (informative) Configuration of low-PIM termination						
Annex B (informative) Test procedure considerations						
Fig	ure 1	- Set-up 1; reverse	IM-test set-up	12		
Fig	ure 2	- Set-up 2; forward	IM-test set-up	13		
Fig	ure 3 ·	- Passive intermod	ulation (PIM) measurement error caused by residual system			
erro	or			14		
Fig	ure A.	1 – Long cable tern	nination	15		
Fig	ure A.	2 – Lumped termin	ation with a linear attenuator	16		
Tab may	ole 1 – y be s	Guide for the desi usceptive to PIM ge	gn, selection of materials and handling of components that energy in the second s	9		
Tab	able 2 – Test set-up conditions10					

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PASSIVE RF AND MICROWAVE DEVICES, INTERMODULATION LEVEL MEASUREMENT –

Part 1: General requirements and measuring methods

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62037-1 has been prepared by technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This first edition of IEC 62037-1 replaces IEC 62037, published in 1999. It constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
46/402/FDIS	46/416/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62037 series, published under the general title *Passive RF and microwave devices intermodulation level measurement*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

PASSIVE RF AND MICROWAVE DEVICES, INTERMODULATION LEVEL MEASUREMENT –

Part 1: General requirements and measuring methods

1 Scope

This part of IEC 62037 deals with the general requirements and measuring methods for intermodulation (IM) level measurement of passive RF and microwave components, which can be caused by the presence of two or more transmitting signals.

The test procedures given in this standard give the general requirements and measurement methods required to characterize the level of unwanted IM signals using two transmitting signals.

The standards in this series address the measurement of PIM, but do not cover the long term reliability of a product with reference to its performance.

This standard is to be used in conjunction with other appropriate part(s) of IEC 62037.

2 Normative references

None.

3 Abbreviations

- CATV Community antenna television
- DUT Device under test
- IM Intermodulation
- PIM Passive intermodulation

4 Characteristics of intermodulation products

PIM interference is caused by sources of non-linearity of mostly unknown nature, location and behaviour. A few examples are inter-metallic contacts, choice of materials, corrosion products, dirt, etc. Most of these effects are subject to changes over time due to mechanical stress, temperature changes, variations in material characteristics (cold flow, etc.) and climatic changes, etc.

The generation of intermodulation products originates from point-sources inside a DUT and propagate equally in all available directions.

The generation of passive intermodulation products (PIM) does not necessarily follow the law of the usual non-linear equation of quadratic form. Therefore, accurate calculation to other power levels causing the intermodulation is not possible and PIM comparisons should be made at the same power level.

Furthermore, PIM generation can be frequency-dependent. When PIM generation is frequency-dependent, the PIM performance shall be investigated over the specified frequency band.

5 Principle of test procedure

Test signals of frequencies f_1 and f_2 with equal specified test port power levels are combined and fed to the DUT. The test signals should contain at least 10 dB less harmonic or selfintermodulation signal level than the expected level generated in the DUT.

The PIM is measured over the specified frequency range. The intermodulation products of order $(2f_1 \pm f_2)$, $(2f_2 \pm f_1)$ etc. are measured.

In most cases, the third order intermodulation signals represent the worst case condition of unwanted signals generated; therefore, the measurement of these signals characterizes the DUT in a sufficient way. However, the test set-ups given in Clause 6 are suitable for measuring other intermodulation products.

In other systems (such as CATV), the 3^{rd} order may not be as applicable in characterizing the DUT.

Intermodulation can be measured in reverse and forward direction. Reverse and forward is referred to the direction of propagation of the most powerful carrier.

6 Test set-up

6.1 General

Experience shows that the generation of intermodulation products originates from pointsources inside a device under test (DUT) and propagates equally in all available directions. Therefore, either the reverse (reflected) or the forward (transmitted) intermodulation signal can be measured.

Two different test set-ups are described in Figure 1 and Figure 2 and are for reference only. Other topologies are possible.

Set-up 1 is for measuring the reverse (reflected) intermodulation signal only, and set-up 2 is for measuring the forward (transmitted) intermodulation signal. The measurement method (reverse or forward) is dependent upon the DUT. The set-ups may be assembled from standard microwave or radio link hardware selected for this particular application. All components shall be checked for lowest self-intermodulation generation.

Experience shows that devices containing magnetic materials (circulators, isolators, etc.) can be prominent sources of intermodulation signal generation.

See Annex B for additional set-up considerations.

6.2 Test equipment

6.2.1 General

Two signal sources or signal generators with power amplifiers are required to reach the specified test port power. The combining and diplexing device may comprise a circulator, hybrid junction, coupler or filter network.

The test set-up self-intermodulation generated (including contribution of the load) should be at least 10 dB below the level to be measured on the DUT. The associated error may be obtained from the graph in Figure 3.