

**SLOVENSKI STANDARD**  
**SIST EN 62639:2012**  
**01-julij-2012**

---

**Fluorescenčne indukcijske sijalke - Zahteve za delovanje**

Fluorescent induction lamps - Performance requirements

Leuchtstoff-Induktionslampen - Anforderungen an die Arbeitsweise

Lampes fluorescentes à induction - Spécification de performance

**Ta slovenski standard je istoveten z: EN 62639:2012**

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

**ICS:**

29.140.30      Fluorescenčne sijalke. Sijalke      Fluorescent lamps.  
Discharge lamps

**SIST EN 62639:2012**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 62639:2012

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 62639**

April 2012

ICS 29.140.30

English version

**Fluorescent induction lamps -  
Performance specification  
(IEC 62639:2012)**

Lampes fluorescentes à induction -  
Spécification de performance  
(CEI 62639:2012)

Leuchtstoff-Induktionslampen -  
Anforderungen an die Arbeitsweise  
(IEC 62639:2012)

This European Standard was approved by CENELEC on 2012-03-27. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Management Centre: Avenue Marnix 17, B - 1000 Brussels**

## Foreword

The text of document 34A/1526/FDIS, future edition 1 of IEC 62639, prepared by SC 34A, "Lamps", of IEC/TC 34, "Lamps and related equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62639:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-12-27
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-03-27

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

## Endorsement notice

The text of the International Standard IEC 62639:2012 was approved by CENELEC as a European Standard without any modification. (standards.iteh.ai)

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60081	1997	Double-capped fluorescent lamps - Performance specifications	EN 60081	1998
IEC 60598-1	-	Luminaires - Part 1: General requirements and tests	EN 60598-1	-
IEC 60929	-	AC and/or DC-supplied electronic control gear for tubular fluorescent lamps - Performance requirements	EN 60929	-
IEC 61347-2-3	-	Lamp controlgear - Part 2-3: Particular requirements for a.c. and/or d.c. supplied electronic control gear for fluorescent lamps	EN 61347-2-3	-
IEC 62532	2011	Fluorescent induction lamps - Safety specifications	EN 62532	2011

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 62639:2012

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>



IEC 62639

Edition 1.0 2012-02

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



Fluorescent induction lamps – Performance specification

Lampes fluorescentes à induction – Spécification de performance

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

PRICE CODE **XB**  
CODE PRIX

ICS 29.140.30

ISBN 978-2-88912-920-1

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions.....	6
4 Lamp requirements.....	7
4.1 General.....	7
4.2 Marking.....	8
4.2.1 General.....	8
4.2.2 Correlated colour temperature (CCT) and colour rendering index ( $R_a$ ).....	8
4.2.3 Polarity.....	8
4.3 Dimensions.....	8
4.4 Starting characteristics.....	8
4.5 Electrical characteristics.....	8
4.6 Photometric characteristics.....	8
4.7 Lumen maintenance.....	9
4.8 Life.....	9
5 Information for ballast design.....	9
6 Information for luminaire design.....	9
7 Data sheets.....	9
7.1 Diagrammatic data sheets for location of lamp dimensions.....	9
7.2 Lamp data sheets.....	18
7.3 Maximum outline sheets.....	44
Annex A (normative) Method of test for starting characteristics.....	55
Annex B (normative) Method of test for electrical and photometric characteristics.....	57
Annex C (normative) Method of test for lumen maintenance and life.....	61
Annex D (informative) Information for ballast design.....	62
Annex E (informative) Information for luminaire design.....	66
Bibliography.....	67
Figure A.1 – Test circuit for measurement of starting characteristics.....	56
Figure B.1 – Schematic set-up for measurement of electrical characteristics of externally coupled induction lamps and photometrical characteristics.....	59
Figure B.2 – Example of calorimetric set-up for measurement of power of internally a-type coupled induction lamps.....	60
Figure D.1 – Circuit for testing ballasts – Lamp voltage, lamp current, phase shift and frequency measured at starting and during operation.....	63
Figure D.2 – Circuit for testing ballasts – Lamp voltage, current and frequency measured at starting.....	64
Figure D.3 – Circuit for testing ballasts – Lamp voltage, current, phase shift and frequency measured during operation.....	65
Table A.1 – Frequencies of specially prepared ballasts.....	55



## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**FLUORESCENT INDUCTION LAMPS –  
PERFORMANCE SPECIFICATION**
**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62639 has been prepared by subcommittee 34A: Lamps, of IEC technical committee 34: Lamps and related equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
34A/1526/FDIS	34A/1555/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[SIST EN 62639:2012](#)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

## INTRODUCTION

Performance standard IEC 62639 follows IEC 62532:2011-01, which is the safety standard for induction lamps.

Requirements are given on marking, dimensions, starting characteristics, electrical characteristics, photometric characteristics, lumen maintenance and life. Further, information is given for designing ballasts and luminaires.

The requirements are detailed by means of lamp data sheets, diagrammatic data sheets and maximum lamp outline sheets.

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-66affbf06795/sist-en-62639-2012>

## FLUORESCENT INDUCTION LAMPS – PERFORMANCE SPECIFICATION

### 1 Scope

This International Standard specifies the performance requirements for fluorescent induction lamps for general lighting purposes.

In this standard, the term “lamp” stands for “induction lamp”.

It may be expected that lamps which comply with this standard will start and operate satisfactorily at voltages between 92 % and 106 % of rated supply voltage and at an ambient air temperature between 10 °C and 50 °C, when operated with ballasts complying with IEC 60929 and IEC 61347-2-3, as far as applicable, and in a luminaire complying with IEC 60598-1.

NOTE For some lamps, additional information for ballast design is given for proper starting at an ambient air temperature of –15 °C.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-667862815267/sist-en-62639-2012)

[https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-667862815267/sist-en-62639-2012)

IEC 60081:1997, *Double-capped fluorescent lamps – Performance specifications*

IEC 60598-1, *Luminaires – Part 1: General requirements and tests*

IEC 60929, *AC and/or DC-supplied electronic control gear for tubular fluorescent lamps – Performance requirements*

IEC 61347-2-3, *Lamp control gear – Part 2-3: Particular requirements for a.c. and/or d.c. supplied electronic control gear for fluorescent lamps*

IEC 62532:2011, *Fluorescent induction lamps – Safety specifications*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62532 and IEC 60081 apply, together with the following.

#### 3.1

##### ambient temperature

$T_{amb}$

average temperature of air or another medium in the vicinity of the lamp

**3.2****stabilization period**

time required after switching on a lamp to reach stable values of luminous flux or lamp voltage

Note 1 to entry: Requirements on luminous flux are given in 4.6 and on tolerance of luminous flux in Clause B.2.

**3.3****reference ballast**

special electronic ballast, which is specified by the design specification of manufacturer

It is designed for the purpose of providing comparison standards for use in testing ballasts, for the selection of reference lamps or for testing regular production lamps under standardized conditions. It is essentially characterized by the fact that, at its rated frequency, it has a stable voltage/current ratio which is relatively uninfluenced by variations in current, temperature and magnetic surroundings, as outlined in the relevant ballast standard.

[SOURCE: IEC 60050-845:1987, 845-08-36, modified]

**3.4****life**

<general term> time during which a lamp is operated until its failure

Note 1 to entry: Switch-off times are not regarded when calculating life.

**3.5****nominal life**

life (in hours) as declared by the manufacturer

It is published together with the switching cycle and failure rate on which it is based.

Note 1 to entry: Example for a short version: 12B10 (12 h switching cycle / 10 % failures);

**4 Lamp requirements****4.1 General**

A lamp, on which compliance with this standard is claimed, shall comply with the requirements of IEC 62532.

A lamp has to comply with further requirements or more stringent requirements, if they published by manufacturer.

A lamp shall be so designed that its performance is reliable in normal and accepted use. In general, this can be achieved by satisfying the requirements of the following subclauses.

The requirements and information given apply to 95 % of production.

NOTE The requirements and tolerances permitted by this standard correspond to the testing of a type test sample, submitted by the manufacturer for that purpose. In principle, this type test sample should consist of units having characteristics typical of the manufacturer's production and being as close to the production centre point values as possible.

It may be expected with the tolerances given in the standard that products manufactures in accordance with the type test sample will comply with the standard of the majority of production. Due to the production spread however, it is inevitable that there will sometimes be products outside the specified tolerances.

Measurements are carried out under reference conditions with values specified on the data sheets, if available. Except where otherwise specified in the annexes, lamps shall be tested in an ambient temperature of between 20 °C and 27 °C.

## 4.2 Marking

### 4.2.1 General

In addition to the marking requirements of IEC 62532, the following is specified.

### 4.2.2 Correlated colour temperature (CCT) and colour rendering index ( $R_a$ )

The value of the correlated colour temperature and colour rendering index shall be provided on the lamp itself or on the packaging (under consideration). The value representing CCT and  $R_a$  may take the form as given in the International Lamp Coding System (ILCOS).

NOTE An  $R_a$  of 80 and a CCT of 3 000 K may be combined in the abbreviation "830".

### 4.2.3 Polarity

The polarity shall be identified by marking the terminals (+, -). Other means of identifying are possible instead, see Clause B.2.

## 4.3 Dimensions

The dimensions of a lamp shall comply with the values specified on the relevant lamp data sheet.

Compliance: By measuring with callipers or equivalent.

## 4.4 Starting characteristics

A lamp shall start fully within the time specified on the relevant lamp data sheet and remain alight.

[SIST EN 62639:2012](https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-529-411)

<https://standards.iteh.ai/catalog/standards/sist/c8b33168-1ce4-4724-9248-529-411>

Compliance: Visual inspection to verify that lamps are starting and remain alight. If the lamp has achieved breakdown at  $\leq U_{\min}$  and stayed alight, it has passed the test.

Conditions and method of test are given in Annex A.

## 4.5 Electrical characteristics

Requirements for lamp voltage and power are given below.

- The initial reading of the voltage at the lamp terminals shall comply with the values specified on the relevant lamp data sheet.
- The initial reading of the power dissipated by a lamp shall not exceed the rated power specified on the relevant lamp data sheet by more than 5 %.

Conditions and method of test are given in Annex B.

## 4.6 Photometric characteristics

Requirements for luminous flux, chromaticity coordinates and colour rendering index are given below.

- The initial reading of the luminous flux of a lamp shall be not less than 90 % and the average of a batch shall be not less than 95 % (under consideration) of the declared value.
- If specified, the initial reading of the chromaticity co-ordinates x and y of a lamp shall be within 5 SDCM (standard deviation of colour matching) from the rated values.
- The initial reading of the general colour rendering index  $R_a$  of a lamp shall be not less than the rated value decreased by three.

Conditions and method of test are given in Annex B.

#### 4.7 Lumen maintenance

The lumen maintenance of a lamp, at any time in its life, shall be not less than 90 % of the rated lumen maintenance value.

Conditions and method of test are given in Annex C.

#### 4.8 Life

Requirements are provided by the lamp manufacturer.

### 5 Information for ballast design

Refer to the relevant lamp data sheet and to Annex D for information for ballast design.

### 6 Information for luminaire design

Refer to the relevant lamp data sheet and to Annex E for information for luminaire design. The regional requirements on EMC should be regarded.

### 7 Data sheets

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

#### 7.1 Diagrammatic data sheets for location of lamp dimensions

62639-IEC-01	rectangular shaped lamps
62639-IEC-02	circular shaped lamps
62639-IEC-03	A110, A130 and A140 shaped lamps
62639-IEC-04	G95 shaped lamps
62639-IEC-05	PS110 shaped lamps
62639-IEC-06	PS180 shaped lamps
62639-IEC-07	R160 shaped lamps
62639-IEC-08	T85 shaped lamps