

Edition 4.2 2012-06

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2012 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore iec.ch/justpublished

Stay up to date on all new EC publications. Just Published details all new publications beleased. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



Edition 4.2 2012-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Prises de courant pour usages industriels -Partie 1: Règles générales

s://standards.iteh.ar

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.120.30 ISBN 978-2-8322-0153-4

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

- O	REWORD5	
NT	RODUCTION7	
1	Scope8	
2		
3	Normative references	
4	General	
5	Standard ratings	
6	Classification14	
7	Marking	
8	Dimensions	
9	Protection against electric shock	
10	Provision for earthing19	
11	Terminals and terminations	
12	Interlocks 34	
13	Resistance to ageing of rubber and thermoplastic material	
14	General construction	
15	Construction of socket-outlets35	
16	Construction of plugs and connectors	
17	Construction of appliance inlets	
18	Construction of appliance inlets	
19	Insulation resistance and dielectric strength	
20	Breaking capacity	
21	Normal operation 42	
22	Temperature rise	
23	Flexible cables and their connection	
24	Mechanical strength	
25	Screws, current-carrying parts and connections	
26	Creepage distances, clearances and distances through sealing compound57	
27	Resistance to heat, to fire and to tracking58	١
28	Corrosion and resistance to rusting59	
29	Conditional short-circuit current withstand test60	
30	Electromagnetic compatibility61	
٩nr	nex A (normative) Guidance and description of test apparatus76	
	nex B (informative) List of the clause numbers that require re-testing84	

Figure 1 – Diagram showing the use of the accessories	62	
Figure 2 – Standard test finger	63	
Figure 3 – Void	64	
Figure 4 – Void	64	
Figure 5 – Circuit diagrams for breaking capacity and normal operation tests	64	
Figure 6 – Apparatus for testing the cable anchorage	65	
Figure 7 – Impact-test apparatus (see also annex A)	66	
Figure 8 – Arrangement for mechanical strength test for plugs and connectors	66	
Figure 9 – Apparatus for flexing test		
Figure 10 – Void	67	
Figure 11a – Void	67	
Figure 11b – Void		
Figure 12 – Void	67	
Figure 13 – Gauges for testing insertability of round unprepared conductors having the maximum specified cross-section. Figure 14 – Examples of terminals Figure 15 – Equipment test arrangement	68	
Figure 14 – Examples of terminals	69	
Figure 15 – Equipment test arrangement	71	
Figure 16 – Diagram of the test circuit for the verification of short-circuit current withstand of a two-pole equipment on a single phase a.c. or d.c.		
Figure 17 – Diagram of the test circuit for the verification of short-circuit current withstand of a three-pole equipment	73	
Figure 18 – Diagram of the test circuit for the verification of short-circuit current withstand of a four-pole equipment		
Figure 19 – Information for the bending test	75	
Figure A.1 – Impact test fixture – Pendulum assembly	78	
Figure A.2 - Impact rest fixture - Pendulum masses - Quantity: 4	80_	
Figure A.3 – Impact test fixture – Pendulum shaft end	81	
Figure A.4 – Impact test fixture – Pendulum anvil		
Figure A.5 – mpact test fixture – Pendulum shaft	82	
Figure A.6 - Impact text fixture - Pendulum pivot	82	
Figure A.7 - Impact test apparatus – Back and mounting plates	83	
Table 1	14	
Table 2	18	
Table 3 – Size for connectable conductors	21	
Table 4-1 – Deflection test forces	27	
Table 4-2	30	
Table 4-3	31	
Table 4-4	33	
Table 5	40	
Table 6 – Breaking capacity	42	
Table 7 – Normal operation	44	
Table 8	45	
Table 9	47	
Table 10	49	

Table 11	50
Table 12	52
Table 13	53
Table 14	54
Table 15	55
Table 16	57
Table A.1 – Impact test release angles	79



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PLUGS, SOCKET-OUTLETS AND COUPLERS FOR INDUSTRIAL PURPOSES –

Part 1: General requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic yields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60309-1 has been prepared by subcommittee 23H: Industrial plugs and socket-outlets, of IEC technical committee 23: Electrical accessories.

This consolidated version of IEC 60309-1 consists of the fourth (1999) [documents 23H/88/FDIS and 23H/91/RVD], its amendment 1 (2005) [documents 23H/174/FDIS and 23H/182/RVD] and its amendment 2 (2012) [documents 23H/282/FDIS and 23H/285/RVD].

The technical content is therefore identical to the base edition and its amendments and has been prepared for user convenience.

It bears the edition number 4.2.

A vertical line in the margin shows where the base publication has been modified by amendments 1 and 2.

Annex A forms an integral part of this standard.

Annex B is for information only.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed,
- · withdrawn,
- · replaced by a revised edition, or
- · amended.

The contents of the corrigendum of May 2014 have been included in this copy

iTex Sandards

https://scandards.iteh.ai)

Occurrent Preview

ttps://standards.iteh.ai

International Standard IEC 60309 is divided into several parts:

Part 1: General requirements, comprising clauses of a general character.

Subsequent parts: Particular requirements dealing with particular types. The clauses of these particular requirements supplement or modify the corresponding clauses in part 1. Where the text of subsequent parts indicates an "addition" to or a "replacement" of the relevant requirement, test specification or explanation of part 1, these changes are made to the relevant text of part 1, which then becomes part of the standard. Where no change is necessary, the words "This clause of part 1 is applicable" are used.

iTex Syntaxas
(https://standxxd.iteh.ai)
Dycur en Preview

Stano ods 2009-1:1999
Stano ods 2009-1:140-a068-4d38-8822-5ccb68d365c0/iec-60309-1-1999

PLUGS, SOCKET-OUTLETS AND COUPLERS FOR INDUSTRIAL PURPOSES –

Part 1: General requirements

1 Scope

This standard applies to plugs and socket-outlets, cable couplers and appliance couplers, with a rated operating voltage not exceeding 1 000 V d.c. or a.c. and 500 Hz a.c., and a rated current not exceeding 800 A, primarily intended for industrial use, either indoors or outdoors.

These accessories are intended to be installed by instructed persons (IEC 60050-195:1998, Amendment 1:2001, 195-04-02) or skilled persons (IEC 60050-195:1998, Amendment 1:2001, 195-04-01) only.

The list of preferred ratings is not intended to exclude other ratings

This standard applies to plugs and socket-outlets, cable couplers and appliance couplers, hereinafter referred to as accessories, for use when the ambient temperature is normally within the range of -25 °C to +40 °C. These accessories are intended to be connected to cables of copper or copper alloy only.

This standard applies to accessories with screwless type terminals or insulation piercing terminals, with a rated current up to and including 32 A for series I and 30 A for series II.

The use of these accessories on building sites and for agricultural, commercial and domestic applications is not precluded.

Socket-outlets or appliance inlets incorporated in or fixed to electrical equipment are within the scope of this standard. This standard also applies to accessories intended to be used in extra-low voltage installations.

This standard does not apply to accessories primarily intended for domestic and similar general purposes.

In locations where special conditions prevail, for example on board ship or where explosions are liable to occur, additional requirements may be necessary.

2 Definitions

Where the terms voltage and current are used, they imply the d.c. or the a.c. r.m.s. values.

For the purpose of this part of IEC 60309, the following definitions apply.

The application of accessories is shown in Figure 1.

2.1

plug and socket-outlet

a means enabling the connection at will of a flexible cable to fixed wiring. It consists of two parts:

2.1.1

socket-outlet

the part intended to be installed with the fixed wiring or incorporated in equipment.

A socket-outlet may also be incorporated in the output circuit of an isolating transformer

2.1.2

plug

the part integral with or intended to be attached directly to one flexible cable connected to the equipment or to a connector

2.2

cable coupler

a means enabling the connection at will of two flexible cables. It consists of two parts:

2.2.1

connector

the part integral with or intended to be attached to one flexible cable connected to the supply

NOTE In general, a connector has the same contact arrangement as a socket-owlet.

2.2.2

plug

the part integral with or intended to be attached to one flexible cable connected to the equipment or to a connector

NOTE The plug of a cable coupler is identical to the plug of a "plug and socket-outlet".

2.3

appliance coupler

a means enabling the connection at will of a flexible cable to the equipment. It consists of two parts:

2.3.1 dards iteh

connector

the part integral with, or intended to be attached to, one flexible cable connected to the supply

NOTE In general, the connector of an appliance coupler is identical to the connector of a cable coupler.

2.3.2

appliance inlet

the part incorporated in, or fixed to, the equipment or intended to be fixed to it

NOTE In general, an appliance inlet has the same contact arrangement as a plug.

2.4

rewirable plug or connector

an accessory so constructed that the flexible cable can be replaced

2.5

non-rewirable plug or connector

an accessory so constructed that the flexible cable cannot be separated from the accessory without making it permanently useless

2.6

mechanical switching device

a switching device designed to close and open one or more electric circuits by means of separable contacts

2.7

switched socket-outlet

a socket-outlet with an associated switching device to disconnect the supply from the socket-outlet contacts

2.8

integral switching device

a mechanical switching device constructed as a part of an accessory covered by this standard

2.9

interlock

a device, either electrical or mechanical, which prevents the contacts of a plug from becoming live before it is in proper engagement with a socket-outlet or connector, and which either prevents the plug from being withdrawn while its contacts are live or makes the contacts dead before separation

2.10

retaining device

a mechanical arrangement which holds a plug or connector in position when it is in proper engagement, and prevents its unintentional withdrawal

2.11

rated current

the current assigned to the accessory by the manufacturer

2.12

insulation voltage

the voltage assigned to the accessory by the manufacturer and to which dielectric tests, clearances and creepage distances are referred

2.13

rated operating voltage

the nominal voltage of the supply for which the accessory is intended to be used

2.14

basic insulation

the insulation necessary for the proper functioning of the accessory and for basic protection against electric shock

2.15

supplementary insulation (protective insulation)

an independent insulation provided in addition to the basic insulation, in order to ensure protection against electric shock in the event of a failure of the basic insulation

2.16

double insulation

insulation comprising both basic insulation and supplementary insulation

2.17

reinforced insulation

an improved basic insulation with such mechanical and electrical qualities that it provides the same degree of protection against electric shock as double insulation

2.18

terminal

a conductive part provided for the connection of a conductor to an accessory

2.18.1

pillar terminal

a terminal in which the conductor is inserted into a hole or cavity, where it is clamped under the shank of the screw or screws. The clamping pressure may be applied directly by the shank of the screw or through an intermediate clamping member to which pressure is applied by the shank of the screw (see Figure 14a)

2.18.2

screw terminal

a terminal in which the conductor is clamped under the head of the screw. The clamping pressure may be applied directly by the head of the screw or through an intermediate part, such as a washer, clamping plate or anti-spread device (see Figures 14b and 14c)

2.18.3

stud terminal

a terminal in which the conductor is clamped under a nut. The clamping pressure may be applied directly by a suitably shaped nut or through an intermediate part, such as a washer, clamping plate or anti-spread device (see Figure 14d)

2.18.4

saddle terminal

a terminal in which the conductor is clamped under a saddle by means of two or more screws or nuts (see Figure 14e)

2.18.5

lug terminal

a screw terminal or a stud terminal, designed for clamping a cable lug or bar by means of a screw or nut (see Figure 14f)

2.18.6

mantle terminal

a terminal in which the conductor is clamped against the base of a slot in a threaded stud by means of a nut. The conductor is clamped against the base of the slot by a suitably shaped washer under the nut, by a central peg if the nut is a cap nut, or by equally effective means for transmitting the pressure from the nut to the conductor within the slot (see Figure 14g)

2.18.7

screwless type terminal

a terminal for the connection and subsequent disconnection of one or more conductors, the connection being made, directly or indirectly, by other means than screws

NOTE Examples of screwless type terminals are given in Figure 14h.

2.18.8

insulation piercing terminal

IPT

a terminal for the connection and subsequent disconnection of one or more conductors, the connection being made by piercing, boring through, cutting through, removing, displacing or making ineffective in some other manner the insulation of the conductor(s) without previous stripping

NOTE 1 The removal of the sheath of the cable, if necessary, is not considered as a previous stripping.

NOTE 2 Examples of IPT are given in Figure 14i.

2.19

clamping unit

the part of a terminal necessary for the clamping and the electrical connection of the conductor

2.20

conditional short-circuit current

the prospective current that an accessory, protected by a specified short-circuit protective device, can satisfactorily withstand for the total operating time of that device under specified conditions of use and behaviour

NOTE This definition differs from IEV 441-17-20 by broadening the concept of current-limiting device into a short-circuit protective device, the function of which is not only to limit the current.

2.21

cap

a part separated or attached, which may be used to provide the degree of protection of a plug or appliance inlet when it is not engaged with a socket-outlet or connector

2.22

lid

a means to ensure the degree of protection on a socket-outlet or a connector

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-441:1984, International Electrotechnical Vocabulary (IEV) – Chapter 441: Switchgear, controlgear and fuses

IEC 60083:1997, Plugs and socket-outlets for domestic and similar general use standardized in member countries of IEC

IEC 60112:1979, Method for determining the comparative and the proof tracking indices of solid insulating materials under moist conditions

IEC 60227, (all parts) Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V

IEC 60228:1978, Conductors of insulated cables

IEC 60245-4(1994, Rubber insulated cables – Rated voltages up to and including 450/750 V – Part 4: Cords and flexible cables

IEC 60269-1:1986, Low-voltage fuses - Part 1: General requirements

IEC 60269-2:1986, Low-voltage fuses – Part 2: Supplementary requirements for fuses for use by authorized persons (fuses mainly for industrial application) – Sections I to III

IEC 60309-4, Plugs, socket-outlets and couplers for industrial purposes – Part 4: Switched socket-outlets and connectors with or without interlock

IEC 60320, (all parts) Appliance couplers for household and similar general purposes

IEC 60529:1989, Degrees of protection provided by enclosures (IP code)

IEC 60664-1:1992, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests

IEC 60695-2-11, Fire hazard testing –Part 2-11: Glowing/hot-wire based test methods – Glowwire flammability test method for end-products

IEC 60695-10-2, Fire hazard testing - Part 10-2: Abnormal heat - Ball pressure test