

SLOVENSKI STANDARD**SIST EN 50288-2-1:2013****01-oktober-2013**

**Večelementni kovinski kabli za analogne in digitalne komunikacije in krmiljenje - 2-
1. del: Področna specifikacija za zaslonjene kable z lastnostmi do 100 MHz -
Hrbtenični kabli za vodoravno montažo in montažo v stavbah**

Multi-element metallic cables used in analogue and digital communication and control -
Part 2-1: Sectional specification for screened cables characterised up to 100 MHz -
Horizontal and building backbone cables

iTeh STANDARD PREVIEW

Mehrdrige metallische Daten- und Kontrollkabel für analoge und digitale Übertragung -
Teil 2-1: Rahmenspezifikation für geschirmte Kabel bis 100 MHz - Kabel für den
Horizontal- und Steigungsbereich

[SIST EN 50288-2-1:2013](#)<https://standards.iteh.ai/catalog/standards/sist/63274268-6323-4779->

Câbles métalliques à éléments multiples utilisés pour les transmissions et les
commandes analogiques et numériques - Partie 2-1: Spécification intermédiaire pour les
câbles blindés pour applications jusqu'à 100 MHz - Câbles horizontaux et verticaux de
bâtiment

Ta slovenski standard je istoveten z: **EN 50288-2-1:2013**

ICS:

33.120.20

Žice in simetrični kabli

Wires and symmetrical
cables**SIST EN 50288-2-1:2013****en**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 50288-2-1:2013](#)

<https://standards.iteh.ai/catalog/standards/sist/63274268-6323-4779-863e-e27f4e016355/sist-en-50288-2-1-2013>

**EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM**

EN 50288-2-1

May 2013

ICS 33.120.10

Supersedes EN 50288-2-1:2003

English version

**Multi-element metallic cables used in analogue and digital communication
and control -**

**Part 2-1: Sectional specification for screened cables characterised
up to 100 MHz -
Horizontal and building backbone cables**

Câbles métalliques à éléments multiples utilisés pour les transmissions et les commandes analogiques et numériques - Partie 2-1: Spécification intermédiaire pour les câbles blindés pour applications jusqu'à 100 MHz - Câbles horizontaux et verticaux de bâtiment

Mehradrige metallische Daten- und Kontrollkabel für analoge und digitale Übertragung - Teil 2-1: Rahmenspezifikation für geschirmte Kabel bis 100 MHz - Kabel für den Horizontal- und

*iTeh STANDARD PREVIEW
(standards.iteh.ai)*

SIST EN 50288-2-1:2013

<https://standards.iteh.ai/catalog/standards/sist/63274268-6323-4779-863e-e27f4e016355/sist-en-50288-2-1-2013>

This European Standard was approved by CENELEC on 2013-03-18. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents

	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms, definitions, symbols and abbreviations	4
3.1 Terms and definitions	4
3.2 Symbols and abbreviations	5
4 Cable construction	5
4.1 Conductor	5
4.2 Insulation	5
4.3 Cabling elements	5
4.4 Identification of cabling elements	5
4.5 Screening of cabling elements	5
4.6 Cable make-up	5
4.7 Filling compound	5
4.8 Interstitial fillers	5
4.9 Screening of the cable core	5
4.10 Moisture barriers	5
4.11 Wrapping layers	6
4.12 Sheath	6
5 Tests and requirements for completed cables	6
5.1 Electrical tests	6
5.2 Mechanical test requirements	9
5.3 Environmental tests	10
5.4 Fire performance tests	10
Annex A (informative) Maximum voltage, current and temperature rating for cables used for POE applications	11
Annex B (informative) Blank Detail Specification	12

Foreword

This document (EN 50288-2-1:2013) has been prepared by CLC/SC 46XC "Multicore, Multipair and Quad Data communication cables," of CLC/TC 46X, "Communication cables".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-03-18
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2016-03-18

This document supersedes EN 50288-2-1:2003.

EN 50288-2-1:2013 includes the following significant technical changes with respect to EN 50288-2-1:2003:

- the addition of the Blank Detail Specification Annex;
- a number minor corrections and updating of references;
- the re-classification of 'ELFEXT' to 'ACR-F'.

This Part 2-1 is to be read in conjunction with EN 50288-1.

The STANDARD PREVIEW

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

[SIST EN 50288-2-1:2013](#)

This standard covers [the Principles and Elements of the Safety Objectives for Electrical Equipment Designed for Use within Certain Voltage Limits \(LVD - 2006/95/EC\) 2013](http://principles-elements-safety-objectives-electrical-equipment-within-certain-voltage-limits-lvd-2006-95-ec-2013)

1 Scope

EN 50288-2-1 is a sectional specification for screened cables, characterised from 1 MHz up to 100 MHz, to be used in horizontal and building backbone wiring as defined in EN 50173.

This sectional specification contains the electrical, mechanical, transmission and environmental performance characteristics of the cables, when tested in accordance with the referenced test methods.

This sectional specification is to be read in conjunction with EN 50288-1, which contains the essential provisions for its application.

The cables covered in this sectional specification are intended to operate with voltages and currents normally encountered in communication systems. These cables are not intended to be used in conjunction with low impedance sources, for example, the electric power supplies of public utility mains.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies

EN 50173	Series	<i>Information technology - Generic cabling systems</i>
EN 50288-1	Series	iTeh STANDARD PREVIEW <i>Multi-element metallic cables used in analogue and digital communication and control - Part 1: Generic specification</i>
EN 50289	Series	<i>Communication cables - Specifications for test methods</i>
EN 50290	Series	https://standards.iteh.ai/catalog/standards/sist/63274268-6323-4779-863e-e27f4e016355/sist-en-50288-2-1-2013
EN 60811	Series	<i>Electric and optical fibre cables - Test methods for non-metallic materials (IEC 60811 series)</i>
IEC 60189-2		<i>Low-frequency cables and wires with PVC insulation and PVC sheath - Part 2: Cables in pairs, triples, quads and quintuples for inside installations</i>

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document the terms and definitions given in EN 50288-1 and the following apply.

3.1.1

screening of cable

a cable is considered screened when the cable core is covered by a continuous conductive layer forming part of the shielding and grounding system

Note 1 to entry: d.c. continuity has to be given and minimum shielding requirements have to be met.

3.2 Symbols and abbreviations

For the purposes of this document, the following abbreviations apply.

EX	Exogenous (derived or originating externally)
POE	Power Over Ethernet

4 Cable construction

4.1 Conductor

The conductor shall be solid copper and meet the requirements of EN 50288-1, 4.1. The conductor shall be plain or metal coated.

The nominal conductor diameter shall be $\geq 0,5$ mm and $\leq 0,8$ mm.

NOTE Constructions with 'copper clad' conductors **do not** meet the requirements.

4.2 Insulation

The insulation shall be of a suitable material according to the relevant part of EN 50290-2.

4.3 Cabling elements

iTeh STANDARD PREVIEW
The cable element shall be a pair or a quad.
(standards.iteh.ai)

4.4 Identification of cabling elements

Unless otherwise specified, the colour coding for identification is given in IEC 60189-2. The colours shall meet the requirements of EN 50288-1, 4.4
SIST EN 50288-2-1:2013
<https://standards.iteh.ai/catalog/standards/sist/63274268-6323-4779-863e-e2744e016355/sist-en-50288-2-1-2013>

4.5 Screening of cabling elements

Where appropriate, screening of the cabling elements shall be applied in accordance with 4.5 of EN 50288-1. Coverage is defined in EN 50290-2-1.

4.6 Cable make-up

The cable elements shall be laid up in concentric layer(s) or units to form the cable core.

4.7 Filling compound

Not applicable.

4.8 Interstitial fillers

Where fillers are used they shall meet the requirements of EN 50288-1, 4.8

4.9 Screening of the cable core

The screening of the cable core shall be applied in accordance with EN 50288-1, 4.9. Coverage is defined in EN 50290-2-1.

4.10 Moisture barriers

Not applicable.

4.11 Wrapping layers

Where wrapping layers are used they shall be in accordance with 4.11 of EN 50288-1.

4.12 Sheath

The sheath shall be of a suitable material according to the relevant part of EN 50290-2.

5 Tests and requirements for completed cables

The following tables give the tests to be applied, together with the respective limits, in order to demonstrate compliance with this specification.

5.1 Electrical tests

5.1.1 Low-frequency and d.c. electrical measurements

Table 1 - Low-frequency and d.c. electrical measurements

EN 50288-1 sub-clause	Parameter	Requirement
5.1.1.1	Conductor loop resistance	$\leq 19,0 \Omega/100 \text{ m}$
5.1.1.2	Conductor resistance unbalance	$\leq 2,0 \%$
5.1.1.3	Dielectric strength conductor/conductor and conductor/screen	1,0 kV d.c. or 0,7 kV a.c. for 1 min or 2,5 kV d.c. or 1,7 kV a.c. for 2 s
5.1.1.4	Insulation resistance	$\geq 5\ 000 \text{ M}\Omega \text{ km}$ when tested in accordance with EN 50289-1-4 https://standards.iteb.ai/catalog/standards/sist/63274268_6323_4779
5.1.1.5	Mutual capacitance	No requirement specified
5.1.1.6	Capacitance unbalance to earth	$\leq 1\ 200 \text{ pF/km}$

5.1.2 High-frequency electrical and transmission requirements

Table 2 - High-frequency electrical and transmission requirements