



IEC 61851-23

Edition 2.0 2023-12

INTERNATIONAL STANDARD



**Electric vehicle conductive charging system –
Part 23: DC electric vehicle supply equipment**
(<https://standards.iteh.ai>)
Document Preview

[IEC 61851-23:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/f71abfa8-9df6-4da0-a228-317f1492a658/iec-61851-23-2023>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

Document Preview

[IEC 61851-23:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/f71abfa8-9df6-4da0-a228-317f1492a658/iec-61851-23-2023>



IEC 61851-23

Edition 2.0 2023-12

INTERNATIONAL STANDARD



**Electric vehicle conductive charging system –
Part 23: DC electric vehicle supply equipment**
(<https://standards.iteh.ai>)
Document Preview

[IEC 61851-23:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/f71abfa8-9df6-4da0-a228-317f1492a658/iec-61851-23-2023>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 43.120

ISBN 978-2-8322-7961-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	15
1 Scope	18
2 Normative references	19
3 Terms and definitions	22
3.1 Electric supply equipment	22
3.2 Insulation	22
3.3 Functions	26
3.4 Vehicle	30
3.5 Cords, cables and connection means	31
3.6 Service and usage	32
3.7 General terms	33
4 General requirements	40
5 Classification	40
5.101 Characteristics of EV supply equipment	40
5.101.1 Separation type	40
5.101.2 Control system	40
5.101.3 System	40
5.101.4 Thermal management system	40
5.101.5 Power distribution system	41
6 Charging modes and functions	41
6.2 Charging modes	41
6.2.1 Mode 1	41
6.2.2 Mode 2	41
6.2.3 Mode 3	41
6.3 Functions provided in Mode 4	41
6.3.1 Mandatory functions in Mode 4	41
6.3.2 Optional functions for Mode 4	62
7 Communications	63
7.1 Digital communication between the EV supply equipment and the EV	63
7.1.101 Basic communication interface	64
8 Protection against electric shock	64
8.101 General provisions	64
8.101.1 General	64
8.101.2 Intended use and reasonably foreseeable misuse	65
8.101.3 Limitation of touch current or touch voltage	65
8.101.4 Threshold of perception and startle reaction	65
8.102 Basic protection	68
8.102.1 General	68
8.102.2 Protection by means of basic insulation of live parts	68
8.102.3 Protection by means of enclosures or barriers	68
8.102.4 Protection by means of limitation of voltage	68
8.102.5 Protection by means of limitation of steady-state touch current	70
8.103 Fault protection	70
8.103.1 General	70
8.103.2 Protective-equipotential-bonding	70

8.103.3	Effective protective conductor continuity between the enclosure and the external protective circuit.....	70
8.103.4	Automatic disconnection of supply	71
8.103.5	Supplementary insulation.....	71
8.103.6	Electrically protective screening	71
8.104	Enhanced protective provision	71
8.104.1	General	71
8.104.2	Double or reinforced insulation	71
8.104.3	Protective separation between circuits.....	72
8.105	Requirements for separated EV supply equipment	72
8.105.1	General	72
8.105.2	Equipotential bonding on side B.....	74
8.105.3	Impedance to protective conductor on side B.....	74
8.105.4	Degrees of protection against access to hazardous-live-parts.....	75
8.105.5	Insulation barriers.....	76
8.105.6	Stored energy	77
8.105.7	Disconnection from vehicle	78
8.105.8	Protective (earthing) conductor from the supply network	78
8.105.9	Residual current protective devices	79
8.105.10	Safety requirements for auxiliary circuits between the EV supply equipment and the EV	79
8.105.11	Protective conductor dimension cross-sectional area	79
9	Conductive electrical interface requirements.....	80
9.1	General.....	80
9.5	Functional description of the DC interface.....	80
9.7	Wiring of the neutral conductor	80
9.101	Avoidance of breaking under load	80
10	Requirements for adaptors	81
11	Cable assembly requirements.....	82
11.1	General.....	82
11.6	Strain relief	82
11.6.101	Strain relief of the EV supply equipment's side B cable assembly	82
11.6.102	Test of the anchorage of the side B cable assembly	83
11.101	Cable breakaway	85
11.102	Surface temperature of the side B cable assembly	85
12	EV supply equipment constructional requirements and tests	87
12.1	General.....	87
12.2	Characteristics of mechanical switching devices	87
12.2.5	Relays	87
12.3	Clearances and creepage distances.....	87
12.4	IP degrees	87
12.4.1	Degrees of protection against solid foreign objects and water for the enclosures	87
12.5	Insulation resistance	88
12.6	Touch current	88
12.6.101	Touch current limit.....	88
12.6.102	Test.....	88
12.6.103	Protection measures for the test touch current more than 3,5 mA	89
12.7	Dielectric withstand voltage	90

12.7.2	Impulse dielectric withstand (1,2 µs/50 µs)	90
12.7.101	Suppression of transient overvoltage at side A (insulation coordination)	90
12.7.102	Protection against transient overvoltages of atmospheric origin or due to switching	92
12.8	Temperature rise	94
12.9	Damp heat functional test	94
12.10	Minimum temperature functional test.....	94
12.11	Mechanical strength.....	94
12.101	Side A current.....	95
12.102	Power supply cords.....	96
12.102.1	General	96
12.102.2	Cross-sectional area.....	96
12.102.3	Cord anchorages and strain relief for non-detachable power supply cords	97
12.103	Stress relief test.....	98
12.104	Abnormal operation and simulated fault condition tests.....	99
12.104.1	General	99
12.104.2	Pass criteria	99
12.104.3	Breakdown of components test	100
12.104.4	Loss of AC supply phase test	100
12.104.5	Inoperative blower/fan motor test.....	100
12.104.6	Clogged filter test	101
12.105	Protection against electrically caused fire	101
12.105.1	General	101
12.105.2	Fire enclosure	101
12.106	Protection against chemical hazards	101
12.106.1	Type of coolant.....	101
12.106.2	Flammability	102
12.106.3	Material compatibility	102
12.107	Enclosures.....	102
12.107.1	General	102
12.107.2	Strength of materials and parts.....	103
12.107.3	Enclosure integrity tests	103
12.108	Components bridging insulation	103
12.108.1	General	103
12.108.2	Capacitors	104
12.109	Isolating transformers	104
13	Overload and short-circuit protection	104
13.1	General.....	104
13.2	Overload protection of the cable assembly.....	104
13.3	Short-circuit protection of the charging cable	104
13.101	Short-circuit protection of the DC connection during energy transfer	105
14	Automatic reclosing of protective devices	106
15	Emergency switching or disconnect (optional)	106
16	Marking and instructions.....	106
16.1	Installation manual of EV charging stations.....	106
16.2	User manual for EV supply equipment	107
16.3	Marking of EV supply equipment.....	108
16.4	Marking of charging cable assemblies case B	108

101 Specific requirements for EV supply equipment	108
101.1 Specific requirements for separated EV supply equipment	108
101.1.1 Operating ranges for voltage, current, and power at side B	108
101.1.2 Voltage and current tolerance at side B	109
101.1.3 Control delay of present current at side B in CCM	111
101.1.4 Descending rate of present current at side B	114
101.1.5 Periodic and random deviation (current ripple at side B during CCM).....	114
101.1.6 Periodic and random deviation (voltage ripple at side B during CVM)	115
101.1.7 Load dump	117
101.1.8 Side B inductance.....	117
101.2 Specific requirement for energy transfer with a thermal management system or thermal sensing only	118
101.2.1 General	118
101.2.2 Temperature limits and self-diagnostics	118
101.2.3 Temperature monitoring.....	119
101.2.4 Tests for thermal management system performance of the EV supply equipment	120
101.3 Specific requirements for temperature-controlled energy transfer.....	129
102 Test methods.....	130
102.1 Technical data	130
102.2 General test conditions	130
102.2.1 Ambient test conditions.....	130
102.2.2 Measuring instruments	131
102.2.3 Test setups.....	131
102.2.4 Test load	134
102.2.5 Operating points for tests	136
Annexes	138
Annex AA (normative) EV supply equipment of system A.....	139
AA.1 General.....	139
AA.2 Circuit diagram	139
AA.3 Specific safety requirements	142
AA.3.1 Fault protection in side B	142
AA.3.2 De-energization of the power supply to the EV	146
AA.3.3 Voltage measurement of side B live parts (DC+/DC-) for vehicle connector unlatch	147
AA.3.4 Overcurrent protection of side B	147
AA.3.5 Short-circuit protection of side B	147
AA.3.6 Latch monitoring for the vehicle connector.....	148
AA.3.7 Protection of the EV disconnection device	149
AA.3.8 Fault conditions and criteria for transfer to error and emergency shutdown	149
AA.3.9 Inrush current limitation by the EV supply equipment.....	154
AA.3.10 Regulation of the present current at side B in CCM.....	155
AA.3.11 Periodic and random deviation (current ripple at side B during CCM).....	156
AA.3.12 Overvoltage protection including load dump.....	157
AA.3.13 Power supply to the EV for the actuation of EV disconnection device	158
AA.3.14 Impedance of the side B circuit.....	158
AA.3.15 Assistance of welding detection	158
AA.3.16 Specific requirements for temperature-controlled energy transfer	159

AA.4 FPT process and communication between the EV supply equipment and the EV for energy transfer control	159
AA.4.1 Forward power transfer states	159
AA.4.2 Communication measures.....	161
AA.4.3 Forward power transfer control process	162
AA.4.4 Measuring current and voltage at side B	168
AA.5 Response to an EV command on charge current.....	170
AA.6 Bidirectional power transfer (optional).....	172
AA.6.1 General	172
AA.6.2 Circuit diagram	172
AA.6.3 Functional requirements	174
AA.6.4 Bidirectional power transfer control process.....	176
AA.7 Optional functions	181
AA.7.1 General	181
AA.7.2 Compatibility check.....	181
AA.7.3 Dynamic control.....	181
AA.7.4 High-current control.....	182
AA.7.5 High-voltage control.....	182
AA.8 Compliance test for user-initiated shutdown	182
AA.9 Specific requirement for energy transfer with thermal management system.....	183
Annex BB (normative) EV supply equipment of system B	184
BB.1 General.....	184
BB.2 Circuit diagrams.....	184
BB.2.1 Circuit diagram	184
BB.2.2 Requirements of IMD and discharge circuit.....	186
BB.3 Parameters of control pilot circuit.....	186
BB.4 Forward power transfer control process under normal condition	187
BB.4.1 Side B regulation	187
BB.4.2 Measuring current and voltage.....	187
BB.4.3 Vehicle coupler mating confirmation	189
BB.4.4 Forward power transfer control sequence	189
BB.4.5 Normal shutdown.....	191
BB.5 Safety requirements under failure mode.....	191
BB.5.1 Error shutdown and emergency shutdown.....	191
BB.5.2 Terminate energy transfer due to an EV supply equipment fault.....	193
BB.5.3 Terminate energy transfer due to an EV fault.....	194
BB.5.4 Digital communication timeout	194
BB.5.5 Loss of electrical continuity of the control pilot.....	195
BB.5.6 Overvoltage fault	195
BB.5.7 Load dump	196
BB.5.8 Short-circuit protection of side B	197
BB.5.9 Lock and latch monitoring for vehicle connector.....	198
BB.5.10 Overcurrent protection of side B	198
BB.5.11 Insulation fault monitoring.....	198
BB.6 Timing sequence diagram of forward power transfer	199
BB.7 Side B current regulation in CCM	200
BB.8 Insulation resistance check before energy transfer.....	202
BB.9 Side B voltage regulation in CVM.....	204
BB.10 Periodic and random deviation (voltage ripple at side B in CVM).....	206

BB.11 Energy transfer control mode	206
BB.11.1 Definition	206
BB.11.2 Typical forward power transfer process	207
BB.12 Standby mode.....	208
BB.13 Smart charging	209
BB.14 Minimum cross-sectional area of the protective conductor	209
Annex CC (normative) EV supply equipment of system C	210
CC.1 General.....	210
CC.2 Circuit diagrams.....	210
CC.2.1 General	210
CC.2.2 Circuit diagram for configuration EE	210
CC.2.3 Circuit diagram for configuration FF.....	213
CC.2.4 Disabled side B	216
CC.3 Process of energy transfer	217
CC.3.1 General	217
CC.3.2 Normal startup.....	219
CC.3.3 Normal shutdown or pause after energy transfer.....	225
CC.3.4 Error and emergency handling.....	229
CC.3.5 Pause by EV supply equipment using ISO 15118-2:2014	241
CC.3.6 Renegotiation initiated by EV or EV supply equipment using ISO 15118-2:2014	251
CC.4 Safety related functions	255
CC.4.1 Safety measures for side B	255
CC.4.2 Vehicle coupler latching function	259
CC.4.3 Loss of electrical continuity of the control pilot conductor	259
CC.4.4 Loss of electrical continuity of the proximity detection conductor	259
CC.4.5 Voltage check at initialization	259
CC.4.6 Minimum cross-sectional area of the protective conductor	259
CC.4.7 Loss of electrical continuity of the protective conductor	259
CC.5 Additional functions.....	260
CC.5.1 Pre-charge	260
CC.5.2 Sleep mode and communication session restart methods	262
CC.5.3 Configuration EE vehicle connector latch position switch (S_{S3}) activation	269
CC.5.4 Configuration EE vehicle connector latch position switch (S_{S3}) verification.....	269
CC.5.5 Handling of operating ranges	270
CC.5.6 Compatibility check.....	277
CC.5.7 Considerations for CCM, CVM and CPM (informative)	281
CC.6 Specific requirements	283
CC.6.1 Requirements for load dump	283
CC.6.2 Side B current regulation	283
CC.6.3 Measuring current and voltage at side B	283
CC.6.4 Overcurrent protection of side B	284
CC.7 General test conditions	284
CC.7.1 Operating points – Definitions	284
CC.7.2 Standard test setup	286
CC.7.3 Definition of measured values at side B	286
CC.7.4 Exemplary approach to set a test point in CCM.....	286

CC.7.5 Test cases	289
CC.7.6 Wake up of EV supply equipment by EV	293
Annex DD (informative) Bidirectional power transfer control	354
DD.1 General.....	354
DD.2 Forward power transfer (FPT) and reverse power transfer (RPT)	354
Annex EE (normative) Test load impedance verification.....	355
EE.1 General.....	355
EE.2 Response curve verification	355
EE.3 Test setup for test load verification (informative).....	358
EE.4 Result	359
Annex FF (normative) Multi-side B separated EV supply equipment.....	360
FF.1 General.....	360
FF.2 Classification and use case of multi-side B EV supply equipment.....	360
FF.2.1 System operation.....	360
FF.2.2 Side B system	360
FF.2.3 Configuration.....	360
FF.3 Constructional requirements of a side B system	363
FF.3.1 Constructional requirements of a side B system according to Annex AA	363
FF.3.2 Constructional requirements of a side B system according to Annex BB	364
FF.3.3 Constructional requirements of a side B system according to Annex CC	364
FF.4 Side B system performance	364
FF.4.1 General performance requirements.....	364
FF.4.2 Performance of multi-side B EV supply equipment providing simultaneous operation.....	364
FF.5 Safety requirements	364
FF.5.1 General safety requirements.....	364
FF.5.2 Short-circuit protection	365
FF.5.3 Overload protection	365
FF.5.4 Access to live parts through an unmated vehicle connector during energy transfer	365
FF.5.5 Additional safety requirements for multi-side B EV supply equipment providing simultaneous operation	366
FF.5.6 Diagnostic check of mechanical disconnection device in the side B system.....	366
FF.5.7 Interconnected side B live parts (DC+/DC-) in multi-side B EV supply equipment	366
Annex GG (informative) Communication and energy transfer process between the EV supply equipment and the EV	367
GG.1 General.....	367
GG.2 System configuration	367
GG.3 Energy transfer control process and state	367
GG.3.1 General	367
GG.3.2 Description of the initialization stage	368
GG.3.3 Description of the energy transfer stage	368
GG.3.4 Description of the shutdown stage	369
Annex HH (informative) Touch current and touch impulse current.....	370
HH.1 General.....	370
HH.2 Current through the human body.....	375
HH.3 Conditional dependent thresholds	376

HH.4 Hazards due to leakage between side B live parts and the protective conductor.....	376
HH.5 Balanced versus unbalanced voltages at side B live parts (DC+/DC-)	377
HH.6 Insulation monitoring device.....	378
HH.7 IMD reaction time.....	379
HH.8 Conclusion.....	379
Bibliography.....	380
 Figure 101 – Example of a coupling session	27
Figure 102 – Voltage V_{T8} to apply to simulate short period overvoltage at side B between DC+ and DC-	52
Figure 103 – Typical voltages between side B live parts (DC+/DC-) and protective conductor under normal operation.....	55
Figure 104 – IMD connection which results in a voltage more than the maximum voltage limits	56
Figure 105 – Examples of a fault between the secondary circuit and the protective conductor.....	59
Figure 106 – Measurement of the touch leakage current.....	67
Figure 107 – Touch time – DC voltage under single fault condition (water wet, fingertip to feet).....	69
Figure 108 – Insulation barriers	76
Figure 109 – Construction types of vehicle adapters	81
Figure 110 – Apparatus to test the side B cable assembly anchorage	83
Figure 111 – Test setup the side B cable assembly anchorage	84
Figure 112 – Example of a side B cable assembly equipped with handle and a warning label attached to the cable	86
Figure 113 – Example setup of SPD for the protection of the EV supply equipment against transients	91
Figure 114 – Example of an SPD-assembly having one voltage switching type SPD between side B live conductors (DC+/DC-) and protective conductor	93
Figure 115 – Symbol ISO 7000-0434B:2004-01	107
Figure 116 – Side B voltage tolerances in CVM	110
Figure 117 – Current control delay for an increasing current request	112
Figure 118 – Current control delay for a decreasing current control request.....	113
Figure 119 – Voltage at side B in CVM operation in steady state with ripple	116
Figure 120 – Setup to measure the maximum side B inductance.....	117
Figure 121 – Reference device (RD) A_0	121
Figure 122 – Test arrangement A_0.....	122
Figure 123 – Reference device RD A_1	122
Figure 124 – Test arrangement A_1.....	123
Figure 125 – Reference device RD C_0	124
Figure 126 – Test arrangement C_0.....	125
Figure 127 – Reference device RD C_1	125
Figure 128 – Test arrangement C_1.....	126
Figure 129 – General test setup for system A	132
Figure 130 – General test setup for system B	133

Figure 131 – General test setup for system C	134
Figure 132 – Test load example	135
Figure 133 – Operating points	137
Figure AA.1 – Overall circuit diagram of system A EV supply equipment and EV	140
Figure AA.2 – Failure detection principle by detection of DC leakage current	144
Figure AA.3 – Example of vehicle connector latch monitoring circuit	148
Figure AA.4 – Example of vehicle inlet with the latch holder covered by a metal plate that inhibits latch holding	149
Figure AA.5 – Flow diagram for forward power transfer	162
Figure AA.6 – Sequence diagram for forward power transfer	163
Figure AA.7 – Representation of the delay between the measurement and the digital communication transmission for system A	169
Figure AA.8 – Acceptable range of the measured current at side B (target current of the EV $I_{EV_trg} = 50$ A)	170
Figure AA.9 – Change in the target current requested by the EV	171
Figure AA.10 – Side B performance of EV supply equipment	172
Figure AA.11 – Circuit diagram of a system A BPT EV supply equipment and EV	173
Figure AA.12 – Flow diagram for bidirectional power transfer	179
Figure AA.13 – Sequence diagram for bidirectional power transfer	180
Figure AA.14 – Transition of applicable maximum current of the EV supply equipment at side B and target current of the EV during dynamic control	181
Figure BB.1 – System B EV supply equipment circuit diagram	185
Figure BB.2 – Representation of delay between the measures current and voltage at side B and the digital communication transmission for system B	187
Figure BB.3 – FPT control sequence for system B	190
Figure BB.4 – Timing sequence diagram of FPT	200
Figure BB.5 – Operating points and test points for side B current regulation in CCM	201
Figure BB.6 – Operating points and test points for side B voltage regulation in CVM	206
Figure BB.7 – Definition of CCM, CVM and CPM	207
Figure BB.8 – Typical FTP process	208
Figure CC.1 – Circuit diagram for a system C EV supply equipment of configuration EE	211
Figure CC.2 – Circuit diagram of a system C EV supply equipment of configuration FF	214
Figure CC.3 – Equivalent disabled side B of the EV supply equipment	216
Figure CC.4 – Example of a sequence diagram	219
Figure CC.5 – Sequence diagram for normal startup	220
Figure CC.6 – Sequence diagram for normal shutdown or pause after energy transfer by EV or EV supply equipment	226
Figure CC.7 – Sequence diagram for EV supply equipment and EV initiated error shutdown	230
Figure CC.8 – Sequence diagram for EV initiated error shutdown based on DIN SPEC 70121 during energy transfer	233
Figure CC.9 – Sequence diagram for an emergency shutdown executed by the EV	236
Figure CC.10 – Sequence diagram for an emergency shutdown executed by the EV supply equipment	239
Figure CC.11 – Sequence diagram for pause before cable-check phase by EV supply equipment using ISO 15118-2:2014	242

Figure CC.12 – Sequence diagram for pause after pre-charge phase and before energy transfer stage by the EV supply equipment using ISO 15118-2:2014	246
Figure CC.13 – Sequence diagram for renegotiation initiated by EV or EV supply equipment using ISO 15118-2:2014	252
Figure CC.14 – Worst case equivalent circuit during pre-charge	260
Figure CC.15 – Restart methods sequence for the EV supply equipment	263
Figure CC.16 – Restart method verification on the EV supply equipment	264
Figure CC.17 – Example of a B1 – B2 transition	265
Figure CC.18 – Example of a B1 – E – B1 – B2 transition	266
Figure CC.19 – Example of a B1 – F – B1 – B2 transition	266
Figure CC.20 – Restart methods sequence for the EV	268
Figure CC.21 – Example of a B – C – B toggle.....	269
Figure CC.22 – Operating points.....	285
Figure CC.23 – Approaching a single test point TP in CCM (example 1)	288
Figure CC.24 – Approaching multiple test points TP_n CCM (example 2).....	289
Figure CC.25 – Test points TP_n	298
Figure CC.26 – Voltage at the vehicle connector.....	306
Figure CC.27 – Test points TP_n for the load dump test	309
Figure CC.28 – Test point matrix for side B current regulation in CCM including static deviation and ripple	314
Figure CC.29 – Test point sequence for side B current regulation in CCM	317
Figure CC.30 – Test point matrix for 0 A mode during energy transfer	318
Figure CC.31 – Test point matrix for side B voltage regulation in CVM during pre-charge	321
Figure CC.32 – Test point matrix for control delay of charging current in CCM.....	327
Figure CC.33 – Test point sequence	329
Figure CC.34 – Test points for voltage measurement during welding detection	344
Figure CC.35 – Test setup for IMD measurement connections	351
Figure EE.1 – Magnitude of the impedance of the test load between DC+ and DC– for system A and system B	356
Figure EE.2 – Magnitude of the impedance of the test load between DC+ and DC– for system A for current ripple measurements	357
Figure EE.3 – Magnitude of the impedance of the test load between DC+ and DC– for system C	357
Figure EE.4 – Test setup for test load verification	358
Figure FF.1 – Example of a multi-side B EV supply equipment with a single PEC	362
Figure FF.2 – Example of a multi-side B EV supply equipment with multiple PECs.....	363
Figure HH.1 – EV and EV supply equipment equivalent circuit	370
Figure HH.2 – Circuit diagram simplification of the circuit in Figure HH.1	373
Figure HH.3 –Thevenin equivalent circuit diagram of the circuit in Figure HH.1.....	373
Figure HH.4 – Leakage current and impulse current in relation to limits in IEC 60479 series	374
Figure HH.5 – Examples of circuits with equivalent impulse current and leakage current through a human body	375

Table 101 – Verification criterion	43
Table 102 – Data/message for the compatibility check test	47
Table 103 – Voltage threshold for emergency shutdown reaction for system B and system C	49
Table 104 – EV supply equipment reaction depending on the present voltage at side B condition	49
Table 105 – Compliance tests for protection against overvoltage at side B between DC+ and DC–	50
Table 106 – Test load setup for protection against overvoltage test	50
Table 107 – Data/messages for protection against overvoltage test	51
Table 108 – Overvoltage condition and verification criterion.....	51
Table 109 – Control circuit supply integrity test.....	52
Table 110 – Touch voltage under normal operation.....	69
Table 111 – Touch voltage under single fault conditions	69
Table 112 – Safety provisions for protection against electric shock for EV supply equipment at side B	72
Table 113 – Minimum protective measures	77
Table 114 – Pull force and torque test values for side B cable assembly anchorage	85
Table 115 – Touch current limits	88
Table 116 – Sizes of conductors of power supply cord	96
Table 117 – Cord strain relief pull force	98
Table 118 – Current ripple limit of the EV supply equipment	115
Table 119 – Test parameter values	126
Table 120 – Recommended circuit parameters of the test load	136
Table AA.1 – Definition of symbols of the overall circuit diagram of a system A EV supply equipment.....	141
Table AA.2 – Parameters and values of the circuit diagram for a system A EV supply equipment.....	142
Table AA.3 – Principle of fault protection	143
Table AA.4 – Requirements for earth leakage current fault monitoring	145
Table AA.5 – Error shutdown times and criteria	150
Table AA.6 – Action and message parameter for error shutdown triggered by the EV supply equipment.....	152
Table AA.7 – Action and message parameter for error shutdown triggered by the EV	152
Table AA.8 – Emergency shutdown times and criteria	153
Table AA.9 – Actions and criteria for emergency shutdown	154
Table AA.10 – System A setup of the test load for regulation of the present current at side B in CCM.....	155
Table AA.11 – System A recommended steps for regulation of the present current at side B in CCM.....	155
Table AA.12 – Specification of measuring instrument.....	157
Table AA.13 – Voltage threshold for emergency shutdown	157
Table AA.14 – Maximum boost current for system A EV supply equipment.....	159
Table AA.15 – FPT states of the FPT EV supply equipment	160
Table AA.16 – FPT control process and states of the FPT EV supply equipment.....	161
Table AA.17 – Test scenarios	165