



SLOVENSKI STANDARD

SIST EN 62439-3:2012

01-november-2012

Nadomešča:

SIST EN 62439-3:2010

Industrijska komunikacijska omrežja za avtomatizacijo z visoko razpoložljivostjo - 3. del: Protokol vzporedne redundance (RPR) in brezprehodna zanka z visoko razpoložljivostjo (IEC 62439-3:2012)

Industrial communication networks - High availability automation networks - Part 3: Parallel Redundancy Protocol (PRP) and High availability Seamless Redundancy (HSR) (IEC 62439-3:2012)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Industrielle Kommunikationsnetze: Hochverfügbare Automatisierungsnetze - Teil 3: Parallelredundanz-Protokoll (PRP) und nahtloser Hochverfügbarkeits-Ring (HSR) (IEC 62439-3:2012)

<https://standards.iteh.ai/catalog/standards/sist/402d6a7e-d3b6-4e29-a3f6-df063641b86e/sist-en-62439-3-2012>

Réseaux de communication industrielle - Réseaux d'automatisme à haute disponibilité - Partie 3 : Protocole de redondance parallèle (PRP) et redondance transparente de haute disponibilité (HSR) (CEI 62439-3:2012)

Ta slovenski standard je istoveten z: EN 62439-3:2012

ICS:

25.040.01	Sistemi za avtomatizacijo v industriji na splošno	Industrial automation systems in general
35.110	Omreževanje	Networking

SIST EN 62439-3:2012

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62439-3:2012

<https://standards.iteh.ai/catalog/standards/sist/402d6a7e-d3b6-4e29-a3f6-df063641b86e/sist-en-62439-3-2012>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62439-3

September 2012

ICS 25.040; 35.040

Supersedes EN 62439-3:2010

English version

**Industrial communication networks -
High availability automation networks -
Part 3: Parallel Redundancy Protocol (PRP) and High-availability
Seamless Redundancy (HSR)
(IEC 62439-3:2012)**

Réseaux industriels de communication -
Réseaux d'automatisme à haute
disponibilité -
Partie 3 : Protocole de redondance
parallèle (PRP) et redondance
transparente de haute disponibilité (HSR)
(CEI 62439-3:2012)

Industrielle Kommunikationsnetze -
Hochverfügbare Automatisierungsnetze -
Teil 3: Parallelredundanz-Protokoll (PRP)
und nahtloser Hochverfügbarkeits-Ring
(HSR)
(IEC 62439-3:2012)

ITEH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62439-3:2012

<https://standards.iteh.ai/catalog/standards/sist/402d6a7e-d3b6-4e29-a3f6-df063641b86e/sist-en-62439-3-2012>

This European Standard was approved by CENELEC on 2012-08-09. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/687/FDIS, future edition 2 of IEC 62439-3, prepared by SC 65C, "Industrial networks", of IEC TC 65, "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62439-3:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-05-09
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-08-09

This document supersedes EN 62439-3:2010.

EN 62439-3:2012 includes the following significant technical changes with respect to EN 62439-3:2010:

- specification of the interconnection of PRP and HSR networks;
- introduction of a suffix for PRP frames;
- clarification and modification of specifications to ensure interoperability;
- slackening of the specifications to allow different implementations;
- consideration of clock synchronization according to IEC 61588;
- introduction of test modes to simplify testing and maintenance.

This standard is to be used in conjunction with EN 62439-1:2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62439-3:2012 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC 61580 series NOTE Harmonized in EN 61580 series (not modified).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-191	-	International Electrotechnical Vocabulary (IEV) - Chapter 191: Dependability and quality of service	-	-
IEC 61588	-	Precision clock synchronization protocol for networked measurement and control systems	-	-
IEC 62439-1	-	Industrial communication networks - High availability automation networks - Part 1: General concepts and calculation methods	EN 62439-1	-
IEC 62439-2	-	Industrial communication networks - High availability automation networks - Part 2: Media Redundancy Protocol (MRP)	EN 62439-2	-
IEC 62439-6	-	Industrial communication networks - High availability automation networks - Part 6: Distributed Redundancy Protocol (DRP)	EN 62439-6	-
IEC 62439-7	-	Industrial communication networks - High availability automation networks - Part 7: Ring-based Redundancy Protocol (RRP)	EN 62439-7	-
ISO/IEC 8802-3	2000	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-
IEEE 802.1D	2004	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	2011	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62439-3:2012

<https://standards.iteh.ai/catalog/standards/sist/402d6a7e-d3b6-4e29-a3f6-df063641b86e/sist-en-62439-3-2012>



IEC 62439-3

Edition 2.0 2012-07

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Industrial communication networks – High availability automation networks –
Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless
Redundancy (HSR)**

**Réseaux industriels de communication – Réseaux d'automatisme à haute
disponibilité –
Partie 3: Protocole de redondance parallèle (PRP) et redondance transparente de
haute disponibilité (HSR)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE **XC**
CODE PRIX

ICS 25.040; 35.040

ISBN 978-2-83220-160-2

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
0 INTRODUCTION	7
0.1 General.....	7
0.2 Changes with respect to the previous edition.....	7
0.3 Patent declaration	8
1 Scope.....	9
2 Normative references	9
3 Terms, definitions, abbreviations, acronyms, and conventions.....	10
3.1 Terms and definitions	10
3.2 Abbreviations and acronyms.....	10
3.3 Conventions	10
4 Parallel Redundancy Protocol (PRP)	10
4.1 PRP principle of operation.....	10
4.1.1 PRP network topology	10
4.1.2 PRP LANs with linear or bus topology	11
4.1.3 PRP LANs with ring topology.....	12
4.1.4 DANP node structure.....	12
4.1.5 PRP attachment of singly attached nodes	13
4.1.6 Compatibility between singly and doubly attached nodes.....	14
4.1.7 Network management.....	14
4.1.8 Implication on configuration.....	14
4.1.9 Transition to non-redundant networks.....	14
4.1.10 Duplicate handling.....	15
4.1.11 Network supervision	19
4.1.12 Redundancy management interface.....	19
4.2 PRP protocol specifications.....	19
4.2.1 Installation, configuration and repair guidelines	19
4.2.2 MAC addresses	20
4.2.3 Multicast MAC addresses	20
4.2.4 IP addresses	20
4.2.5 Nodes.....	20
4.2.6 Duplicate Accept mode (testing only).....	21
4.2.7 Duplicate Discard mode.....	21
4.3 PRP_Supervision frame	24
4.3.1 Supervision frame for DANP	24
4.3.2 PRP_Supervision frame contents	27
4.3.3 PRP_Supervision frame for RedBox	27
4.3.4 Reception of a PRP_Supervision frame and NodesTable.....	27
4.4 Bridging node.....	28
4.5 Constants.....	28
4.6 PRP service specification	28
5 High-availability Seamless Redundancy (HSR).....	28
5.1 HSR objectives.....	28
5.2 HSR principle of operation.....	29
5.2.1 Basic operation with a ring topology	29
5.2.2 DANH node structure.....	30

5.2.3	Topology	31
5.2.4	RedBox structure	39
5.3	HSR node specifications	41
5.3.1	HSR operation	41
5.3.2	DANH receiving from its link layer interface	41
5.3.3	DANH receiving from an HSR port	42
5.3.4	DANH forwarding rules	43
5.3.5	CoS	43
5.3.6	Clock synchronization	43
5.3.7	Deterministic medium access	44
5.4	HSR RedBox specifications	44
5.4.1	RedBox properties	44
5.4.2	RedBox receiving from interlink	44
5.4.3	RedBox forwarding on the ring	46
5.4.4	RedBox receiving from an HSR port	46
5.4.5	RedBox receiving from its link layer interface	47
5.4.6	Redbox ProxyNodeTable handling	47
5.4.7	RedBox CoS	48
5.4.8	RedBox clock synchronization	48
5.4.9	RedBox medium access	48
5.5	QuadBox specification	48
5.6	Duplicate Discard method	48
5.7	Frame format for HSR	48
5.7.1	Frame format for all frames	48
5.7.2	HSR Supervision frame	50
5.8	Constants	52
5.9	HSR service specification	53
6	Protocol Implementation Conformance Statement (PICS)	54
7	PRP/HSR Management Information Base (MIB)	55
	Annex A (normative) Use of IEC 61588 and IEEE C37.238 for IEC 62439-3	69
	Annex B (informative) Deterministic medium access in HSR	83
	Bibliography	84
	Figure 1 – PRP example of general redundant network	11
	Figure 2 – PRP example of redundant network as two LANs (bus topology)	12
	Figure 3 – PRP example of redundant ring with SANs and DANPs	12
	Figure 4 – PRP with two DANPs communicating	13
	Figure 5 – PRP RedBox, transition from single to double LAN	15
	Figure 6 – PRP frame extended by an RCT	16
	Figure 7 – PRP VLAN-tagged frame extended by an RCT	17
	Figure 8 – PRP padded frame closed by an RCT	17
	Figure 9 – Duplicate Discard algorithm boundaries	18
	Figure 10 – HSR example of ring configuration for multicast traffic	29
	Figure 11 – HSR example of ring configuration for unicast traffic	30
	Figure 12 – HSR structure of a DANH	31
	Figure 13 – HSR example of topology using two independent networks	32

Figure 14 – HSR example of peer coupling of two rings	33
Figure 15 – HSR example of connected rings	34
Figure 16 – HSR example of coupling two redundant PRP LANs to a ring	35
Figure 17 – HSR example of coupling from a ring node to redundant PRP LANs	36
Figure 18 – HSR example of coupling from a ring to two PRP LANs	37
Figure 19 – HSR example of coupling three rings to one PRP LAN	38
Figure 20 – HSR example of meshed topology	39
Figure 21 – HSR structure of a RedBox	40
Figure 22 – HSR frame without a VLAN tag	49
Figure 23 – HSR frame with VLAN tag	49
Figure 24 – HSR node with management counters	53
Figure 25 – HSR RedBox with management counters	54
Figure A.1 – PTP one-step clock synchronization and delay measurement	71
Figure A.2 – PTP two-step clock synchronization and delay measurement	72
Figure A.3 – Two-step and one-step transparent clocks translator	73
Figure A.4 – Two-step to one-step translation	73
Figure A.5 – Connection of a Grandmaster Clock to an Ordinary Clock over PRP	74
Figure A.6 – HSR with one GMC	76
Figure A.7 – PTP messages sent and received by an HSR node (one-step)	77
Figure A.8 – PTP messages sent and received by an HSR node (two-step)	78
Figure A.9 – Attachment of a GMC to an HSR ring through a RedBox	80
Figure A.10 – PRP to HSR coupling by Transparent Clocks	81
Figure A.11 – PRP to HSR coupling by BCs	82
Table 1 – NodesTable attributes	22
Table 2 – PRP_Supervision frame with no VLAN tag	25
Table 3 – PRP_Supervision frame with (optional) VLAN tag	26
Table 4 – PRP constants	28
Table 5 – HSR_Supervision frame with no VLAN tag	50
Table 6 – HSR_Supervision frame with optional VLAN tag	51
Table 7 – HSR Constants	52

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
HIGH AVAILABILITY AUTOMATION NETWORKS –**
**Part 3: Parallel Redundancy Protocol (PRP) and
High-availability Seamless Redundancy (HSR)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62439-3 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2010. This edition constitutes a technical revision. The main changes with respect to the previous edition are listed below:

- specification of the interconnection of PRP and HSR networks;
- introduction of a suffix for PRP frames;
- clarification and modification of specifications to ensure interoperability;
- slackening of the specifications to allow different implementations;
- consideration of clock synchronization according to IEC 61588;
- introduction of test modes to simplify testing and maintenance.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/687/FDIS	65C/705/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This International Standard is to be read in conjunction with IEC 62439-1:2011.

A list of the IEC 62439 series can be found, under the general title *Industrial communication networks – High availability automation networks*, on the IEC website.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 62439-3:2012](#)

<https://standards.iteh.ai/catalog/standards/sist/402d6a7e-d3b6-4e29-a3f6-df063641b86e/sist-en-62439-3-2012>

0 INTRODUCTION

0.1 General

IEC 62439-3 standard belongs to IEC 62439 series, *Industrial communication networks – High availability automation networks*, specifying the HSR and PRP redundancy protocols, and was adopted by TC57 WG10 as the redundancy method for demanding substation automation networks based on IEC 61850 series, introducing new requirements.

0.2 Changes with respect to the previous edition

The major changes with respect to IEC 62439-3:2010 are listed below.

Aligning the sequence number between PRP and HSR, to enable coupling of HSR and PRP networks and simplify the implementation of dual-mode nodes in hardware. At the same time, introduce a suffix in the PRP Redundancy Control Trailer to allow better identification, future extensions and coexistence with other protocols that also happen to use a trailer. This change is not backwards-compatible, so means are provided to identify the version and ensure that the networks are homogeneous.

Removing all implementation restrictions on the Duplicate Discard algorithm (especially references to the drop window algorithm and references to connection orientation) since other methods such as hash tables can be used.

Removing the purging of the duplicate table. Replace this specific method by requiring that any Duplicate Discard algorithm provides a mechanism to remove old entries, thus ensuring that a node can properly reboot.

Making node tables optional for simple nodes to simplify hardware implementation.

Suppression of explicit mention of the HSR-PRP mode (PRP with HSR Tags), but allow it through the Mode N (no forwarding).

Introducing Mode T (forward through) to allow maintenance laptops to configure an open ring when attached to one end and Mode M (mixed) to allow forwarding of non-HSR-tagged frames in a closed ring.

Recommending the position of connectors, rather than impose it.

Defining the behaviour of an HSR node when non-HSR frames are encountered without requiring the recording of the source addresses and specify how IEEE 802.1D:2004, Table 7-10 frames are treated.

Prefixing the supervision frames on HSR by an HSR tag to simplify the hardware implementation and introduce a unique EtherType for HSR to simplify processing.

Changing the rule for the RedBox to allow more than one PRP network to be connected to an HSR ring, and introduce an identifier per RedBox pair.

Specifying tagging of IEC 61588 frames to follow IEEE C37.238 recommendations (informal).

Suppressing MAC address substitution.

Adapting the MIB to above changes.

0.3 Patent declaration

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning Filtering of redundant frames in a network node given in 5.2.3.3.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

Siemens Aktiengesellschaft
80333 München, Germany

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning Reception of redundant and non-redundant frames (ABB Schweiz AG – WO 2006/053459 A1, EP 1825657, US 20070223533, CN 101057483) given in 4.2.7, concerning Identifying improper cabling of devices (ABB Schweiz AG – EP 2 015 501 A1) given in 4.3, concerning Critical device with increased availability (ABB Schweiz AG – EP 2 090 950 A1) given in 4.4, concerning Ring coupling nodes for high availability networks (ABB Schweiz AG – WO 2010/010120 A1) given in 5.2.3.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

ABB Schweiz AG
Brown Boveri Strasse 6
5400 Baden, Switzerland

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (<http://patents.iec.ch>) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –

Part 3: Parallel Redundancy Protocol (PRP) and High-availability Seamless Redundancy (HSR)

1 Scope

The IEC 62439 series is applicable to high-availability automation networks based on the ISO/IEC 8802-3 (Ethernet) technology.

This part of the IEC 62439 series specifies two redundancy protocols designed to provide seamless recovery in case of single failure of an inter-bridge link or bridge in the network, which are based on the same scheme: duplication of the LAN, resp. duplication of the transmitted information.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-191, *International Electrotechnical Vocabulary – Chapter 191 : Dependability and quality of service* <https://standards.iteh.ai/catalog/standards/sist/402d6a7e-d3b6-4e29-a3f6-df063641b86e/sist-en-62439-3-2012>

IEC 61588, *Precision clock synchronization protocol for networked measurement and control systems*

IEC 62439-1, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*

IEC 62439-2, *Industrial communication networks – High availability automation networks – Part 2: Media Redundancy Protocol (MRP)*

IEC 62439-6, *Industrial communication networks – High availability automation networks – Part 6: Distributed Redundancy Protocol (DRP)*

IEC 62439-7, *Industrial communication networks – High availability automation networks – Part 7: Ring-based Redundancy Protocol (RRP)*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

IEEE 802.1D:2004, *IEEE Standard for Local and Metropolitan Area Networks – Media Access Control (MAC) Bridges*

IEEE 802.1Q:2011, *IEEE Standard for Local and Metropolitan Area Networks – Media Access Control (MAC) Bridges and Virtual Bridge Local Area Network*