

**SLOVENSKI STANDARD
SIST EN ISO 13503-2:2007****01-januar-2007**

Industrija za predelavo nafte in zemeljskega plina - Tekočine in materiali za zaključna dela - 2. del: Merjenje lastnosti podpornih materialov, ki se uporabljajo v postopkih frakcioniranja in pri filtrskih zasipih s prodom (ISO 13503-2:2006)

Petroleum and natural gas industries - Completion fluids and materials - Part 2:
Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations (ISO 13503-2:2006)

iTeh STANDARD PREVIEW

Erdöl- und Erdgasindustrie - Komplettierungsflüssigkeiten und -materialien - Teil 2:
Messung der Eigenschaften von Stützmaterialien zum Einsatz bei hydraulischen Fraktionierungs- und in Kiespackungsvorgängen (ISO 13503-2:2006)

[SIST EN ISO 13503-2:2007](#)

<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950->

Industries du pétrole et du gaz naturel - Fluides de complétiion et matériaux - Partie 2:
Mesurage des propriétés des matériaux de soutenement utilisés dans les opérations de fracturation hydraulique et de remplissage de gravier (ISO 13503-2:2006)

Ta slovenski standard je istoveten z: EN ISO 13503-2:2006

ICS:

75.180.30	Oprema za merjenje prostornine in merjenje	Volumetric equipment and measurements
-----------	--	---------------------------------------

SIST EN ISO 13503-2:2007**en,fr**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN ISO 13503-2:2007](#)

<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-ac9f28c4f4fa/sist-en-iso-13503-2-2007>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN ISO 13503-2

November 2006

ICS 75.100

English Version

Petroleum and natural gas industries - Completion fluids and materials - Part 2: Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations (ISO 13503-2:2006)

Industries du pétrole et du gaz naturel - Fluides de complétiion et matériaux - Partie 2: Mesurage des propriétés des matériaux de soutènement utilisés dans les opérations de fracturation hydraulique et de remplissage de gravier (ISO 13503-2:2006)

Erdöl- und Erdgasindustrie - Komplettierungsflüssigkeiten und -materialien - Teil 2: Messung der Eigenschaften von Stützmaterialien zum Einsatz bei hydraulischen Fraktionierungs- und in Kiespackungsvorgängen (ISO 13503-2:2006)

This European Standard was approved by CEN on 22 September 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950->

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
 COMITÉ EUROPÉEN DE NORMALISATION
 EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

EN ISO 13503-2:2006 (E)

Foreword

This document (EN ISO 13503-2:2006) has been prepared by Technical Committee ISO/TC 67 "Materials, equipment and offshore structures for petroleum and natural gas industries" in collaboration with Technical Committee CEN/TC 12 "Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2007, and conflicting national standards shall be withdrawn at the latest by May 2007.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Endorsement notice

The text of ISO 13503-2:2006 has been approved by CEN as EN ISO 13503-2:2006 without any modifications.

**THE STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN ISO 13503-2:2007](#)
<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-ac9f28c4f4fa/sist-en-iso-13503-2-2007>

INTERNATIONAL STANDARD

**ISO
13503-2**

First edition
2006-11-01

Petroleum and natural gas industries — Completion fluids and materials —

Part 2:

Measurement of properties of proppants used in hydraulic fracturing and

iTeh ST[®]gravel-packing operations

(standards.iteh.ai)
Industries du pétrole et du gaz

Industries du pétrole et du gaz naturel — Fluides de compléti

SIST EN ISO 13503-2:2007
Partie 2: Mesurage des propriétés des matériaux de soutènement utilisés dans les opérations de fracturation hydraulique et de remplissage de gravier



Reference number
ISO 13503-2:2006(E)

© ISO 2006

ISO 13503-2:2006(E)**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN ISO 13503-2:2007](#)

<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-ac9f28c4f4fa/sist-en-iso-13503-2-2007>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Abbreviations	1
4 Standard proppant sampling procedure	2
4.1 General.....	2
4.2 Particle segregation.....	2
4.3 Equipment	2
4.4 Number of required samples — Bulk.....	4
4.5 Sampling —Bulk material	5
4.6 Sampling — Bagged material	5
5 Sample handling and storage.....	5
5.1 Sample reduction.....	5
5.2 Sample splitting.....	5
5.3 Sample and record retention and storage.....	5
6 Sieve analysis	6
6.1 Purpose.....	6
6.2 Description	6
6.3 Equipment and materials	SIST EN ISO 13503-2:2007
6.4 Procedure	https://standards.itech.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-15036f5e0a7c/sev-2007
6.5 Calculation of the mean diameter, median diameter and standard deviation.....	7
6.6 Sieve calibration	9
7 Proppant sphericity and roundness	11
7.1 Purpose.....	11
7.2 Description	12
7.3 Apparatus capability.....	12
7.4 Procedure	12
7.5 Alternate method for determining average sphericity and roundness	13
8 Acid solubility	13
8.1 Purpose.....	13
8.2 Description	13
8.3 Equipment and materials	14
8.4 Procedure	14
9 Turbidity test	15
9.1 Purpose.....	15
9.2 Description	16
9.3 Equipment and materials	16
9.4 Equipment calibration	16
9.5 Procedure	16
10 Procedures for determining proppant bulk density, apparent density and absolute density....	17
10.1 Purpose.....	17
10.2 Description	17
10.3 Bulk density.....	17
10.4 Apparent density.....	19
10.5 Absolute density	21

ISO 13503-2:2006(E)

11	Proppant crush-resistance test	21
11.1	Purpose	21
11.2	Description.....	21
11.3	Equipment and materials	22
11.4	Sample preparation.....	22
11.5	Crush-resistance procedure	23
12	Loss on ignition of resin-coated proppant.....	25
12.1	Objective	25
12.2	Apparatus and materials	25
12.3	Loss-on-ignition procedure for whole-grain proppant	25
	Annex A (informative) Formazin solution preparation.....	27
	Bibliography	28

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN ISO 13503-2:2007](#)
<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-ac9f28c4f4fa/sist-en-iso-13503-2-2007>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13503-2 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 3, *Drilling and completion fluids, and well cements*.

iTeh STANDARD PREVIEW

ISO 13503 consists of the following parts, under the general title *Petroleum and natural gas industries — Completion fluids and materials*:

- *Part 1: Measurement of viscous properties of completion fluids* SIST EN ISO 13503-2:2007
<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-ac9f28c4f4f5/sist-en-iso-13503-2-2007>
- *Part 2: Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations*
- *Part 3: Testing of heavy brines*
- *Part 4: Procedure for measuring stimulation and gravel-pack fluid leakoff under static conditions*
- *Part 5: Procedures for measuring the long-term conductivity of proppants*

Introduction

This part of ISO 13503 is a compilation and modification of API RP 56 [1], API RP 58 [2] and API RP 60 [3].

The procedures have been developed to improve the quality of proppants delivered to the well site. They are for use in evaluating certain physical properties used in hydraulic fracturing and gravel-packing operations. These tests should enable users to compare the physical characteristics of various proppants tested under the described conditions and to select materials useful for hydraulic fracturing and gravel-packing operations.

The procedures presented in this part of ISO 13503 are not intended to inhibit the development of new technology, material improvements or improved operational procedures. Qualified engineering analysis and judgment are required for their application to a specific situation.

In this part of ISO 13503, where practical, US Customary (USC) units are included in brackets for information.

Annex A of this part of ISO 13503 is for information only.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 13503-2:2007
<https://standards.iteh.ai/catalog/standards/sist/84589008-9d4e-4fce-8950-ac9f28c4f4fa/sist-en-iso-13503-2-2007>

Petroleum and natural gas industries — Completion fluids and materials —

Part 2: Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations

1 Scope

This part of ISO 13503 provides standard testing procedures for evaluating proppants used in hydraulic fracturing and gravel-packing operations.

NOTE “Proppants” mentioned henceforth in this part of ISO 13503 refer to sand, ceramic media, resin-coated proppants, gravel-packing media and other materials used for hydraulic fracturing and gravel-packing operations.

The objective of this part of ISO 13503 is to provide a consistent methodology for testing performed on hydraulic fracturing and/or gravel-packing proppants.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

2 Normative references

SIST EN ISO 13503-2:2007

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ASTM E11, *Standard Specification for Wire Cloth and Sieves for Testing Purposes*

3 Abbreviations

API	American Petroleum Institute
ASTM	American Society for Testing and Materials
ASG	apparent specific gravity
FTU	formazin turbidity unit
HCl	hydrochloric acid
HF	hydrofluoric acid
LOI	loss on ignition
NTU	nephelometric turbidity unit

4 Standard proppant sampling procedure

4.1 General

Before any sample is taken, consider what tests will be performed, as each test requires a different volume. It is very important that both the supplier and customer obtain the best representative sample possible. Unless the sample is truly representative of a total shipment or container, testing and correlation with specifications/standards is very difficult. It is unlikely that sampling/testing methods in the field duplicate the producer's system. The standard procedures included within this part of ISO 13503 are to assist in obtaining representative samples. However, there are inherent variations associated with sampling, testing equipment and the procedures that can lead to inconsistent results. A sample that is representative of a truckload [23 000 kg (50 700 lb)] or a railcar load [90 000 kg (198 000 lb)] can be an initial source of wide variation when making comparisons. All parties shall take care to insure uniform sampling. The customer and the supplier shall agree on sampling and testing methods/techniques.

For the best representation, continuous sampling is ideal. Although many proppant suppliers utilize automatic sampling, it is usually impractical at the job site. If sampling is conducted while unloading a container or at the site, consideration should be given to the number or frequency of samples.

If bulk containers are filled from a flowing stream of proppant material, sampling procedures in accordance with 4.5 shall be applied. If bulk containers are filled using sacked proppant material, sampling procedures in accordance with 4.6 shall be applied.

4.2 Particle segregation

iTeh STANDARD PREVIEW (standards.itech.ai)

It is important to have a basic understanding of segregation when sampling proppant. Depending on the size, shape, distribution and mechanisms involved, there is usually a certain amount of error or variability involved in sampling due to segregation. The sampling procedures described here are the result of much experience and are designed to minimize the effects of segregation of particles by size.

SIST EN ISO 13503-2:2007

Particles, such as proppants, naturally find the path of least resistance when moved or when force is applied. During transfer or movement, particles of differing size and mass naturally separate or segregate. The degree of segregation depends on the mechanisms involved in the transfer or movement.

There are several forces, such as gravity, acting on a stream of particles as it flows. Within a moving stream, fine particles drop through the voids or gaps and coarser particles move to the outside. The fine particles migrate and usually rest close to the area where they land. The heavier, coarser particles bounce or roll much further, stratifying the material by size.

4.3 Equipment

The following equipment shall be used to compile representative proppant material samples.

4.3.1 Box sampling device, with a 13 mm (0,50 in) slot opening.

The length of the 13 mm (0,50 in) slot shall be longer than the thickness of the stream being sampled. The volume of the sampler shall be large enough so as to not overflow while cutting through the entire stream. A box sampling device meeting these criteria is shown in Figure 1.

4.3.2 Sample reducer, of appropriate size for handling sack-size samples and reducing the material to 1/16 of the original mass; see Figure 2.

4.3.3 Sample splitter, of appropriate size; see Figure 3.