

Edition 2.0 2017-10

INTERNATIONAL STANDARD

Global maritime distress and safety system (GMDSS) + F W Part 3: Digital selective calling (DSC) equipment – Operational and performance requirements, methods of testing and required testing results

> <u>IEC 61097-3:2017</u> https://standards.iteh.ai/catalog/standards/sist/ab35b655-10e2-4080-b617-de702f35f074/iec-61097-3-2017





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications. standard

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or also once a month by email.ps://standards.iteh.ai/catalog/standardneed/further assistance/please contact the Customer Service de702f35f074/iec-Centre csc@iec.ch.



Edition 2.0 2017-10

INTERNATIONAL STANDARD

Global maritime distress and safety system (GMDSS) + EW
Part 3: Digital selective calling (DSC) equipment - Operational and performance requirements, methods of testing and required testing results

<u>IEC 61097-3:2017</u> https://standards.iteh.ai/catalog/standards/sist/ab35b655-10e2-4080-b617-de702f35f074/iec-61097-3-2017

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.060.20; 47.020.70 ISBN 978-2-8322-4901-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

H(OREWORD		10
1	Scope		12
2	Normativ	ve references	12
3	Terms, c	definitions and abbreviated terms	14
	3.1 Te	rms and definitions	14
		breviated terms	
4		ance requirements	
		ject	
		st requirements	
	4.2.1	General	
	4.2.2	Test site	
	4.2.3	Environment tests	
	4.2.4	Environmental test procedure	
	4.2.5	Performance checks	
	4.2.6	Normal test conditions	21
	4.2.7	Extreme test conditions	
	4.2.8	Unspecified test conditions	
	4.2.9	·	
	4.2.10	General conditions of measurement Artificial antennas ANDARD PREVIEW	22
	4.2.11		
	4.2.12	Standard test signals and ards.iteh.ai) Measurement uncertainty	24
	4.2.13	Reference bandwidths for spurious measurements	
	4.2.14	Interpretation of measurement results/ab35b655-10e2-4080-b617-	25
	4.2.15	Testing method terminology74/iec-61097-3-2017	26
	4.3 Fu	nctional requirements	26
	4.3.1	Display of information	26
	4.3.2	User interface	26
	4.3.3	Categories of calls	26
	4.3.4	General purpose equipment characteristics	27
	4.3.5	Construction	27
	4.3.6	Memory	29
	4.3.7	Warm-up period	30
	4.3.8	Protection of the antenna input circuit	30
	4.3.9	Protection of the transmitter	30
	4.3.10	Antenna static protection	31
	4.3.11	Safety precautions	31
	4.3.12	Compass safe distance	31
	4.3.13	Audio interface	
	4.3.14	Activation of transmitter and maximum transmission time	32
	4.3.15	Data interface	32
	4.4 Op	erational requirements	
	4.4.1	Basic requirements	
	4.4.2	Additional requirements	
	4.4.3	Distress alerts	
	4.4.4	Other calls	
	4.4.5	Self-identification	
	4.5 Sc	anning efficiency	45

4.5.1	Requirements	
4.5.2	Method of test and required results	
4.6 Wa	tch and scanning facilities	
4.6.1	Requirements	
4.6.2	Method of test and required results	
4.7 Brid	dge alert management (BAM)	
4.7.1	Classification of BAM alerts	
4.7.2	Alert management	
	rt source identification and reporting in ALF sentence	
4.8.1	General requirements	
4.8.2	Receipt of distress or urgency call	
4.8.3	Receipt of calls other than distress or urgency	
4.8.4	No position data received by equipment	
4.9 Sof	tware and firmware maintenance	
4.9.1	Requirements	. 55
4.9.2	Methods of testing and required test results	. 55
5 Technica	l characteristics	. 56
5.1 Ger	neral	. 56
5.1.1	Frequency	. 56
5.1.2	Calling sensitivity	. 57
5.1.3	Calling sensitivity Nominal modulation rate DARD PREVIEW	.57
5.1.4	Residual modulation	. 57
5.2 Tec	Residual modulation (Standards:iteh.ai)	
5.2.1		
5.2.2	Requirements <u>IEC 61097-3:2017</u> Method of test and required results six/ab35b655-10e2-4080-b617	. 58
5.3 Exp	pansion sequencede702f35f074/iec-61097-3-2017	
5.3.1	Requirements	. 58
5.3.2	Methods of test and required results	.58
5.4 Equ	uipment for the automatic/semi-automatic service	.58
5.4.1	Requirements	. 58
5.4.2	Methods of test and required results	. 59
Annex A (info	rmative) Digital interface sentence to parameter group number	
equivaler	nce	. 60
Annex B (info	rmative) DSC remote control communication	.61
B.1 Ger	neral	.61
B.2 Use	e of AUC	.61
B.3 Use	e of AUQ	.61
B.4 Use	e of AUS	.61
B.5 Use	e of CUL	. 62
B.6 Use	e of OCC	. 62
B.7 Use	e of EPV	. 62
B.8 Met	thods of testing and required results	.63
B.8.1	General	
B.8.2	Standby information test	.63
B.8.3	Creating sending distress automated procedure test	
B.8.4	Receiving distress automated procedure test	
B.8.5	Create sending non-distress automated procedure test	
B.8.6	Receive non-distress automated procedure tests	
B.8.7	·	.69

B.8.8 Multiple automated procedures test	70
Annex C (normative) Interface and automation requirements, methods of testing and required test results	71
C.1 General	71
C.2 Naming convention of DSC message types	71
C.3 Test setup	71
C.3.1 General	71
C.3.2 Test methods	73
C.4 Non automated features	73
C.4.1 Non automated features requirements	73
C.4.2 Non automated features tests	77
C.5 Standby	92
C.5.1 Standby requirements	
C.5.2 Standby tests	
C.6 Sending distress automated procedure	
C.6.1 Sending distress automated procedure requirements	
C.6.2 Sending distress automated procedure tests	
C.7 Receiving distress automated procedure	
C.7.1 Receiving distress automated procedure requirements	
C.7.2 Receiving distress automated procedure tests	114
C.8 Sending non-distress automated procedure P.R.E.V.I.F.W.	
C.8.1 Sending non-distress automated procedure requirements	
C.8.2 Sending non-distress automated procedure tests	
TO (1) 00 0 0 0 0 1	
C.9.1 Receiving non-distress automated procedure requirements	135
C.10 Communications automated procedure	
C.10.1 Communications automated procedure requirements	
C.10.2 Communications automated procedure tests	
C.11 Multiple automated procedures and parallel event handling	
C.11.1 Multiple automated procedures and parallel event handling	
requirements	141
C.11.2 Multiple automated procedures and parallel event handling tests	
C.12 Error handling in the automated procedures	
C.12.1 Error handling requirements	
C.12.2 Error handling tests	
Annex D (normative) DSC message composition	
D.1 Default values	158
D.2 The default DROBOSE	
D.3 Allowable non-distress DSC message parameters	
Annex E (normative) Radius-centre point conversion and rounding algorithm	
E.1 Radius-centre point conversion	
E.2 Rounding	
E.3 Special cases for either form of area data entry	
Annex F (normative) Automated non-distress channel/frequency selection algorithm	
F.1 General	
F.2 VHF	
F.3 HF	
Annex G (normative) DSC message detection and decoding	164

Annex H	(normative) Audible annunciation and BAM alert signalling	166
H.1	Aural alert specifications	166
H.2	Alerting with critical errors	167
H.3	Default aural alert sounds	167
Annex I (r	normative) Shipborne watchkeeping receivers	169
I.1	General and operational requirements	169
1.1.1	General	169
1.1.2	Construction	169
1.2	Technical requirements	169
1.2.1	Frequency bands and channels	169
1.3	MF and MF/HF watchkeeping receiver	171
1.3.1	Maximum usable sensitivity	171
1.3.2	Adjacent channel selectivity	172
1.3.3	Co-channel rejection	172
1.3.4	RF intermodulation response	173
1.3.5	Spurious response rejection	173
1.3.6	Blocking immunity	174
1.3.7	Dynamic range	175
1.3.8	Conducted spurious emissions into the antenna	
1.3.9	Protection of receiver antenna input circuits Stop/start of scanning efficiency	176
1.3.10	Stop/start of scanning efficiency	176
1.4	VHF watchkeeping receivern dards.itch.ai)	177
1.4.1	Maximum usable sensitivity	177
1.4.2	Adjacent channel selecti <u>vity 61097-3.2017</u>	
1.4.3	Co-channel/dejection/tatiog/standards/sist/ab35b655-10e2-4080-b617-	
1.4.4	Intermodulation res <mark>poักริธ</mark> 5 <u>1074/iec-61097-3-2017</u>	
1.4.5	Spurious response rejection	
1.4.6	Blocking immunity	
1.4.7	Dynamic range	
1.4.8	Conducted spurious emissions conveyed to the antenna	
Annex J (normative) Shipborne VHF radiotelephone transmitter and receiver	182
J.1	General and operational requirements	182
J.1.1	General	182
J.1.2	•	
J.1.3	•	
J.1.4	•	
J.2	Switching time	
J.2.1	•	
J.2.2		
J.2.3	•	
J.3	Transmitter	
J.3.1		
J.3.2	, ,	
J.3.3	•	
J.3.4	•	
J.3.5		
J.3.6	, , , , , , , , , , , , , , , , , , , ,	
J.3.7		
J.3.8	Audio frequency harmonic distortion of the emission	187

J.3.9	Adjacent channel power	188
J.3.10	Conducted spurious emissions conveyed to the antenna	189
J.3.11	Residual modulation of the transmitter	189
J.3.12	Transient frequency behaviour of the transmitter	190
J.3.13	Antenna VSWR integrity behaviour and monitor	
J.4 Trar	nsmitter with integrated DSC encoder	191
J.4.1	Frequency error (carrier)	191
J.4.2	Frequency error (demodulated signal)	192
J.4.3	Carrier power	192
J.4.4	Modulation index	193
J.4.5	Modulation rate	193
J.4.6	Residual modulation	193
J.4.7	Modulator attack time	194
J.4.8	Adjacent channel power	194
J.5 Rec	eiver	195
J.5.1	General	195
J.5.2	Harmonic distortion and rated audio frequency output power	
J.5.3	Audio frequency response	
J.5.4	Maximum usable sensitivity	
J.5.5	Amplitude response of the receiver limiter	
J.5.6	Co-channe rejection ratio D.A.R.D. P.R.E.V.I.E.W.	
J.5.7		
J.5.8	Adjacent channel selectivity	199
J.5.9	Intermodulation response	
J.5.10	Blocking immunity https://standards.iich.ai/catalog/standards/sist/ab35b655-10e2-4080-b617-	201
J.5.11	Conducted spurious emissions conveyed to the antenna	202
J.5.12	Receiver hum and noise level	
J.5.13	Squelch operation	
J.5.14	Squelch hysteresis	
J.5.15	Scanning characteristics of multiple watch facilities	
	eiver with integrated DSC decoder	
	lex operation	
J.7.1	General	
J.7.2	Acoustic feedback	
J.7.3	Receiver desensitization with simultaneous transmission and reception	
0.1.0	(full-duplex operation)	205
J.7.4	Receiver spurious response rejection	206
J.8 Elec	ctromagnetic compatibility	206
J.8.1	Conducted spurious emission	206
J.8.2	Radiated spurious emission	206
J.8.3	Immunity to electromagnetic environment	206
J.9 Pow	ver measuring receiver specification	206
J.9.1	IF filter	
J.9.2	Attenuation indicator	208
J.9.3	RMS value indicator	208
J.9.4	Oscillator and amplifier	208
Annex K (norn	native) Shipborne MF and HF transmitters and receivers	209
•	neral and operational requirements	
K.1.1	General	

K.1.2	Composition	209
K.1.3	Frequency indication	209
K.1.4	Control panel priority	209
K.1.5	Labels	210
K.1.6	Classes of emission	210
K.1.7	Frequency bands	210
K.2 Tra	nsmitter	211
K.2.1	General	211
K.2.2	Frequency error for SSB telephony	211
K.2.3	Output power and intermodulation products for SSB telephony	211
K.2.4	Unwanted frequency modulation	213
K.2.5	Sensitivity of the microphone	213
K.2.6	Sensitivity of the 600 Ω line input for SSB telephony	214
K.2.7	Automatic level control and/or limiter for SSB telephony	214
K.2.8	Audio frequency response using SSB telephony	215
K.2.9	Power of out-of-band emissions of SSB telephony	216
K.2.10	Power of conducted spurious emissions of SSB telephony	217
K.2.11	Residual hum and noise power for SSB telephony	218
K.2.12	Carrier suppression	218
K.2.13	Continuous operation on SSB telephony	219
K.3 Tra	nsmitter with DSC encoder and NBDP. P.R.V.I.E.W.	220
K.3.1	Frequency error (standards.iteh.ai) Output power	220
K.3.2	Output power (Standards.item.ar)	220
K.3.3	Power of out-of-band emission of DSC	221
K.3.4	Power of conducted spurious emission of DSC 10e2-4080-b617-	222
K.3.5	Residual frequency modulation of DSC-3-2017.	223
K.3.6	Modulation rate of DSC	224
K.3.7	Switching time for NBDP	224
K.4 Red	ceiver	225
K.4.1	Audio frequency output levels	225
K.4.2	Frequency error for SSB telephony	225
K.4.3	Unwanted frequency modulation	226
K.4.4	Audio frequency pass band	226
K.4.5	Maximum usable sensitivity (MUS)	227
K.4.6	Harmonic content in output	228
K.4.7	Adjacent signal selectivity for J3E class of emission	228
K.4.8	Blocking for J3E class of emission	229
K.4.9	Intermodulation for J3E class of emission	230
K.4.10	Reciprocal mixing	231
K.4.11	Spurious response rejection ratio	231
K.4.12	Audio frequency intermodulation	233
K.4.13	Conducted spurious emissions into the antenna	233
K.4.14	Internally generated spurious signals	234
K.4.15	AGC efficiency	234
K.4.16	AGC time constants (attack and recovery time)	235
K.4.17	Switching time for NBDP	236
K.4.18	Protection of input circuits	236
K.5 Red	ceiver with DSC decoder	237
K 5 1	Maximum usable sensitivity	237

K.5.	2 Adjacent signal selectivity	237
K.5.	3 Co-channel rejection	238
K.5.	4 Intermodulation response	239
K.5.	5 Spurious response rejection	239
K.5.	6 Blocking immunity	241
K.5.	, 0	241
	(informative) Relationship between bit error rate (BER) input and symbols rate (SER) output	243
L.1	General	
L.2	Measurement of the relationship between BER at the input of a DSC decoder and the symbol error rate at the output of the decoder	
L.3	Conclusion	
	(informative) Delays in equipment and its effect on narrow band direct ting (NBDP)	247
M.1	General	247
M.2	Short distance	247
M.3	Long distance	247
Annex N	(informative) Sentence to support DSC remote control	249
N.1	General	249
N.2	AUC – Automated procedure control	249
N.3	AUQ – Automatic procedure query	251
N.4	AUS – Automated procedure status	252
N.5	CUL - Cyclic procedu (Stiandards.iteh.ai)	
N.6	ECI – Enhanced selective calling information	256
N.7	FSS – Frequency selection set <u>EC 61097-3:2017</u> OCC – Occupation control de 702f35f074/iec-61097-3-2017	258
N.8	OCC – Occupation control de/02f35f074/iec-61097-3-2017	260
Bibliogra	phy	∠0 I
Figure 1	- Interfaces of a DSC	33
Figure 2	- DSC Interface overview	36
Figure C	.1 – Sending distress procedure	96
•	.2 – Receiving distress procedure	
Figure C	.3 – Sending non-distress automated procedure	124
•	.4 – Receiving non-distress procedure	
	.1 – Loading DSC defaults	
-	.1 – Circle-radius to lat-lon box	
•	.1 – Tests and error checks	
	1 – Modulation pre-emphasis curve (for a modulation index of 3, +1 dB –3 dB	
•	2 – Transient frequency behaviour test configuration	•
Ū	3 – Modulator attack time test configuration	
•	-	
-	4 – Receiver audio frequency response	
•	5 – IF filter specification	
•	.1 – Limits for automatic level control	
-	.2 – Limits for audio frequency response	
•	.3 – Limits for unwanted emission (MF/HF transmitter)	
Figure L.	1 – Symbol error rate (%) versus bit error rate (%) – Individual call	244
Figure L.	2 – Symbol error rate (%) versus bit error rate (%) – Distress call	245

Figure L.3 – Symbol error rate (%) versus bit error rate (%) – All ship call	246
Figure L.4 – Symbol error rate (%) versus transmitted calls – Distress call – EUT 1	246
Table 1 – Reference bandwidths applicable for spurious measurement	25
Table 2 – IEC 61162-1 sentences received by the DSC equipment for position information	34
Table 3 – IEC 61162-1 sentences transmitted by the DSC equipment	34
Table 4 – IEC 61162-1 sentences received by the DSC equipment	35
Table 5 – IEC 61162-1 sentences transmitted by the DSC equipment for BNWAS	
Table 6 – IEC 61162-1 sentences transmitted by the DSC equipment for BAM	35
Table 7 – IEC 61162-1 sentences received by the DSC equipment for BAM	35
Table 8 – Classification of GMDSS equipment alerts for alert management purposes	48
Table 9 – Alert text in ALF sentence for cause Distress	51
Table 10 – Alert text in ALF sentence for cause Urgency	52
Table 11 – Alert text in ALF sentence for received calls other than Distress and Urgency	52
Table 12 – Alert text in ALF sentence for cause No position data received by equipment	53
Table 13 – Alert text in ALF sentence for cause Antenna or Antenna tuner failure	
Table 14 – Alert text in ALF sentence for cause Transmission power inhibit or failure	55
Table A 1 – Conversion from IEC 61162-1 to IEC 61162-3.a.i.	60
Table B.1 – Property identifiers	
Table C.1 – Geographic area tests IEC 61097-32017	84
Table C.2 – DSC messages to send from the EUT de/02/35/10/4/rec-61097-3-2017	87
Table C.3 – DSC messages to send from the EUT	143
Table C.4 – DSC messages	148
Table C.5 – DSC messages	148
Table C.6 – DSC messages to send from the TE	150
Table D.1 - Default DROBOSE	160
Table D.2 – Allowable parameter combinations	160
Table H.1 – Audible characteristics	166
Table H.2 – Non configurable alert sounds	168
Table H.3 – Recommended alert sounds	168
Table J.1 – Selectivity characteristic	207
Table J.2 – Attenuation points close to carrier	207
Table J.3 – Attenuation points distant from carrier	208
Table K.1 – Distress frequencies	210
Table K.2 – Power of any out-of-band emission	217
Table K.3 – Power of any conducted spurious emission	218
Table K.4 – Power of any conducted spurious emission	223
Table K.5 – Power of any conducted spurious emission	228
Table K.6 – Adjacent signal selectivity	229
Table K.7 – Input level of the test signal	237

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) -

Part 3: Digital selective calling (DSC) equipment – Operational and performance requirements, methods of testing and required testing results

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

 IEC 61097-3:2017
- 4) In order to promote international uniformity GEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61097-3 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This second edition cancels and replaces the first edition published in 1994. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) changes in the operation of DSC which have been developed by IMO and ITU since the first edition was published;
- b) compliance with bridge alert management (BAM);

- c) optional addition of remote operation of the DSC functionality. This facility can also used for type approval testing of the performance of the DSC equipment;
- d) incorporation of the radio frequency test methods for MF, MF/HF and VHF transceivers and watch receivers for convenience of testing.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
80/861/FDIS	80/866/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61097 series, published under the general title *Global maritime distress and safety system (GMDSS)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed.
- withdrawn. iTeh STANDARD PREVIEW
- replaced by a revised edition, standards.iteh.ai)
- amended.

IEC 61097-3:2017

A bilingual version of this publication may be issued at a later date 1080-b617-

de702f35f074/jec-61097-3-2017

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) -

Part 3: Digital selective calling (DSC) equipment – Operational and performance requirements, methods of testing and required testing results

1 Scope

This part of IEC 61097 specifies the performance requirements, technical characteristics, operational requirements and methods of testing of shipborne DSC equipment for use with MF, MF/HF and VHF installations in the GMDSS, including those required by Chapter IV of the 1974 International Convention for Safety of Life at Sea (SOLAS) as amended, and is associated with IEC 60945 (Shipborne radio equipment forming part of the global maritime distress and safety system and marine navigational equipment).

This document incorporates applicable parts of the performance standards of IMO Resolutions A.803(19), A.804(19) and A.806(19) (DSC facilities for VHF, MF and MF/HF radio installations), IMO MSC/Circ.862 (describing the operation of the distress button), the provisions of the ITU Radio Regulations, the technical characteristics of DSC equipment and the operational procedures for its use contained in Recommendations ITU-R M.493, M.541, M.689, M.821 and M.1082, and takes into account the general requirements contained in IMO Resolution A.694(17).

Recommendation ITU-R M.493-14 desc<u>ribes classes A</u>, B, D, E, H and M of DSC equipment. This document specifies tests procedures for a DSCt/equipment of Class A and B which are applicable to the SOLAS requirements 2135074/iec-61097-3-2017

Class A, which includes all of the facilities defined in Annex 1, 3 and 4 of Recommendation ITU-R M.493-14 and which will comply with the IMO GMDSS carriage requirements for MF/HF installations and/or VHF installations;

Class B, which provides minimum facilities for equipment on ships not required to use Class A equipment and which will comply with the minimum IMO GMDSS carriage requirements for MF and/or VHF installations.

This document also includes requirements and methods of testing for the RF part of the MF, MF/HF and VHF installations, specified in the annexes of this document for reference.

NOTE All text whose meaning is identical to that in IMO Resolution A.803(19), A.804(19), A.806(19), MSC.68(68), and to that in IMO Circular MSC/Circ.862, and to that in Recommendations ITU-R M.493, M.541, M 689, M.821, and M.1082 is printed in italics and the references indicated in brackets. Text referencing IMO Resolution A.803(19) includes references to A.804(19) and A.806(19) unless otherwise stated.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results

IEC 61162-1, Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners

IEC 61162-2, Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 2: Single talker and multiple listeners, high-speed transmission

IEC 61162-450, Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 450: Multiple talkers and multiple listeners - Ethernet interconnection

IEC 61162-460:2015, Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 460: Multiple talkers and multiple listeners - Ethernet interconnection - Safety and security

IEC 62288, Maritime navigation and radiocommunication equipment and systems - Presentation of navigation-related information on shipborne navigational displays - General requirements, methods of testing and required test results

IEC 61924-2:2012, Maritime navigation and radiocommunication equipment and systems - Integrated navigation systems - Part 2: Modular structure for INS - Operational and performance requirements, methods of testing and required test results

Recommendation ITU-R M.493-14:2015, Digital selective-calling system for use in the maritime mobile service

Recommendation ITU-R M.541-10:2015, Operational procedures for use of digital selective-calling equipment in the maritime mobile service

iTeh STANDARD PREVIEW

Recommendation ITU-R M.689-3:2012, International maritime VHF radiotelephone system with automatic facilities based on DSC signalling format 1 21

Recommendation ITU-R M.821-1:1997 <u>ECOptional (expansion of the digital selective-calling system for use in the maritime mobile service dards/sist/ab35b655-10e2-4080-b617-</u>

de702f35f074/iec-61097-3-2017

Recommendation ITU-R M.1084-5:2012, Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service

Recommendation ITU-R M.1082-1:1997, International maritime MF/HF radiotelephone system with automatic facilities based on digital selective calling signalling format

ITU Radio Regulations:2016

IMO Resolution A.694(17), General requirements for shipborne radio equipment forming part of the global maritime distress and safety system and for electronic navigational aids

IMO Resolution A.803(19), Performance standards for shipborne VHF radio installations capable of voice communication and digital selective calling, as amended by Resolution MSC.68(68):1997, Annex 1

IMO Resolution A.804(19), Performance standards for shipborne MF radio installations capable of voice communication and digital selective calling, as amended by Resolution MSC.68(68):1997, Annex 2

IMO Resolution A.806(19), Performance standards for shipborne MF/HF radio installations capable of voice communication, narrow-band direct-printing and digital selective calling, as amended by Resolution MSC.68(68):1997, Annex 3

IMO MSC.1/Circ.1389, Guidance on procedures for updating shipborne navigation and communication equipment