

SLOVENSKI STANDARD

oSIST prEN ISO 3746:2006

01-februar-2006

5_i gh_U!`8 c`c Ub`fUj b`nj c b`a c]b`nj c bY`YbYf[]Y`j ffcj `fi dUn
a Yf`Yb`Ya `nj c bY[U`hU_U!`bZ`fa U`hj bU`a Y`tcXUn`a Yf]bc`d`cg_j]`cžg_`Yb`Ybc
c_fc[`j]fU`fi dU`bUX`cXVc`bc`fUj b]bc`fIGC`#`G' +(*.&\$)\$ Ł

Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Survey method using an enveloping measurement surface over a reflecting plane (ISO/DIS 3746:2005)

Akustik - Ermittlung der Schalleistungs- und der Schallenergiepegel von Geräuschquellen aus Schalldruckmessungen - Hüllflächenverfahren der Genauigkeitsklasse 3 über einer reflektierenden Ebene (ISO/DIS 3746:2005)

Acoustique - Détermination des niveaux de puissance acoustique et des niveaux d'énergie acoustique a partir de la pression acoustique - Méthode de contrôle employant une surface de mesure enveloppante au-dessus d'un plan réfléchissant (ISO/DIS 3746:2005)

Ta slovenski standard je istoveten z: prEN ISO 3746

ICS:

17.140.01	OE`•cā } aī ^!b } bāā à æ^ } b`Á@`] aī aī] [z] [Acoustic measurements and noise abatement in general
-----------	---	---

oSIST prEN ISO 3746:2006

en

November 2005

ICS

Will supersede EN ISO 3746:1995

English Version

Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Survey method using an enveloping measurement surface over a reflecting plane (ISO/DIS 3746:2005)

Acoustique - Détermination des niveaux de puissance acoustique et des niveaux d'énergie acoustique à partir de la pression acoustique - Méthode de contrôle employant une surface de mesure enveloppante au-dessus d'un plan réfléchissant (ISO/DIS 3746:2005)

This draft European Standard is submitted to CEN members for parallel enquiry. It has been drawn up by the Technical Committee CEN/TC 211.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

This document (prEN ISO 3746:2005) has been prepared by Technical Committee ISO/TC 43 "Acoustics" in collaboration with Technical Committee CEN/TC 211 "Acoustics", the secretariat of which is held by DS.

This document is currently submitted to the parallel Enquiry.

This document will supersede EN ISO 3746:1995.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

Endorsement notice

The text of ISO 3746:2005 has been approved by CEN as prEN ISO 3746:2005 without any modifications.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST EN ISO 3746:2011](https://standards.iteh.ai/catalog/standards/sist/7f40b929-b4f7-45fe-9df5-76157ac04236/sist-en-iso-3746-2011)

<https://standards.iteh.ai/catalog/standards/sist/7f40b929-b4f7-45fe-9df5-76157ac04236/sist-en-iso-3746-2011>



DRAFT INTERNATIONAL STANDARD ISO/DIS 3746

ISO/TC 43/SC 1

Secretariat: DS

Voting begins on:
2005-11-24

Voting terminates on:
2006-04-24

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane

Acoustique — Détermination des niveaux de puissance acoustique et des niveaux d'énergie acoustique à partir de la pression acoustique — Méthode de contrôle employant une surface de mesure enveloppante au-dessus d'un plan réfléchissant

[Revision of second edition (ISO 3746:1995 and ISO 3746:1995/Cor 1:1995)]

ICS 17.140.01

iTeh Standards
(<https://standards.iteh.ai>)

ISO/CEN PARALLEL ENQUIRY

The CEN Secretary-General has advised the ISO Secretary-General that this ISO/DIS covers a subject of interest to European standardization. **In accordance with the ISO-lead mode of collaboration as defined in the Vienna Agreement, consultation on this ISO/DIS has the same effect for CEN members as would a CEN enquiry on a draft European Standard.** Should this draft be accepted, a final draft, established on the basis of comments received, will be submitted to a parallel two-month FDIS vote in ISO and formal vote in CEN.

In accordance with the provisions of Council Resolution 15/1993 this document is circulated in the English language only.

Conformément aux dispositions de la Résolution du Conseil 15/1993, ce document est distribué en version anglaise seulement.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

SIST EN ISO 3746:2011

<https://standards.iteh.ai/catalog/standards/sist/7f40b929-b4f7-45fe-9df5-76157ae04236/sist-cn-iso-3746-2011>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
1.1 General	1
1.2 Types of noise and noise sources.....	1
1.3 Test environment.....	1
1.4 Measurement uncertainty.....	1
2 Normative references.....	2
3 Terms and definitions	2
4 Test environment.....	5
4.1 General	5
4.2 Criterion for background noise.....	5
4.3 Criterion for acoustic adequacy of test environment.....	5
5 Instrumentation	6
5.1 General	6
5.2 Calibration.....	6
6 Definition, location, installation and operation of noise source under test.....	6
6.1 General	6
6.2 Auxiliary equipment	6
6.3 Noise source location	7
6.4 Installation and mounting conditions	7
6.5 Operation of source during test.....	7
7 Reference box and measurement surface.....	8
7.1 Reference box.....	8
7.2 Measurement surface.....	8
8 Determination of sound power levels and sound energy levels.....	11
8.1 Determination of environmental correction.....	11
8.2 Microphone positions on the measurement surface.....	11
8.3 Determination of sound power levels	12
8.4 Determination of sound energy levels of a noise	14
9 Measurement uncertainty	15
10 Information to be recorded.....	16
10.1 General	16
10.2 Noise source under test.....	17
10.3 Test environment.....	17
10.4 Instrumentation	17
10.5 Acoustical data	17
11 Information to be reported.....	18
Annex A (normative) Determination of the environmental correction	19
Annex B (normative) Microphone arrays on a hemispherical measurement surface	21
Annex C (normative) Microphone arrays on a parallelepiped measurement surface	26
Annex D (informative) Guidance on the development of information on measurement uncertainty	31
Bibliography.....	38

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3746 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1.

This third edition cancels and replaces the second edition (ISO 3746:1995), which has been technically revised.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

SIST EN ISO 3746:2011

<https://standards.iteh.ai/catalog/standards/sist/7f40b929-b4f7-45fe-9df5-76157ae04236/sist-en-iso-3746-2011>

Introduction

0.1 This International Standard is one of the series ISO 3740 to ISO 3747, that specifies methods to determine the emitted sound power level and sound energy level of noise sources including machinery, equipment and their sub-assemblies. Guidelines to select one of those methods are provided in ISO 3740:2001. The selection will depend on the environment of the available test facility and on the precision of the sound power level or sound energy level values required. It may be necessary to establish a test code for the individual noise source in order to select the appropriate sound measurement surface and microphone array from among those allowed in each standard, and to give requirements on test unit mounting, loading and operating conditions under which the sound power levels or sound energy levels are to be obtained. The sound power emitted by a given source into the test environment is calculated from the mean square sound pressure that is measured over a hypothetical measurement surface enclosing the source, and the area of that surface. The sound energy for a single machine event is calculated from this sound power and the time over which it existed.

0.2 This International Standard provides a survey grade of accuracy (grade 3) as defined in ISO 12001 when performed within industrial buildings or outdoors. Ideally, the test source should be mounted on a sound reflecting plane located in a large open space. For sources normally installed on the floor of machine rooms, corrections are defined to account for undesired reflections from nearby objects, walls and the ceiling, and for the residual background noises that occur there.

0.3 The method specified in this International Standard permits the determination of the sound power level and the sound energy level with frequency weighting 'A' applied.

0.4 For applications where greater accuracy is required, reference can be made to ISO 3744, ISO 3745 or an appropriate part of ISO 9614. If the relevant criteria for the measurement environment specified in this International Standard are not met, it might be possible to refer to another standard from this series, or to an appropriate part of ISO 9614.

0.5 This International Standard cancels and replaces ISO 3746:1995.

SIST EN ISO 3746:2011

<https://standards.iteh.ai/catalog/standards/sist/7f40b929-b4f7-45fe-9df5-76157ae04236/sist-en-iso-3746-2011>

Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane

1 Scope

1.1 General

This International Standard specifies methods determining the sound power levels of a noise source from sound pressure levels measured on a surface enveloping a noise source (machinery or equipment) in a test environment for which requirements are given. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source, with frequency-weighting A applied, is calculated using those measurements.

NOTE Differently shaped measurement surfaces can yield differing estimates of the sound power level of a given noise source and a test code should give detailed information on the selection of the surface.

1.2 Types of noise and noise sources

The methods specified in this International Standard are suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

This International Standard is applicable to all types and sizes of noise source (e.g. stationary or slowly moving plant, installation, machine, component or sub-assembly), provided the conditions for the measurements can be met.

NOTE The conditions for measurements given in this International Standard could be impracticable for very tall or very long sources such as chimneys, ducts, conveyors and multi-source industrial plants. A test code for the determination of noise emission of specific sources can provide alternative methods in such cases.

1.3 Test environment

The test environments that are applicable for measurements made in accordance with this International Standard may be located indoors or outdoors, with one or more sound-reflecting planes present on or near which the noise source under test is mounted.

1.4 Measurement uncertainty

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this International Standard, for measurements made with frequency weighting A applied. The uncertainty conforms with that of the survey grade of accuracy (grade 3) defined in ISO 12001.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3744, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering methods for an essentially free field over a reflecting plane*

ISO 7574-1, *Acoustics – Statistical methods for determining and verifying stated noise emission values of machinery and equipment – Part 1: General considerations and definitions*

ISO 12001, *Acoustics – Noise emitted by machinery and equipment – Rules for the drafting and presentation of a noise test code*

IEC 60942:2003, *Electroacoustics – Sound calibrators*

IEC 61672-1:2002, *Electroacoustics – Sound level meters – Part 1: Specifications*

Guide to the expression of uncertainty in measurement (GUM). International Organization for Standardization, Geneva, Switzerland. ISBN 92-67-10188-9, First Edition 1993, corrected and reprinted 1995.

3 Terms and definitions

For the purposes of this International Standard, the following definitions apply.

3.1 sound pressure

p

a fluctuating pressure superimposed on the static pressure by the presence of sound, expressed in pascals

3.2 sound pressure level

L_p

ten times the logarithm to the base 10 of the ratio of the square of the sound pressure, p , to the square of a reference value, p_0 , expressed in decibels

$$L_p = 10 \lg \frac{p^2}{p_0^2} \text{ dB} \quad (1)$$

The reference value, p_0 , is 20 μPa ($2 \times 10^{-5} \text{ Pa}$).

3.3 time-averaged sound pressure level

$L_{p,T}$

level of the time-averaged square of the sound pressure over the measurement time interval T , expressed in decibels

$$L_{p,T} = 10 \lg \left[\frac{1}{T} \int_0^T \frac{p^2(t)}{p_0^2} dt \right] \text{ dB} \quad (2)$$

NOTE 1 In general, the subscript “ T ” is omitted since time-averaged sound pressure levels are necessarily determined over a certain measurement time interval.

NOTE 2 Time-averaged sound pressure levels are often A-weighted, in which case they are denoted by $L_{pA,T}$, which is usually abbreviated to L_{pA} .

3.4**single-event sound pressure level** L_E

level of the time-integrated square of the sound pressure of an isolated single sound event (burst of sound or transient sound) of specified duration T (or specified measurement time interval $T = t_2 - t_1$) normalized to reference time interval $T_0 = 1$ s, expressed in decibels

$$L_E = 10 \lg \left[\frac{1}{T_0} \int_{t_1}^{t_2} \frac{p^2(t)}{p_0^2} dt \right] \text{ dB} = L_{p,T} + 10 \lg \left[\frac{T}{T_0} \right] \text{ dB} \quad (3)$$

3.5**measurement time interval** T

portion or a multiple of an operational period or operational cycle of the noise source under test for which the time-averaged sound pressure level is determined, expressed in seconds

3.6**reflecting plane**

reflecting planar surface on which the noise source under test is located

3.7**frequency range of interest**

the range of octave bands with nominal midband frequencies from 125 Hz to 8000 Hz

3.8**reference box**

hypothetical rectangular parallelepiped terminating on the reflecting plane(s) on which the noise source under test is located, that just encloses the source including all the significant sound radiating components and any test table on which the source is mounted (see 6.3)

3.9**characteristic source dimension** d_0

distance from the origin of the co-ordinate system to the farthest corner of the reference box (see 7.1), expressed in metres

3.10**measurement distance** d

distance from the reference box to a parallelepiped measurement surface, expressed in metres

3.11**measurement radius** r

radius of a hemispherical measurement surface, expressed in metres

3.12**measurement surface**

hypothetical surface of area S , on which the microphone positions are located at which the sound pressure levels are measured, enveloping the noise source under test and terminating on the reflecting plane(s) on which the source is located

3.13**background noise**

noise from all sources other than the noise source under test

NOTE Background noise may include contributions from airborne sound, structure-borne vibration, and electrical noise in the instrumentation.

3.14

background noise correction

K_1
correction applied to the mean (energy-average) of the time-averaged sound pressure levels at all the microphone positions on the measurement surface, to account for the influence of background noise, expressed in decibels

NOTE The background noise correction is frequency dependent, and in the case of A-weighting is denoted K_{1A} .

3.15

environmental correction

K_2
correction applied to the mean (energy-average) of the time-averaged sound pressure levels at all the microphone positions on the measurement surface, to account for the influence of reflected or absorbed sound, expressed in decibels

NOTE 1 The environmental correction is frequency dependent, and in the case of A-weighting is denoted K_{2A} .

NOTE 2 In general, the environmental correction depends on the area of the measurement surface and usually K_2 increases with S .

3.16

surface time-averaged sound pressure level

$\overline{L_p}$
mean (energy average) of the time-averaged sound pressure levels at all the microphone positions on the measurement surface, with the background noise correction, K_1 , and the environmental correction, K_2 , applied, expressed in decibels

3.17

surface single-event sound pressure level

$\overline{L_E}$
mean (energy average) of the single-event sound pressure levels at all the microphone positions on the measurement surface, with the background noise correction, K_1 , and the environmental correction, K_2 , applied, expressed in decibels

3.18

sound power

W
rate per unit time at which airborne sound energy is radiated by a source, expressed in watts

3.19

sound power level

L_W
ten times the logarithm to the base 10 of the ratio of the sound power of a source, W , to a reference value, W_0 , expressed in decibels

$$L_W = 10 \lg \frac{W}{W_0} \text{ dB} \quad (4)$$

The reference value, W_0 , is 1 pW (10^{-12} W).

NOTE The frequency weighting is indicated in the symbol, so the A-weighted sound power level is L_{WA} .

3.20

sound energy

J
energy of a single burst of sound or transient sound emitted by a source, expressed in joules