

SLOVENSKI STANDARD SIST EN 1395-4:2007

01-april-2007

BUXca Yý U. SIST EN 1395:1999

Jfc Y'Vf]n[Ub^Y'Ë'DfYj nYa b]'dfYg_i g]'cdfYa Y'nU'j fc Y'Vf]n[Ub^Y'Ë'("XY'. D`UnYa g_c'Vf]n[Ub^Y

Thermal spraying - Acceptance inspection of thermal spraying equipment - Part 4: Plasma spraying

Thermisches Spritzen Abnahmeprüfungen für Anlagen zum thermischen Spritzen - Teil 4: Plasmaspritzen (standards.iteh.ai)

Projection thermique - Contrôle d'acceptation3du4matériel de projection thermique - Partie 4: Projection plasmadards.iteh.ai/catalog/standards/sist/38b9cb80-79ea-4396-a404-0667bc250c4d/sist-en-1395-4-2007

Ta slovenski standard je istoveten z: EN 1395-4:2007

ICS:

25.220.20 Površinska obdelava Surface treatment

SIST EN 1395-4:2007 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 1395-4:2007</u> https://standards.iteh.ai/catalog/standards/sist/38b9cb80-79ea-4396-a404-0667bc250c4d/sist-en-1395-4-2007

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 1395-4

January 2007

ICS 25.220.20

Supersedes EN 1395:1996

English Version

Thermal spraying - Acceptance inspection of thermal spraying equipment - Part 4: Plasma spraying

Projection thermique - Contrôle d'acceptation du matériel de projection thermique - Partie 4: Projection plasma

Thermisches Spritzen - Abnahmeprüfungen für Anlagen zum thermischen Spritzen - Teil 4: Plasmaspritzen

This European Standard was approved by CEN on 23 December 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

<u>SIST EN 1395-4:2007</u> https://standards.iteh.ai/catalog/standards/sist/38b9cb80-79ea-4396-a404-0667bc250c4d/sist-en-1395-4-2007



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents					
Foreword					
1	Scope	4			
2	Normative references	4			
3	Terms and definitions	4			
4	Principles of acceptance inspection	4			
5	Procedure of acceptance inspection	5			
6	Designation	6			
7	Inspection report	6			
Ann	nex A (informative) Inspection report for plasma spraying equipment (initial test/retest)	7			
Rihli	liography	q			

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 1395-4:2007</u> https://standards.iteh.ai/catalog/standards/sist/38b9cb80-79ea-4396-a404-0667bc250c4d/sist-en-1395-4-2007

Foreword

This document (EN 1395-4:2007) has been prepared by Technical Committee CEN/TC 240 "Thermal spraying and thermally sprayed coatings", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2007, and conflicting national standards shall be withdrawn at the latest by July 2007.

This document together with EN 1395-1, 1395-2, 1395-3, 1395-5, 1395-6 and 1395-7 supersedes EN 1395:1996.

EN 1395 consists of the following Parts, under the general title *Thermal spraying — Acceptance inspection of thermal spraying equipment*:

- Part 1: General requirements;
- Part 2: Flame spraying including HVOF;
- Part 3: Arc spraying;

iTeh STANDARD PREVIEW

— Part 4: Plasma spraying;

(standards.iteh.ai)

Part 5: Plasma spraying in chambers;

SIST EN 1395-4:2007

— Part 6: Manipulator systems: .iteh.ai/catalog/standards/sist/38b9cb80-79ea-4396-a404-

0667bc250c4d/sist-en-1395-4-2007

— Part 7: Powder feed systems.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

1 Scope

This European Standard specifies requirements for the acceptance inspection of thermal spraying equipment, in this case plasma spraying, used in spray jobs to produce thermally sprayed coatings of reproducible quality.

This part should be used in conjunction with EN 1395-1, which includes general requirements and explanations of procedures.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 657:2005, Thermal spraying — Terminology, classification

EN 1274:2004, Thermal spraying — Powders — Composition, technical supply conditions

EN 1395-7, Thermal spraying — Acceptance inspection of thermal spraying equipment — Part 7: Powder feed systems

3 Terms and definition Teh STANDARD PREVIEW

For the purposes of this document, the terms and definitions given in EN 657:2005 and the following apply.

3.1

SIST EN 1395-4:2007

high voltage ignition device unit that generates a high voltage (kV) and low current (mA) between the electrodes of the plasma spraying torch in order to ignite the arc

4 Principles of acceptance inspection

4.1 General

The following clauses reveal state of the art technology in thermal spray equipment and the minimum requirements concerning a stable parameter setting and maintenance according to the classes given in Annex A.

4.2 High-voltage ignition device

Other components and functions of the spraying equipment and other machines and/or equipment operated near by to the spraying equipment shall not be affected by operation of the high-voltage ignition device.

4.3 Plasma gases

The plasma spraying equipment shall be designed and installed in such a manner, that safe operation with plasma gases specified by the user will be achieved.

4.4 Plasma spray nozzle

Processing of the spraying powder shall be possible without producing any disturbing deposits on and/or in the nozzle. Nozzles with different shapes and powder ports (internal or external) may be used for special applications.

4.5 Spraying powder feed unit

The powder feed unit shall be suitable for operation with the spraying equipment to be taken.

The unit shall permit uniform processing of the powder required. It shall be possible to adjust the powder feed rate. The set points shall be constant and reproducible, which is a precondition for this being adequate and constant carrier gas pressure and flow.

5 Procedure of acceptance inspection

5.1 General

Spraying equipment shall be deemed properly supplied for all suitable spraying applications and for use with all suitable spraying materials required for the spraying process if it complies with the following requirements:

5.2 Electrical power

Proof of the power rating required shall be given by 20 min of spraying with the parameters for aluminium oxide according to EN 1274:2004, 12.1 as recommended by the equipment manufacturer.

During the test, the following items will be examined:

— electrical control;

iTeh STANDARD PREVIEW

— gas control;

(standards.iteh.ai)

cooling water temperature.

SIST EN 1395-4:2007

Limits of deviation: see Annex At Glass A and Glass B sist/38b9cb80-79ea-4396-a404-

0667bc250c4d/sist-en-1395-4-2007

After stabilisation of arc and plasma, the deviation of the voltage (variable parameter) from the set point shall not exceed 3 % (Class A) and 12 % (Class B).

5.3 High-voltage ignition device

The high-voltage ignition device shall be deemed to meet the requirements given in 4.2 if it does not interfere with any appliances and functions of the spraying equipment during the test as specified in 5.2. There should be no excessive erosion wear visible on the nozzle (spark).

5.4 Plasma gases

The system shall be deemed to comply with the specified requirements if the following requirements are satisfied by the acceptance inspection. The values of gas pressure and gas flow shall not deviate by more than \pm 1,5 % (Class A) and \pm 5 % (Class B) from the set points over a 20 min period of spraying. If the secondary gas is the variable parameter, the deviations from the set point shall not exceed 3 % (Class A) and 12 % (Class B) after stabilisation. Setting the primary gas pressure and/or flow rate shall not affect the corresponding values of the secondary gas and carrier gas and vice versa.

5.5 Plasma spray nozzle

The nozzle shall be deemed to comply with the requirements specified in 4.4 if there are no disturbing deposits of spraying material on or in the nozzle when testing as specified in 5.2.

5.6 Powder feed unit

The suitability of the system to process powders as specified in 4.5 shall be tested according to EN 1395-7.

6 Designation

Acceptance inspection of the thermal spraying equipment for plasma spraying shall be designated as follows:

Acceptance inspection according to EN 1395-4.

7 Inspection report

An example for the inspection report is given in Annex A.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 1395-4:2007</u> https://standards.iteh.ai/catalog/standards/sist/38b9cb80-79ea-4396-a404-0667bc250c4d/sist-en-1395-4-2007

Annex A

(informative)

Inspection report for plasma spraying equipment (initial test/retest)

The initial test/retest fulfils the requirements of the acceptance inspection according to EN 1395-4.

Manufacture	er:											
Year of man	ufacture:											
Type of equi	pment:											
Type of spra	ıying gun:											
Powder used	d for testing:.											
Type of pow	der feed unit	·			Size range:							
CE-docume	ntation comp	lete: yes /	no									
ITeh S Item tested, where applicable https://standards.it				DAR lards Set point TEN 1395- g/standards/	continuous testing actual value maximum			Limit		Evaluation		
					sist/38b9c	b80 <u>-7</u> 9ea 2007	deviation 1-4396-%404-	Class A	Class B	passed	failed	
Electrical	current	Α						± 1,5	± 5			
power	voltage	V						± 1,5	± 5			
Primary gas	pressure	bar						± 1,5	± 5			
	flow	NI/min ¹						± 1,5	± 5			
Secondary	pressure	bar						± 1,5	± 5			
gas	flow	NI/min ¹⁾						± 1,5	± 5			
Carrier gas	pressure	bar						± 1,5	± 5			
J	flow	NI/min ¹⁾						± 1,5	± 5			
	flow	l/min						± 5	± 10			
Cooling water	inlet temperature to spray gun	°C						5 °C	10 °C			

7

¹⁾ Referred to temperature 0 °C and normal pressure (1 013,25 hPa).