

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

Specification for radio disturbance and immunity measuring apparatus and methods –
Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements

CISPR 16-1-4:2019

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-4: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Antennes et emplacements d'essai pour les mesures des perturbations rayonnées





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch



CISPR 16-1-4

Edition 4.2 2023-04
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

**Specification for radio disturbance and immunity measuring apparatus and
methods –
Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and
test sites for radiated disturbance measurements**

CISPR 16-1-4:2019

**Spécifications des méthodes et des appareils de mesure des perturbations
radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-4: Appareils de mesure des perturbations radioélectriques et de
l'immunité aux perturbations radioélectriques – Antennes et emplacements
d'essai pour les mesures des perturbations rayonnées**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.100.10; 33.100.20

ISBN 978-2-8322-6846-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

REDLINE VERSION

VERSION REDLINE



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE
COMITÉ INTERNATIONAL SPÉCIAL DES PERTURBATIONS RADIOÉLECTRIQUES

Specification for radio disturbance and immunity measuring apparatus and methods –
Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements

CISPR 16-1-4:2019

Spécifications des méthodes et des appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques –
Partie 1-4: Appareils de mesure des perturbations radioélectriques et de l'immunité aux perturbations radioélectriques – Antennes et emplacements d'essai pour les mesures des perturbations rayonnées



CONTENTS

FOREWORD	10
1 Scope	12
2 Normative references	12
3 Terms, definitions and abbreviated terms	13
3.1 Terms and definitions.....	13
3.2 Abbreviated terms.....	18
4 Antennas for measurement of radiated radio disturbance	19
4.1 General.....	19
4.2 Physical parameter (measurand) for radiated disturbance measurements	19
4.3 Antennas for the frequency range 9 kHz to 150 kHz.....	19
4.3.1 General.....	19
4.3.2 Magnetic field antenna.....	20
4.3.3 Shielding of loop antenna	22
4.4 Antennas for the frequency range 150 kHz to 30 MHz.....	22
4.4.1 Electric field antenna	22
4.4.2 Magnetic field antenna.....	22
4.4.3 Balance and electric field discrimination of antennas	22
4.5 Antennas for the frequency range 30 MHz to 1 000 MHz	22
4.5.1 General.....	22
4.5.2 Low-uncertainty antenna for use if there is an alleged non-compliance to the electric disturbance field strength limit	23
4.5.3 Antenna characteristics.....	23
4.5.4 Balance of antenna	25
4.5.5 Cross-polar response of antenna	26
4.6 Antennas for the frequency range 1 GHz to 18 GHz.....	27
4.6.1 General.....	27
4.6.2 Receive antenna	28
4.7 Special antenna arrangements – large-loop antenna system.....	29
5 Test sites for measurement of radio disturbance field strength for the frequency range of 9 kHz to 30 MHz	30
5.1 General.....	30
5.2 Radio-frequency ambient environment of a test site	30
5.3 Measurement distance and test volume	31
5.4 Set-up table and antenna positioner.....	31
5.5 Validation procedure of test site.....	31
5.5.1 General.....	31
5.5.2 Normalized site insertion loss (NSIL)	35
5.5.3 Reference site method	35
5.5.4 Acceptance criterion	36
6 Test sites for measurement of radio disturbance field strength for the frequency range of 30 MHz to 1 000 MHz	36
6.1 General.....	36
6.2 OATS	36
6.2.1 General.....	36
6.2.2 Weather-protection enclosure	37
6.2.3 Obstruction-free area	37
6.2.4 Radio-frequency ambient environment of a test site	38

6.2.5	Ground plane	39
6.3	Suitability of other test sites	39
6.3.1	Other ground-plane test sites	39
6.3.2	Test sites without ground plane (FAR)	39
6.4	Test site validations	40
6.4.1	General.....	40
6.4.2	Overview of test site validations.....	40
6.5	Basic parameters of the NSA method for OATS and SAC.....	41
6.5.1	General equation and table of theoretical NSA values.....	41
6.5.2	Antenna calibration	45
6.6	Reference site method for OATS and SAC.....	45
6.6.1	General.....	45
6.6.2	Antennas not permitted for RSM measurements	46
6.6.3	Determination of the antenna pair reference site attenuation on a REFTS	46
6.6.4	Determination of the antenna pair reference site attenuation using an averaging technique on a large OATS.....	47
6.7	Validation of an OATS by the NSA method	50
6.7.1	Discrete frequency method	50
6.7.2	Swept frequency method.....	51
6.8	Validation of a weather-protection-enclosed OATS or a SAC	52
6.9	Possible causes for exceeding site acceptability limits	54
6.10	Site validation for FARs	55
6.10.1	General.....	55
6.10.2	RSM for FAR sites	59
6.10.3	NSA method for FAR sites	61
6.10.4	Site validation criteria for FAR sites	63
6.11	Evaluation of set-up table and antenna tower.....	63
6.11.1	General.....	63
6.11.2	Evaluation procedure for set-up table influences	64
7	Test sites for measurement of radio disturbance field strength for the frequency range 1 GHz to 18 GHz	65
7.1	General.....	65
7.2	Reference test site.....	66
7.3	Test site validation.....	66
7.3.1	General.....	66
7.3.2	Acceptance criterion for site validation	67
7.4	Antenna requirements for S_{VSWR} standard test procedure	67
7.4.1	General.....	67
7.4.2	Transmit antenna	68
7.4.3	Antennas and test equipment for the S_{VSWR} reciprocal test procedure	70
7.5	Required positions for site validation testing	71
7.5.1	General.....	71
7.5.2	Descriptions of S_{VSWR} measurement positions in a horizontal plane (Figure 23).....	71
7.5.3	Descriptions of S_{VSWR} additional measurement positions (Figure 24)	72
7.5.4	Summary of S_{VSWR} measurement positions	73
7.6	S_{VSWR} site validation – standard test procedure	76
7.7	S_{VSWR} site validation – reciprocal test procedure using an isotropic field probe	77

7.8	<i>S</i> VSWR conditional measurement position requirements	78
7.9	<i>S</i> VSWR site validation test report.....	79
7.10	Limitations of the <i>S</i> VSWR site validation method.....	79
7.11	Alternative test sites	80
8	Common mode absorption devices	80
8.1	General.....	80
8.2	CMAD <i>S</i> -parameter measurements	80
8.3	CMAD test jig.....	80
8.4	Measurement method using the TRL calibration.....	81
8.5	Specification of ferrite clamp-type CMAD	83
8.6	CMAD performance (degradation) check using spectrum analyzer and tracking generator.....	84
9	Reverberating chamber for total radiated power measurement	86
9.1	<u>General.....</u>	
9.2	<u>Chamber</u>	
9.2.1	<u>Chamber size and shape</u>	
9.2.2	<u>Door, openings in walls, and mounting brackets.....</u>	
9.2.3	<u>Stirrers</u>	
9.2.4	<u>Test for the efficiency of the stirrers</u>	
9.2.5	<u>Coupling attenuation</u>	
10	TEM-cells waveguides for immunity to radiated disturbance measurements.....	89
Annex A (normative)	Parameters of antennas	90
A.1	General.....	90
A.2	Preferred antennas	90
A.2.1	General.....	90
A.2.2	Calculable antenna	90
A.2.3	Low-uncertainty antennas	90
A.3	Simple dipole antennas	91
A.3.1	General.....	91
A.3.2	Tuned dipole	92
A.3.3	Shortened dipole.....	92
A.4	Broadband antenna parameters	93
A.4.1	General.....	93
A.4.2	Antenna type	94
A.4.3	Specification of the antenna.....	94
A.4.4	Antenna calibration	95
A.4.5	Antenna user information	95
Annex B (XXX) (Void)	96
Annex C (normative)	Large-loop antenna system for magnetic field induced-current measurements in the frequency range of 9 kHz to 30 MHz	97
C.1	General.....	97
C.2	Construction of an LLAS	97
C.3	Construction of a large-loop antenna (LLA)	97
C.4	Validation of an LLAS	102
C.5	Construction of the LLAS verification dipole antenna.....	105
C.6	Conversion factors	107
C.6.1	General.....	109
C.6.2	Current conversion factors for an LLAS with non-standard diameter	110
C.6.3	Conversion of LLAS measured current to magnetic field strength.....	111

C.7 Examples	113
Annex D (normative) Construction details for open area test sites in the frequency range of 30 MHz to 1 000 MHz (see Clause 6)	115
D.1 General.....	115
D.2 Ground plane construction	115
D.2.1 Material	115
D.2.2 Roughness	115
D.3 Services to EUT	116
D.4 Weather-protection enclosure construction	116
D.4.1 Materials and fasteners.....	116
D.4.2 Internal arrangements	117
D.4.3 Size	117
D.4.4 Uniformity with time and weather	117
D.5 Turntable and set-up table	117
D.6 Receive antenna mast installation.....	118
Annex E (xxx) (Void)	119
Annex F (informative) Basis for ± 4 dB site acceptability criterion (see Clause 6)	120
F.1 General.....	120
F.2 Error analysis.....	120
Annex G (informative) Examples of uncertainty budgets for site validation of a COMTS using RSM with a calibrated antenna pair (see 6.6)	122
G.1 Quantities to be considered for antenna pair reference site attenuation calibration using the averaging technique	122
G.2 Quantities to be considered for antenna pair reference site attenuation calibration using a REFTS	123
G.3 Quantities to be considered for COMTS validation using an antenna pair reference site attenuation	124
Annex H (informative) Definition of uncertainty in cross-polar response measurement	125
H.1 General.....	125
H.2 Example uncertainty estimate	127
H.3 Rationale for the estimates of input quantities in Table H.1 and Table H.3	128
H.4 Measurement of XPR below 100 MHz at an OATS	129
Annex I (informative) Measurement uncertainties of COMTS validation results in the frequency range 9 kHz to 30 MHz	131
I.1 Quantities to be considered for COMTS validation using the NSIL method	131
I.2 Quantities to be considered for COMTS validation using the RSM method	133
Annex J (normative) Derivation of NSIL values in the frequency range 9 kHz to 30 MHz	135
J.1 General.....	135
J.2 Magnetic field antenna factor	135
J.3 Site insertion loss	137
J.4 Normalized site insertion loss	138
J.5 NSIL tables	142
Annex K (informative) Recommendations for the design of test sites in the frequency range 9 kHz to 30 MHz	147
K.1 General.....	147
K.2 Dimensions and quality of the ground plane	147
K.3 Obstruction free area	148
K.4 Resonance-free area	148

Annex L (informative) Accuracy of NSIL values in the frequency range of 9 kHz to 30 MHz	150
L.1 General	150
L.2 Cross check of NEC with analytic formulas	150
L.3 Recommended NEC versions	151
L.4 Instabilities at the lower frequency end	152
L.5 Extrapolation methods to solve instabilities	152
L.6 Reducing the number of segments to solve instabilities	152
Annex M (informative) Example calculation for 10 m SACs that do not fulfil the ±4 dB criterion within 9 kHz to 30 MHz	153
Annex N (normative) Calibration of the sum of magnetic field antenna factors in the frequency range of 9 kHz to 30 MHz	156
N.1 General	156
N.2 Calibration procedure	156
N.3 Measurement uncertainties	157
Bibliography	159

Figure 34 – Example of size-compliant loop antenna	21
Figure 1 – Schematic of radiation from EUT reaching an LPDA antenna directly and via ground reflection at a 3 m site, showing the beamwidth half-angle, φ , at the reflected ray	24
Figure 2 – RX antenna E-plane radiation pattern example, with limit area shaded for 3 m distance and 2 m EUT width	28
Figure 3 – Determination of maximum useable EUT width using half-power beamwidth	29
Figure 4 – Determination of maximum useable EUT height using half-power beamwidth	29
Figure 35 – General arrangement of the three measurement orientations H_x , H_y and H_z , where d is the measurement distance and h is the height of the reference point	32
Figure 36 – Antenna positions	33
Figure 37 – Antenna positions	34
Figure 38 – Test set-up for V _{DIRECT} with power amplifier and attenuator	35
Figure 5 – Obstruction-free area of a test site with a turntable	38
Figure 6 – Obstruction-free area with stationary EUT	38
Figure 7 – Test point locations for 3 m and 10 m test distances	47
Figure 8 – Paired test point locations for all test distances	49
Figure 9 – Example of paired test point selection for a test distance of 10 m	49
Figure 10 – Illustration of an investigation of influence of antenna mast on APR	50
Figure 11 – Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements	53
Figure 12 – Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements	53
Figure 13 – Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements for a smaller EUT	54
Figure 14 – Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements for a smaller EUT	54
Figure 15 – Measurement positions for FAR site validation	57
Figure 16 – Example of one measurement position and antenna tilt for FAR site validation	59
Figure 17 – Typical quasi free-space test site reference SA measurement set-up	61

Figure 18 – Theoretical free-space NSA as a function of frequency for different measurement distances [see Equation (16)].....	63
Figure 19 – Position of the antenna relative to the edge above a rectangle set-up table (top view).....	65
Figure 20 – Antenna position above the set-up table (side view)	65
Figure 21 – Transmit antenna E-plane radiation pattern example (this example is for informative purposes only).....	69
Figure 22 – Transmit antenna H-plane radiation pattern (this example is for informative purposes only)	70
Figure 23 – S_{VSWR} measurement positions in a horizontal plane (see 7.5.2 for description).....	71
Figure 24 – S_{VSWR} positions (height requirements)	73
Figure 25 – S_{VSWR} conditional measurement position requirements	79
Figure 26 – Definition of the reference planes inside the test jig	81
Figure 27 – The four configurations for the TRL calibration	83
Figure 28 – Limits for the magnitude of S_{11} , measured according to the provisions of 8.1 to 8.3	84
Figure 29 – Example of a 50Ω adaptor construction in the vertical flange of the jig	85
Figure 30 – Example of a matching adaptor with balun or transformer	85
Figure 31 – Example of a matching adaptor with resistive matching network	86
Figure 32 – Example of a typical paddle stirrer	
Figure 33 – Range of coupling attenuation as a function of frequency for a chamber using the stirrer shown in Figure 32	
Figure A.1 – Short dipole antenna factors for $R_L = 50 \Omega$	93
Figure C.1 – The LLAS, consisting of three mutually perpendicular large-loop antennas	99
Figure C.2 – An LLA containing two opposite slits, positioned symmetrically with respect to the current probe C	100
Figure C.3 – Construction of an LLA slit.....	100
Figure C.4 – Example of an LLA slit construction using a strap of printed circuit board to obtain a rigid construction	101
Figure C.5 – Construction of the metal box containing the current probe.....	101
Figure C.6 – Example showing the routing of several cables from an EUT to minimize capacitive coupling from the leads to the LLAS	102
Figure C.7 – The eight positions of the LLAS verification dipole during validation of an LLA	103
Figure C.8 – Validation factor for an LLA of 2 m diameter Reference validation factors for loops of 2 m, 3 m, and 4 m diameters	104
Figure C.9 – Construction of the LLAS verification dipole antenna	107
Figure C.10 – Conversion factors C_{dA} [for conversion into dB($\mu\text{A}/\text{m}$)] and C_{dV} [for conversion into dB($\mu\text{V}/\text{m}$)] for two standard measuring distances d	
Figure C.11 – Sensitivity S_D of a large-loop antenna with diameter D relative to a large-loop antenna having a diameter of 2 m	
Figure C.10 – Sensitivity S_D of an LLA with diameter D relative to an LLA with 2 m diameter	110
Figure C.11 – Conversion factor C_{dA} [for conversion into dB($\mu\text{A}/\text{m}$)] for three standard measurement distances d	112
Figure D.1 – The Rayleigh criterion for roughness in the ground plane	116
Figure J.1 – Investigation of wire radius, normalized to 0,001 m	139

Figure J.2 – Investigation of feed point location (not to scale)	140
Figure J.3 – Variation of NSIL values for various set-ups, for a distance of 3 m, $h = 1,3$ m.....	142
Figure J.4 – Specification of feed point location for tabular values (not to scale).....	143
Figure J.5 – Calculation examples, loop diameter 60 cm, feed point location per Figure J.4	145
Figure K.1 – Recommended minimum dimensions of the ground plane (top view)	147
Figure K.2 – Recommended obstruction free area (top view)	148
Figure L.1 – Comparison of NSIL values by analytic formulas and computer simulation	151
Figure M.1 – Example site validation result.....	154
Figure M.2 – U_{lab} calculated from site validation result.....	155
Figure M.3 – Frequency-dependent correction factor	155
Figure N.1 – Antenna arrangement for the sum of antenna factors method	157
Table 9 – Maximum frequency step size	32
Table 10 – Acceptance criterion	36
Table 1 – Site validation methods applicable for OATS, OATS-based, SAC, and FAR site types	40
Table 2 – Theoretical normalized site attenuation, A_N – recommended geometries for broadband antennas ^a (1 of 2)	43
Table 3 – Example template for A_{APR} data sets	46
Table 4 – RSM frequency steps	46
Table 5 – Maximum dimensions of test volume versus test distance	55
Table 6 – Frequency ranges and step sizes for FAR site validation.....	59
Table 7 – S_{VSWR} measurement position designations (1 of 3).....	74
Table 8 – S_{VSWR} reporting requirements	79
Table C.1 – Reference validation factors of Figure C.8 for loops of 2 m, 3 m, and 4 m diameters.....	105
Table C.2 – Sensitivity S_D of an LLA with diameter D relative to an LLA with 2 m diameter (Figure C.10).....	111
Table C.3 – Magnetic field strength conversion factor C_{dA} for three measurement distances (Figure C.11).....	113
Table D.1 – Maximum roughness for 3 m, 10 m and 30 m measurement distances	116
Table F.1 – Error budget.....	120
Table G.1 – Antenna pair reference site attenuation calibration using the large-OATS averaging technique.....	122
Table G.2 – Antenna pair reference site attenuation calibration using REFTS	123
Table G.3 – COMTS validation using an antenna pair reference site attenuation.....	124
Table H.1 – Example uncertainty estimate for XPR measurement in a FAR and assumed $\alpha_{\text{xpT}} = 22$ dB, $\alpha_{\text{xpR}} = 34$ dB	128
Table H.2 – Uncertainties depending on other values of A_{xpT} (other assumptions as in Table H.1).....	129
Table H.3 – Example uncertainty estimate for XPR measurement at an OATS and assumed $\alpha_{\text{xpT}} = 22$ dB, $\alpha_{\text{xpR}} = 34$ dB	130
Table I.1 – Example measurement uncertainty budget for COMTS validation using the NSIL method	131

Table I.2 – Example measurement uncertainty budget for COMTS validation using the RSM method	133
Table J.1 – Calculation examples (loop diameter 60 cm, $d = 3$ m, $h = 1,3$ m)	145
Table J.2 – Calculation examples (loop diameter 60 cm, $d = 5$ m, $h = 1,3$ m)	145
Table J.3 – Calculation examples (loop diameter 60 cm, $d = 10$ m, $h = 1,3$ m)	146
Table K.1 – Skin depth for some practical materials at 9 kHz	148
Table L.1 – Recommended NEC implementations	151
Table L.2 – Observed instabilities	152
Table M.1 – Measurement uncertainty of radiated disturbance results from 9 kHz to 30 MHz	153
Table M.2 – Influence of δA_j on U_{lab}	153
Table N.1 – Example of an uncertainty budget for sum of antenna factors method	157

iTeh STANDARD PREVIEW (standards.iteh.ai)

[CISPR 16-1-4:2019](#)

<https://standards.iteh.ai/catalog/standards/sist/99f4288-add7-4c2e-b215-e836bfff67d/cispr-16-1-4-2019>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

CISPR 16-1-4 edition 4.2 contains the fourth edition (2019-01) [documents CIS/A/1262/FDIS and CIS/A/1275/RVD], its amendment 1 (2020-06) [documents CIS/A/1316/FDIS and CIS/A/1320/RVD] and its amendment 2 (2023-04) [documents CIS/A/1389/FDIS and CIS/A/1393/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- provisions are added to address test site validation in the frequency range from 30 MHz to 1000 MHz using the reference site method, to take into account the receive antenna radiation pattern in the frequency range from 1 GHz to 18 GHz, and further details on test site validation using the NSA method with broadband antennas in the frequency range from 30 MHz to 1 000 MHz.

International Standard CISPR 16-1-4 has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

It has the status of a basic EMC publication in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of CISPR 16 series, under the general title *Specification for radio disturbance and immunity measuring apparatus and methods*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

[CISPR 16-1-4:2019](#)

[1-4-2019](#)

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.