



SLOVENSKI STANDARD
SIST EN 50518-2:2010/AC:2011
01-oktober-2011

**Nadzorni in sprejemni centri za alarme - 2. del: Zahteve za tehnične zmogljivosti -
Popravek**

Monitoring and alarm receiving centre - Part 2: Requirements for technical facilities

Notruf- und Serviceleitstellen (NSL) - Teil 2: Anforderungen an die technische
Ausrüstung

Centre de contrôle et de réception (d'alarme - Partie 2: Exigences pour les installations
techniques

iTeh STANDARD PREVIEW

(standards.iteh.ai)

[SIST EN 50518-2:2010/AC:2011](https://standards.iteh.ai/catalog/standards/sist/4bdef24e-2971-4ec7-a0d0-6001681188cd/sist-en-50518-2-2010-ac-2011)

Ta slovenski standard je istoveten z: EN 50518-2:2010/AC:2011

ICS:

13.320 Alarmni in opozorilni sistemi Alarm and warning systems

SIST EN 50518-2:2010/AC:2011 en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50518-2:2010/AC:2011](https://standards.iteh.ai/catalog/standards/sist/4bdeff4e-2971-4ec7-a0d0-6001881f88ed/sist-en-50518-2-2010-ac-2011)

<https://standards.iteh.ai/catalog/standards/sist/4bdeff4e-2971-4ec7-a0d0-6001881f88ed/sist-en-50518-2-2010-ac-2011>



Corrigendum to EN 50518-2:2010

English version

3.2 Abbreviations

Add:

I&HAS Intrusion and Hold-up Alarm System(s)

Annex A ARC availability calculations

Replace:

$$FT_3 = (4 \times 30) = 60 \text{ min}$$

by:

$$FT_3 = (4 \times 30) = 120 \text{ min}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/4bdef4e-2971-4ec7-a0d0-6001881f88ed/sist-en-50518-2-2010-ac-2011>

Replace:

$$SF = 540 + 244 + 60 = 884 \text{ min}$$

by:

$$SF = 540 + 244 + 120 = 904 \text{ min}$$

Replace:

$$MA = \left(1 - \frac{884}{43\,800}\right) \times 100 = 98,07 \%$$

by:

$$MA = \left(1 - \frac{904}{43\,800}\right) \times 100 = 97,94 \%$$
