

SLOVENSKI STANDARD SIST EN 3841-506:2005

01-april-2005

Aeronavtika - Odklopniki - Preskusne metode - 506. del: Lastnosti vibracij

Aerospace series - Circuit breakers - Test methods - Part 506: Vibration performance

Luft- und Raumfahrt - Schutzschalter - Prüfverfahren - Teil 506: Schwingungsverhalten iTeh STANDARD PREVIEW

Série aérospatiale - Disjoncteurs - Méthodes d'essais - Partie 506 : Tenue aux vibrations

Ta slovenski standard je istoveten 2: SISTEN 3841-506:2004 https://standards.iteh.avcatalog/stan

633dbcb035a5/sist-en-3841-506-2005

ICS:

Š^œ+\æ4 Å;^•[|b\æ Aerospace electric ^|^\dã}æ4]!^{ æ4 Áã¢\ ã equipment and systems 49.060

SIST EN 3841-506:2005 en SIST EN 3841-506:2005

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 3841-506

December 2004

ICS 49.060

English version

Aerospace series - Circuit breakers - Test methods - Part 506: Vibration performance

Série aérospatiale - Disjoncteurs - Méthodes d'essais -Partie 506 : Tenue aux vibrations Luft- und Raumfahrt - Schutzschalter - Prüfverfahren - Teil 506: Schwingungsverhalten

This European Standard was approved by CEN on 10 September 2004.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

<u>SIST EN 3841-506:2005</u> https://standards.iteh.ai/catalog/standards/sist/59f9ed7b-79ef-4d89-b7d9-633dbcb035a5/sist-en-3841-506-2005



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents		
Fore	eword	3
1	Scope	4
2	Normative references	4
3	Method	4
3.1	Mounting	4
3.2	Procedure	4
	Poguiroment	E

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

This document (EN 3841-506:2004) has been prepared by the European Association of Aerospace Manufacturers - Standardization (AECMA-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of AECMA, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2005, and conflicting national standards shall be withdrawn at the latest by June 2005.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

EN 3841-506:2004 (E)

1 Scope

This standard specifies a method of verifying the vibration performance of circuit breakers.

It shall be used together with EN 3841-100.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7137, Aircraft – Environmental conditions and test procedures for airborne equipment

EN 3841-100, Aerospace series – Circuit breakers – Test methods – Part 100: General

MIL-STD-810F, Environmental engineering considerations and laboratory tests 1)

3 Method

3.1 Mounting iTeh STANDARD PREVIEW

The circuit breakers shall be mounted on the vibrator according to 4.2 and 4.3 of EN 3841-100. The means of mounting shall be designed so as to transmit vibrations over the whole frequency range without absorption or natural resonance.

SIST EN 3841-506:2005

https://standards.iteh.ai/catalog/standards/sist/59f9ed7b-79ef-4d89-b7d9-

The electrical connection shall be made with the cables of the sections specified in EN 3841-100, Table 1. The connection cables shall be attached to the vibration support approximately 100 mm from the terminals. The circuit breakers and the cables shall be mounted with the torque indicated in the product standard.

3.2 Procedure

The circuit breakers shall be subjected to:

- the sinusoidal vibration test according to ISO 7137, test procedure 2.2;
- the random vibration test according to ISO 7137, test procedure 2.2;
- sinusoidal vibration test at low frequencies according to ISO 7137, test procedure 2.2;
- the gunfire vibration test according to MIL-STD-810F, method 519.3, if specified.

The test shall be carried out in three mounting positions along the main axis of the circuit breakers, in the closed and open position.

The test conditions and vibration values shall conform to the technical specification.

¹⁾ Published by: Department of Defense (DOD), the Pentagon, Washington D.C. 20301 USA.

The test periods at sinusoidal vibration shall include determination of the resonant frequencies and a period to be determined as follows:

— resonance: if applicable, 30 min per resonance;

— sweep: remainder of total time specified.

During the test the contacts do not close for a period \geq 10 µs (circuit breakers in the open position) or open for a period \geq 10 µs (circuit breakers in the closed position).

3.3 Requirement

Requirements in accordance with technical specification and product standard.

iTeh STANDARD PREVIEW (standards.iteh.ai)