

ETSI TS 102 545-2 V1.2.1 (2009-03)

Technical Specification

Broadband Radio Access Networks (BRAN); HiperMAN; Conformance Testing for WiMAX/HiperMAN 1.3.1; Part 2: Test Suite Structure and Test Purposes (TSS&TP)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/56c063b2-ab5e-4a03-a880-7c82dadf7b8/etsi-ts-102-545-2-v1.2.1-2009-03>



Reference

 RTS/BRAN-004T008-2-R1

Keywords

 ATS, broadband, DLC, FWA, HiperMAN, MAC, point-to-multipoint, radio, testing, TSS&TP
ETSI

 650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

 Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse (06) N° 7803/88
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp
Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.

© WIMAX Forum 2009.

All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions.....	10
3.2 Abbreviations	10
4 Test Suite Structure (TSS).....	12
4.1 Structure	12
4.2 Test groups	15
4.2.1 Protocol services.....	15
4.2.1.1 Packet convergence sublayer Encapsulation.....	15
4.2.1.2 Packet convergence sublayer Classification.....	15
4.2.1.3 Payload Header Suppression.....	15
4.2.1.4 MAC PDU Formats.....	15
4.2.1.5 ARQ	15
4.2.1.6 Radio Link Control (RLC)	15
4.2.1.7 Registration, IP connectivity and TFTP.....	15
4.2.1.8 Dynamic services	15
4.2.1.9 Bandwidth allocation and polling.....	16
4.2.1.10 General Handover functionality.....	16
4.2.1.11 Sleep mode.....	16
4.2.1.12 Idle mode	16
4.2.1.13 Multicast Traffic connections.....	16
4.2.1.14 Supported Cryptographic Suites.....	16
4.2.1.15 Privacy and key management.....	16
4.2.1.16 Security version 2.....	16
4.2.1.17 Channel descriptors and maps.....	16
4.2.1.18 Multicast and Broadcast Services	16
4.2.1.19 Adaptive Antenna Support.....	16
4.2.1.20 Reset and re-registration	16
4.2.1.21 Clock comparison	17
4.2.2 Main test types.....	17
4.2.2.1 Valid Behaviour (BV) tests.....	17
4.2.2.2 Invalid Behaviour (BI) tests	17
4.2.2.3 Inopportune Behaviour (BO) tests	17
4.2.2.4 Timer and counter (TI) tests.....	17
5 Test Purposes (TP)	17
5.1 Introduction	17
5.1.1 TP definition conventions.....	17
5.1.2 TP Identifier naming conventions.....	18
5.1.3 Sources of TP definitions.....	20
5.1.4 TP selection criteria name convention.....	21
5.2 Test purposes for BS (BS).....	22
5.2.1 CS Options: Encapsulation (CSOE)	22
5.2.1.1 IP version 4 (IP4)	22
5.2.1.2 IP version 6 (IP6).....	22
5.2.1.3 IP version 4 with ROHC (IP4R)	23
5.2.1.4 IP version 6 with ROHC (IP6R)	23
5.2.1.5 Ethernet (ENET)	24
5.2.1.6 IP version 4 over Ethernet.....	24

5.2.1.7	IP version 6 over Ethernet.....	25
5.2.2	CS Options: Classification.....	25
5.2.2.1	Classifier DSx Signalling (CDS).....	26
5.2.2.2	IPv4 classification (IP4C).....	27
5.2.2.3	IPv6 classification (IP6C).....	29
5.2.2.4	Ethernet classification (ENTC).....	30
5.2.2.4.1	Pure Ethernet Classification (PETC).....	30
5.2.2.4.2	IPv4 over Ethernet (IP4oE).....	31
5.2.2.4.3	IPv6 over Ethernet (IP6oE).....	34
5.2.2.5	VLAN (VLAN).....	36
5.2.2.5.1	IP over VLAN (IPoV).....	36
5.2.3	Payload Header Suppression (PHS).....	37
5.2.4	MAC PDU Construction (MAC).....	43
5.2.4.1	PDU Concatenation (CAT).....	47
5.2.4.2	Fragmentation (FRAG).....	47
5.2.4.3	Packing (PACK).....	50
5.2.4.4	Cyclic Redundancy Check (CRC).....	51
5.2.5	Automatic Repeat Request (ARQ).....	52
5.2.5.1	Receiver Operations (RXD).....	54
5.2.5.2	Transmit Data (TXD).....	57
5.2.5.3	Reset (RE).....	62
5.2.6	Radio Link Control (RLC).....	65
5.2.6.1	Initial Ranging (IRNG).....	65
5.2.6.2	Periodic Ranging (PRNG).....	70
5.2.6.3	Downlink Burst Profile Management (DBPC).....	73
5.2.6.3.1	Change to a Less Robust Profile (LRP).....	74
5.2.6.3.2	Change to a More Robust Profile (MRP).....	74
5.2.6.4	Negotiate Basic Capabilities (SBC).....	75
5.2.6.5	Feedback Mechanism (FBK).....	76
5.2.6.5.1	Feedback Polling.....	76
5.2.6.5.2	Fast-Feedback.....	76
5.2.6.6	MAC-support for HARQ (HARQ).....	77
5.2.6.6.1	DL HARQ Operation.....	77
5.2.6.6.2	UL HARQ Operation.....	79
5.2.7	Registration, IP Connectivity and Parameter Transfer (INI).....	80
5.2.7.1	Registration (REG).....	80
5.2.7.2	IP Connectivity (IPC).....	81
5.2.8	Dynamic Services (DS).....	83
5.2.8.1	Dynamic Services Addition (DSA).....	83
5.2.8.2	Dynamic Services Change (DSC).....	96
5.2.8.3	Dynamic Services Deletion (DSD).....	111
5.2.8.4	QoS Parameter Sets (QPS).....	118
5.2.9	Bandwidth Allocation and Polling (BWA).....	128
5.2.9.1	CDMA Bandwidth Request (CBR).....	130
5.2.9.2	Request/Grant (REQ).....	130
5.2.9.3	Multicast Polling (MCP).....	137
5.2.10	General Handover Functionality (GHF).....	140
5.2.10.1	Network topology acquisition (NTA).....	140
5.2.10.1.1	Network advertisement (NWA).....	140
5.2.10.1.2	Scanning (SCAN).....	140
5.2.10.2	HO process (HO).....	141
5.2.10.2.1	Process at Serving BS (SVG).....	141
5.2.10.2.2	Process at Target BS (TGT).....	144
5.2.11	Sleep Mode (SLM).....	147
5.2.11.1	Power Saving Class Type 1 (PW1).....	147
5.2.11.2	Power Saving Class Type 2 (PW2).....	151
5.2.11.3	Power Saving Class Type 3 (PW3).....	151
5.2.11.4	Periodic Ranging during Sleep Mode (PRSM).....	151
5.2.12	Idle Mode (IDM).....	152
5.2.12.1	Transition to Idle Mode (TDIM).....	152
5.2.12.1.1	Valid Behaviour.....	152
5.2.12.1.2	Timer.....	153

5.2.12.2	Paging (PG).....	153
5.2.12.3	Power Down Update (PWD).....	154
5.2.12.4	Network Re-Entry (NWR)	155
5.2.12.5	Location update (LOC)	157
5.2.13	Multicast Traffic Connections (MTC).....	158
5.2.14	Supported Cryptographic Suites (SCS).....	158
5.2.14.1	No data encryption, No data authentication and No key encryption	158
5.2.14.2	CCM-mode 128-bit AES, CCM-Mode and AES Key Wrap with 128-bit key (AES)	159
5.2.15	Privacy and Key Management (PKM).....	160
5.2.15.1	PKM Version 1 Authentication/Authorization (AUTH1).....	160
5.2.15.1.1	Initialization (INIT).....	160
5.2.15.1.2	Operational (OPN).....	165
5.2.15.2	Encryption Key Transfer (TEK)	168
5.2.15.2.1	Initialization (INIT).....	168
5.2.15.2.2	Operational (OPN).....	170
5.2.15.3	Security Association Management (SAM).....	172
5.2.15.4	Encryption and Key Scheduling (EKS).....	173
5.2.15.4.1	Key Usage (KU)	174
5.2.15.4.2	Encryption (ENC).....	175
5.2.15.4.3	Decryption (DEC)	177
5.2.15.5	Certificates (CERT)	179
5.2.16	Security version 2 (SEC)	179
5.2.16.1	BS/SEC/PKMv2/AUTH/NWE - Initial Network Entry.....	179
5.2.16.2	BS/SEC/PKMv2/AUTH/REA - Reauthorization.....	180
5.2.16.3	BS/SEC/PKMv2/AUTH/HAN - Handover process	180
5.2.16.3a	BS/SEC/PKMv2/AUTH/IDM - Idle Mode	183
5.2.16.4	BS/SEC/PKMv2/AUTH/AKI - Initial authorization AK.....	184
5.2.16.5	BS/SEC/PKMv2/AUTH/AKR - Reauthorization AK.....	185
5.2.16.6	BS/SEC/PKMv2/TEK - Traffic Encryption Key	186
5.2.16.7	BS/SEC/PKMv2/GSA - Group Security Association	187
5.2.17	Channel Descriptors and Maps (CDM)	187
5.2.17.1	Map and Frame Structure (MFS)	187
5.2.17.2	Channel Descriptors (CD).....	190
5.2.17.3	Channel Descriptor Change (CDC).....	192
5.2.17.3.1	Uplink (UL).....	192
5.2.17.3.2	Downlink (DL)	193
5.2.17.4	MAP IEs (MAP)	195
5.2.18	Multicast and Broadcast Services (MBS)	196
5.2.19	Adaptive Antenna Support (AAS).....	198
5.2.20	Reset and Re-registration (RER)	200
5.2.21	Clock Comparison (CCC).....	202
5.3	Test purposes for SS (SS).....	202
5.3.1	CS Options: Encapsulation (CSOE)	202
5.3.1.1	IP version 4 (IP4)	202
5.3.1.2	IP version 6 (IP6)	203
5.3.1.3	IP version 4 with ROHC/ECRTP (IP4R).....	203
5.3.1.4	IP version 6 with ROHC/ECRTP (IP6R).....	204
5.3.1.5	Ethernet (ENET)	204
5.3.1.6	IP version 4 over Ethernet (IP4oE)	205
5.3.1.7	IP version 6 over Ethernet (IP6oE)	205
5.3.2	CS Options: Classification (CSOC).....	205
5.3.2.1	Classifier DSx Signalling (CDS).....	205
5.3.2.2	IPv4 Classification (IP4C)	207
5.3.2.3	IPv6 Classification (IP6C)	209
5.3.2.4	Ethernet Classification (ENTC)	211
5.3.2.4.1	Pure Ethernet Classification (PETC).....	211
5.3.2.4.2	IPv4 over Ethernet (IP4oE)	212
5.3.2.4.3	IPv6 over Ethernet (IP6oE)	215
5.3.2.5	VLAN (VLAN).....	217
5.3.2.5.1	IP over VLAN (IPoV)	217
5.3.3	Payload Header Suppression (PHS).....	218
5.3.4	MAC PDU Construction (MAC).....	222

5.3.4.1	PDU Concatenation (CAT)	225
5.3.4.2	Fragmentation (FRAG)	225
5.3.4.3	Packing (PACK)	227
5.3.4.4	Cyclic Redundancy Check (CRC).....	228
5.3.5	Automatic Repeat Request (ARQ).....	230
5.3.5.1	Receiver Operations (RXD).....	232
5.3.5.2	Transmitter Operations (TXD).....	235
5.3.5.3	Reset (RE).....	239
5.3.6	Radio Link Control (RLC).....	242
5.3.6.1	Initial Ranging (IRNG)	242
5.3.6.2	Periodic Ranging (PRNG).....	249
5.3.6.3	Downlink Burst Profile Management (DBPC).....	261
5.3.6.3.1	To a Less Robust Profile (LRP)	261
5.3.6.3.2	To a More Robust Profile (MRP)	263
5.3.6.4	Negotiate Basic Capabilities (SBC)	267
5.3.6.5	Feedback Mechanism (FBK)	269
5.3.6.5.1	Feedback Polling	269
5.3.6.5.2	Fast-Feedback.....	270
5.3.6.5.3	Channel Reporting.....	272
5.3.6.6	MAC-support for HARQ (HARQ)	273
5.3.6.6.1	UL HARQ Operation	274
5.3.7	Registration, IP Connectivity and Parameter Transfer (INI)	276
5.3.7.1	Registration (REG).....	276
5.3.7.2	IP Connectivity (IPC).....	279
5.3.8	Dynamic Services (DS)	281
5.3.8.1	Dynamic Services Addition (DSA).....	281
5.3.8.2	Dynamic Services Change (DSC).....	293
5.3.8.3	Dynamic Services Deletion (DSD).....	306
5.3.8.4	QoS Parameter Sets (QPS).....	309
5.3.9	Bandwidth Allocation and Polling (BWA).....	314
5.3.9.1	CDMA Bandwidth Request (CBR).....	314
5.3.9.2	Request/Grant (REQ).....	315
5.3.9.3	Multicast Polling (MCP)	320
5.3.10	General Handover Functionality (GHF).....	322
5.3.10.1	Network Topology Acquisition (NTA).....	322
5.3.10.1.1	Network advertisement (NWA).....	322
5.3.10.1.2	Scanning (SCAN).....	322
5.3.10.2	HO process (HO)	324
5.3.10.2.1	HO initiation (INI).....	324
5.3.10.2.2	HO cancellation (CCL).....	326
5.3.10.2.3	HO Termination (TER)	327
5.3.10.2.4	Drops during HO (DRO).....	328
5.3.10.3	Network Re-Entry (NWR)	328
5.3.11	Sleep Mode (SLM)	331
5.3.11.1	Power saving class type 1 (PW1).....	331
5.3.11.1.1	Valid behaviour	331
5.3.11.1.2	Timer	336
5.3.11.2	Power saving class type 2 (PW2).....	336
5.3.11.3	Power saving class type 3 (PW3).....	336
5.3.11.4	Periodic Ranging during Sleep Mode (PRSM)	337
5.3.12	Idle Mode (IDM)	338
5.3.12.1	Transition to Idle Mode (TDIM).....	338
5.3.12.1.1	Valid Behaviour.....	338
5.3.12.1.2	Timer	339
5.3.12.2	Broadcast Paging message (PG)	340
5.3.12.3	Power Down Update (PWD).....	340
5.3.12.4	Network Re-Entry (NWR)	340
5.3.12.5	Location Update (LOC)	342
5.3.13	Multicast Traffic Connections (MTC).....	343
5.3.14	Supported Cryptographic Suites (SCS).....	343
5.3.14.1	No data encryption, No data authentication and No key encryption	343
5.3.14.2	CCM-mode 128-bit AES, CCM-Mode and AES Key Wrap with 128-bit key (AES)	344

5.3.15	Privacy and Key Management (PKM).....	345
5.3.15.1	PKM Version 1 Authentication/Authorization (AUTH1)	345
5.3.15.1.1	Initialization (INIT).....	345
5.3.15.1.2	Operational (OPN).....	350
5.3.15.2	Encryption Key Transfer (TEK)	355
5.3.15.2.1	Initialization (INIT).....	355
5.3.15.2.2	Operational (OPN).....	358
5.3.15.3	Security Association Management (SAM).....	365
5.3.15.4	Encryption and Key Scheduling (EKS).....	366
5.3.15.4.1	Key Usage (KU).....	366
5.3.15.4.2	Encryption (ENC).....	368
5.3.15.4.3	Decryption (DEC)	371
5.3.15.5	Certificates (CERT)	375
5.3.16	Security version 2 (SEC)	379
5.3.16.1	SS/SEC/PKMv2/AUTH/NWE - Initial Network Entry	379
5.3.16.2	SS/SEC/PKMv2/AUTH/REA - Reauthorization	381
5.3.16.2a	SS/SEC/PKMv2/AUTH/HAN - Handover Process	383
5.3.16.2b	SS/SEC/PKMv2/AUTH/IDM - Idle Mode	384
5.3.16.3	SS/SEC/PKMv2/AUTH/TEK - Initial authorization TEK.....	386
5.3.16.4	SS/SEC/PKMv2/AUTH/EAP/FSM - EAP Auth FSM.....	386
5.3.16.5	SS/SEC/PKMv2/TEK/FSM - TEK FSM	397
5.3.17	Channel Descriptors and Maps (CDM)	402
5.3.17.1	Map and Frame Structure (MFS)	402
5.3.17.1.1	Initialization (INIT).....	402
5.3.17.1.2	Operational (OPN).....	404
5.3.17.1.3	Relevance (RLV).....	405
5.3.17.2	Channel Descriptors (CD).....	406
5.3.17.3	Channel Descriptor Change (CDC).....	407
5.3.17.3.1	Uplink (UL).....	407
5.3.17.3.2	Downlink (DL).....	408
5.3.17.4	MAP IEs (MAP)	409
5.3.18	Multicast and Broadcast Services (MBS).....	411
5.3.19	Adaptive Antenna Support (AAS).....	412
5.2.20	Reset and Re-registration (RER)	413
5.3.21	Clock Comparison (CCC).....	416
Annex A (informative):	Bibliography	417
History		418

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN).

The present document is part 2 of a multi-part deliverable covering Broadband Radio Access Networks (BRAN); HiperMAN; Conformance Testing for WiMAX/HiperMAN 1.3.1, as identified below:

Part 1: "Protocol Implementation Conformance Statement (PICS) proforma";

Part 2: "Test Suite Structure and Test Purposes (TSS&TP)";

Part 3: "Abstract Test Suite (ATS)".

PRELIMINARY
iTech STANDARD
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/52a06362-ab5e-4a03-a880-7c82dad7b8/etsi-ts-102-545-2-v1.2.1-2009-03>

1 Scope

The present document contains the Test Suite Structure (TSS) and Test Purposes (TP) to test the BRAN HiperMAN Data Link Control (DLC) layer.

The objective of the present document is to provide a basis for conformance tests for HiperMAN equipment giving a high probability of air interface inter-operability between different manufacturers' HiperMAN equipment.

The ISO standard for the methodology of conformance testing (ISO/IEC 9646-1 [5] and ISO/IEC 9646-2 [6]) as well as the ETSI rules for conformance testing (ETS 300 406 [4]) are used as a basis for the test methodology.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI TS 102 178 (V1.3.1): "Broadband Radio Access Networks (BRAN); HiperMAN; Data Link Control (DLC) Layer".
- [2] IEEE P802.16 (2004): "Standard for Local and Metropolitan Area Networks - Part 16: Air Interface for Fixed Broadband Wireless Access Systems".
- [3] IEEE 802.16e-2005 and IEEE 802.16-2004/Cor 1-2005: "IEEE Standard for Local and Metropolitan Area Networks - Part 16: Air Interface for Fixed and Mobile Broadband Wireless Access Systems. Amendment for Physical and Medium Access Control Layers for Combined Fixed and Mobile Operation in Licensed Bands".
- [4] ETSI ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [5] ISO/IEC 9646-1 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts". (See also ITU-T Recommendation X.290 (1991)).
- [6] ISO/IEC 9646-2 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification". (See also ITU-T Recommendation X.291 (1991)).

- [7] ISO/IEC 9646-6 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 6: Protocol profile test specification".
- [8] ISO/IEC 9646-7 (1995): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [9] IEEE 802.3: "IEEE Standard for Information technology-Telecommunications and information exchange between systems-Local and metropolitan area networks-Specific requirements Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications".
- [10] ISO 3166: "Codes for the representation of names of countries and their subdivisions".
- [11] ETSI TS 102 545-1: "Broadband Radio Access Networks (BRAN); HiperMAN; Conformance Testing for WiMAX/HiperMAN 1.3.1; Part 1: Protocol Implementation Conformance Statement (PICS) proforma".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ISO/IEC 9646-7 [8], TS 102 178 [1], IEEE P802.16-2004 [2] and IEEE 802.16e-2005 [3] apply.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in ISO/IEC 9646-1 [5], ISO/IEC 9646-6 [7], ISO/IEC 9646-7 [8], TS 102 178 [1], IEEE P802.16-2004 [2], IEEE 802.16e-2005 [3] and the following apply:

AAS	Adaptive Antenna System
ACK	ACKnowledgment
AES	Advanced Encryption Standard
AK	Authorization Key
ARQ	Automatic Repeat reQuest
ATM	Asynchronous Transfer Mode
AUTH	AUTHentication/AUTHorization
BE	Best Effort
BI	Invalid Behaviour
BO	inOpportune Behaviour
BPSK	Binary Phase Shift Keying
BS	Base Station
BSN	Block Sequence Number
BV	Valid Behaviour
BW	BandWidth
CBC	Cipher Block Chaining
CC	Chase Combining
CD	Channel Descriptors
CDC	Channel Descriptor Change
CDM	Channel Descriptors and Maps
CDS	Classifier DSx Signalling

CERT	Certificates
CID	Connection IDentifier
CINR	Carrier to noise and INterference Ratio
CRC	Cyclic Redundancy Check
CS	Convergence Sublayer
DBPC	Downlink Burst Profile Change Request
DCD	Downlink Channel Descriptor
DEC	Decryption
DES	Data Encryption Standard
DIUC	Downlink Interval Usage Code
DL	DownLink
DLC	Data Link Control layer
DS	Dynamic Services
DSA	Dynamic Service Addition
DSC	Dynamic Service Change
DSD	Dynamic Service Deletion
DSx	Dynamic Service addition, change or deletion
ECB	Electronic Control Block
EKS	Encryption and Key Scheduling
ENC	Encryption
ENET	Ethernet
FC	Frame Count
FDD	Frequency Division Duplexing
FPC	Fast Power Control
FRAG	Fragmentation
FSM	Finite State Machine
FWA	Fixed Wireless Access
HARQ	Hybrid Automatic Repeat Request
HMAC	Hashed Message Authentication Code
HT	Header Type
IE	Information Element
INI	Registration, IP Connectivity, and Parameter Transfer
INIT	Initialization
IP	IPv4 and IPv6
IPC	IP Connectivity
IRNG	Initial Ranging
IUT	Implementation Under Test
KEK	Key Encryption Key
KU	Key Usage
LRP	To a Less Robust Profile
MAC	Medium Access Control
MAP	Map and Frame Structure
MCP	Multicast Polling
MRP	To a More Robust Profile
NACK	Negative ACKnowledgment
OFDM	Orthogonal Frequency Division Multiplexing
OFDMA	Orthogonal Frequency Division Multiple Access
OPN	Operation
PACK	Packing
PDU	Protocol Data Unit
PHS	Payload Header Suppression
PKM	Privacy and Key Management
PMP	Point-to-MultiPoint
PRNG	Periodic Ranging
QoS	Quality of Service
QPS	QoS Parameter Sets
RE	Reset
REG	Registration
REQ	REQuest
RER	Reset and Re-registration
RLC	Radio Link Control
RLV	Relevance

RNG	RaNGing
RSP	ReSPonse
RXD	Receive Data
SA	Security Association
SAID	Security Association IDentity
SAM	Security Association Management
SAP	Service Access Point
SBS	Serving Base Station
SBC	Negotiate Basic Capabilities
SDU	Service Data Unit
SET	Setup
SF	Service Flow
SS	Subscriber Station
TBS	Target Base Station
TDD	Time Division Duplexing
TEK	Encryption Key Transfer
TFTP	Trivial File Transfer Protocol
TI	Timer and counter
TLV	Type, Length, Value
TP	Test Purposes
TSS	Test Suite Structure
TXD	Transmit Data
UCD	Uplink Channel Descriptor
UGS	Unsolicited Grant Service
UL	Uplink
VLAN	Virtual Local Area Network

4 Test Suite Structure (TSS)

4.1 Structure

Figure 1 shows the DLC Test Suite Structure (TSS) including its subgroups defined for conformance testing.

Group	Function	Sub-function
CS options: Encapsulation		
	Ipv4	
	Ipv6	
	Ipv4 with ROHC / EC RTP	
	Ipv6 with ROHC / EC RTP	
	Ethernet	
	Ipv4 over Ethernet	
	Ipv6 over Ethernet	
CS options: Classification		
	Classifier DSx Signalling	
	Ipv4 Classification	
		General Ipv4 classification
		Ipv4 classification with ROHC
		Ipv4 classification with EC RTP
	Ipv6 Classification	
		General Ipv6 classification
		Ipv6 classification with ROHC
		Ipv6 classification with EC RTP
	Ethernet classification	
		Pure Ethernet classification
		Ipv4 over Ethernet <Includes ROHC and EC RTP>
		Ipv6 over Ethernet <Includes ROHC and EC RTP>
Payload Header Suppression		
MAC PDU Formats		
	PDU concatenation	

Group	Function	Sub-function
	Fragmentation	
	Packing	
	CRC	
ARQ		
	Receiver operations	
	Transmitter operations	
	Reset	
Radio Link Control (Initial Network Entry and MAC Support of PHY layer)		
	Initial Ranging	
	Periodic Ranging	
	Downlink Burst Profile Management	
		To a Less Robust Profile
		To a More Robust Profile
	Negotiate Basic Capabilities	
	Feedback mechanism	
	MAC support for H-ARQ	
	Support of different MAP IEs	TBD list of functions in terms of DL-MAP IEs and UL-MAP IEs; MAP Relevance
Registration, IP connectivity and TFTP		
	Registration	
	IP Connectivity	
Dynamic Services (Service flow management)		
	Service Addition	
	Service Change	
	Service Deletion	
	QoS Parameter Sets	
Bandwidth Allocation and Polling		
	CDMA Bandwidth Request	
	Request/Grant mechanism	
	Multicast polling	
General Handover functionality		
	Network topology acquisition	
		Network Advertisement
		Scanning
		Association
	HO initiation <operations with Serving BS>	
		Initiated by MS
		Initiated by BS
	Network Re-Entry	
		Acquisition of DL and UL parameters
		HO Ranging
		Capabilities Exchange
		EAP based Authentication/ Authorization
		Registration
	HO optimization	< All options prescribed by the Mobility Profile >
Sleep mode		
	General functions	
	Power saving class type 1	
	Power saving class type 2	< Leave empty >
	Power saving class type 3	< Leave empty >
	Periodic ranging during Sleep Mode	
Idle mode		
	Transition to Idle Mode	
	Paging	