

SLOVENSKI STANDARD
SIST EN 300 392-12-3 V1.3.1:2006
01-julij-2006

Df]nYa b]`gbcdcj b]`fUX]c`fH9HF5ŁĘ; c j cf]b`dcXUh_`fUŽ8ŁĘ%&"XY. `8cdc`b]`bY
għcf]hj Ygħċċdb`Y' "dcXXY. →Ybhżi_UWYU[c j cfY Y[U i XY Yħi YbWUfHDŁ

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 3: Talking Party Identification (TPI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [SIST EN 300 392-12-3 V1.3.1:2006](https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b0fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006)
[EN 300 392-12-3 Version 1.3.1](https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b0fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006)
[dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006](https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b0fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006)

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	------------------------------------	--------------------------------------

SIST EN 300 392-12-3 V1.3.1:2006 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 392-12-3 V1.3.1:2006](#)

<https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b6fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006>

ETSI EN 300 392-12-3 V1.3.1 (2006-04)

European Standard (Telecommunications series)

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 12: Supplementary services stage 3;
Sub-part 3: Talking Party Identification (TPI)**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 300 392-12-3 V1.3.1:2006

<https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b6fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006>



Reference

REN/TETRA-03167

Keywords

air interface, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 392-12-3 V1.3.1:2006](#)

<https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b6fc-dc267c4f8e07?format=pdf&version=3-v1-3-1-2006>

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	8
2 References	8
3 Definitions and abbreviations.....	9
3.1 Definitions	9
3.2 Abbreviations	10
4 SS-TPI service description.....	10
4.1 General	10
4.2 SS-TPI services offered over the TNSSSAP	10
4.2.1 ACTIVATE indication	11
4.2.2 ACTIVATE request	12
4.2.3 DEFINE indication	12
4.2.4 DEFINE request.....	12
4.2.5 INFORM indication.....	13
4.2.6 INTERROGATE indication.....	13
4.2.7 INTERROGATE request.....	13
4.2.8 INTERROGATE BY NAME indication	14
4.2.9 INTERROGATE BY NAME request.....	14
4.3 Parameter description.....	14
iTeh STANDARD PREVIEW	
5 Signalling protocol for the support of SS-TPI (standards.iteh.ai)	18
5.1 SS-TPI operational requirements	18
5.1.1 Served user MS	18
5.1.2 Group controlling SwMI	18
5.1.3 Served user SwMI	18
5.1.4 Talking/sending user SwMI	18
5.1.5 Authorized user MS	18
5.1.6 Authorized user SwMI	19
5.1.7 Managed user home SwMI	19
5.2 Coding requirements	19
5.2.1 SS-TPI PDUs	19
5.2.1.1 ACTIVATE PDU.....	19
5.2.1.2 ACTIVATE ACK PDU	20
5.2.1.3 DEFINE PDU	20
5.2.1.4 DEFINE ACK PDU	21
5.2.1.5 INFORM PDU	21
5.2.1.6 INTERROGATE PDU	24
5.2.1.7 INTERROGATE ACK PDU	25
5.2.1.8 INTERROGATE BY NAME PDU.....	26
5.2.1.9 INTERROGATE BY NAME ACK PDU	27
5.2.1.10 NAME REQ PDU	27
5.2.1.11 NAME ACK PDU	28
5.2.1.12 NAME REQ BIS PDU	28
5.2.1.13 TX PRIORITY REQUEST PDU	29
5.2.1.14 TX DEMAND PRIORITY PDU.....	29
5.2.2 TETRA PDU information element coding	29
5.2.2.1 Activated/defined/interrogated party short number address.....	29
5.2.2.2 Activated/defined/interrogated/talking/sending party short subscriber identity.....	29
5.2.2.3 Activated/defined/interrogated/talking/sending party extension.....	29
5.2.2.4 Activation failure cause.....	29
5.2.2.5 Activation request	29
5.2.2.6 Activation result.....	30
5.2.2.7 Activation state	31

5.2.2.8	Address type of activated/defined/interrogated/talking/sending party	31
5.2.2.9	Void.....	32
5.2.2.10	Definition failure cause	32
5.2.2.11	Definition result	32
5.2.2.12	Void.....	32
5.2.2.13	External talking/sending party number digit	32
5.2.2.14	Interrogation failure cause.....	33
5.2.2.15	Interrogation by name failure cause	33
5.2.2.16	Interrogation result.....	33
5.2.2.17	Length of the mnemonic name.....	34
5.2.2.18	Multiple user mask and Multiple user mask present	34
5.2.2.19	Mnemonic name character string	34
5.2.2.19a	Number of external talking/sending party number digits	34
5.2.2.20	Range type for activated/defined/interrogated party/parties or for mnemonic name/names	34
5.2.2.21	SS-CLIR invoked for talking/sending party.....	34
5.2.2.22	Text encoding scheme.....	34
5.2.2.23	TPI PDU type.....	35
5.2.2.24	TX demand priority.....	35
5.2.2.25	SS-TPI profile	36
5.2.2.26	SS-TPI profile ACK information element.....	36
5.2.3	Additional coding requirements over the ISI	36
5.3	SS-TPI state definitions	37
5.3.1	States at the served user MS	37
5.3.2	States at the group controlling SwMI	37
5.3.2.1	State for SS-TPI activation, deactivation, definition or interrogation	37
5.3.2.2	States for SS-TPI invocation and operation	37
5.3.2.2.1	TPI-Idle	37
5.3.2.2.2	TPI-Activated	37
5.3.2.2.3	TPI-Option-TX-Priority	37
5.3.2.2.4	TPI-Option-Name	37
5.3.2.2.5	TPI-Options-Name-and-TX-Priority	38
5.3.2.2.6	TPI-Option-Name-Caller Name Waiting	38
5.3.2.2.7	TPI-Options-Name-and-TX-Priority-Caller Name Waiting	38
5.3.3	Served user SwMI..... d267c48e07/sist-en-300-392-12-3-v1-3-1-2006	38
5.3.3.1	TPI-Idle	38
5.3.3.2	TPI-Activated	38
5.3.3.3	TPI-Option-TX-Priority	38
5.3.3.4	TPI-Option-Name-Requested	38
5.3.3.5	TPI-Options-Name-and-TX-Priority	38
5.3.4	Talking/sending user SwMI	38
5.3.4.1	TPI-Idle	39
5.3.4.2	TPI-Name-Requested	39
5.3.4.3	TPI-TX-Priority-Requested	39
5.3.5	Authorized user MS	39
5.3.6	Authorized user SwMI	39
5.3.7	Managed user home SwMI	39
5.4	SS-TPI signalling procedures	39
5.4.1	Actions at the served user MS	39
5.4.1.1	Normal procedures	39
5.4.1.2	Exceptional procedures	41
5.4.2	Actions at the group controlling SwMI	41
5.4.2.1	Normal procedures	41
5.4.2.2	Exceptional procedures	42
5.4.3	Actions at the served user SwMI	43
5.4.3.1	Normal procedures	43
5.4.3.1.1	Individual call	43
5.4.3.1.2	Group call	45
5.4.3.2	Exceptional procedures	45
5.4.4	Actions at the talking/sending user SwMI	46
5.4.4.1	Normal procedures	46
5.4.4.1.1	Group call	46
5.4.4.1.2	Individual call	46

5.4.4.2	Exceptional procedures	47
5.4.5	Actions at authorized user MS	47
5.4.5.1	Normal procedures	47
5.4.5.2	Exceptional procedures	47
5.4.6	Actions at the authorized user SwMI	48
5.4.7	Actions at the managed user home SwMI	48
5.4.7.1	Normal procedures	48
5.4.7.1.1	Case where the managed user home SwMI coincides with the authorized user SwMI	48
5.4.7.1.2	Case where the managed user home SwMI is different from the authorized user SwMI	48
5.4.7.2	Exceptional procedures	48
5.5	SS-TPI impact of interworking with other networks	49
5.6	Protocol interactions between SS-TPI and other supplementary services and ANFs	50
5.6.1	Interaction with Calling Line Identification Presentation (SS-CLIP)	50
5.6.2	Interactions with Calling/Connected Line Identification Restriction (SS-CLIR)	50
5.6.3	Interactions with Call Authorized by Dispatcher (SS-CAD)	51
5.6.3.1	Individual call	51
5.6.3.2	Group call	52
5.6.4	Interactions with Connected Line identification Presentation (SS-COLP)	52
5.6.5	Interactions with ISI Mobility Management (ANF-ISIMM)	52
5.7	SS-TPI parameter values (timers)	53
Annex A (informative): Examples of message sequences.....	54	
A.1	Example message sequence for normal operation of SS-TPI in a group call in the case where transmission is not granted automatically at set-up time	54
A.2	Example message sequence for normal operation of SS-TPI in a group call where transmission is granted automatically to the calling user at set-up time	54
A.3	Example message sequence for normal operation of SS-TPI in a group call where transmission is granted automatically to another user than the calling user at set-up time	55
A.4	Example message sequence for exceptional operation of SS-TPI in a group call where the originating SwMI does not support the sending of name	55
A.5	Example message sequence for normal operation of SS-TPI in an individual call for the calling user	60
A.6	Example message sequence for normal operation of SS-TPI in an individual call for the connected user	61
Annex B (informative): Specification and Description Language (SDL) representation of procedures	62	
B.1	SDL representation of SS-TPI at the served user MS	63
B.2	SDL representation of SS-TPI at the group controlling SwMI	65
B.3	SDL representation of SS-TPI at the served user SwMI	71
B.4	SDL representation of SS-TPI at the talking/sending user SwMI	76
B.5	SDL representation of SS-TPI at the authorized user MS	79
B.6	SDL representation of SS-TPI at the authorized user SwMI	81
B.7	SDL representation of SS-TPI at the managed user home SwMI	83
Annex C (informative): Bibliography	85	
Annex D (informative): Change Requests	86	
History	87	

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA).

The present document is part 12, subpart 3 of a multi-part deliverable covering the Voice plus Data (V+D), as identified below:

- EN 300 392-1: "General network design";
EN 300 392-2: "Air Interface (AI)";
EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";
ETS 300 392-4: "Gateways basic operation";
EN 300 392-5: "Peripheral Equipment Interface (PEI)";
EN 300 392-7: "Security";
EN 300 392-9: "General requirements for supplementary services";
EN 300 392-10: "Supplementary services stage 1";
EN 300 392-11: "Supplementary services stage 2";
EN 300 392-12: "Supplementary services stage 3";
EN 300 392-12-1: "Call Identification (CI)";
ETS 300 392-12-2: "Call Report (CR)";
EN 300 392-12-3: "Talking Party Identification (TPI)";
EN 300 392-12-4: "Call Forwarding (CF)";
ETS 300 392-12-5: "List Search Call (LSC)";
EN 300 392-12-6: "Call Authorized by Dispatcher (CAD)";
ETS 300 392-12-7: "Short Number Addressing (SNA)";
EN 300 392-12-8: "Area Selection (AS)";
ETS 300 392-12-9: "Access Priority (AP)";
EN 300 392-12-10: "Priority Call (PC)";
ETS 300 392-12-11: "Call Waiting (CW)";
EN 300 392-12-12: "Call Hold (HOLD)";

- ETS 300 392-12-13: "Call Completion to Busy Subscriber (CCBS)";
 EN 300 392-12-14: "Late Entry (LE)";
 EN 300 392-12-16: "Pre-emptive Priority Call (PPC)";
 EN 300 392-12-17: "Include Call (IC)";
 EN 300 392-12-18: "Barring of Outgoing Calls (BOC)";
 EN 300 392-12-19: "Barring of Incoming Calls (BIC)";
 ETS 300 392-12-20: "Discreet Listening (DL)";
 EN 300 392-12-21: "Ambience Listening (AL)";
 EN 300 392-12-22: "Dynamic Group Number Assignment (DGNA)";
 ETS 300 392-12-23: "Call Completion on No Reply (CCNR)";
 ETS 300 392-12-24: "Call Retention (CRT)";
 ETS 300 392-13: "SDL model of the Air Interface (AI)";
 ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";
 TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";
 TS 100 392-16: "Network Performance Metrics";
 TR 100 392-17: "TETRA V+D and DMO specifications";
 TS 100 392-18: "Air interface optimized applications".
- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- NOTE: Part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and will not be updated according this version of the standard.
<https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b6fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006>

National transposition dates	
Date of adoption of this EN:	21 April 2006
Date of latest announcement of this EN (doa):	31 July 2006
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2007
Date of withdrawal of any conflicting National Standard (dow):	31 January 2007

1 Scope

The present document specifies the stage 3 description of the Supplementary Service Talking Party Identification (SS-TPI) for the Terrestrial Trunked Radio (TETRA).

The SS-TPI supplementary service enables the party/parties participating in a call to receive the identification of the talking/sending party. The SS-TPI is activated against individual identity in individual call and against group identity in group calls.

Man-Machine Interface (MMI) and charging principles are outside the scope of the present document.

The supplementary service stage 3 description is preceded by the stage 1 and the stage 2 description of the service, according to the method described in ITU-T Recommendation I.130 [10]. The stage 1 description specifies the service from the user's point of view. The stage 2 description identifies the functional capabilities and the information flows needed to support the supplementary service as specified in its stage 1 description. The present stage 3 description specifies the protocols at the air interface and at the various Inter-System Interfaces (ISI) to support SS-TPI.

NOTE: According to ITU-T Recommendation I.130 [10], the stage 3 description of any telecommunication service addresses the network implementation aspects. Consequently it comprises two steps: the specifications of all protocols at the various reference points involved in any of the service procedures (notably the service operation) are the first step of the stage 3 description, and the specifications of the functions of the corresponding network entities are its second step.

The latter have not been provided since they can be derived from the specification of the functional entity actions in the stage 2 description.

The present document is applicable to Voice plus Data individual call or group call, more specifically to the following entities:

(standards.iteh.ai)

- the MS of listening/receiving users during an individual call or a group call;
- to the originating Switching and Management Infrastructures (SwMIs) in an individual call or a group call; SIST EN 300 392-12-3 V1.3.1:2006
<https://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b61c-d267c4f8-07/sist-en-300-392-12-3-v1-3-1-2006>
- to the group home SwMI and the participating SwMI for a group call;
- to the terminating SwMI for an individual call;
- and, optionally, to the home SwMI of the group or of the MSs involved, for managing the supplementary service.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [2] ETSI EN 300 392-3-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 1: General design".

- [3] ETSI EN 300 392-3-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 2: Additional Network Feature Individual Call (ANF-ISIIC)".
- [4] ETSI EN 300 392-3-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 3: Additional Network Feature Group Call (ANF-ISIGC)".
- [5] ETSI EN 300 392-3-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 5: Additional Network Feature for Mobility Management (ANF-ISIMM)".
- [6] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
- [7] ETSI ETS 300 392-10-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 3: Talking Party Identification (TPI)".
- [8] ETSI ETS 300 392-11-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 3: Talking Party Identification (TPI)".
- [9] ETSI EN 300 392-12-6: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 6: Call Authorized by Dispatcher (CAD)".
- [10] ITU-T Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [11] ITU-T Recommendation Z.100: "Specification and Description Language (SDL)".

iTeh STANDARD PREVIEW

3 Definitions and abbreviations (standards.iteh.ai)

[SIST EN 300 392-12-3 V1.3.1:2006](#)

3.1 Definitions

<http://standards.iteh.ai/catalog/standards/sist/4d5dd5ba-b877-4d91-b6fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006>

For the purposes of the present document, the terms and definitions given in EN 300 392-9 [6] and the following apply:

authorized user: identified user who is allowed to define, activate, deactivate and/or interrogate the SS-TPI parameters

served user: listening/receiving party in a call, that receives the SS-TPI information

NOTE: In a group call, all parties except the talking/sending party will be served users. In an individual call, if SS-TPI is provided to the calling and the connected users:

- if the call is half-duplex, whenever one of the two parties becomes the talking/sending user, the other party is the served user;
- if the call is duplex, both of them are served users.

served user SwMI: in the case of an individual call, SwMI where the served user is registered, or in the case of a group call, any SwMI where served users are registered different from the group controlling SwMI

NOTE: The protocol specified for the start of the call in the present document for such SwMI applies independently of whether or not the/a served user is registered in that SwMI at that time (i.e. the user registered in that SwMI involved the call may be talking/sending at set-up time, and become served user only later during the call).

talking/sending user: party to whom transmission permission has been granted during a group call or a half-duplex individual call

talking/sending user SwMI: SwMI where the talking/sending user is registered

NOTE: That definition applies without restriction in the case of an individual call. In the case of a group call, the talking/sending user SwMI exists only when it is different from the group controlling SwMI. The protocol specified for the start of the call in the present document for such SwMI applies independently of whether or not the talking/sending user is registered in that SwMI at that time (i.e. the user registered in that SwMI involved the call may be listening/receiving at set-up time, i.e. thus the/a served user, and become talking/sending user only later during the call).

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ANF-ISIGC	Additional Network Feature - Inter-System Interface Group Call
ANF-ISIIC	Additional Network Feature - Inter-System Interface Individual Call
ANF-ISIMM	Additional Network Feature - Inter-System Interface Mobility Management
ANF-ISISS	Additional Network Feature - Inter-System Interface Supplementary Service
CMCE	Circuit Mode Control Entity
GTSI	Group TETRA Subscriber Identity
ISI	Inter-System Interface
ITSI	Individual TETRA Subscriber Identity
LS	Line Station
MS	Mobile Station
PDU	Protocol Data Unit
ROSE	Remote Operation Service Element
SNA	Short Number Address
SS	Supplementary Service
SS-CAD	Supplementary Service-Call Authorized by Dispatcher
SS-CLIR	Supplementary Service-Calling/connected Line Identification Restriction
SS-COLP	Supplementary Service-Connected Line identification Presentation
SSI	Short Subscriber Identity
SS-TPI	Supplementary Service-Talking Party Identification
SwMI	Switching and Management Infrastructure
TNSS-SAP	TETRA Network layer Supplementary Services - Service Access Point

4 SS-TPI service description

4.1 General

SS-TPI enables a listening/receiving user in an individual or a group call to be provided with the identity of the talking/sending party, and on an optional basis, with its mnemonic name and/or with the level of priority of its request for transmission grant.

This clause describes SS-TPI specific services offered by the Circuit Mode Control Entity (CMCE) at the Supplementary Services service access point (TNSS-SAP) of the TETRA voice plus data layer 3 service boundary in a TETRA Mobile Station (MS) or TETRA Line Station (LS). The SS-TPI service access point is used in conformance testing as a normative boundary in MSs and LSs.

NOTE: As the present document only deals with the SS-TPI all the service primitives has been shown without a TNSS-TPI-prefix e.g. the TNSS-TPI-ACTIVATE request is shorten into an ACTIVATE request.

4.2 SS-TPI services offered over the TNSSSAP

NOTE 1: As man-machine interface or user applications are outside the scope of the present document service primitives are used to define information exchange to and from the standardized part of the MS. Those primitives may be only indirectly accessible.

The SS-TPI service primitives at the served user MS TNSS-SAP shall be:

- INFORM indication.

The SS-TPI service primitives at the authorized user MS TNSS-SAP shall be:

- ACTIVATE request;
- ACTIVATE indication;
- DEFINE request;
- DEFINE indication;
- INFORM indication;
- INTERROGATE request;
- INTERROGATE indication;
- INTERROGATE BY NAME request;
- INTERROGATE BY NAME indication.

Any user to whom SS-TPI is provided should have the possibility to use the INTERROGATE primitives mentioned above, limited to its own ITSI and to GTSIs of groups he is member of.

NOTE 2: Formally, when such user is using the INTERROGATE primitives to know whether SS-TPI has been activated for him, and if yes with which optional subscription parameters, he is acting as a served user. While when he is using those primitives to know his mnemonic name, he is acting as a talking/sending user (since that name is going to be delivered to the served user(s)). However no difference has been made between the two cases, since during a call any user can be in turn a served user and talking/sending user.

4.2.1 ACTIVATE indication

SIST EN 300 392-12-3 V1.3.1:2006

<http://standards.etsi.org/catalog/standards/sist/4d5dd5ba-b877-4d91-b6fc-dc267c4f8e07/sist-en-300-392-12-3-v1-3-1-2006>

The ACTIVATE indication primitive shall be sent to the user application by the MS CMCE over TNSS-SAP to inform it of the result of a previous ACTIVATE request.

If the previous request has been addressed to a SwMI for more than one identity, that SwMI may send its corresponding response either in one single request which applies to all those identities or in multiple requests.

The ACTIVATE indication primitive shall contain the SS-TPI parameters listed in table 1.

Table 1: Parameters for the primitive ACTIVATE indication

Parameter	Indication
Activation result	M (see note 1)
TETRA identity/identities	M (see note 2)
Activation state	C (see notes 1 and 3)

NOTE 1: There shall be only one activation result and one activation state per indication primitive.
 NOTE 2: It is optional to support more than one identity.
 NOTE 3: Conditional on the activation result.

4.2.2 ACTIVATE request

The ACTIVATE request primitive shall be sent to the MS CMCE by the user application by over TNSS-SAP to activate SS-TPI.

The activation process shall support one TETRA identity in a request. Optionally it may support a list and/or range of identities. Such identity/identities may be those of either individual users or of groups.

The ACTIVATE request primitive shall contain the SS-TPI parameters listed in table 2.

Table 2: Parameters for the primitive ACTIVATE request

Parameter	Request
Access priority	O
TETRA identity/identities	M (see note 1)
Activation request	M (see note 2)
NOTE 1: It is optional to support more than one identity.	
NOTE 2: There shall be only one activation request per request primitive.	

4.2.3 DEFINE indication

The DEFINE indication primitive shall be sent to the user application by the MS CMCE over TNSS-SAP to inform it of the result of a previous DEFINE request.

If the previous request has been addressed to a SwMI for more than one identity, that SwMI may send its corresponding response either in one single request which applies to all those identities or in multiple requests.

The DEFINE indication primitive shall contain the SS-TPI parameters listed in table 3.

Table 3: Parameters for the primitive DEFINE indication

Parameter	SIST EN 300 392-12-3 V1.3.1:2006 https://standards.iteh.ai/catalog/standards/sist/4d5dd5b418774491.html	Indication
Definition result	dc26/c418e0//sist-en-300-392-12-3-v1-3	M (see note 1)
TETRA identity/identities	dc26/c418e0//sist-en-300-392-12-3-v1-3	M (see note 2)
Activation state		C (see notes 1 and 3)
NOTE 1: There shall be only one definition result and one activation state per indication primitive.		
NOTE 2: It is optional to support more than one identity.		
NOTE 3: Conditional on the definition result.		

4.2.4 DEFINE request

The DEFINE request primitive shall be sent to the MS CMCE by the user application by over TNSS-SAP to give a mnemonic name to a user.

The definition process shall support one TETRA identity in a request. Optionally it may support a list and/or range of identities. Such identity/identities may only be those of individual users (since the groups have no mnemonic names).

The DEFINE request primitive shall contain the SS-TPI parameters listed in table 4.

Table 4: Parameters for the primitive DEFINE request

Parameter	Request
Access priority	O
TETRA identity/identities	M (see note 1)
TETRA mnemonic name/names	M (see note 2)
Activation request	C (see note 3)
NOTE 1: It is optional to support more than one identity.	
NOTE 2: There shall be as many mnemonic names as there are identities.	
NOTE 3: There shall be only one activation request per request primitive.	

4.2.5 INFORM indication

The INFORM indication primitive shall be sent to the user application by the MS CMCE over TNSS-SAP as a result of SS-TPI operation. The INFORM indication primitive shall contain the SS-TPI parameters listed in table 5.

Table 5: Parameters for the primitive INFORM indication

Parameter	Indication
SS-CLIR invoked for talking/sending party	M
Talking/sending party identity	C (see note 1)
Talking/sending party mnemonic name	O (see note 2)
Tx demand priority	O
NOTE 1: Conditional on SS-CLIR not having been invoked for talking/sending party.	
NOTE 2: Shall not be present if SS-CLIR has been invoked for talking/sending party.	

4.2.6 INTERROGATE indication

The INTERROGATE indication primitive shall be sent to the user application by the MS CMCE over TNSS-SAP to inform it of the result of a previous INTERROGATE request.

If the previous request has been addressed to a SwMI for more than one identity, that SwMI may send its corresponding response either in one single request which applies to all those identities or in multiple requests.

The INTERROGATE indication primitive shall contain the SS-TPI parameters listed in table 6.

Table 6: Parameters for the primitive INTERROGATE indication

Parameter	Indication
Interrogation result	M (see note 1)
TETRA identity/identities	M (see note 2)
TETRA mnemonic name/names	C (see notes 3 and 4)
Activation state	C (see notes 1 and 3)
NOTE 1: There shall be only one interrogation result and one activation state per indication primitive.	
NOTE 2: It is optional to support more than one identity.	
NOTE 3: Conditional on the interrogation result.	
NOTE 4: If that parameter is present (see note 3), there shall be as many mnemonic names as there are identities.	

4.2.7 INTERROGATE request

The INTERROGATE request primitive shall be sent to the MS CMCE by the user application by over TNSS-SAP to know the SS-TPI activation status of a user and his mnemonic name.

The interrogation process shall support one TETRA identity in a request. Optionally it may support a list and/or range of identities. Such identity/identities may be those of either individual users or of groups.

The INTERROGATE request primitive shall contain the SS-TPI parameters listed in table 7.

Table 7: Parameters for the primitive INTERROGATE request

Parameter	Request
Access priority	O
TETRA identity/identities	M (see note)
NOTE: It is optional to support more than one identity.	