

TECHNICAL REPORT



Multimedia systems and equipment – Multimedia signal transmission –
Dependable line code with error correction

(standards.iteh.ai)

[IEC TR 63094:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/1b20fa44-5f08-4531-89a5-d9fe9d3771a1/iec-tr-63094-2017>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.



IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IEC'S STANDARD PREVIEW
(standards.iec.ch)
IEC TR 63014:2017
<https://standards.iec.ch/catalog/standards/tr/63014-2017>
d9fe9d3771a1/iec-tr-63014-2017

TECHNICAL REPORT



**Multimedia systems and equipment – Multimedia signal transmission –
Dependable line code with error correction**

STANDARD PREVIEW
(standards.iteh.ai)

IEC TR 63094:2017
<https://standards.iteh.ai/catalog/standards/sist/1b20fa44-5f08-4531-89a5-d9fe9d3771a1/iec-tr-63094-2017>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.60; 35.110

ISBN 978-2-8322-4337-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	8
2 Normative references	8
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	9
4 4b/10b line code	9
4.1 Overview.....	9
4.2 Forward error correction (FEC)	9
4.3 Embedded clock	9
4.4 DC balance	9
4.5 4b/10b data encoding.....	10
4.6 Frame format	10
4.6.1 Frame.....	10
4.6.2 Setup command.....	10
4.6.3 Idle command	11
4.7 Encoding.....	11
4.8 Decoding	11
4.9 Error handling	11
4.9.1 1-bit error	11
4.9.2 2-bit error	12
4.9.3 Over 3-bit error	12
Annex A (informative) Real-time scheduling.....	13
Annex B (informative) Characteristics of embedded clock	14
Annex C (informative) Characteristics of DC balance	15
Annex D (informative) Implementation of a decoder	16
Bibliography.....	17
Figure 1 – A humanoid robot.....	6
Figure A.1 – EDF scheduling	13
Table 1 – The 4b/10b data transform	10
Table 2 – Setup command	10
Table 3 – Idle command.....	11
Table 4 – The 4b/10b look-up	11
Table B.1 – The length of successive 0 or 1 in case of 1-bit error	14
Table C.1 – An example of the isomery of 0 and 1 in a successive 10-bit window	15

iTech STANDARD PREVIEW
(standards.itech.ai)

IEC TR 63094:2017
<https://standards.itech.ai/catalog/standards/sist/1b20fa44-5f08-4531-89a5-d9f69d3771a1/iec-tr-63094-2017>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTIMEDIA SYSTEMS AND EQUIPMENT –
MULTIMEDIA SIGNAL TRANSMISSION –
DEPENDABLE LINE CODE WITH ERROR CORRECTION**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 63094, which is a technical report, has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
100/2823A/DTR	100/2871/RVDTR

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC TR 63094:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/1b20fa44-5f08-4531-89a5-d9fe9d3771a1/iec-tr-63094-2017>

INTRODUCTION

This document defines a line code that incorporates error correction capability to communicate reliably among multimedia components, I/O peripherals and computers. A number of complex multimedia machines, in particular robots, automobiles, and network routers, have a growing demand for distributed processing. In addition, modernization of facilities such as factories, offices, schools, and homes is creating a ubiquitous and multimedia computing environment. Unlike conventional PC applications for documentation and Internet applications that exchange texts without hard time constraints, these types of cooperative computing require reliable real-time responses to physical events occurring in the real world. In order for distributed nodes to cooperate in real-time, an interconnecting network shall realize real-time and dependable communication without re-sending on noisy environments. The 4b/10b provides a dependable line code for such real-time communications between multimedia components, I/O peripherals and/or computers by providing embedded clock, DC balance, error detection and error correction features.

The real-time aspect means that the exactness of the system including operations and communications depends not only on the result, but also on the time it took to achieve the result. In the narrow sense, the real-time aspect means that the time constraint, including deadlines or cycles, must be met.

Real-time tasks with the time constraints are generally scheduled and executed by a real-time scheduler and a real-time operating system. Most real-time scheduling algorithms assume that the WCET (worst-case execution time) of each task is given. A real-time scheduling algorithm converts a time constraint of each real-time task to a priority. Most real-time operating systems based on such real-time schedulers pre-empt and execute tasks in order of priority at every tick to meet the time constraint.

As real-time scheduling algorithms, the earliest deadline first (EDF) scheduler, the rate monotonic (RM) scheduler, and their variations have been established, as explained in Annex A. These algorithms commonly schedule tasks based on priorities determined by the time constraints.

Most real-time scheduling algorithms assume that the WCRT (worst-case response time) of each communication packet is given in case of communication. In order to apply real-time scheduling algorithms to real-time communications, pre-emptive communication, which is achieved by Responsive Link (ISO/IEC 24740), and the error correction capability to prevent the re-sending a broken packet are required.

A line code is a lowest-level communication protocol on a communication line. Most current line codes have a few typical functions including embedded clock, DC balance and basic error detection features. The 8b/10b codec is a major example, which is used for PCI Express, USB 3.0, SATA, IEEE1394b, and 10GbE. But no conventional line code has an error correction capability.

When an encoded code (a 10b code) is broken during communication, the multi-bits of the decoded code (the 8b code) are corrupted. In other words, when a single bit error occurs in an encoded 10-bit code, the decoded 8-bit code (a byte) is completely broken.

When an error is detected on the decoder, the broken data is normally re-transmitted under an upper-level communication protocol. However, re-transmission is not allowed in order to realize real-time communication.

It is hard for a bit-level error correction code that includes the Hamming code and the BCH code to incorporate error correction capability, because multi-bits of the decoded code are broken even if a single-bit error occurs on the encoded code.

In order to incorporate error correction capability on the 8b/10b codec, a block-level error correction including RS (Reed-Solomon) is required as a large packet-level error correction. But the block-level error correction is not suitable for real-time communication, because the communication latency becomes longer as it is impossible to correct the corrupted data until all corresponding packets are received.

The line code 4b/10b has the following distinctive features for real-time communications:

- a) embedded clock;
- b) DC balance;
- c) error detection;
- d) error correction.

No conventional line code supports the above features at one time. For example, the industry-wide standard 8b/10b codec can be easily replaced with the 4b/10b line code for highly reliable communications.

Figure 1 shows a distributed control configuration of a humanoid robot as one of the typical applications of the 4b/10b line code. The electronic control part of the humanoid robot consists of several control nodes with local sensing and actuating devices. The distributed controllers are connected to each other by Responsive Link. In this figure, rectangles represent node controllers, and dotted lines show communication links such as the Responsive Link that is a point-to-point serial link.




Figure 1 – A humanoid robot

For a humanoid robot to walk stably, a servo loop of 1 ms or shorter is needed. In this configuration, the farthest two nodes can exchange a 16-byte packet within 5 μ s. Since the time is guaranteed not to fluctuate, the distributed control of a humanoid is considered to be sufficiently possible. Since many actuators that generate noises are embedded inside the robot, the line code is required for noise tolerance. The 4b/10b is the line code that has error correction capability.

Currently many I/O interfaces and communication standards, including PCI Express (PCIe), USB 3.0, SATA, IEEE 1394b, and 10GbE use the 8b/10b codec as a line code. The 8b/10b has a lot of functions and its code rate is relatively high (about 80 %). However if one bit error occurs in an encoded data (10b), the decoded data (8b) will be broken completely. Therefore when the 8b/10b codec is used on noisy environment such as inside the robot, an upper-level error correction code is required. For error correction, it is hard to apply any bit-level error codec including the Hamming code and the BCH code, because multiple decoded bits (1-byte) will be broken even if an encoded bit is inverted. So, block-level error correction including

Reed-Solomon, which is long latency ECC that is not suitable for real-time applications, is required. Hence, a reliable line code with ECC is required for such applications.

Patent

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents as listed below:

PATENT No. 5900850 (Japan)

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holder of these patent rights has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of these patent rights is registered with IEC. Information may be obtained from:

Headquarters for Research Coordination and Administration
2-15-45 Mita, Minato-ku,
Tokyo 108-8345 Japan

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (<http://patents.iec.ch>) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

<https://standards.iteh.ai/catalog/standards/sist/1b20fa44-5f08-4531-89a5-d9fe9d3771a1/iec-tr-63094-2017>

MULTIMEDIA SYSTEMS AND EQUIPMENT – MULTIMEDIA SIGNAL TRANSMISSION – DEPENDABLE LINE CODE WITH ERROR CORRECTION

1 Scope

This document specifies the line code 4b/10b for dependable multimedia signal transmission required for complex machines, such as robots and automobiles. This document corresponds to the functions specified in layer 1 to layer 2 of the OSI reference model (ISO/IEC 7498).

The purpose of this document is to facilitate the development and use of the 4b/10b in dependable systems by providing a line code protocol. This document provides a line code protocol for interconnections among distributed real-time systems, including embedded systems, control systems, amusement systems, robot systems, and intelligent buildings. The 4b/10b can achieve the line code with ECC (error code correction). The 4b/10b is the line code that realizes embedded clock, DC balance, error detection and error correction at a time; it is not possible to satisfy these functions in one codec by conventional schemes, and the 4b/10b line code can achieve highly reliable and dependable digital communications.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 Terms and definitions

3.1.1

byte

B

group of eight bits

3.1.2

half byte

HB

unit for transmitting, the size of which is 10 bits

3.1.3

4b

original half byte (4-bit) data

3.1.4

10b

encoded 10-bit data for transmitting

3.1.5

symbol

unit for encoding, the size of which is 10 bits

3.1.6

frame

unit for transmitting, the size of which is 10 bits

3.2 Abbreviated terms

ECC error correction code

DC direct current

WCET worst case execution time

WCRT worst case response time

4 4b/10b line code

4.1 Overview

The line code 4b/10b handles a 10-bit frame encoded by 4-bit digits. The original 4 bits of information digits are encoded into a 10-bit frame by the look-up table shown in Table 1. A byte (8 bits) is divided into two half bytes (4b). A half byte (4b) is encoded to a symbol (10b). A frame consists of a symbol and is transmitted to the communication line. Since four bits are encoded to ten bits by the 4b/10b line code, the communication speed at 1 000 MHz is approximately equal to 400 Mbit/s.

4.2 Forward error correction (FEC)

The line code 4b/10b should provide error-free transmission for reliable real-time control. Error correction should be performed by hardware. The 4b/10b performs line-code-level error correction. Original four-bit data (4b) are encoded to 10-bit transmitting data with embedded clock, DC balance, 2-bit error detection, and 1-bit error correction for a half byte of data (4 bits of information digits).

The Hamming distance of any digits in a symbol (10b code) is longer than or equals 4 for 1-bit error correction and 2-bit error detection.

4.3 Embedded clock

The line code 4b/10b ensures that successive 0 bits or 1 bits are within five bits, even if a 1-bit error/symbol occurs. Characteristics of the embedded clock are shown in Annex B.

In the case of inside symbol digits, successive 0 bits or 1 bits are within five bits.

In the case of inter-symbol digits, successive 0 bits or 1 bits are within five bits.

When each symbol has 1-bit error, if the distance of error bits is greater than four-bit, the successive 0 or 1 bits are within five bits.

In the case of two-bit errors, discontinuity of digits is not guaranteed.

4.4 DC balance

In order for the line code 4b/10b not to allow a current to flow in the communication cable, the numbers of 0 and 1 in a symbol are same for DC balance. But DC balance between successive symbols is not necessary. Characteristics of the DC balance are shown in Annex C.