

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Low-voltage switchgear and controlgear –
Part 5-2: Control circuit devices and switching elements – Proximity switches
(standards.iteh.ai)

Appareillage à basse tension –
Partie 5-2: Appareils et éléments de commutation pour circuits de commande –
DéTECTEURS DE PROXIMITÉ

IEC STANDARD PREVIEW
IEC 60947-5-2:2019
<https://standards.iteh.ai/catalog/standards/sist/aa7a7cc7-1514-4c37-8717-a320a0e420e7/iec-60947-5-2-2019>





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22.000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67.000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

67 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Low-voltage switchgear and controlgear –
Part 5-2: Control circuit devices and switching elements – Proximity switches

Appareillage à basse tension –
Partie 5-2: Appareils et éléments de commutation pour circuits de commande –
Détecteurs de proximité

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.120.40; 29.130.20

ISBN 978-2-8322-7445-3

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD	9
1 Scope	12
2 Normative references	13
3 Terms and definitions	14
3.1 Basic terms and definitions	17
3.2 Parts of a proximity switch	18
3.3 Operation of a proximity switch	20
3.4 Switching element characteristics	22
4 Classification	24
4.1 General.....	24
4.2 Classification according to sensing means	26
4.3 Classification according to the mechanical installation	26
4.4 Classification according to the construction form and size.....	26
4.5 Classification according to switching element function	26
4.6 Classification according to type of output	26
4.7 Classification according to method of connection	26
5 Characteristics	26
5.1 General.....	26
5.1.1 Summary of characteristics	26
5.1.2 Operation of an inductive or capacitive proximity switch	26
5.1.3 Operation of an ultrasonic proximity switch	27
5.1.4 Operation of a photoelectric proximity switch	27
5.1.5 Operation of a magnetic proximity switch	27
5.2 Operating conditions	27
5.2.1 Operating conditions of inductive and capacitive proximity switches	27
5.2.2 Operating distance (s) of an ultrasonic proximity switch.....	28
5.2.3 Operating distance (s) of a photoelectric proximity switch.....	29
5.3 Rated and limiting values for the proximity switch and switching element(s).....	31
5.3.1 Voltages	31
5.3.2 Currents	31
5.3.3 Rated supply frequency	32
5.3.4 Frequency of operating cycles (f).....	32
5.3.5 Normal load and abnormal load characteristics	32
5.3.6 Short-circuit characteristics	32
5.4 Utilization categories for the switching element.....	32
6 Product information	33
6.1 Nature of information – Identification.....	33
6.2 Marking.....	34
6.2.1 General	34
6.2.2 Terminal identification and marking	34
6.2.3 Functional markings.....	34
6.3 Instructions for installation, operation and maintenance	34
6.4 Environmental information	35
6.4.1 Environmentally conscious design process (ECD process)	35

6.4.2	Procedure to establish material declaration	35
7	Normal service, mounting and transport conditions	35
7.1	Normal service conditions	35
7.1.1	General	35
7.1.2	Ambient air temperature	35
7.1.3	Altitude	36
7.1.4	Climatic conditions	36
7.2	Conditions during transport and storage	36
7.3	Mounting	36
8	Constructional and performance requirements	36
8.1	Constructional requirements	36
8.1.1	Materials	36
8.1.2	Current-carrying parts and their connections	37
8.1.3	Clearances and creepage distances	38
8.1.4	Actuation	38
8.1.5	Void	38
8.1.6	Void	38
8.1.7	Terminals	38
8.1.8	Void	40
8.1.9	Provisions for protective earthing	40
8.1.10	Degree of protection	40
8.1.11	Requirements for proximity switches with integrally connected cables	40
8.1.12	Class II proximity switches	41
8.1.13	Chemical stress	41
8.1.14	Equipment design	41
8.1.15	Protection against artificial optical radiation	41
8.1.16	Biological and chemical effects	42
8.1.17	Unattended operation	42
8.1.18	Safety related security	42
8.1.19	Requirements for embedded software	42
8.2	Performance requirements	42
8.2.1	Operating conditions	42
8.2.2	Temperature-rise	46
8.2.3	Dielectric properties	47
8.2.4	Ability to make and break under normal load and abnormal load conditions	48
8.2.5	Conditional short-circuit current	49
8.2.6	Electromagnetic compatibility (EMC)	49
8.3	Physical dimensions	53
8.4	Shock and vibration and special environmental conditions	53
8.4.1	Shock	53
8.4.2	Vibration	53
8.4.3	Results to be obtained	53
8.4.4	Special environmental conditions – damp heat, salt mist, vibration and shock	54
9	Tests	54
9.1	Kinds of tests	54
9.1.1	General	54
9.1.2	Type tests	54

9.1.3	Routine tests	54
9.1.4	Sampling tests	54
9.1.5	Special tests	54
9.2	Compliance with constructional requirements	55
9.2.1	General	55
9.2.2	Materials	55
9.3	Performances	55
9.3.1	Test sequences	55
9.3.2	General test conditions	56
9.3.3	Performance under no load, normal load and abnormal load condition.....	58
9.3.4	Performance under short-circuit current conditions	64
9.4	Testing of operating distances	65
9.4.1	Inductive, capacitive, non-mechanical magnetic and ultrasonic proximity switches	65
9.4.2	Photoelectric proximity switches	66
9.5	Testing for the frequency of operating cycles	69
9.5.1	General	69
9.5.2	Method for measuring the frequency of operating cycles.....	70
9.5.3	Results to be obtained	72
9.5.4	Photoelectric proximity switches	72
9.6	Verification of the electromagnetic compatibility.....	74
9.6.1	General	74
9.6.2	Immunity.....	74
9.6.3	Emission.....	75
9.7	Test results and test report	75
Annex A (informative)	Typical dimensions and operating distances of proximity switches.....	76
A.1	MODEL IA, IB – INDUCTIVE CYLINDRICAL PROXIMITY SWITCHES WITH THREADED BARREL (IA) OR SMOOTH BARREL (IB) WITH CABLE OR CONNECTOR	76
A.1.1	(IA, IB) Dimensions	76
A.1.2	(IA, IB) Rated operating distances	79
A.1.3	(IA, IB) Installation (mounting) threaded barrel (IA) and smooth barrel (IB).....	80
A.1.4	(IA, IB) Frequency of operating cycles (<i>f</i>).....	80
A.2	MODEL IC – INDUCTIVE RECTANGULAR PROXIMITY SWITCHES WITH SQUARE CROSS-SECTION	81
A.2.1	(IC) Dimensions	81
A.2.2	(IC) Rated operating distance	83
A.2.3	(IC) Installation (mounting).....	84
A.2.4	(IC) Frequency of operating cycles (<i>f</i>).....	85
A.3	MODEL ID – INDUCTIVE RECTANGULAR PROXIMITY SWITCHES WITH RECTANGULAR CROSS-SECTION.....	86
A.3.1	(ID) Dimensions	86
A.3.2	(ID) Installation (mounting).....	87
A.3.3	(IC) Frequency of operating cycles (<i>f</i>).....	88
A.4	MODEL IX (IN, IS, FLATPACK, CUBICAL INDUCTIVE RECTANGULAR AND CUBICAL PROXIMITY SWITCHES WITH SMALL SIZES)	88

IT'S STANDARD PREVIEW

(standards.iteh.ai)

IEC 60947-5-2:2019

<https://standards.iteh.ai/catalog/standards/sist/aa9a7ce6-f314-4c57-87f7-4520abc420e7/iec-60947-5-2-2019>

A.4.1	(IX) Dimensions	88
A.4.2	(Flatpack) Dimensions	89
A.4.3	(Cubical) Dimensions	90
A.4.4	(IX) Rated operating distance	92
A.4.5	(IX) Installation (mounting)	92
A.4.6	(IX) Frequency of operating cycles (f)	92
A.5	MODEL CA – CAPACITIVE CYLINDRICAL PROXIMITY SWITCHES WITH THREADED BARREL	93
A.5.1	(CA) Dimensions	93
A.5.2	(CA) Rated operating distance (s_n)	94
A.5.3	(CA) Installation (mounting)	94
A.5.4	(CA) Frequency of operating cycles (f)	95
A.6	MODEL CB – CAPACITIVE PROXIMITY SWITCHES WITH SMOOTH BARREL	95
A.7	MODEL CC – CAPACITIVE RECTANGULAR PROXIMITY SWITCHES WITH SQUARE CROSS-SECTION	95
A.7.1	(CC) Dimensions	95
A.7.2	(CC) Rated operating distances (s_n)	96
A.7.3	(CC) Installation (mounting)	97
A.7.4	(CC) Frequency of operating cycles (f)	97
A.8	MODEL CD – CAPACITIVE RECTANGULAR PROXIMITY SWITCHES WITH RECTANGULAR CROSS-SECTION	98
A.8.1	(CD) Dimensions	98
A.8.2	(CD) Rated operating distance (s_n)	98
A.8.3	(CD) Installation (mounting)	98
A.8.4	(CD) Frequency of operating cycles (f)	99
A.9	MODEL CX – CAPACITIVE PROXIMITY SWITCHES WITH OTHER FORMS, DIMENSIONS AND SMALL SIZES	99
A.10	MODEL UA – THREADED BARREL ULTRASONIC CYLINDRICAL PROXIMITY SWITCHES	99
A.10.1	(UA) Dimensions	99
A.10.2	(UA) Sensing range	100
A.10.3	(UA) Installation (mounting)	100
A.10.4	(UA) Frequency of operating cycles (f)	100
A.11	MODEL UD – ULTRASONIC RECTANGULAR PROXIMITY SWITCHES WITH RECTANGULAR CROSS-SECTION	101
A.11.1	(UD) Dimensions	101
A.11.2	(UD) Sensing range	101
A.11.3	(UD) Installation (mounting)	101
A.11.4	(UD) Frequency of operating cycles (f)	101
Annex B (normative)	Class II proximity switches insulated by encapsulation – Requirements and tests	102
B.1	General	102
B.2	Terms and definitions	102
B.6	Marking	102
B.8	Constructional and functional requirements	103
B.9	Tests	103
Annex C (normative)	Additional requirements for proximity switches with integrally connected cables	106
C.1	General	106

C.2	Terms and definitions.....	106
C.8	Constructional and performance requirements	106
C.9	Tests	107
Annex D (normative) Integral connectors for plug-in proximity switches		111
Annex E (normative) Additional requirements for proximity switches suitable for use in strong magnetic fields.....		119
E.1	Preamble	119
E.3	Terms and definitions.....	119
E.4	Classification	119
E.8	Construction and performance requirements.....	120
E.9	Tests	121
Annex F (informative) Symbols for proximity switches.....		124
F.1	General.....	124
F.2	Standard symbols for proximity switches.....	124
F.3	Additional symbols for photoelectric proximity switches.....	126
F.3.1	Sensor principles.....	126
F.3.2	Optical actuation means	126
F.3.3	Functional symbol definitions.....	126
Bibliography.....		128

Figure 1	– Relationship between operating distances of inductive and capacitive proximity switches (see 8.2.1.3 and 9.4.1).....	28
Figure 2	– Ultrasonic proximity switch operating distances.....	28
Figure 3	– Relationship between operating distances of ultrasonic proximity switches (see 8.2.1.3 and 9.4.1).....	29
Figure 4	– Sensing range and operating range of photoelectric proximity switches (see 8.2.1.3 and 9.4)	30
Figure 5	– Relationship between U_e and U_B	31
Figure 6	– Method of measuring the operating distance (see 9.3.2.1 and 9.4.1).....	57
Figure 7	– Test circuit for the verification of time delay before availability (see 8.2.1.7 and 9.3.3.2.1)	59
Figure 8	– Signal output across load in Figure 7 (see 9.3.3.2.1).....	60
Figure 9	– Test circuit for the verification of minimum operational current OFF-state current, voltage drop and independent action (see 9.3.3.2.2, 9.3.3.2.3, 9.3.3.2.4 and 9.3.3.2.5).....	61
Figure 10	– Test circuit for the verification of making and breaking capability (see 9.3.3.5).....	64
Figure 11	– Short-circuit testing (see 9.3.4.2)	65
Figure 12	– Testing of the sensing range (see 9.4.2)	68
Figure 13	– Methods for measuring the frequency of operating cycle of inductive, capacitive and non-mechanical magnetic proximity switches (if applicable).....	70
Figure 14	– Methods for measuring the frequency of operating cycles (f), ultrasonic proximity switch	71
Figure 15	– Output signal of direct current proximity switch during the measurement of frequency of operating cycles (f).....	71
Figure 16	– Measurement means for turn-on time t_{ON} and turn-off time t_{OFF}	72
Figure 17	– Turn-on time t_{ON} measurement.....	73

Figure 18 – Turn-off time t_{off} measurement	73
Figure A.1 – (IA) – Dimensions for threaded barrel – cable type	76
Figure A.2 – (IB) – Dimensions for smooth barrel – cable type	77
Figure A.3 – Type A dimensions – Body M5x0,5, M8x1, Ø 4, Ø 6,5 with connector M5/M8	78
Figure A.4 – Type B dimensions – Body M5x0,5, M8x1, Ø 4, Ø 6,5 with connector M8/M12	78
Figure A.5 – Type C dimensions – Body M12x1, M18x1, M30x1,5 with connector M12	79
Figure A.6 – (IA, IB) – Installation (mounting) ^a	80
Figure A.7 – Dimensions of Type I1C26 (in millimetres)	82
Figure A.8 – Dimensions of Types I2C40 and I1C40 (in millimetres)	82
Figure A.9 – Dimensions of Types I2IMC and I1IMC (IMC) 40 x 40 (cube)	83
Figure A.10 – Installation of a I1C proximity switch in damping material.....	84
Figure A.11 – (IC) Installation of I2C in damping material ^a	85
Figure A.12 – (ID) Dimensions	86
Figure A.13 – (IDC) Dimensions.....	87
Figure A.14 – (ID) Installation in damping material.....	88
Figure A.15 – (IN) with cable or connector M8 entry.....	89
Figure A.16 – (IS) with cable or connector M8 entry.....	89
Figure A.17 – (Flatpack) with cable or connector M8 entry.....	90
Figure A.18 – (5 mm x 5 mm) Cubical with cable.....	91
Figure A.19 – (8 mm x 8 mm) Cubical with cable.....	91
Figure A.20 – (8 mm x 8 mm) Cubical with M8 connector.....	92
Figure A.21 – (CA) Dimensions.....	93
Figure A.22 – (CA) Installation (mounting)	95
Figure A.23 – Model CC Dimensions.....	96
Figure A.24 – (CC) Installation (mounting)	97
Figure A.25 – (CD) Dimensions in millimetres	98
Figure A.26 – (CD) Installation (mounting)	99
Figure A.27 – (UA) Dimensions.....	100
Figure A.28 – (UD) Dimensions of Type D80.....	101
Figure B.1 – Encapsulated device	103
Figure B.2 – Test device	105
Figure D.1 – M12 thread 3-pin integral connector for AC proximity switches	111
Figure D.2 – M12 thread 5-pin integral connector for DC proximity switches	112
Figure D.3 – 8 mm thread 3-pin integral connector for DC proximity switches	113
Figure D.4 – 8 mm thread 4-pin integral connector for DC proximity switches	114
Figure D.5 – M12 thread 4-pin integral connector for AC proximity switches	115
Figure D.6 – M12 thread 5-pin integral connector for AC proximity switches	116
Figure D.7 – M12 thread 6-pin integral connector for AC proximity switches	117
Figure D.8 – M5 thread 4-pin/3-pin integral connector for DC proximity switches	118
Figure E.1 – Examples of test configuration for verification of the immunity to an alternating field.....	122

Figure E.2 – Example of test configuration for verification of the immunity in a constant magnetic field	123
Figure F.1 – Examples of symbols for proximity switches.....	125
Figure F.2 – Examples of symbols for proximity switches.....	127
Table 1 – Classification of proximity switches	25
Table 2 – Cross reference between active optical signal and output function	27
Table 3 – Utilization categories for switching elements	33
Table 4 – Test conditions for glow-wire test	37
Table 5 – Connection and wiring identification	39
Table 6 – Burn threshold.....	47
Table 7 – Verification of making and breaking capacities of switching elements under normal conditions corresponding to the utilization categories ^a	48
Table 8 – Verification of making and breaking capacities of switching elements under abnormal conditions corresponding to the utilization categories ^a	49
Table 9 – Acceptance criteria.....	50
Table 10 – Immunity tests (1 of 2).....	51
Table 11 – Target sizes of ultrasonic proximity switches	57
Table 12 – Test voltages.....	63
Table A.1 – (IA, IB) – Preferred and secondary series smooth and threaded barrel cable types	77
Table A.2 – (IA) – Dimensions of nuts.....	77
Table A.3 – (Types A, B, C) – Preferred and secondary series, smooth and threaded barrel connector types.....	79
Table A.4 – (IA, IB) – Rated operating distances.....	80
Table A.5 – (IA, IB) – Frequency of operating cycles (<i>f</i>) in operating cycles per second – Minimum requirements.....	81
Table A.6 – (IC) – Rated operating distance	84
Table A.7 – (IC) – Frequency of operating cycles (<i>f</i>) in operating cycles per second – Minimum requirements.....	85
Table A.8 – (ID) – Dimensions	86
Table A.9 – (IC) – Frequency of operating cycles (<i>f</i>) in operating cycles per second – Minimum requirements.....	88
Table A.10 – (IX) – Rated operating distances IN, IS, flatpack, cubical	92
Table A.11 – (IX) – Frequency of operating cycles IN, IS, flatpack and cubical (<i>f</i>) in operating cycles per second	93
Table A.12 – (CA) – Dimensions	94
Table A.13 – (CA) – Rated operating distances.....	94
Table A.14 – (CC) – Rated operational distance	97
Table A.15 – (UA) – Dimensions	100
Table C.1 – Material characteristics	107
Table C.2 – Examples of standard cable types.....	108
Table C.3 – Tensile forces	109

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR –**Part 5-2: Control circuit devices and switching elements –
Proximity switches**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60947-5-2 has been prepared by subcommittee 121A: Low-voltage switchgear and controlgear, of IEC technical committee 121: Switchgear and controlgear and their assemblies for low voltage.

This fourth edition cancels and replaces the third edition published in 2007 and Amendment 1:2012. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- update of the scope;
- adaptation and update of the construction requirements according to IEC Guide 116 (e.g. material requirements, artificial optical radiation, instruction requirements, hot surface, unattended operation, foreseeable misuse...);
- modification of the specifications concerning the sensing range and operating distance;

- new definitions for photoelectric proximity switch type D with background suppression;
- integration of the requirements and test procedures of photoelectric proximity switch type D with background suppression;
- update of EMC requirements in Table 9 and Table 10;
- integration of environmental information requirements and environmental condition by referencing Annexes O, W and Q of IEC 60947-1:2007, IEC 60947-1:2007/AMD1:2010 and IEC 60947-1:2007/AMD2:2014;
- modification of impulse withstand voltage test (5.3.1.3, 9.3.3.4.5);
- modification of the references in the (normative) standard body to the (informative) Annex A;
- major update of Annex A (definitions update, new dimensions and shapes);
- update of C.9.1.1;
- update of Annex D in order to consider new connector types and normative references;
- update of Annex F (additional symbols for photoelectric proximity switches).

The text of this standard is based on the following documents:

FDIS	Report on voting
121A/313/FDIS	121A/322/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 60947 series, under the general title *Low-voltage switchgear and controlgear*, can be found on the IEC website.

This International Standard should be used in conjunction with IEC 60947-1:2007, IEC 60947-1:2007/AMD1:2010 and IEC 60947-1:2007/AMD2:2014.

The provisions of the general rules, IEC 60947-1, are applicable to this document, where specifically called for. General rules, clauses and subclauses thus applicable, as well as tables, figures and annexes are identified by a reference to IEC 60947-1, for example 1.2.3, Table 4 or Annex A of IEC 60947-1:2007.

The following differing practices of a less permanent nature exist in the countries indicated below.

- 8.1.7.3: recommendations are given in the National US Electrical Code about connections means;
- 8.1.7.4: in the United States of America, there are other documents that define conductor colour coding schemes that can apply to the installation of proximity switches;
- 8.1.15.2: for European Union Countries: in certain ranges the defined limits of exposure values in IEC 60825-1:2014 exceed the requirements of the European directive 2006/25/EC Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artificial optical radiation).

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 60947-5-2:2019](https://standards.iteh.ai/catalog/standards/sist/aa9a7ce6-f314-4c57-87f7-a320a0e420e7/iec-60947-5-2-2019)

<https://standards.iteh.ai/catalog/standards/sist/aa9a7ce6-f314-4c57-87f7-a320a0e420e7/iec-60947-5-2-2019>

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 5-2: Control circuit devices and switching elements – Proximity switches

1 Scope

This part of IEC 60947 applies to inductive and capacitive proximity switches that sense the presence of metallic and/or non-metallic objects, ultrasonic proximity switches that sense the presence of sound reflecting objects, photoelectric proximity switches that sense the presence of objects and non-mechanical magnetic proximity switches that sense the presence of objects with a magnetic field.

Products covered by the scope of this document are not subjected to defined behaviours under fault conditions. Proximity switches with defined behaviour are covered by IEC 60947-5-3 and have to fulfil additional requirements.

These proximity switches are self-contained, have semiconductor switching element(s) and are intended to be connected to circuits, the rated voltage of which does not exceed 250 V 50 Hz/60 Hz AC RMS or 300 V DC.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Examples of typical applications for in-scope products:

- factory automation and machinery industry;
- logistic and packaging industry; [IEC 60947-5-2:2019](https://standards.iteh.ai/catalog/standards/sist/aa9a7ce6-f314-4c57-87f7-a320a0e420e7/iec-60947-5-2-2019)
- conveyor belts, lifts; <https://standards.iteh.ai/catalog/standards/sist/aa9a7ce6-f314-4c57-87f7-a320a0e420e7/iec-60947-5-2-2019>
- process industry;
- power plants.

Special applications (e.g. corrosive atmosphere) can cause additional requirements.

This document is not intended to cover proximity switches with analogue outputs.

The object of this document is to state for proximity switches:

- definitions;
- classification;
- characteristics;
- product information;
- normal service, mounting and transport conditions;
- constructional and performance requirements;
- tests to verify rated characteristics.

Products covered by the scope of this document are expected to be selected, installed, and maintained by skilled personnel only.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-6:2007, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14:2009, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60068-2-27:2008, *Environmental testing – Part 2-27: Tests – Test Ea and guidance: Shock*

IEC 60068-2-30:2005, *Environmental testing – Part 2-30: Tests – Test Db: Damp heat, cyclic (12 h + 12 h cycle)*

IEC 60364 (all parts), *Low-voltage electrical installations*

IEC 60417, *Graphical symbols for use on equipment* (available at <http://www.graphical-symbols.info/equipment>)

IEC 60445:2017, *Basic and safety principles for man-machine interface, marking and identification – Identification of equipment terminals, conductor terminations and conductors*

IEC 60695-2-10:2013, *Fire hazard testing – Part 2-10: Glowing/hot-wire based test methods – Glow-wire apparatus and common test procedure*

IEC 60695-2-11:2014, *Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products (GWEPT)*

IEC 60695-2-12:2010, *Fire hazard testing – Part 2-12: Glowing/hot-wire based test methods – Glow-wire flammability index (GWFI) test method for materials*

IEC 60695-2-12:2010/AMD1:2014

IEC 60825-1:2014, *Safety of laser products – Part 1: Equipment classification and requirements*

IEC 60947-1:2007, *Low-voltage switchgear and controlgear – Part 1: General rules*

IEC 60947-1:2007/AMD1:2010

IEC 60947-1:2007/AMD2:2014

IEC 60947-5-3, *Low-voltage switchgear and controlgear – Part 5-3: Control circuit devices and switching elements – Requirements for proximity devices with defined behaviour under fault conditions (PDDB)*

IEC 61000-4-2:2008, *Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test*

IEC 61000-4-3:2006, *Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test*

IEC 61000-4-3:2006/AMD1:2007

IEC 61000-4-3:2006/AMD2:2010