
Goriva za motorna vozila - Etanol kot komponenta za dodajanje motornemu bencinu - Zahteve in preskusne metode

Automotive fuels - Ethanol as a blending component for petrol - Requirements and test methods

Kraftstoffe für Kraftfahrzeuge - Ethanol zur Verwendung als Blendkomponente in Ottokraftstoff - Anforderungen und Prüfverfahren

Carburants pour automobiles - Ethanol comme base de mélange à l'essence - Exigences et méthodes d'essais

[SIST EN 15376:2008](https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008)

[https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-](https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008)

[3741d68dd3ef/sist-en-15376-2008](https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008)

Ta slovenski standard je istoveten z: EN 15376:2007

ICS:

71.080.60	Alkoholi. Etri	Alcohols. Ethers
75.160.20	Tekoča goriva	Liquid fuels

SIST EN 15376:2008**en,fr,de**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 15376:2008

<https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 15376

December 2007

ICS 75.160.20

English Version

**Automotive fuels - Ethanol as a blending component for petrol -
Requirements and test methods**

Carburants pour automobiles - Ethanol comme base de
mélange à l'essence - Exigences et méthodes d'essais

Kraftstoffe für Kraftfahrzeuge - Ethanol zur Verwendung als
Blendkomponente in Ottokraftstoff - Anforderungen und
Prüfverfahren

This European Standard was approved by CEN on 10 November 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

SIST EN 15376:2008

<https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Sampling	5
4 Requirements and test methods	5
4.1 Dyes and markers	5
4.2 Additives	5
4.3 Denaturing	5
4.4 Generally applicable requirements and related test methods	6
4.5 Climate dependent requirements and related test methods	8
4.6 Precision and dispute	8
Bibliography	9

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 15376:2008

<https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008>

Foreword

This document (EN 15376:2007) has been prepared by Technical Committee CEN/TC 19 "Gaseous and liquid fuels, lubricants and related products of petroleum, synthetic and biological origin", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2008, and conflicting national standards shall be withdrawn at the latest by June 2008.

This document has been prepared under mandate M/344 given to CEN by the European Commission and the European Free Trade Association along with other standards intended to be complementary to the regulatory measures contained in various EU Directives [1], [2] and [3].

If bio-ethanol is meant for use as automotive fuel component, this document applies. It is intended to call up this European Standard in EN 228, in order to define the quality of (bio)ethanol which is added/blended to the petrol.

Some of the test methods included in this document are the subject of inter-laboratory testing to determine the applicability of the method and its precision in relation to different sources of ethanol. At this moment in time, some precision statements are yet unknown and identified test methods and limits may change in future revisions of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

EN 15376:2007 (E)

1 Scope

This document specifies requirements and test methods for marketed and delivered ethanol to be used as an extender for automotive fuel for petrol engine vehicles in accordance with the requirements of EN 228.

NOTE 1 This document gives all relevant characteristics, requirements and test methods for (bio)ethanol, which are known at this time to be necessary to define the product to be used up to a maximum 5 % (V/V) blending component for automotive petrol fuel. If the percentage or use is expanded, the requirements need to be restudied.

NOTE 2 For the purposes of this document, the term “% (m/m)” and “% (V/V)” are used to represent the mass fraction and the volume fraction respectively.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 228, *Automotive fuels — Unleaded petrol — Requirements and test methods*

EN 15484:2007, *Ethanol as a blending component for petrol — Determination of inorganic chloride — Potentiometric method*

EN 15485:2007, *Ethanol as a blending component for petrol — Determination of sulfur content — Wavelength dispersive X-ray fluorescence spectrometric method*

EN 15486:2007, *Ethanol as a blending component for petrol — Determination of sulfur content — Ultraviolet fluorescence method*

EN 15487:2007, *Ethanol as a blending component for petrol — Determination of phosphorus content — Ammonium molybdate spectrometric method*

EN 15488:2007, *Ethanol as a blending component for petrol — Determination of copper content — Graphite furnace atomic absorption spectrometric method*

EN 15489:2007, *Ethanol as a blending component for petrol — Determination of water content — Karl-Fischer coulometric titration method*

EN 15491:2007, *Ethanol as a blending component for petrol — Determination of total acidity — Colour indicator titration method*

EN 15492:2007, *Ethanol as a blending component for petrol — Determination of inorganic chloride content — Ion chromatographic method*

EN ISO 3170:2004, *Petroleum liquids — Manual sampling (ISO 3170:2004)*

EN ISO 4259:2006, *Petroleum products — Determination and application of precision data in relation to methods of test (ISO 4259:2006)*

EC/2870/2000 - Method I, Appendix II, Method B, *Determination of real alcoholic strength by volume of spirit drinks — Measurement by electronic densimetry (based on the resonant frequency oscillation of a sample in an oscillation cell*, Commission Regulation (EC) No 2870/2000 of 19 December 2000, laying down Community reference methods for the analysis of spirit drinks

EC/2870/2000 – Method II, *Determination of total dry extract of spirit drinks by gravimetry*, Commission Regulation (EC) No 2870/2000 of 19 December 2000, laying down Community reference methods for the analysis of spirit drinks

EC/2870/2000 – Method III, *Determination of volatile substances and methanol of spirit drinks*, Commission Regulation (EC) No 2870/2000 of 19 December 2000, laying down Community reference methods for the analysis of spirit drinks

3 Sampling

Samples shall be taken as described in EN ISO 3170 and/or in accordance with the requirements of national standards or regulations for the sampling of alcohol. The national requirements shall be set out in detail or shall be referred to by reference in a national annex to this document.

In view of the sensitivity of some of the test methods referred to in this document, particular attention shall be paid to compliance with any guidance on sampling containers included in the test method standard.

It is essential that for sampling of ethanol the containers used to take and store the samples before testing are not contaminated with water and/or sulfur.

4 Requirements and test methods

4.1 Dyes and markers

The use of dyes or markers is allowed.

4.2 Additives

[SIST EN 15376:2008](https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-000000000000/sist-en-15376-2008)

[https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-](https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-000000000000/sist-en-15376-2008)

For distribution purposes, it is recommended that ethanol producers and downstream distributors and petrol blenders consider the need to add anti-corrosion additives to fuel grade ethanol. Suitable fuel additives without known harmful side effects and that are compatible with the finished petrol are recommended in the appropriate amount. These should not infringe patents through commingling.

4.3 Denaturing

Denaturants, as required by European and national customs regulations are permitted, provided they do not cause harmful side effects to vehicles and petroleum distribution systems.

Where denaturing of the automotive ethanol is required, it is strongly recommended to select denaturants from the list below that are known to be non harmful to vehicle systems:

- automotive petrol conforming to EN 228,
- Ethyltertbutylether (ETBE),
- Methyltertbutylether (MTBE),
- Tertiary Butyl Alcohol (TBA),
- 2-methyl-1-propanol (isobutanol) and
- 2-propanol (isopropanol).

EN 15376:2007 (E)

Any or all of these denaturants may be used alone or together, except isobutanol and isopropanol that are easily removed, so it is advisable to use them in combination with another denaturant.

NOTE The concentration of denaturant(s) is at the discretion of national authorities and should not contradict EN 228 requirements.

4.4 Generally applicable requirements and related test methods

4.4.1 When tested by the methods indicated in Table 1, ethanol before denaturing shall be in accordance with the limits specified in Table 1. The test methods listed in Table 1 have been shown to be applicable to ethanol in an interlaboratory test programme [4]. Precision data from this programme are incorporated in the test method.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 15376:2008](https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008)

<https://standards.iteh.ai/catalog/standards/sist/e18377bc-44ed-47d8-9ed0-3741d68dd3ef/sist-en-15376-2008>

Table 1 - Generally applicable requirements and test methods for undenatured ethanol

Property	Unit	Limits		Test method ^a
		minimum	maximum	
Ethanol content + higher saturated alcohols	% (m/m)	98,7		EC/2870/2000 – Method I, Appendix II, Method B ^b
Higher saturated (C3-C5) mono-alcohols content	% (m/m)		2,0	EC/2870/2000 – Method III ^b
Methanol content	% (m/m)		1,0	EC/2870/2000 – Method III ^b
Water content	% (m/m)		0,300	EN 15489 ^c
Inorganic chloride content	mg/l		20,0	EN 15484 or EN 15492 ^d
Copper content	mg/kg		0,100	EN 15488
Total acidity (expressed as acetic acid)	% (m/m)		0,007	EN 15491
Appearance		Clear and bright		Visual inspection ^b
Phosphorus content	mg/l		0,50	EN 15487
Involatile material content	mg/100ml		10	EC/2870/2000 – Method II ^e
Sulfur content	mg/kg		10,0	EN 15485 or EN 15486 ^f

^a See 4.4.1.

^b For ethanol purity, higher saturated (C3 C5) mono-alcohols content, methanol content and appearance, an improved test method is under development in CEN. See 4.6.3.

^c A cross check validation may show that a Karl Fischer volumetric method is also applicable, but in cases of dispute the indicated method shall be used.

^d See 4.6.2.

^e For involatile material an improved test method is under development in CEN [5].

^f See 4.6.2. These methods have special provisions for ethanol which are not incorporated in the usual petroleum test methods such as EN ISO 20846 [6] and EN ISO 20884 [7].

NOTE 1 A maximum sulfate content limit will be added once a test method standard (momentarily under development as a revision of EN 15492) has been published.

NOTE 2 To adequately limit the strong acidity and the alkaline substance, which cannot be sufficiently determined via pH_e [8], test method(s) are under development in CEN and a limit will be added once test method standards have been published.