



SLOVENSKI STANDARD

SIST EN 2395:2005

01-november-2005

BUXca Yý U.
SIST EN 2395:2001

Aerospace series - Aluminium alloy AL-P2014A-T4 or T42 - Sheet and strip - 0,4 mm < a < 6 mm

Aerospace series - Aluminium alloy AL-P2014A-T4 or T42 - Sheet and strip - 0,4 mm < a < 6 mm

iTeh STANDARD PREVIEW

Alphabets (standards.itech.si)

Luft- und Raumfahrt - Aluminiumlegierung AL-P2014A-T4 oder T42 - Bleche und Bänder
- 0,4 mm < a < 6 mm

SIST EN 2395:2005

<https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169->

Série aérospatiale - Alliage d'aluminium AL-P2014A-T4 ou T42 - Tôles et bandes - 0,4 mm < a < 6 mm

Ta slovenski standard je istoveten z: EN 2395:2005

ICS:

49.025.20 Aluminij Aluminium

SIST EN 2395:2005 en

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 2395:2005

<https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169-8927-3bb096d80092/sist-en-2395-2005>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 2395

June 2005

ICS 49.025.20

Supersedes EN 2395:1994

English version

**Aerospace series - Aluminium alloy AL-P2014A-T4 or T42 -
Sheet and strip - $0,4 \text{ mm} \leq a \leq 6 \text{ mm}$**

Série aérospatiale - Alliage d'aluminium AL-P2014A-T4 ou
T42 - Tôles et bandes - $0,4 \text{ mm} \leq a \leq 6 \text{ mm}$

Luft- und Raumfahrt - Aluminiumlegierung AL-2014A-
T4 oder T42 - Bleche und Bänder - $0,4 \text{ mm} \leq a \leq 6 \text{ mm}$

This European Standard was approved by CEN on 22 April 2005.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

iTeh STANDARD PREVIEW
STANDARDS ITALIA
<https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169-8927-3bb096d80092/sist-en-2395-2005>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

This document (EN 2395:2005) has been prepared by the European Association of Aerospace Manufacturers - Standardization (AECMA-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of AECMA, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2005, and conflicting national standards shall be withdrawn at the latest by December 2005.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 2395:1994.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 2395:2005

<https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169-8927-3bb096d80092/sist-en-2395-2005>

Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-2.

1 Scope

This standard specifies the requirements relating to:

Aluminium alloy AL-P2014A
T4 or T42
Sheet and strip
 $0,4 \text{ mm} \leq a \leq 6 \text{ mm}$

for aerospace application.

2 Normative references

iTeh STANDARD PREVIEW (standards.iteh.ai)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.[EN 2395:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169>

EN 4258, Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use.

EN 4400-2, Aerospace series — Aluminium and aluminium alloy wrought products — Technical specification — Part 2: Sheet and strip.¹⁾

EN 4500-2, Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 2: Specific rules for aluminium, aluminium alloys and magnesium alloys.¹⁾

1) Published as AECMA Prestandard at the date of publication of this standard.

EN 2395:2005 (E)

| | | | | | | | | | | | | | | | | |
|-----|------------------------------|---------|------|---------------------------|------|-----|------|------|------|------|------|---------|--------|------|----------------|--|
| 1 | Material designation | | | Aluminium alloy AL-P2014A | | | | | | | | | | | | |
| 2 | % Chemical composition | Element | Si | Fe | Cu | Mn | Mg | Cr | Ni | Zn | Ti | Ti + Zr | Others | | Al Base | |
| | | | min. | 0,50 | — | 3,9 | 0,40 | 0,20 | — | — | — | — | — | — | | |
| | | | max. | 0,9 | 0,50 | 5,0 | 1,2 | 0,8 | 0,10 | 0,10 | 0,25 | 0,15 | 0,20 | 0,05 | 0,15 | |
| 3 | Method of melting | | | — | | | | | | | | | | | | |
| 4.1 | Form | | | Sheet and strip | | | | | | | | | | | | |
| 4.2 | Method of production | | | Rolled | | | | | | | | | | | | |
| 4.3 | Limit dimension(s) | | mm | 0,4 ≤ a ≤ 6 | | | | | | | | | | | | |
| 5 | Technical specification | | | EN 4400-2 | | | | | | | | | | | | |

| | | | | | | | | | | | | | | |
|-----|-------------------------|--|--|--|---|--|--|--|--------------------|--|--|--|--|--|
| 6.1 | Delivery condition | | | F | O | T4 | | | | | | | | |
| | Heat treatment | | | — | — | 500 °C ≤ θ ≤ 510 °C / WQ, θ ≤ 40 °C + θ = ambient / t ≥ 5 d | | | | | | | | |
| 6.2 | Delivery condition code | | | F | A | U | | | | | | | | |
| 7 | Use condition | | | T42 | | | | | T4 | | | | | |
| | Heat treatment | | | Delivery condition + 500 °C ≤ θ ≤ 510 °C / WQ, θ ≤ 40 °C + θ = ambient / t ≥ 5 d | | | | | Delivery condition | | | | | |

iTeh STANDARD PREVIEW

Characteristics
(standards.iteh.ai)

| | | | | | | | | | | | | | | | | | | | | | | |
|-----|------------------------------------|-----------------------|-------------------|---|---------------|---------------|---------------|-------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 8.1 | Test sample(s) | | | See EN 4400-2. | | | | | | | | | | | | | | | | | | |
| 8.2 | Test piece(s) | | | SIST EN 2395:2005 See EN 4400-2. | | | | | | | | | | | | | | | | | | |
| 8.3 | Heat treatment | | | https://standards.iteh.ai/catalog/standards/see/7968e8b3-4432-4169-8927-58090d0002/sist-en-2395-2005 Delivery condition: T4 | | | | | | | | | | | | | | | | | | |
| 9 | Dimensions concerned | | mm | 0,4 ≤ a ≤ 1,6 | 1,6 < a ≤ 3,2 | 3,2 < a ≤ 6 | 0,4 ≤ a ≤ 6 | | | | | | | | | | | | | | | |
| 10 | Thickness of cladding on each face | | % | — | — | — | — | | | | | | | | | | | | | | | |
| 11 | Direction of test piece | | | — | — | — | LT | | | | | | | | | | | | | | | |
| 12 | T | Temperature | θ | °C | — | — | — | Ambient | | | | | | | | | | | | | | |
| 13 | | Proof stress | R _{p0,2} | MPa | — | — | — | ≥ 255 | | | | | | | | | | | | | | |
| 14 | C | Strength | R _m | MPa | — | — | — | ≥ 400 | | | | | | | | | | | | | | |
| 15 | | Elongation | A | % | — | — | — | A _{50 mm} ≥ 14 | | | | | | | | | | | | | | |
| 16 | Reduction of area | | Z | % | — | — | — | — | | | | | | | | | | | | | | |
| 17 | Hardness | | | — | — | — | — | | | | | | | | | | | | | | | |
| 18 | Shear strength | | R _c | MPa | — | — | — | — | | | | | | | | | | | | | | |
| 19 | Bending | | k | — | 1,5; α = 180° | 2,5; α = 180° | 3,5; α = 180° | — | | | | | | | | | | | | | | |
| 20 | Impact strength | | | — | | | | | | | | | | | | | | | | | | |
| 21 | C | Temperature | θ | °C | — | | | | | | | | | | | | | | | | | |
| 22 | | Time | | h | — | | | | | | | | | | | | | | | | | |
| 23 | | Stress | σ _a | MPa | — | | | | | | | | | | | | | | | | | |
| 24 | | Elongation | a | % | — | | | | | | | | | | | | | | | | | |
| 25 | | Rupture stress | σ _R | MPa | — | | | | | | | | | | | | | | | | | |
| 26 | | Elongation at rupture | A | % | — | | | | | | | | | | | | | | | | | |
| 27 | Notes (see line 98) | | | — | | | | | | | | | | | | | | | | | | |

| | | | | | | |
|----|-------------------------|---|--|-----------------------|------------------------------|----------------------------|
| 38 | Intergranular corrosion | - | See EN 4400-2. | | | |
| | | 7 | Dimensions (mm) | $0,4 \leq a \leq 1,6$ | $1,6 < a \leq 3,2$ | $3,2 < a \leq 6$ |
| | | | Depth of penetration (μm) | ≤ 125 | ≤ 150 | ≤ 200 |
| 44 | External defects | - | See EN 4400-2. | | | |
| 82 | Batch uniformity | - | See EN 4400-2. | | | |
| | | 5 | T4 | | | |
| | | 7 | Electrical conductivity | γ | MS/m | 18,5 (Typical value) |
| | | | or | | | |
| | | 7 | Hardness | HB | 115 (Typical value) | |
| | | | | | $\delta \leq 16$ per product | $\Delta \leq 24$ per batch |
| | | | | | | |
| 95 | Marking inspection | - | See EN 4400-2. | | | |
| 96 | Dimensional inspection | - | See EN 4400-2. | | | |
| 98 | Notes | - | - | | | |
| 99 | Typical use | - | - | | | |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 2395:2005

<https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169-8927-3bb096d80092/sist-en-2395-2005>

EN 2395:2005 (E)

| | | | | |
|-----|---|-----------------------|---|---|
| 100 | - | Product qualification | - | See EN 4400-2. Qualification programme to be agreed between manufacturer and purchaser. |
| | | | | <p style="text-align: center;">iTeh STANDARD PREVIEW (standards.iteh.ai)</p> <p style="text-align: center;">SIST EN 2395:2005 https://standards.iteh.ai/catalog/standards/sist/7968e8b3-4d32-4169-8927-3bb096d80092/sist-en-2395-2005</p> |