

INTERNATIONAL STANDARD



**Fixed capacitors for use in electronic equipment –
Part 21: Sectional specification – Fixed surface mount multilayer capacitors
of ceramic dielectric, Class 1**

IEC 60384-21:2019

<https://standards.iteh.ai/catalog/standards/iec/52e10e0f-ed05-48f2-9f11-b99e0f265026/iec-60384-21-2019>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC 60384-21:2019

<https://standards.iteh.ai/en/standards/iec/3/3e10e0f-ed05-48f2-9f11-b99e0f265026/iec-60384-21-2019>

INTERNATIONAL STANDARD



**Fixed capacitors for use in electronic equipment –
Part 21: Sectional specification – Fixed surface mount multilayer capacitors
of ceramic dielectric, Class 1**

<https://standards.iteh.ai/catalog/standards-iec/32e10e0f-ed05-48f2-9f11-b99e0f265026/iec-60384-21-2019>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.060.10

ISBN 978-2-8322-6514-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	6
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	9
4 Information to be given in a detail specification.....	10
4.1 General.....	10
4.2 Outline drawing and dimensions	10
4.3 Mounting.....	10
4.4 Rating and characteristics.....	10
4.4.1 General	10
4.4.2 Nominal capacitance range.....	10
4.4.3 Particular characteristics	11
4.4.4 Soldering.....	11
4.5 Marking.....	11
5 Marking	11
5.1 General.....	11
5.2 Information for marking	11
5.3 Marking on the body	11
5.4 Requirements for marking	11
5.5 Marking of the packaging	11
5.6 Additional marking	11
6 Preferred ratings and characteristics	12
6.1 Preferred characteristics	12
6.2 Preferred values of ratings	12
6.2.1 Rated temperature (T_P)	12
6.2.2 Rated voltage (U_R).....	12
6.2.3 Category voltage (U_C).....	12
6.2.4 Preferred values of nominal capacitance and associated tolerance values.....	12
6.2.5 Temperature coefficient (α)	13
6.2.6 Dimensions.....	15
7 Quality assessment procedures	16
7.1 Primary stage of manufacture	16
7.2 Structurally similar components	16
7.3 Certified records of released lots	16
7.4 Qualification approval	16
7.4.1 General	16
7.4.2 Qualification approval on the basis of the fixed sample size procedures	16
7.4.3 Tests	17
7.5 Quality conformance inspection	22
7.5.1 Formation of inspection lots.....	22
7.5.2 Test schedule	22
7.5.3 Delayed delivery.....	22
7.5.4 Assessment levels	22
8 Test and measurement procedures.....	23
8.1 General.....	23

8.2	Preliminary drying	23
8.3	Measuring conditions	24
8.4	Mounting	24
8.5	Visual examination and check of dimensions	24
8.5.1	General	24
8.5.2	Visual examination	24
8.5.3	Requirements	24
8.6	Electrical tests	26
8.6.1	Capacitance	26
8.6.2	Tangent of loss angle ($\tan \delta$)	26
8.6.3	Insulation resistance	27
8.6.4	Voltage proof	27
8.7	Temperature coefficient (α) and temperature cycle drift	28
8.7.1	General	28
8.7.2	Preliminary drying	28
8.7.3	Measuring conditions	28
8.7.4	Requirements	28
8.8	Shear test	29
8.9	Substrate bending test	29
8.9.1	General	29
8.9.2	Initial measurement	29
8.9.3	Final inspection	29
8.10	Resistance to soldering heat	29
8.10.1	General	29
8.10.2	Initial measurement	29
8.10.3	Test conditions	29
8.10.4	Recovery	31
8.10.5	Final inspection, measurements and requirements	31
8.11	Solderability	31
8.11.1	General	31
8.11.2	Test conditions	32
8.11.3	Recovery	32
8.11.4	Final inspection, measurements and requirements	32
8.12	Rapid change of temperature	33
8.12.1	General	33
8.12.2	Initial measurement	33
8.12.3	Number of cycles	33
8.12.4	Recovery	33
8.12.5	Final inspection, measurements and requirements	33
8.13	Climatic sequence	33
8.13.1	General	33
8.13.2	Initial measurement	33
8.13.3	Dry heat	33
8.13.4	Damp heat, cyclic, Test Db, first cycle	33
8.13.5	Cold	34
8.13.6	Damp heat, cyclic, Test Db, remaining cycles	34
8.13.7	Final inspection, measurements and requirements	34
8.14	Damp heat, steady state	35
8.14.1	General	35

8.14.2	Initial measurement	35
8.14.3	Test conditions	35
8.14.4	Recovery	35
8.14.5	Final inspection, measurements and requirements.....	35
8.15	Endurance	36
8.15.1	General	36
8.15.2	Initial measurement	36
8.15.3	Test conditions	36
8.15.4	Recovery	37
8.15.5	Final inspection, measurements and requirements.....	37
8.16	Robustness of terminations (only for capacitors with strip termination).....	37
8.16.1	General	37
8.16.2	Test conditions	37
8.16.3	Final inspection and requirements	38
8.17	Component solvent resistance (if required)	38
8.18	Solvent resistance of the marking (if required)	38
8.19	Accelerated damp heat, steady state (if required).....	38
8.19.1	General	38
8.19.2	Initial measurement	38
8.19.3	Conditioning	38
8.19.4	Recovery	39
8.19.5	Final measurements	39
Annex A (normative) Guidance for the specification and coding of dimensions of fixed surface mount multilayer capacitors of ceramic dielectric, Class 1		40
Annex B (informative) Combination of temperature coefficient and tolerance for the reference temperature of 25 °C.....		41
Annex X (informative) Cross-reference for reference to IEC 60384-21:2011.....		42
Bibliography.....		43
Figure 1 – Fault: crack or fissure.....		24
Figure 2 – Fault: crack or fissure.....		24
Figure 3 – Separation or delamination		25
Figure 4 – Exposed electrodes.....		25
Figure 5 – Principal faces		25
Figure 6 – Reflow temperature profile		31
Figure A.1 – Dimensions.....		40
Table 1 – Preferred tolerances on nominal capacitance		13
Table 2 – Nominal temperature coefficient and tolerance		14
Table 3 – Combination of temperature coefficient and tolerance		15
Table 4 – Fixed sample size test plan for qualification approval – Assessment level EZ.....		18
Table 5 – Tests schedule for qualification approval.....		19
Table 6 – Lot-by-lot inspection		23
Table 7 – Periodic tests		23
Table 8 – Tangent of loss angle limits		26
Table 9 – Test voltages.....		28

Table 10 – Temperature cyclic drift limits.....	29
Table 11 – Reflow temperature profiles for Sn-Ag-Cu alloy	30
Table 12 – Maximum capacitance change.....	31
Table 13 – Maximum capacitance change.....	33
Table 14 – Number of damp heat cycles	34
Table 15 – Final inspection, measurements and requirements	34
Table 16 – Test conditions for damp heat, steady state.....	35
Table 17 – Final inspection, measurements and requirements	36
Table 18 – Endurance test conditions ($U_C = U_R$)	36
Table 19 – Endurance test conditions ($U_C \neq U_R$)	37
Table 20 – Final inspection, measurements and requirements	37
Table 21 – Initial requirements.....	38
Table 22 – Conditioning	39
Table A.1 – Dimensions	40
Table B.1 – Combination of temperature coefficient and tolerance for the reference temperature of 25 °C	41
Table X.1 – Reference to IEC 60384-21 for clause/subclause.....	42
Table X.2 – Reference to IEC 60384-21 for figure/table	42

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

IEC 60384-21:2019

<https://standards.iteh.ai/catalog/standards-iec/32e10e0f-ed05-48f2-9f11-b99e0f265026/iec-60384-21-2019>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –**Part 21: Sectional specification –
Fixed surface mount multilayer capacitors
of ceramic dielectric, Class 1**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60384-21 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This third edition cancels and replaces the second edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) revision of the structure in accordance with ISO/IEC Directives, Part 2:2016 to the extent practicable, and for harmonizing with IEC 60384-22;
- b) deletion of the description on the permissible reactive power in 6.2.2 because it is not appropriate for the purposes of this document;
- c) the dimensions of 0201M in Annex A have been added.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
40/2639/FDIS	40/2651/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60384 series, published under the general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 21: Sectional specification – Fixed surface mount multilayer capacitors of ceramic dielectric, Class 1

~~1~~ **General**

1 Scope

This part of IEC 60384 is applicable to fixed unencapsulated surface mount multilayer capacitors of ceramic dielectric, Class 1, for use in electronic equipment. These capacitors have metallized connecting pads or soldering strips and are intended to be mounted on printed boards, or directly onto substrates for hybrid circuits.

Capacitors for electromagnetic interference suppression are not included, but are covered by IEC 60384-14.

~~1.2~~ **Object**

The object of this document is to prescribe preferred ratings and characteristics and to select from IEC 60384-1 the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor. Test severities and requirements prescribed in detail specifications referring to this sectional specification ~~should be~~ are of equal or higher performance levels; lower performance levels are not permitted.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60063:~~1963~~, Preferred number series for resistors and capacitors
Amendment 1 (1967)
Amendment 2 (1977)

IEC 60068-1:~~1988~~ 2013, Environmental testing – Part 1: General and guidance

IEC 60068-2-58:~~2004~~ 2015, Environmental testing – Part 2-58: Tests – Test Td – Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)
IEC 60068-2-58:2015/AMD1:2017

IEC 60384-1:~~2008~~ 2016, Fixed capacitors for use in electronic equipment – Part 1: Generic specification

IEC 61193-2:2007, Quality assessment systems – Part 2: Selection and use of sampling plans for inspection of electronic components and packages

ISO 3:1973, Preferred numbers – Series of preferred numbers

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60384-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

surface mount multilayer capacitor

multilayer capacitor whose small dimensions and nature or shape of terminations make it suitable for surface mounting in hybrid circuits and on printed boards

3.2

fixed capacitors, capacitor of ceramic dielectric, Class 1

capacitor specially designed and suited for resonant circuit application where low losses and high stability of capacitance are essential or where a precisely defined temperature coefficient is required, for example for compensating temperature effects in the circuit

Note 1 to entry: The ceramic dielectric is defined by its ~~rated~~ nominal temperature coefficient (α).

3.3

subclass

for a given nominal temperature coefficient, the subclass is defined by the tolerance on the temperature coefficient

Note 1 to entry: See Table 2.

Note 2 to entry: The nominal temperature coefficient value and its tolerance refer to the temperature interval of +20 °C to +85 °C, but because in practice TC curves are not strictly linear, it is necessary to define limiting capacitance deviation ($\Delta C/C$) for other temperatures (see Table 3).

3.4

category temperature range

~~range of~~ ambient temperatures range for which the capacitor has been designed to operate continuously

Note 1 to entry: This is given by the lower and upper category temperature.

3.5

rated temperature

T_R

maximum ambient temperature at which the rated voltage may be continuously applied

3.6

rated ~~d.c.~~ voltage

U_R

maximum DC voltage that may be applied continuously to a capacitor at any temperature between the lower category temperature and the rated temperature

Note 1 to entry: The maximum DC voltage is the sum of the DC voltage and peak AC voltage or peak pulse voltage applied to the capacitor.

3.7

category voltage

U_C

maximum voltage that ~~may~~ can be applied continuously to a capacitor at its upper category temperature

4 Information to be given in a detail specification

4.1 General

The detail specification shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included, they shall be listed in 1.9 of the detail specification and indicated in the test schedules, for example by an asterisk.

NOTE The information given in 4.2 may be presented in tabular form if more convenient.

The information in 4.2 to 4.5 shall be given in each detail specification and the values quoted shall preferably should be selected from those given in the appropriate clause of this sectional specification.

4.2 Outline drawing and dimensions

There shall be an illustration of the capacitors as an aid to easy recognition and for comparison of the capacitors with others.

Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given in the detail specification. All dimensions shall preferably be stated in millimetres; however, when the original dimensions are given in inches, the converted metric dimensions in millimetres shall be added.

Normally the numerical values shall be given for the length, width and height of the body. When necessary, for example when a number of items (sizes and capacitance/voltage ranges) are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitors.

4.3 Mounting

The detail specification shall give guidance on methods of mounting for normal use. Mounting for test and measurement purposes (when required) shall be in accordance with 8.4 of this sectional specification.

4.4 Rating and characteristics

4.4.1 General

The ratings and characteristics shall be in accordance with the relevant clauses of this sectional specification, together with 4.4.2, 4.4.3 and 4.4.4.

4.4.2 Nominal capacitance range

See 6.2.4.1.

NOTE When products approved to the detail specification have different ranges, the following statement should be added: "The range of capacitance values available in each voltage range is given in the register of approvals, available for example on the IECQ on-line certificate system website: www.iecq.org".

4.4.3 Particular characteristics

Additional characteristics may be listed when they are considered necessary to specify adequately the component for design and application purposes.

4.4.4 Soldering

The detail specification shall prescribe the test methods, severities and requirements applicable for the solderability and the resistance to soldering heat tests.

4.5 Marking

The detail specification shall specify the content of the marking on the capacitor and on the packaging. Deviations from Clause 5 of this sectional specification shall be specifically stated.

5 Marking

5.1 General

See IEC 60384-1:2016, 2.4, with the details of 5.2 to 5.6.

5.2 Information for marking

The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- nominal capacitance;
- rated voltage (DC voltage may be indicated by the symbol: $\overline{\text{---}}$ [IEC 60417-5031(2002-10)] or ---);
- tolerance on nominal capacitance;
- temperature coefficient and its tolerance as applicable (in accordance with 6.2.5);
- year and month (or week) of manufacture;
- manufacturer's name or trade mark;
- climatic category;
- manufacturer's type designation;
- reference to the detail specification.

5.3 Marking on the body

These capacitors are generally not marked on the body. If some markings can be applied, they shall be clearly marked with as many as possible of the items stated in 5.2 as is considered useful. Any duplication of information in the marking on the capacitor should be avoided.

5.4 Requirements for marking

Any marking shall be legible and not easily smeared or removed by rubbing with fingers.

5.5 Marking of the packaging

The packaging containing the capacitor(s) shall be clearly marked with all the information listed in 5.2.

5.6 Additional marking

Any additional marking shall be so applied that no confusion can arise.

6 Preferred ratings and characteristics

6.1 Preferred characteristics

~~The values given in the detail specification shall preferably be selected from the following.~~

Preferred climatic categories only shall be given in the preferred characteristics.

The capacitors covered by this document are classified into climatic categories in accordance with the general rules given in IEC 60068-1:2013, Annex A.

The lower and upper category temperatures and the duration of the damp heat, steady state test shall be chosen from the following:

- lower category temperature: -55 °C, -40 °C, -25 °C, -10 °C and +10 °C;
- upper category temperature: +70 °C, +85 °C, +100 °C, +125 °C and +150 °C;
- duration of the damp heat,
steady state test (40 °C, 93 % RH): 4, 10, 21 and 56 days.

The severities of the cold and dry heat tests are the lower and upper category temperatures respectively.

NOTE The resistance to humidity resulting from the above climatic category is for the capacitors in their unmounted state. The climatic performance of the capacitors after mounting is greatly influenced by the mounting substrate, the mounting method (see 8.4) and the final coating.

6.2 Preferred values of ratings

6.2.1 Rated temperature (T_R)

For capacitors covered by this sectional specification, the rated temperature is equal to the upper category temperature, unless the upper category temperature exceeds 125 °C.

6.2.2 Rated voltage (U_R)

The preferred values of the rated voltage are the values of the R5 series of ISO 3. If other values are needed, they shall be chosen from the R10 series.

The sum of the DC voltage and the peak AC voltage or the peak to peak AC voltage, whichever is the greater, applied to the capacitor shall not exceed the rated voltage. ~~The value of the peak a.c. voltage shall not exceed the value determined by the permissible reactive power.~~

6.2.3 Category voltage (U_C)

When the rated temperature is defined as the upper category temperature, the category voltage is equal to the rated voltage as defined in IEC 60384-1:2016, 2.2.5. If the upper category temperature exceeds 125 °C, or the rated voltages exceed 500 V, the category voltage shall be given in the detail specification.

6.2.4 Preferred values of nominal capacitance and associated tolerance values

6.2.4.1 Preferred values of nominal capacitance

Nominal capacitance values shall be taken from the number series of IEC 60063; the E6, E12 and E24 series are preferred.

6.2.4.2 Preferred tolerances on nominal capacitance

See Table 1.