



SLOVENSKI STANDARD

SIST ISO 14240-2:2006

01-september-2006

Soil quality -- Determination of soil microbial biomass -- Part 2: Fumigation-extraction method

Soil quality -- Determination of soil microbial biomass -- Part 2: Fumigation-extraction method

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Qualité du sol -- Détermination de la biomasse microbienne du sol -- Partie 2: Méthode par fumigation-extraction

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>

Ta slovenski standard je istoveten z: ISO 14240-2:1997

ICS:

13.080.30

Biološke lastnosti tal

Biological properties of soils

SIST ISO 14240-2:2006

en

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST ISO 14240-2:2006

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>

**Soil quality — Determination of soil
microbial biomass —**

**Part 2:
Fumigation-extraction method**

*Qualité du sol — Détermination de la biomasse microbienne du sol —
Partie 2: Méthode d'extraction par fumigation*
(standards.iteh.ai)

SIST ISO 14240-2:2006

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 14240-2 was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 4, *Biological methods*.

ISO 14240 consists of the following parts, under the general title *Soil quality — Determination of soil microbial biomass*:

- *Part 1: Substrate-induced respiration method*
- *Part 2: Fumigation-extraction method*

ITEH STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 14240-2:2006

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet central@iso.ch
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

Introduction

Soil consists of both living and nonliving components which exist in a complex and heterogeneous environment. Soil microflora is responsible for the degradation of organic matter, stability of aggregates and most nutrient cycling which occurs in soils. The purpose of determining the microbial biomass of soils is to allow assessment of the continued maintenance of soil fertility, the potential ability to degrade added organic materials, and the effects of added materials on the natural microbial population.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 14240-2:2006

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

This page intentionally left blank

SIST ISO 14240-2:2006

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>

Soil quality — Determination of soil microbial biomass —

Part 2:

Fumigation-extraction method

1 Scope

This part of ISO 14240 specifies a method for the estimation of microbial biomass of soils by measurement of total extractable organic biomass material mainly from freshly killed microorganisms. The method is also applicable to the estimation of microbial nitrogen and microbial ninhydrin-reactive nitrogen in soil, but this part of ISO 14240 describes only the measurement of extractable organic carbon. The fumigation-extraction (FE) method is applicable to aerobic and anaerobic (water-logged, paddy) soils over the whole range of soil pH. Biomass can be also measured in soils containing actively decomposing substrates and soils supersaturated with potassium sulfate solution.

NOTE — Chloroform fumigation also affects soil fauna. The contribution of carbon from these organisms is generally small (< 5 %) and can usually be neglected.

2 Normative references

[SIST ISO 14240-2:2006](https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006)

<https://standards.iteh.ai/catalog/standards/sist/f0d914bc-3448-4604-b80f-fb46c76b0263/sist-iso-14240-2-2006>

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 14240. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 14240 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 10381-6:1993, *Soil quality — Sampling — Part 6: Guidance on the collection, handling and storage of soil for the assessment of aerobic microbial processes in the laboratory.*

ISO 10694:1995, *Soil quality — Determination of organic and total carbon after dry combustion (elementary analysis).*

ISO 11465:1993, *Soil quality — Determination of dry matter and water content on a mass basis — Gravimetric method.*

3 Definition

For the purposes of this part of ISO 14240, the following definition applies.

3.1 soil microbial biomass

mass of intact microbial cells in a given soil

NOTE — This parameter can be estimated from the measurement of the carbon or nitrogen content of these cells or by the measurement of their ability to mineralize an added carbon source. Dead cells and cell fragments may be detected when carbon or nitrogen analysis is used but only intact cells will be detected when respiration is measured.

4 Principle

Through fumigation of the soil sample, intact microbial cells are lysed and the microbial organic matter released. Nonliving soil organic matter is not seriously affected by such fumigation. Soil samples are fumigated with chloroform for 24 h. The organic carbon extracted using 0,5 mol/l potassium sulfate is determined in fumigated and unfumigated samples, and the difference in extracted organic carbon is used to determine microbial biomass carbon. The method is usually termed fumigation-extraction (FE).

5 Materials and reagents

5.1 Soils

Guidance for the collection, handling and storage of soil (ISO 10381-6) shall be followed, as far as applicable. Sieve the soil samples at approximately 40 % water-holding capacity (WHC) if homogeneous samples are required.

Determine the soil WHC in accordance with annex A.

The water content of samples shall be higher than 30 % WHC to ensure uniform chloroform distribution and effective fumigation. Take care to avoid smearing and compaction of wet soil in this method. Samples of waterlogged soils do not have to be dried prior to analysis.

5.2 Reagents

Reagents of recognized analytical grade shall be used, including:

5.2.1 Silicone grease (medium viscosity).

5.2.2 Ethanol-free chloroform.

WARNING — In the presence of light, ethanol-free chloroform degrades rapidly to form phosgene gas (COCl_2) which is odourless and highly toxic.

5.2.3 Potassium sulfate solution, $c(\text{K}_2\text{SO}_4) = 0,5 \text{ mol/l}$ ($\rho = 87,135 \text{ g/l}$).

5.2.4 Soda lime.

6 Apparatus

6.1 Room, or incubator, capable of being maintained at $(25 \pm 2) ^\circ\text{C}$.

6.2 Implosion-protected desiccator.

6.3 Filter paper¹⁾.

6.4 Glass beakers.

6.5 Petri dishes.

6.6 Polyethylene bottles, of capacity 250 ml.

1) Whatman No. 42, Schleicher & Schüll 595 1/2, Machery & Nagel 261 G 1/4, are examples of suitable products available commercially. This information is given for the convenience of users of this part of ISO 14240 and does not constitute an endorsement by ISO of these products.

6.7 Vacuum line (water-pump or electric pump).

6.8 Horizontal or overhead shaker.

6.9 Freezer, operation at (–15 to –20) °C.

6.10 Antibumping granules.

7 Fumigation and extraction

7.1 Fumigation

Line the desiccator (6.2) with moist filter paper (6.3) for fumigation of the soil samples.

Weigh at least three samples of moist soil (5.1), each containing a mass equivalent to 25 to 50 g of oven-dry soil, into glass beakers (6.4) or Petri dishes (6.5) and place them in the desiccator with a beaker containing 25 ml of ethanol-free chloroform (5.2.2) and a few antibumping granules (6.10), and a beaker with soda lime (5.2.4). Evacuate the desiccator until the chloroform has boiled vigorously for approximately 2 min. Close the vacuum tap on the desiccator and incubate in the dark (6.1) at (25 ± 2) °C for 22 h to 24 h.

If there is insufficient soil available, use smaller samples provided the ratio of soil mass to volume of extractant is kept the same (1:4). In soils containing more than 20 % organic material (as determined according to ISO 10694), increase the ratio soil:extract above 1:4 (to a maximum of 1:30 for soils containing 95 % organic matter, e.g. L-layer) in order to obtain sufficient extracted matter. Record the mass of soil used.

After fumigation is completed, remove the beaker containing the chloroform and the filter paper from the desiccators. Remove the chloroform vapour from the soil by repeated evacuation (6 times for 2 min each) in the desiccator. The samples are ready for extraction.

Place three unfumigated, moist control samples (50 g dry mass) into polyethylene bottles (6.6) and immediately extract with 200 ml of the potassium sulfate (5.2.3), as indicated in 7.2.

7.2 Extraction

To extract organic carbon, transfer the soil quantitatively to polyethylene bottles (6.6), add 200 ml of potassium sulfate (5.2.3), shake the bottles on a horizontal shaker (6.8) at 200 r/min for 30 min or an overhead shaker at 60 r/min for 45 min and filter the extracts through a folded filter paper (6.3). Extract the unfumigated controls and filter the extracts in the same way.

If not analyzed at once, store the extracts of fumigated and unfumigated soil samples in the freezer (6.9) at between –15 °C and –20 °C. Homogenize frozen extracts before use, after thawing at room temperature.

NOTES

1 A white precipitate occurs during storage of the potassium sulfate soil extracts (especially if the samples are frozen) because they are usually supersaturated with calcium sulfate (CaSO_4). It is unnecessary to dissolve this excess CaSO_4 because it does not interfere with any of the analytical procedures described in this method.

2 Cell membranes of young, living roots are also affected by chloroform fumigation. In soils containing large amounts of living roots, the pre-extraction procedure given in annex B should be used.

8 Determination of carbon in the extracts

The carbon content of microorganisms in a soil sample is determined analytically and can be used to make comparisons between different soil samples. Where a figure for actual microbial biomass is required, then such analyses are multiplied by a conversion factor derived from experiments correlating a known cell mass to carbon analysis after fumigation-extraction. All conversion factors used are related to this initial factor.