

First edition
1996-12-15

Corrected and reprinted
1998-07-15

**Information technology — 130 mm optical
disk cartridges for information
interchange — Capacity: 2,6 Gbytes per
cartridge**

*Technologies de l'information — Cartouches de disque optique de 130 mm
pour l'échange d'information — Capacité: 2,6 Gbytes par cartouche*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

[https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-
d26203857af7/iso-iec-14517-1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)



Contents

	Page
Section 1 - General	1
1 Scope	1
2 Conformance	2
2.1 Optical Disk Cartridge (ODC)	2
2.2 Generating system	2
2.3 Receiving system	2
2.4 Compatibility statement	2
3 Normative reference	2
4 Definitions	2
4.1 band	2
4.2 case	2
4.3 clamping zone	2
4.4 control track	2
4.5 Cyclic Redundancy Check (CRC)	2
4.6 defect management	2
4.7 direct overwrite	2
4.8 disk reference plane	2
4.9 entrance surface	2
4.10 Error Correction Code (ECC)	2
4.11 format	2
4.12 hub	2
4.13 interleaving	2
4.14 Kerr rotation	3
4.15 land and groove	3
4.16 logical track	3
4.17 mark	3
4.18 mark edge	3
4.19 mark edge recording	3
4.20 optical disk	3
4.21 optical disk cartridge (ODC)	3
4.22 physical track	3
4.23 polarization	3
4.24 pre-recorded mark	3

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

©ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

4.25	read power	3
4.26	recording layer	3
4.27	Reed-Solomon code	3
4.28	space	3
4.29	spindle	3
4.30	substrate	3
4.31	track pitch	3
4.32	write-inhibit hole	3
4.33	write-once functionality	3
4.34	zone	3
5	Conventions and notations	4
5.1	Representation of numbers	4
5.2	Names	4
6	List of acronyms	4
7	General description of the optical disk cartridge	5
8	General requirements	5
8.1	Environments	5
8.1.1	Test environment	5
8.1.2	Operating environment	5
8.1.3	Storage environment	6
8.1.4	Transportation	6
8.2	Temperature shock	6
8.3	Safety requirements	6
8.4	Flammability	6
9	Reference Drive	6
9.1	Optical system	6
9.2	Optical beam	8
9.3	Read channels	8
9.4	Tracking	8
9.5	Rotation of the disk	8
Section 2 - Mechanical and physical characteristics		9
10	Dimensional and physical characteristics of the case	9
10.1	General description of the case	9
10.2	Relationship of Sides A and B	9
10.3	Reference axes and case reference planes	9
10.4	Case drawings	9
10.5	Dimensions of the case	9
10.5.1	Overall dimensions	9
10.5.2	Location hole	10
10.5.3	Alignment hole	10
10.5.4	Surfaces on Reference Planes P	11
10.5.5	Insertion slots and detent features	12
10.5.6	Gripper slots	12
10.5.7	Write-inhibit holes	13
10.5.8	Media sensor holes	13
10.5.9	Head and motor window	14
10.5.10	Shutter	14
10.5.11	Slot for shutter opener	15

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

10.5.12	Shutter sensor notch	15
10.5.13	User label areas	16
10.6	Mechanical characteristics	16
10.6.1	Materials	16
10.6.2	Mass	16
10.6.3	Edge distortion	16
10.6.4	Compliance	16
10.6.5	Shutter opening force	16
10.7	Drop test	16
11	Dimensional, mechanical and physical characteristics of the disk	17
11.1	General description of the disk	17
11.2	Reference axis and plane of the disk	17
11.3	Dimensions of the disk	17
11.3.1	Hub dimension	17
11.4	Mechanical characteristics	18
11.4.1	Material	18
11.4.2	Mass	18
11.4.3	Moment of inertia	18
11.4.4	Imbalance	18
11.4.5	Axial deflection	19
11.4.6	Axial acceleration	19
11.4.7	Radial runout	19
11.4.8	Radial acceleration	19
11.4.9	Tilt	20
11.5	Optical characteristics	20
11.5.1	Index of refraction	20
11.5.2	Thickness	20
11.5.3	Birefringence	20
11.5.4	Vertical Birefringence	20
11.5.5	Reflectance	20
12	Interface between cartridge and drive	21
12.1	Clamping method	21
12.2	Clamping force	21
12.3	Capture cylinder	21
12.4	Disk position in the operating condition	21
Section 3 - Format of information		36
13	Track geometry	36
13.1	Track shape	36
13.2	Direction of track spiral	36
13.3	Track pitch	36
13.4	Logical track number	36
13.5	Physical track number	36
14	Track format	36
14.1	Physical track layout	36
14.2	Logical track layout	37
14.3	Radial alignment	37
14.4	Sector number	37
15	Sector format	37
15.1	Sector layout	37

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

15.2 Sector Mark	38
15.3 VFO fields	39
15.4 Address Mark (AM)	40
15.5 ID fields	40
15.6 Postamble (PA)	41
15.7 Gap	41
15.8 Flag	41
15.9 Auto Laser Power Control (ALPC)	42
15.10 Sync	42
15.11 Data field	42
15.11.1 User data bytes	42
15.11.2 CRC and ECC bytes	42
15.11.3 Bytes for the Sector Written Flag (SWF)	43
15.11.4 Bytes following the SWF in the Data field of the 512-byte sector format	43
15.11.5 Resync bytes	43
15.12 Buffer field	43
16 Recording code	43
17 Formatted Zone	44
17.1 General description of the Formatted Zone	44
17.2 Division of the Formatted Zone	44
17.2.1 Lead-in Zone	46
17.2.2 Manufacturer Zones	46
17.2.3 User Zone	47
17.2.4 Reflective Zone	47
17.2.5 Control Track Zones	47
17.3 Control Track PEP Zone	47
17.3.1 Recording in the PEP Zone	47
17.3.2 Format of the tracks of the PEP Zone	48
17.4 Control Track SFP Zones	52
17.4.1 Duplicate of the PEP information	52
17.4.2 Media information	53
17.4.3 System Information	55
18 Layout of the User Zone	57
18.1 General description of the User Zone	57
18.2 Divisions of the User Zone	57
18.3 User Area	57
18.4 Defect Management Areas (DMAs)	60
18.5 Disk Definition Structure (DDS)	60
18.6 Rewritable Zone	62
18.6.1 Location	63
18.6.2 Partitioning	63
18.7 Embossed Zone	63
18.7.1 Location	63
18.7.2 Partitioning	63
18.7.3 Parity sectors	63
18.8 Write Once Zone	64
18.8.1 Location	64
18.8.2 Partitioning	64
19 Defect Management in the Rewritable and Write Once Zones	64


 (standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

19.1 Initialization of the disk	64
19.2 Certification	64
19.2.1 Slipping Algorithm	64
19.2.2 Linear Replacement Algorithm	65
19.3 Disks not certified	65
19.4 Write procedure	65
19.5 Primary Defect List (PDL)	65
19.6 Secondary Defect List (SDL)	66
Section 4 - Characteristics of embossed information	67
20 Method of testing	67
20.1 Environment	67
20.2 Use of the Reference Drive	67
20.2.1 Optics and mechanics	67
20.2.2 Read power	68
20.2.3 Read channels	68
20.2.4 Tracking	68
20.3 Definition of signals	68
21 Signal from grooves	70
21.1 Cross-track signal	70
21.2 Cross Track Minimum Signal	70
21.3 Push-pull signal	71
21.4 Divided push-pull signal	71
21.5 Phase depth	72
21.6 Track location	72
22 Signals from Headers	72
22.1 Sector Mark Signals	72
22.2 VFO signals	72
22.3 Address Mark, ID and PA signals	72
22.4 Timing jitter	73
23 Signals from embossed Recording fields	73
23.1 Signal amplitude	73
23.2 Modulation method offset	73
23.3 Timing Jitter	74
23.4 Byte Errors	74
24 Signals from Control Track PEP marks	74
Section 5 - Characteristics of the recording layer	75
25 Method of testing	75
25.1 Environment	75
25.2 Reference Drive	75
25.2.1 Optics and mechanics	75
25.2.2 Read power	75
25.2.3 Read Channel	75
25.2.4 Tracking	75
25.2.5 Signal detection for testing purposes	75
25.3 Write conditions	75
25.3.1 Write pulse and power	75
25.3.2 Write magnetic field	76

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

25.3.3	Pulse power determination	76
25.3.4	Media power sensitivity	76
25.4	Erase conditions	77
25.4.1	Erase power	77
25.4.2	Erase magnetic field	77
25.5	Definition of signals	77
26	Magneto-optical characteristics	77
26.1	Figure of merit for magneto-optical signal	77
26.2	Imbalance of magneto-optical signal	78
27	Write characteristics	78
27.1	Resolution	78
27.2	Narrow-band signal-to-noise ratio	79
27.3	Cross-talk ratio	79
27.3.1	Rewritable track test method	79
27.3.2	Embossed track test method	80
27.4	Timing Jitter	80
27.5	Media thermal interaction	80
28	Erase power determination	81
Section 6 - Characteristics of user data		82
29	Method of testing	82
29.1	Environment	82
29.2	Reference Drive	82
29.2.1	Optics and mechanics	82
29.2.2	Read power	82
29.2.3	Read amplifiers	82
29.2.4	Mark Quality	82
29.2.5	Channel bit clock	83
29.2.6	Binary-to-digital converters	83
29.2.7	Error correction	83
29.2.8	Tracking	83
30	Minimum quality of a sector	83
30.1	Headers	83
30.1.1	Sector Mark	83
30.1.2	ID fields	83
30.2	User-written data	83
30.2.1	Recording field	83
30.2.2	Byte errors	83
30.2.3	Modulation method offset	84
30.2.4	Timing jitter	84
31	Data interchange requirements	84
31.1	Tracking	84
31.2	User-written data	84
31.3	Embossed data	84
31.4	Quality of disk	84

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

Annexes

A - Air cleanliness class 100 000	85
B - Edge distortion test	86
C - Compliance test	88
D - Test method for measuring the adsorbent force of the hub	90
E - CRC for ID fields	92
F - Interleave, CRC, ECC, Resync for the data field	93
G - Determination of Resync pattern	99
H - Read Channel for measuring NBSNR and jitter	104
J - Timing jitter measuring procedure	106
K - Definition of write pulse shape	108
L - Measurement of figure of merit	110
M - Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media	111
N - Requirements for interchange	113
P - Measurement implementation for Cross-track signal	115
Q - Office environment	116
R - Derivation of the operating climatic environment	117
S - Transportation	122
T - Sector retirement guidelines	123
U - Track deviation measurement	124
V - Values to be implemented in existing and future standards	128
W - Measurement of the vertical birefringence of the substrate	129
X - Guidelines for the use of Type WO and WO-DOW ODCs	131
Y - Laser power calibration for evaluation of media power sensitivity	132

iTeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 14517 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Optical disk cartridges for information interchange*.

Annexes A to P form an integral part of this International Standard. Annexes Q to Y are for information only.

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

<https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

Information technology — 130 mm optical disk cartridges for information interchange — Capacity: 2,6 Gbytes per cartridge

Section 1 - General

1 Scope

This International Standard defines a series of related 130 mm optical disk cartridges (ODCs) by using a number of Type designations.

A disk has two sides, called Side A and Side B. Each side can have a nominal capacity of 1,3 Gbytes.

Type R/W provides for data to be written, read and erased many times over the recording surface of the corresponding disk side, using thermo-magnetic and magneto-optical effects.

Type P-ROM provides for a part of the disk surface to be pre-recorded and reproduced by stamping or other means. This part of the disk is read without recourse to the magneto-optical effect. All parts which are not pre-recorded provide for data to meet the requirements of Type R/W.

Type O-ROM provides for the whole of the disk surface to be pre-recorded and reproduced by stamping or other means. The corresponding disk sides are read without recourse to the magneto-optical effect.

Type DOW provides for data to be written and read many times over the recording surface of the corresponding disk side, using the direct overwrite thermo-magnetic and magneto-optical effects requiring a single external magnetic field.

Type P-DOW provides for a part of the disk surface to be pre-recorded and reproduced by stamping or other means. This part of the disk is read without recourse to the magneto-optical effect. All parts which are not pre-recorded provide for data to meet the requirements of Type DOW.

Type WO provides write once, read multiple functionality using the thermo-magnetic and magneto-optical effects.

Type WO-DOW provides write once, read multiple functionality using the direct overwrite thermo-magnetic and magneto-optical effects.

In addition, for each Type, this International Standard provides for cartridges with a sector size of 512 bytes and cartridges with a sector size of 1 024 bytes. All sectors of a disk are the same size.

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the environments in which the cartridges are to be operated and stored;
- the mechanical, physical and dimensional characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written, including the physical disposition of the tracks and sectors, the error correction codes, the modulation methods used;
- the characteristics of the embossed information on the disk;
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

This International Standard provides for interchange between optical disk drives. Together with a Standard for volume and file structure it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical Disk Cartridge: A claim of conformance shall specify the Type of the ODC. It shall be in conformance with this International Standard if it meets all mandatory requirements specified therein for that Type.

2.2 Generating system: A claim of conformance with this International Standard shall specify which of Types R/W, DOW, P-ROM, P-DOW, O-ROM, WO and WO-DOW is(are) supported. A system generating an ODC for interchange shall be in conformance with this International Standard if it meets the mandatory requirements of this Standard for the Type(s) supported.

2.3 Receiving system: A claim of conformance with this International Standard shall specify which Type(s) is(are) supported.

A system receiving an ODC for interchange shall be in conformance with this International Standard if it is able to process any recording made on the cartridge according to 2.1 on the Type(s) specified.

2.4 Compatibility statement: A claim of conformance with this International Standard shall include a statement listing any other International Optical Disk Cartridge Standard supported by the system for which conformance is claimed. This statement shall specify the number of the standard(s), including, where appropriate, the ODC Type(s), or the Types of side, and whether support includes reading only or both reading and writing.

3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 950:1991, *Safety of information technology equipment, including electrical business equipment.*

[ISO/IEC 14517:1996](https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996)

4 Definitions <https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996>

For the purposes of this International Standard, the following definitions apply.

4.1 band: An annular area within the user zone on the disk having a constant clock frequency.

4.2 case: The housing for an optical disk, that protects the disk and facilitates disk interchange.

4.3 clamping zone: The annular part of the disk within which the clamping force is applied by the clamping device.

4.4 control track: A track containing the information on media parameters and format necessary for writing, reading and erasing the remaining tracks on the optical disk.

4.5 Cyclic Redundancy Check (CRC): A method for detecting errors in data.

4.6 defect management: A method for handling the defective areas on the disk.

4.7 direct overwrite: a thermo-magnetic recording method using a specially designed media that does not require a separate erase pass.

4.8 disk reference plane: A plane defined by the perfectly flat annular surface of an ideal spindle onto which the clamping zone of the disk is clamped, and which is normal to the axis of rotation.

4.9 entrance surface: The surface of the disk on to which the optical beam first impinges.

4.10 Error Correction Code (ECC): An error-detecting code designed to correct certain kinds of errors in data.

4.11 format: The arrangement or layout of information on the disk.

4.12 hub: The central feature on the disk which interacts with the spindle of the disk drive to provide radial centring and the clamping force.

4.13 interleaving: The process of allocating the physical sequence of units of data so as to render the data more immune to burst errors.

4.14 Kerr rotation: The rotation of the plane of polarization of an optical beam upon reflection from the recording layer as caused by the magneto-optical Kerr effect.

4.15 land and groove: A trench-like feature of the disk, applied before the recording of any information, and used to define the track location. The groove is located nearer to the entrance surface than the land with which it is paired to form a track.

4.16 logical track: Either 31 consecutive sectors for 512-byte sector disks or 17 consecutive sectors for disks with 1 024-byte sector in one or more physical tracks. The first sector of each logical track is assigned sector number 0.

4.17 mark: A feature of the recording layer which may take the form of a magnetic domain, a pit, or any other type or form that can be sensed by the optical system. The pattern of marks represents the data on the disk.

NOTE - Subdivisions of a sector which are named "mark" are not marks in the sense of this definition.

4.18 mark edge: The transition between a region with a mark and one without a mark or vice versa, along the track.

4.19 mark edge recording: A recording method which uses a mark edge to represent a Channel bit.

4.20 optical disk: A disk that will accept and retain information in the form of marks in a recording layer, that can be read with an optical beam.

4.21 optical disk cartridge (ODC): A device consisting of a case containing an optical disk.

4.22 physical track: The path which is followed by the focus of the optical beam during one revolution of the disk. This path is not directly addressable.

4.23 polarization: The direction of polarization of an optical beam is the direction of the electric vector of the beam.

NOTE - The plane of polarization is the plane containing the electric vector and the direction of propagation of the beam. The polarization is right-handed when to an observer looking in the direction of propagation of the beam, the end-point of the electric vector would appear to describe an ellipse in the clockwise sense.

4.24 pre-recorded mark: A mark so formed as to be unalterable by magneto-optical means.

4.25 read power: The read power is the optical power, incident at the entrance surface of the disk, used when reading.

NOTE - It is specified as a maximum power that may be used without damage to the written data. Lower power may be used providing that the signal-to-noise ratio and other requirements of this International Standard are met.

4.26 recording layer: A layer of the disk on, or in, which data is written during manufacture and/or use.

4.27 Reed-Solomon code: An error detection and/or correction code which is particularly suited to the correction of errors which occur in bursts or are strongly correlated.

4.28 space: The area between marks along the track.

4.29 spindle: The part of the disk drive which contacts the disk and/or hub.

4.30 substrate: A transparent layer of the disk, provided for mechanical support of the recording layer, through which the optical beam accesses the recording layer.

4.31 track pitch: The distance between adjacent track centrelines, measured in a radial direction.

4.32 write-inhibit hole: A hole in the case which, when detected by the drive to be open, inhibits both write and erase operations.

4.33 write-once functionality: A technique whereby a rewritable MO ODC is restricted to initialization and writing once only; erase is not permitted.

4.34 zone: An annular area of the disk.

5 Conventions and notations

5.1 Representation of numbers

- A measured value is rounded off to the least significant digit of the corresponding specified value. It implies that a specified value of 1,26 with a positive tolerance of +0,01, and a negative tolerance of -0,02 allows a range of measured values from 1,235 to 1,275.
- Letters and digits in parentheses represent numbers in hexadecimal notation.
- The setting of a bit is denoted by ZERO or ONE.
- Numbers in binary notation and bit combinations are represented by strings of digits 0 and 1.
- Numbers in binary notation and bit combinations are shown with the most significant bit to the left.
- Negative values of numbers in binary notation are given in TWO's complement.
- In each field the data is recorded so that the most significant byte (byte 0) is recorded first. Within each byte the least significant bit is numbered 0 and is recorded last, the most significant bit (numbered 7 in an 8-bit byte) is recorded first. This order of recording applies also to the data input of the Error Detection and Correction circuits and their output.
- Unless otherwise stated, groups of decimal digits of the form xx .. x/yy ... y indicate that the value xx ... x applies to 1 0 24-byte sectors and that the value yy ... y applies to 512-byte sectors.

5.2 Names

The names of entities, e.g. specific tracks, fields, etc., are given with a capital initial.

iTech STANDARD PREVIEW
(standards.iteh.ai)

6 List of acronyms

ALPC	Auto Laser Power Control	ISO/IEC 14517:1996
AM	Address Mark	https://standards.iteh.ai/catalog/standards/sist/d9939777-4693-4fa7-adc0-d26203857af7/iso-iec-14517-1996
CRC	Cyclic Redundancy Code	
DDS	Disk Definition Structure	
DMA	Defect Management Area	
DMP	Defect Management Pointers	
DOW	Direct overwrite	
ECC	Error Correction Code	
EDAC	Error Detection And Correction	
ID	Identifier	
LBA	Logical Block Address	
LSB	Least Significant Byte	
MO	Magneto-Optical	
MSB	Most Significant Byte	
NBSNR	Narrow-Band Signal-to-Noise Ratio	
ODC	Optical Disk Cartridge	
O-ROM	Optical Read Only Memory	
PA	Postamble	
PDL	Primary Defect List	
PEP	Phase-Encoded Part of the Control Tracks	
P-DOW	Partial ROM direct overwrite	
P-ROM	Partial Read Only Memory	
RLL(1,7)	Run Length Limited (code)	
R-S	Reed-Solomon (code)	
R/W	Rewritable	
R-S/LDC	Reed-Solomon Long Distance Code	
SCSI	Small Computer System Interface	

SDL	Secondary Defect List
SFP	Standard Formatted Part of the Control Tracks
SM	Sector Mark
TIA	Time Interval Analyzer
VFO	Variable Frequency Oscillator
WO	Write Once
WO-DOW	Write once direct overwrite
ZCAV	Zoned Constant Angular Velocity

7 General description of the optical disk cartridge

The optical disk cartridge which is the subject of this International Standard consists of a case containing an optical disk.

The case is a protective enclosure for the disk. It has access windows covered by a shutter. The windows are automatically uncovered by the drive when the cartridge is inserted into it.

The optical disk consists of two sides assembled together with their recording layers on the inside.

The optical disk may be recordable on both sides. Data can be written onto the disk as marks in the form of magnetic domains in the recording layer and can be erased from it with a focused optical beam, using the thermo-magnetic effect. Data may be written over existing data by modulating the intensity of the optical beam. The data can be read with a focused optical beam, using the magneto-optical effect. The beam accesses the recording layer through the transparent substrate of the disk.

Part of the disk or the entire disk may contain read-only data in the form of pre-embossed pits. This data can be read using the diffraction of the optical beam by the embossed pits.

The entire disk may be used for write once recording of data using the thermo-magnetic effect. This data can be read using the magneto-optic effect.

8 General requirements

8.1 Environments

8.1.1 Test environment

The test environment is the environment where the air immediately surrounding the optical disk cartridge has the following properties:

temperature	: 23 °C ± 2 °C
relative humidity	: 45 % to 55 %
atmospheric pressure	: 60 kPa to 106 kPa
air cleanliness	: Class 100 000 (see annex A)

No condensation on or in the optical disk cartridge shall occur. Before testing, the optical disk cartridge shall be conditioned in this environment for 48 h minimum. It is recommended that, before testing, the entrance surface of the disk be cleaned according to the instructions of the manufacturer of the disk.

Unless otherwise stated, all tests and measurements shall be made in this test environment.

8.1.2 Operating environment

This International Standard requires that an optical disk cartridge which meets all requirements of this Standard in the specified test environment provides data interchange over the specified ranges of environmental parameters in the operating environment. (See also annex Q).

The operating environment is the environment where the air immediately surrounding the optical disk cartridge has the following properties:

temperature	: 5 °C to 55 °C
relative humidity	: 3 % to 85 %
absolute humidity	: 1 g/m ³ to 30 g/m ³