



SLOVENSKI STANDARD
SIST EN 50599:2014

01-september-2014

Simetrično komunikacijsko okabljenje z zaslonjenimi premimi povezovalnimi vrvicami in premimi vrvicami za delovna območja v skladu z EN 50173-4 za uporabo v razredu D - Podrobna specifikacija

Balanced communication cabling in accordance with EN 50173-4 screened straight patch cords and straight work area cords for class D applications - detail specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50599:2014](https://standards.iteh.ai/catalog/standards/sist/dcdac8c9-e29d-41d0-9568-100819655b7/sist-en-50599-2014)

Ta slovenski standard je istoveten z: EN 50599:2014

ICS:

33.120.10 Koaksialni kabli. Valovodi Coaxial cables. Waveguides

SIST EN 50599:2014

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50599:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/dcdac8c9-e29d-41d0-9568-10b8ff9655b7/sist-en-50599-2014>

EUROPEAN STANDARD

EN 50599

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2014

ICS 33.120.10

English Version

Generic cabling systems - Specification for the testing of
balanced communication cabling in accordance with EN 50173-4
- Screened straight patch cords and straight work area cords for
class D applications - Detail specification

Anwendungsneutrale Kommunikationsverkabelung -
Spezifikation zur Prüfung der symmetrischen
Kommunikationsverkabelung nach EN 50173-4 -
Geschirmte gerade Schnüre und Geräteanschlusskabel für
Anwendungen der Klasse D - Bauartspezifikation

This European Standard was approved by CENELEC on 2013-09-16. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Detail specification for screened cords for Class D channels	5

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50599:2014](https://standards.iteh.ai/catalog/standards/sist/dcdac8c9-e29d-41d0-9568-10b8ff9655b7/sist-en-50599-2014)

<https://standards.iteh.ai/catalog/standards/sist/dcdac8c9-e29d-41d0-9568-10b8ff9655b7/sist-en-50599-2014>

Foreword

This document (EN 50599:2014) has been prepared by CLC/TC 46X "Communication cables".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-11-30
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2016-09-16

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 50599:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/dcdac8c9-e29d-41d0-9568-10b8ff9655b7/sist-en-50599-2014>

1 Scope

This detail specification describes screened patch cords and application-specific cords enabling the construction of Class D channels as defined in the EN 50173 series of standards.

This detail specification describes cords of which the transmission characteristics are up to 100 MHz for digital communication. The test configuration is detailed in EN 61935-2.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50173-4, *Information technology — Generic cabling systems — Part 4: Homes*

EN 50288-1, *Multi-element metallic cables used in analogue and digital communication and control — Part 1: Generic specification*

EN 50288-2-2, *Multi-element metallic cables used in analogue and digital communication and control — Part 2-2: Sectional specification for screened cables characterised up to 100 MHz — Work area and patch cord cables*

EN 50289-1-13, *Communication cables — Specifications for test methods — Part 1-13: Electrical test methods — Coupling attenuation or screening attenuation of patch cords / coaxial cable assemblies / pre-connectorised cables*

EN 50289-4-17, *Communication cables — Specifications for test methods — Part 4-17: Test methods for UV resistance evaluation of the sheath of electrical and optical fibre cable*

EN 60603-7-3, *Connectors for electronic equipment — Part 7-3: Detail specification for 8-way, shielded, free and fixed connectors, for data transmission with frequencies up to 100 MHz (IEC 60603-7-3)*

EN 60794-1-2, *Optical fibre cables — Part 1-2: Generic specification — Basic optical cable test procedures (IEC 60794-1-2)*

EN 61935-2:2010, *Testing of balanced communication cabling in accordance with standards series EN 50173 — Part 2: Patch cords and work area cords (IEC 61935-2:2010)*

EN 61935-2-20, *Testing of balanced communication cabling in accordance with series EN 50173 — Part 2-20: Patch cords and work area cords — Blank detail specification for class D applications (IEC 61935-2-20)*

EN 62012-1:2002, *Multicore and symmetrical pair/quad cables for digital communications to be used in harsh environments — Part 1: Generic specification (IEC 62012-1:2002)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

straight cord


cord of which the respective pins of the connectors are mated together (1 to 1, 2 to 2,...)

3.2

cross over cord

cord that is not a straight cord and of which the respective pins of connectors are mated following a specific combination, (e.g.: 1 to 3, 2 to 6, 3 to 1, 4 to 4, 5 to 5, 6 to 2, 7 to 7, 8 to 8)

4 Detail specification for screened cords for Class D channels

[1] Issued by :		[2] Document: Edition : Date:		
[3] Available from:		[4] Sectional specification for the cords : Blank Detail specification :		EN 61935-2 EN 61935-2-20
[5] Additional references : EN 50288-1 ; EN 50288-2-2 ; EN 50173-4 ; EN 60603-7-3				
[6] Cord description::Straight cord. Screened twisted pair cable, 4 pair with stranded copper conductors, used for work area connection, with nominal impedance of 100 Ω or 120 Ω for use in Class D Channels .				
[7] Cable assembly construction:				
				
EN 61935-2:2010, 4.1	EN 50288-1 4.12	EN 50288-2-2 4.12	Conductor Material Sheath Material Nominal thickness Colour Overall length Diameter Marking	Stranded annealed copper PVC, ZH ns 10 m max 6 mm max Acc customer
	https://standards.iteh.ai/catalog/standards/sist-en-50599-2014/10b8ff9655b77/sist-en-50599-2014		Packaging: lac8c9-e29d-41d0-9568-	
Visual examination	EN 61935-2:2010, 5.1			
[8]				
Minimum bending radius for static bending:			24 mm	
Minimum bending radius for dynamic bending:			48 mm	
Temperature range for installation			0 – 50 °C	
Operating temperature range under static conditions: from -10 °C to +60 °C				

[9] Characteristics	[10] EN 50288-1 subclause	[11] EN 50288-2-2 subclause	[12] Recommended severities/Requirements	[13] Comments			
Electrical Characteristics	5.1	5.1					
DC loop resistance	5.1.1.1	5.1.1	Assumed to be met by design				
Resistance unbalance	5.1.1.2	5.1.1	Assumed to be met by design				
Wire Map	EN 61935-2:2010, 5.2						
Transmission characteristics	6.3	6.3					
Propagation Delay		EN 61935-2:2010, 5.3	Assumed to be met by design				
Differential phase delay (skew)		EN 61935-2:2010, 5.4	Assumed to be met by design				
Insertion loss		EN 61935-2:2010, 5.5	MHz	2 m	5 m	10 m	Values are in dBs
			1	0,14	0,24	0,4	
			16	0,56	0,92	1,53	
			100	1,44	2,4	4,0	
Near-end crosstalk (Pair to pair)	6.3.4	EN 61935-2:2010, 5.7	MHz	2 m	5 m	10 m	Values are in dBs
			1	65,0	65,0	65,0	
			16	50,3	49,5	48,7	
			100	35,0	34,7	34,5	
Return loss		EN 61935-2:2010, 5.6	4≤f<25 19,8+3×log f 25≤f≤100 38-10×log f	Values are in dBs			
Screening attenuation	EN 50289-1-13	EN 50289-1-13	40dB				
Transfer impedance	6.2.7	6.2.7	na				
Coupling attenuation		EN 61935-2:2010, 7.8	type II 30 – 100 MHz : ≥ 55dB 100 – 1000 MHz : ≥ 55 – 20 log(f/100).				
Mechanical and dimensional characteristics	5.2	5.2					
Tensile performance of the cord		EN 61935-2:2010, 7.2	≥ 50 N				
Flexure		EN 61935-2:2010, 7.3	500 flex				
Bending		EN 61935-2:2010, 7.4	24 mm RL : 4 ≤ f < 25 19,8+3×log f 25 ≤ f ≤ 100 38-10×log f	Values are in dBs			
Twisting		EN 61935-2:2010, 7.5	Applicable				
Crushing		EN 61935-2:2010, 7.6	800 N				
Dust test		EN 61935-2:2010, 7.7	2 cycles				
Impact test of the cable	6.4.9	6.4.9	1 J				
Shock	EN 62012-1:2002, 3.4.4	EN 62012-1	15 g / 11 ms				
Bump	EN 62012-1:2002, 3.4.3	EN 62012-1	na				
Vibrations	EN 62012-1:2002, 3.4.2	EN 62012-1	10 – 500 Hz Amplitude= 0,35mm Acc=50m/s ² 10 sweeping /axe,	10μs			
Water immersion	EN 60794-1-2, method F10		na				
Damp heat steady state	EN 62012-1:2002, 3.5.2	EN 62012-1	na				