



SLOVENSKI STANDARD

SIST EN 50603:2014

01-april-2014

Simetrično komunikacijsko okabljenje z zaslonjenimi ravnimi povezovalnimi vrvicami in ravnimi vrvicami za delovna območja v skladu z EN 50173-4 za uporabo v razredu E - Podrobna specifikacija

Balanced communication cabling in accordance with EN 50173-4 screened straight patch cords and straight work area cords for class E applications - detail specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50603:2014](https://standards.iteh.ai/catalog/standards/sist/c4c92ba8-3696-42e7-aa6c-368d6c71903c/sist-en-50603-2014)

Ta slovenski standard je istoveten z: **EN 50603:2014**

ICS:

33.040.50	Vodi, zveze in tokokrogi	Lines, connections and circuits
35.110	Omreževanje	Networking

SIST EN 50603:2014

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50603:2014](#)

<https://standards.iteh.ai/catalog/standards/sist/c4c92ba8-3696-42e7-aa6c-968d6c7f903c/sist-en-50603-2014>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 50603

February 2014

ICS 33.120.10

English version

**Generic cabling systems -
Specification for the testing of balanced communication cabling in
accordance with EN 50173-4 -
Screened straight patch cords and straight work area cords for class E
applications -
Detail specification**

Systemes de câblage générique -
Spécification relative aux essais de
câblage de télécommunications
symétriques selon l'EN 50173-4 -
Cordons droits de brassage et cordons
droits de zone de travail écrantés pour les
applications de classe E -
Spécification particulière

Anwendungsneutrale
Kommunikationsverkabelung -
Spezifikation zur Prüfung der
symmetrischen
Kommunikationsverkabelung nach EN
50173-4 -
Geschirmte gerade Schnüre und
Geräteanschlusskabel für Anwendungen
der Klasse E -
Bauartspezifikation

SIST EN 50603:2014

<https://standards.iteh.ai/catalog/standards/sist/c4c926a8-3696-42c7-aad0-968d6c7f903c/sist-en-50603-2014>

This European Standard was approved by CENELEC on 2013-09-23. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Detail specification for screened cords for Class E channels	5

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 50603:2014](https://standards.iteh.ai/catalog/standards/sist/c4c92ba8-3696-42e7-aa6c-968d6c7f903c/sist-en-50603-2014)

<https://standards.iteh.ai/catalog/standards/sist/c4c92ba8-3696-42e7-aa6c-968d6c7f903c/sist-en-50603-2014>

Foreword

This document (EN 50603:2014) has been prepared by CLC/TC 46X "Communication cables".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-09-23
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2016-09-23

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 50603:2014](https://standards.iteh.ai/catalog/standards/sist/c4c92ba8-3696-42e7-aa6c-968d6c7f903c/sist-en-50603-2014)

<https://standards.iteh.ai/catalog/standards/sist/c4c92ba8-3696-42e7-aa6c-968d6c7f903c/sist-en-50603-2014>

1 Scope

This detail specification describes straight screened patch cords and patch cords and application-specific cords enabling the construction of Class E channels as defined in the EN 50173 series of standards.

This detail specification describes cords of which the transmission characteristics are up to 250 MHz for digital communication. The test configuration is detailed in EN 61935-2.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50173-4, *Information technology — Generic cabling systems — Part 4: Homes*

EN 50288-1, *Multi-element metallic cables used in analogue and digital communication and control — Part 1: Generic specification*

EN 50288-5-2, *Multi-element metallic cables used in analogue and digital communication and control — Part 5-2: Sectional specification for screened cables characterised up to 250 MHz — Work area and patch cord cables*

EN 50289-1-13, *Communication cables — Specifications for test methods — Part 1-13: Electrical test methods — Coupling attenuation or screening attenuation of patch cords / coaxial cable assemblies / pre-connectorised cables*

EN 50289-4-17, *Communication cables — Specifications for test methods — Part 4-17: Test methods for UV resistance evaluation of the sheath of electrical and optical fibre cable*

EN 60603-7-5, *Connectors for electronic equipment — Part 7-5: Detail specification for 8-way, shielded, free and fixed connectors, for data transmissions with frequencies up to 250 MHz (IEC 60603-7-5)*

EN 60794-1-2, *Optical fibre cables — Part 1-2: Generic specification — Basic optical cable test procedures (IEC 60794-1-2)*

EN 61935-2-2010, *Testing of balanced communication cabling in accordance with standards series EN 50173 — Part 2: Patch cords and work area cords (IEC 61935-2:2010)*

EN 61935-2-20, *Testing of balanced communication cabling in accordance with series EN 50173 — Part 2-20: Patch cords and work area cords — Blank detail specification for class D applications (IEC 61935-2-20)*

EN 62012-1:2002, *Multicore and symmetrical pair/quad cables for digital communications to be used in harsh environments — Part 1: Generic specification (IEC 62012-1:2002)*

3 Terms and definitions

3.1

straight cord


cord of which the respective pins of the connectors are mated together (1 to 1, 2 to 2,...)

3.2

cross over cord

cord that is not a straight cord and of which the respective pins of connectors are mated following a specific combination, (e.g.: 1 to 3, 2 to 6, 3 to 1, 4 to 4, 5 to 5, 6 to 2, 7 to 7, 8 to 8)

4 Detail specification for screened cords for Class E channels

[1] Issued by :		[2] Document: Edition : Date:		
[3] Available from:		[4] Sectional specification for the cords :		EN 61935-2
		Blank Detail specification :		EN 61935-2-20
[5] Additional references : EN 50288-1 ; EN 50288-5-2 ; EN 50173-4 ; EN 60603-7-5				
[6] Cord description:: Straight cord. Screened twisted pair cable, 4 pair with stranded copper conductors, used for work area connection, with nominal impedance of 100 for Class E channels .				
[7] Cable assembly construction:				
				
EN 61935-2:2010, 4.1	EN 50288-1 4.12	EN 50288-5-2 4.12	Conductor Material Sheath Material Nominal thickness Colour Overall length Diameter Marking	Stranded annealed copper PVC, ZH ns 10 m max 6 mm max Acc customer
	2.2.13	2.2.13	Packaging	
Visual examination	EN 61935-2:2010, 5.1			
[8]				
Minimum bending radius for static bending:			24 mm	
Minimum bending radius for dynamic bending:			48 mm	
Temperature range for installation			0 – 50 °C	
Operating temperature range under static conditions: from -10 °C to +60 °C				

[9] Characteristics	[10] EN 50288-1 subclause	[11] EN 50288-5-2 subclause	[12] Recommended severities/Requirements	[13] Comments			
Electrical Characteristics	5.1	5.1					
DC loop resistance	5.1.1.1	5.1.1	Assumed to be met by design				
CS Resistance unbalance	5.1.1.2	5.1.1	Assumed to be met by design				
Wire Map	EN 61935-2:2010, 5.2						
Transmission characteristics	6.3	6.3					
Propagation Delay		EN 61935-2:2010, 5.3	Assumed to be met by design				
Differential phase delay (skew)		EN 61935-2:2010, 5.4	Assumed to be met by design				
Insertion loss		EN 61935-2:2010, 5.5	MHz	2 m	5 m	10 m	Values are in dB
			1	0,10	0,20	0,35	
			16	0,39	0,73	1,30	
			100	1,00	1,89	3,38	
			250	1,62	3,10	5,56	
Near-end crosstalk (Pair to pair)	6.3.4	EN 61935-2:2010, 5.7	MHz	2 m	5 m	10 m	Values are in dB
			1	65,0	65,0	65,0	
			16	62,6	61,0	59,5	
			100	46,2	45,1	44,2	
			250	38,7	38	37,6	
Return loss		EN 61935-2:2010, 5.6	$4 \leq f < 25$ $19,8+3 \times \log f$ $25 \leq f \leq 250$ $38-10 \times \log f$	Values are in dB			
Screening attenuation	EN 50289-1-13	EN 50289-1-13	$\geq 40\text{dB}$				
Transfer impedance	6.2.7	6.2.7	na				
Coupling attenuation	6.2.8	EN 61935-2:2010, 7.8	type II 30 – 100 MHz : $\geq 55\text{dB}$ 100 – 1000 MHz : $\geq 55 - 20 \log(f/100)$.	Values are in dB			
Mechanical and dimensional characteristics	5.2	5.2					
Tensile performance of the cord		EN 61935-2:2010, 7.2	≥ 50 N				
Flexure		EN 61935-2:2010, 7.3	500 flex				
Bending		EN 61935-2:2010, 7.4	24 mm RL : $4 \leq f < 25$ $19,8+3 \times \log f$ $25 \leq f \leq 250$ $38-10 \times \log f$	Values are in dB			
Twisting		EN 61935-2:2010, 7.5	Applicable				
Crushing		EN 61935-2:2010, 7.6	800 N				
Dust test		EN 61935-2:2010, 7.7	2 cycles				
Impact test of the cable	6.4.9	6.4.9	1 J				
Shock	EN 62012-1:2002, 3.4.4	EN 62012-1	15 g / 11 ms				
Bump	EN 62012-1:2002, 3.4.3	EN 62012-1	na				
Vibrations	EN 62012-1:2002, 3.4.2	EN 62012-1	10 – 500 Hz Amplitude= 0,35mm Acc=50m/s ² 10 sweeping /axe,	10 μ s			
Water immersion	EN 60794-1-2, method F10		na				