# INTERNATIONAL STANDARD

ISO 8670-3

First edition 2000-03-01

### Ostomy collection bags —

### Part 3:

## Determination of odour transmission of colostomy and ileostomy bags

Poches de recueil pour stomie—
Partie 3: Détermination de la fuite d'odeur des poches de recueil pour colostomie et iléostomie hai



#### **PDF** disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8670-3:2000 https://standards.iteh.ai/catalog/standards/sist/1472b172-c07b-4450-ad4f-c3da363442c7/iso-8670-3-2000

#### © ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 8670 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 8670-3 was prepared by Technical Committee ISO/TC 173, *Technical systems and aids for disabled or handicapped persons*, Subcommittee SC 3, *Aids for ostomy and incontinence*.

ISO 8670 consists of the following parts, under the general title Ostomy collection bags:

- Part 1: Vocabulary (standards.iteh.ai)
- Part 2: Requirements and test methods ISO 8670-3:2000
- https://standards.iteh.ai/catalog/standards/sist/1472b172-c07b-4450-ad4f-— Part 3: Determination of odour transmission of colostomy and ileostomy bags

© ISO 2000 – All rights reserved

ISO 8670-3:2000(E)

#### Introduction

This test is designed to determine the odour transmission of one-piece and multiple-piece ostomy bag systems. Good odour barrier properties are very important for ostomy bags. Detection of oxygen transmission is usually used to assess the efficacy of barrier materials against odour transmission, but this measurement is not always helpful in choosing suitable materials for ostomy bags because odour barrier properties are not always related to oxygen transmission. The organoleptic test described has been found to distinguish between systems which are considered to be odour-proof and those which are not. By enclosing the bag in a glass jar, any significant transmission of odour through the film will build up into a strong odour. In this method, as in practice, any faint odours will dissipate and be unnoticeable.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

### Ostomy collection bags —

#### Part 3:

### Determination of odour transmission of colostomy and ileostomy bags

#### 1 Scope

This part of ISO 8670 specifies a test method for the determination of odour transmission of colostomy and ileostomy bags. This method covers one-piece and multiple-piece systems having both closed-, and open-ended bags.

#### 2 Terms and definitions

For the purposes of this part of ISO 8670, the following terms and definitions apply.

#### 2.1

### (standards.iteh.ai)

#### ostomy bag

flexible container for collecting body effluent from a stoma 3:2000

https://standards.iteh.ai/catalog/standards/sist/1472b172-c07b-4450-ad4f-c3da363442c7/iso-8670-3-2000

2.2

#### closed-ended bag

[ISO 8670-1:1988, 2.1]

flexible container, without an opening for drainage, for collecting body effluent from a stoma

NOTE Adapted from ISO 8670-1:1988, 2.3.

2.3

#### open-ended bag

flexible container, with an opening for drainage, for collecting body effluent from a stoma

NOTE Adapted from ISO 8670-1:1988, 2.4.

2.4

#### one-piece ostomy system

effluent collection system in which all the component parts are removed from the body when the bag is changed

[ISO 8670-1:1988, 2.8]

2.5

#### multiple-piece flange system

effluent collection system in which a component is positioned around the stoma; this component allows an effluent collection bag to be attached or removed, while itself remaining in position

NOTE This definition also includes two-piece ostomy system [ISO 8670-1:1988, 2.9] and multiple-piece flange system [ISO 8670-2:1996, 2.4].

© ISO 2000 – All rights reserved

#### ISO 8670-3:2000(E)

#### 2.6

#### stoma

abnormal opening established on the body surface

[ISO 8670-2:1996, 2.10]

#### 3 Principle

Odoriferous material (fresh onion) is sealed inside an ostomy bag. The ostomy bag is placed in a sealed jar and the jar sniffed after four hours to detect whether a strong onion odour is transmitted through the bag.

#### 4 Reagents

- **4.1** Fresh onion (Allium cepa).
- 4.2 Distilled or deionized water.

#### 5 Apparatus

- **5.1 Glass jar**, of capacity 2,0 l  $\pm$  1,0 l with a top opening of 100 mm  $\pm$  50 mm diameter, capable of being sealed by means of a glass or metal lid.
- 5.2 Glass beakers, of a suitable size to fit inside the glass jar. (standards.iteh.ai)
- **5.3** Water bath or oven, capable of being controlled at 34  $^{\circ}$ C  $\pm$  1  $^{\circ}$ C.

ISO 8670-3:2000

- **5.4 Stopwatch**, or other similar stiming device: atalog/standards/sist/1472b172-c07b-4450-ad4f-c3da363442c7/iso-8670-3-2000
- 5.5 Stainless steel chopping knife or mechanical chopping device.

NOTE A blender (mixer) is suitable for the purpose of this test.

- **5.6 Balance**, or similar weighing device with an accuracy of at least  $\pm$  0,1 g.
- **5.7 Equipment**, for making welded joints in plastic materials.
- **5.8** Metal, plastic or glass **plate** for closing the stoma opening of the bag. The plate shall be at least as big as the adhesive plate of the bag and it shall be impermeable to onion odour.
- **5.9** Sealing film, taken from another bag of the type being tested.
- 5.10 Double-sided tape.

#### 6 Detection of odour

Three persons with normal sense of smell shall be chosen as sniffers to judge the presence of odour at the end of the test.

#### 7 Procedure

- **7.1** If a filter is present, seal the filter from either the outside or the inside as appropriate by means of sealing bag film taken from another bag of the type being tested to which double-sided tape has been applied. The sealing film shall be stuck so that there is at least 10 mm width of seal around the filter.
- **7.2** When testing open-ended bags, the opening of the bag shall be sealed by welding.
- **7.3** When testing multiple-piece products, assemble the bag to the flange.
- **7.4** Chop the onions using the knife or the mechanical chopping device so that the pieces are less than 5 mm in size. Place 20 g  $\pm$  2 g in the bag through the bag opening, ensuring that none of the onion comes into contact with the outer surface of the bag or with the flange.
- NOTE One way of avoiding contamination is to weigh the onion on a square of bag film, which is then folded over to make a parcel of the onion. The parcel is then inserted into the bag through the bag opening and the onion is released into the bag. The piece of used film is left in the bag during the test.

Cut onions shall be wrapped in aluminium foil and stored at room temperature no longer than 1 h before the test.

- **7.5** Seal the bag opening by means of a metal, plastic or glass plate, ensuring that there are no creases which could create leaks.
- 7.6 Add 50 ml  $\pm$  10 ml of water to the bottom of the jar and place the upturned beaker on the bottom of the jar to form a platform. Place the bag on top of the beaker in such a way that it is not in contact with the water. Seal the jar and place it in the water bath or oven at a temperature of 34 °C  $\pm$  1 °C. Start the stopwatch.
- NOTE The purpose of the water is to create humidity in the jar similar to that found underneath clothing. The odour transmission properties of some materials are affected by humidity and temperature.
  - ISO 8670-3:2000
- 7.7 After 10 min open the jart and sniff for any onion odour 4 odour is present and suspected to be due to a false positive result, then repeat the test. c3da363442c7/iso-8670-3-2000
- NOTE The purpose of the 10 min check is to overcome problems caused by contamination on the outside of the bag. It may well be that the breakthrough time is below 10 min and that is the reason for doing the 10 min check once only.
- **7.8** After a minimum of 4 h and a maximum of 4,5 h determine whether a strong odour of onion is detectable by the procedure given in 7.9.
- **7.9** Remove the closure from the jar and allow one sniffer to sniff the atmosphere inside the jar. Close the jar after a maximum time of 5 s. After a minimum of 1 min, remove the closure from the jar and allow the next sniffer to sample the atmosphere inside the jar. Repeat the procedure until each of the three sniffers has sampled the atmosphere inside the jar once.

Odour emanating from bag films and adhesives shall be ignored and only the odour due to onion shall be recorded.

NOTE The length of time for which the jar is opened is kept to a minimum to prevent the smell of onion decreasing.

It is recommended that a negative control is run using a bag with no onion, as bag films and adhesives may have odours of their own.

- **7.10** Record the result of the sniffing as either "strong odour" or "no odour". If the three sniffers are not in full agreement, a majority opinion shall be used.
- "A majority opinion" means that if two out of three sniffers find a strong odour, the result is reported as "strong odour". If only one sniffer finds a strong odour, the result is reported as "no odour".

To determine what constitutes a "strong odour" it is recommended that a bag made from low-density polyethylene (LDPE) is used as a positive control.

© ISO 2000 – All rights reserved

**7.11** Wash the jar thoroughly and change the water before the next test.

#### 8 Test report

The test report shall include the following information:

- a) reference to this part of ISO 8670;
- b) the date of testing;
- c) the identity of the bag;
- d) whether a strong odour of onion was detectable in the jar at the end of the test period or whether there was no odour;
- e) any deviation from the test procedure.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

# iTeh STANDARD PREVIEW (standards.iteh.ai)