

SLOVENSKI STANDARD

SIST EN 61158-5-10:2012

01-september-2012

Nadomešča:

SIST EN 61158-5-10:2008

**Industrijska komunikacijska omrežja - Specifikacije za procesno vodilo - 5-10. del:
Definicija opravil na aplikacijskem nivoju - Elementi tipa 10 (IEC 61158-5-10:2010)**

Industrial communication networks - Fieldbus specifications - Part 5-10: Application layer service definition - Type 10 elements (IEC 61158-5-10:2010)

Industrielle Kommunikationsnetze - Feldbusse - Teil 5-10: Dienstfestlegungen des Application Layer (Anwendungsschicht) - Typ 10-Elemente (IEC 61158-5-10:2010)

Réseaux de communication industriels - Spécifications des bus de terrain - Partie 5-10: Définition des services des couches d'application - Éléments de type 10 (CEI 61158-5-10:2010)

Ta slovenski standard je istoveten z: EN 61158-5-10:2012

ICS:

25.040.40	Merjenje in krmiljenje industrijskih postopkov	Industrial process measurement and control
35.100.70	Uporabniški sloj	Application layer
35.110	Omreževanje	Networking

SIST EN 61158-5-10:2012

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 61158-5-10:2012](https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012)

<https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 61158-5-10

June 2012

ICS 25.040.40; 35.100.70; 35.110

Supersedes EN 61158-5-10:2008

English version

**Industrial communication networks -
Fieldbus specifications -
Part 5-10: Application layer service definition -
Type 10 elements
(IEC 61158-5-10:2010)**

Réseaux de communication industriels -
Spécifications des bus de terrain -
Partie 5-10: Définition des services des
couches d'application -
Éléments de type 10
(CEI 61158-5-10:2010)

Industrielle Kommunikationsnetze -
Feldbusse -
Teil 5-10: Dienstfestlegungen des
Application Layer (Anwendungsschicht) -
Typ 10-Elemente
(IEC 61158-5-10:2010)

**ITeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 61158-5-10:2012](https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-)

<https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed->

This European Standard was approved by CENELEC on 2012-03-28. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/606/FDIS, future edition 2 of IEC 61158-5-10, prepared by SC 65C, "Industrial networks", of IEC/TC 65, "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61158-5-10:2012.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-12-28
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-03-28

This document supersedes EN 61158-5-10:2008.

EN 61158-5-10:2012 includes the following significant technical change with respect to EN 61158-5-10:2008:

- corrections;
- improvements;
- optimization of the synchronization;
- optimization of the startup time from power down.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61158-5-10:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following note has to be added for the standard indicated:

IEC/TR 61158-1:2010 NOTE Harmonized as CLC/TR 61158-1:2010 (not modified).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60559	-	Binary floating-point arithmetic for microprocessor systems	HD 592 S1	-
IEC 61131-1	-	Programmable controllers - Part 1: General information	EN 61131-1	-
IEC 61131-3	-	Programmable controllers - Part 3: Programming languages	EN 61131-3	-
IEC 61158-5-3	2010	Industrial communication networks - Fieldbus specifications - Part 5-3: Application layer service definition - Type 3 elements	EN 61158-5-3	2012
IEC 61158-6-3	2010	Industrial communication networks - Fieldbus specifications - Part 6-3: Application layer protocol specification - Type 3 elements	EN 61158-6-3	2012
IEC 61158-6-10	2010	Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements	EN 61158-6-10	2012
IEC 61375-1	-	Electric railway equipment - Train bus - Part 1: Train communication network	-	-
ISO/IEC 646	-	Information technology - ISO 7-bit coded character set for information interchange	-	-
ISO/IEC 7498-1	-	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	-	-
ISO/IEC 7498-3	-	Information technology - Open Systems Interconnection - Basic Reference Model: Naming and addressing	-	-
ISO/IEC 8822	-	Information technology - Open Systems Interconnection - Presentation service definition	-	-
ISO/IEC 8824-1	-	Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation	-	-
ISO/IEC 8859-1	-	Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No.1	-	-
ISO/IEC 9545	-	Information technology - Open Systems Interconnection - Application Layer structure	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 10646-1	-	Information technology - Universal Multiple-Octet Coded Character Set (UCS) - Part 1: Architecture and Basic Multilingual Plane	-	-
ISO/IEC 10731	-	Information technology - Open Systems Interconnection - Basic reference model - Conventions for the definition of OSI services	-	-
ISO 8601	-	Data elements and interchange formats - Information interchange - Representation of dates and times	-	-
IEEE 802	2001	IEEE standard for local and metropolitan area networks: overview and architecture	-	-
IEEE 802.1AB	2005	IEEE Standard for Local and metropolitan area networks Station and Media Access Control Connectivity Discovery	-	-
IEEE 802.1D	2004	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	2005	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-
IEEE 802.3	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications	-	-
IETF RFC 1305	-	Network Time Protocol Version 3 Specification and Implementation	-	-
IETF RFC 768	-	User Datagram Protocol	-	-
IETF RFC 3636	-	Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)	-	-
IETF RFC 3621	-	Power Ethernet MIB	-	-
IETF RFC 3490	-	Internationalizing Domain Names in Applications (IDNA)	-	-
IETF RFC 3418	-	Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)	-	-
IETF RFC 791	-	Internet Protocol - DARPA Internet Program Protocol Specification	-	-
IETF RFC 2863	-	The Interfaces Group MIB	-	-
IETF RFC 826	-	Ethernet Address Resolution Protocol	-	-
IETF RFC 1034	-	Domain names - concepts and facilities	-	-
IETF RFC 2737	-	Entity MIB (Version 2)	-	-
IETF RFC 2674	-	Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions	-	-
IETF RFC 792	-	Internet Control Message Protocol	-	-
IETF RFC 1112	-	Host Extensions for IP Multicasting	-	-
IETF RFC 1952	-	GZIP file format specification version 4.3	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IETF RFC 2131	-	Dynamic Host Configuration Protocol	-	-
IETF RFC 2365	-	Administratively Scoped IP Multicast	-	-
IETF RFC 3330	-	Special-Use IPv4 Addresses	-	-
The Open Group C706	-	CAE Specification DCE11: Remote Procedure- Call	-	-

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 61158-5-10:2012](#)

<https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 61158-5-10:2012](https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012)

<https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012>



IEC 61158-5-10

Edition 2.0 2010-08

INTERNATIONAL STANDARD



**Industrial communication networks – Fieldbus specifications –
Part 5-10: Application layer service definition – Type 10 elements**

STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 61158-5-10:2012
<https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XU**

ICS 25.04.40; 35.100.70; 35.110

ISBN 978-2-88912-107-6

CONTENTS

FOREWORD.....	14
INTRODUCTION.....	16
1 Scope.....	17
1.1 Overview.....	17
1.2 Specifications.....	18
1.3 Conformance.....	18
2 Normative references.....	18
3 Terms, definitions, abbreviations, symbols and conventions.....	20
3.1 Referenced terms and definitions.....	20
3.2 Additional terms and definitions for distributed automation.....	21
3.3 Additional terms and definitions for decentralized periphery.....	23
3.4 Additional terms and definitions for media redundancy.....	31
3.5 Abbreviations and symbols.....	32
3.6 Additional abbreviations and symbols for distributed automation.....	33
3.7 Additional abbreviations and symbols for decentralized periphery.....	33
3.8 Additional abbreviations and symbols for media redundancy.....	34
3.9 Conventions.....	34
4 Concepts.....	37
5 Data type ASE.....	37
5.1 General.....	37
5.2 Formal definition of data type objects.....	40
5.3 FAL defined data types.....	41
5.4 Data type ASE service specification.....	84
6 Communication model for common services.....	84
6.1 Concepts.....	84
6.2 ASE data types.....	84
6.3 ASEs.....	85
7 Communication model for distributed automation.....	185
7.1 Concepts.....	185
7.2 ASE data types.....	191
7.3 ASEs.....	195
7.4 ARs.....	412
7.5 Summary of FAL classes.....	416
7.6 Summary of FAL services.....	417
8 Communication model for decentralized periphery.....	419
8.1 Concepts.....	419
8.2 ASE data types.....	436
8.3 ASEs.....	436
8.4 Behavior of an IO device.....	709
8.5 Behavior of an IO controller.....	753
8.6 Application characteristics.....	756
Annex A (informative) Device instances.....	759
Annex B (informative) Components of an Ethernet interface.....	761
Annex C (informative) Scheme of MAC address assignment.....	765
Annex D (informative) Collection of objects.....	766
Annex E (informative) Measurement of the fast startup time.....	767
Bibliography.....	768

Figure 1 – Data type class hierarchy example	38
Figure 2 – NetworkTime date relation	63
Figure 3 – PTCP applications.....	98
Figure 4 – Clock drift measurement	109
Figure 5 – Multiple synchronization.....	110
Figure 6 – MRP stack	112
Figure 7 – Ring topology with one manager and clients.....	123
Figure 8 – MRM in an open ring	123
Figure 9 – More than one MRM in the ring	124
Figure 10 – Media redundancy diagnosis dependencies	125
Figure 11 – Locating the destination for redundant RT frames	165
Figure 12 – Example of periods at a local port	172
Figure 13 – FAL ASEs communication architecture.....	187
Figure 14 – Runtime object model.....	188
Figure 15 – Relationship between engineering and runtime	189
Figure 16 – Navigation in the runtime object model.....	190
Figure 17 – Operating state block diagram.....	229
Figure 18 – Device status model for the common diagnosis	230
Figure 19 – ACCO ASE structure	261
Figure 20 – Productive operation of data connections	262
Figure 21 – Quality code transfer – standard behavior	274
Figure 22 – Startup of a connection	275
Figure 23 – Quality code with communication fault.....	275
Figure 24 – Quality code when a connection is cleared	276
Figure 25 – Quality code when a connection is deactivated	276
Figure 26 – Quality code during the transfer of "incorrect" connection data.....	277
Figure 27 – Quality code for provider in "CBAReady" state	278
Figure 28 – Quality code when clearing an object from the provider.....	278
Figure 29 – Quality code when a connection is forced.....	279
Figure 30 – Quality code at QoS violation	279
Figure 31 – Push mode	286
Figure 32 – Pull mode overview	287
Figure 33 – Detailed sequence chart of the pull mode.....	288
Figure 34 – QoS and ORPC communication channel	289
Figure 35 – QoS Violation within Pull Mode	290
Figure 36 – Monitoring the providers heartbeat	291
Figure 37 – State machine RemoteACCO	293
Figure 38 – State machine RemoteACCOProvider	293
Figure 39 – State machine RemoteACCOProvider _{ORPC}	294
Figure 40 – State machine AR _{ORPC} – Provider	294
Figure 41 – State machine GetConnectionData – Provider.....	295
Figure 42 – State machine ProviderConnection.....	295
Figure 43 – State machine ProvConnActivation.....	296
Figure 44 – State machine WorkerORPC	296
Figure 45 – Communication stack of distributed automation devices	297
Figure 46 – Application relations between devices	298
Figure 47 – Communication relations	298
Figure 48 – RT communication channel	300

Figure 49 – Interaction between provider and consumer	302
Figure 50 – State machine AR _{SRT} – Consumer	304
Figure 51 – State machine AR _{SRT} – Provider	305
Figure 52 – State machine AccoDataCR – Consumer	306
Figure 53 – State machine AccoDataCR – Provider	306
Figure 54 – RT frame layout	307
Figure 55 – Establishing an AccoDataCR	308
Figure 56 – Flowchart of the copy cycle for local connections	309
Figure 57 – State machine connect attempt	313
Figure 58 – Productive operation of data connections (ORPC channel).....	320
Figure 59 – Productive operation of data connections (RT channel).....	321
Figure 60 – Productive operation of data connections (Local channel).....	321
Figure 61 – Data flow for cyclic RT	322
Figure 62 – Failure of the provider in productive operation (ORPC push mode)	324
Figure 63 – Failure of the provider in productive operation (ORPC pull mode)	325
Figure 64 – Scenario 1: Provider failure in productive operation (RT).....	326
Figure 65 – Scenario 2: Recovery from provider failure in productive operation (RT)	327
Figure 66 – Failure of the consumer (push mode)	327
Figure 67 – Failure of the consumer (pull mode)	328
Figure 68 – Failure of the consumer.....	329
Figure 69 – Failure of the provider when setting up connections	331
Figure 70 – Information levels.....	332
Figure 71 – ACCO ASE status model for the common diagnosis	332
Figure 72 – ACCO ASE status model for the detailed diagnosis	333
Figure 73 – Structure of the transmitted connection data	375
Figure 74 – Example of communication between controlling devices and field devices.....	421
Figure 75 – Example of communication between an engineering station and several controlling and field devices.....	421
Figure 76 – Example of communication between field devices and a server station.....	422
Figure 77 – Example of communication between field devices	422
Figure 78 – Structural units of one arbitrary API of an IO device (general)	424
Figure 79 – Example 1 structural units for interfaces and ports within API 0.....	425
Figure 80 – Example 2 structural units for interfaces and ports within API 0.....	426
Figure 81 – Overview of application processes	428
Figure 82 – IO device with APs, slots and subslots	429
Figure 83 – Application Process with application process objects (APOs)	432
Figure 84 – Access to a remote APO	433
Figure 85 – Access to a remote APO for provider/consumer association.....	434
Figure 86 – Example of one AR with two AREPs.....	435
Figure 87 – Relation of a record data object to one real object.....	437
Figure 88 – Relation of a record data object to two real objects	438
Figure 89 – Overview IO ASE service interactions	448
Figure 90 – Example of a resource model at the alarm source	524
Figure 91 – General isochronous application model (example).....	588
Figure 92 – ASE relations in an IO device operating in isochronous mode	594
Figure 93 – State machine relations in an IO device operating in isochronous mode.....	594
Figure 94 – SyncCtl state diagram	598
Figure 95 – Output state diagram.....	600
Figure 96 – Input state diagram	605

Figure 97 – Assignment of communication relationship to application relationship	687
Figure 98 – Implicit application relationship	691
Figure 99 – Example IO application relationship (one-to-one)	692
Figure 100 – Example IO application relationship one-to-many	693
Figure 101 – Overview ASE state machines for IO device	709
Figure 102 – State diagram application startup IO device	711
Figure 103 – State diagram neighborhood check	719
Figure 104 – State diagram PD parameter check IO device	728
Figure 105 – State diagram for a submodule.....	738
Figure 106 – State diagram IO controller during startup	754
Figure 107 – Example of network topology including slower wireless segments	757
Figure 108 – Example of media redundancy including wireless segments	758
Figure A.1 – Instance model	759
Figure B.1 – Scheme of an Ethernet interface	761
Figure B.2 – Scheme of an Ethernet interface with bridging ability	762
Figure B.3 – Scheme of an Ethernet interface with optical ports.....	763
Figure B.4 – Scheme of an Ethernet interface with bridging ability using radio communication.....	764
Figure B.5 – Scheme of an Ethernet interface with radio communication.....	764
Figure C.1 – Scheme of MAC address assignment.....	765
Figure D.1 – Example for an intersection of IO device, slot, and AR.....	766
Figure E.1 – Measurement of the fast startup time	767
Table 1 – V2 octets	42
Table 2 – L2 octets	42
Table 3 – PERSISTDEF	45
Table 4 – VARTYPE	45
Table 5 – ITEMQUALITYDEF	46
Table 6 – STATEDEF	49
Table 7 – GROUPEXCEPTIONDEF	49
Table 8 – ACCESSRIGHTSDEF	50
Table 9 – HRESULT	50
Table 10 – E2 octets	52
Table 11 – E2 value range	53
Table 12 – Unipolar2.16 octets	53
Table 13 – Unipolar2.16 value range	53
Table 14 – N2 value range	55
Table 15 – N4 value range	55
Table 16 – X2 value range	56
Table 17 – X4 value range	57
Table 18 – C4 value range	57
Table 19 – T2 value range	59
Table 20 – T2 value range	59
Table 21 – D2 value range	60
Table 22 – R2 value range	60
Table 23 – UUID for decentralized peripherals	61
Table 24 – UUID for distributed automation	62
Table 25 – NetworkTime values	63
Table 26 – NetworkTime octets	63

<https://standards.iteh.ai/catalog/standards/sist/50b236b3-6d3c-4b7f-b8ed-7e6ceb35190/sist-en-61158-5-10-2012>
 ITCI STANDARD PREVIEW
 (standards.iteh.ai)

SIST EN 61158-5-10:2012

Table 27 – UNICODEString values	65
Table 28 – UTF-8 character encoding scheme	65
Table 29 – OctetString2+Unsigned8 octets	76
Table 30 – Float32+Unsigned8 octets	77
Table 31 – Unsigned8+Unsigned8 octets	77
Table 32 – Data Types for Value in a VARIANT	80
Table 33 – Unsigned16_S octets	81
Table 34 – Unsigned16_S meaning	81
Table 35 – Integer16_S octets	81
Table 36 – Integer16_S meaning	82
Table 37 – Unsigned8_S octets	82
Table 38 – Unsigned8_S meaning	82
Table 39 – OctetString_S octets	83
Table 40 – OctetString_S status bits	83
Table 41 – F message trailer with 4 octets	83
Table 42 – F message trailer with 5 octets	84
Table 43 – Get	90
Table 44 – Set	92
Table 45 – Identify	95
Table 46 – Hello	96
Table 47 – Start bridge	103
Table 48 – Start slave	104
Table 49 – Start master	105
Table 50 – Stop bridge	106
Table 51 – Stop slave	107
Table 52 – Stop master	107
Table 53 – Sync state change	108
Table 54 – Start MRM	117
Table 55 – Stop MRM	118
Table 56 – Redundancy state change	119
Table 57 – Start MRC	120
Table 58 – Stop MRC	121
Table 59 – Neighborhood changed	121
Table 60 – MRP network/connection parameters	126
Table 61 – MRM parameters	127
Table 62 – MRC parameters	127
Table 63 – Set Prov Data	128
Table 64 – Set Prov Status	129
Table 65 – PPM Activate	130
Table 66 – Close	131
Table 67 – Start	131
Table 68 – Error	132
Table 69 – Get Cons Data	132
Table 70 – Get cons status	133
Table 71 – Set RedRole	133
Table 72 – CPM activate	134
Table 73 – APMS Activate	138
Table 74 – APMR Activate	139
Table 75 – APMS A Data	140

iTech STANDARD PREVIEW

(standards.iteh.ai)

SIST EN 61158-5-10:2012

[https://standards.iteh.ai/catalog/standards/sist/30b236b3-6d3c-4b7f-b8ed-](https://standards.iteh.ai/catalog/standards/sist/30b236b3-6d3c-4b7f-b8ed-7e6ceb3f5190/sist-en-61158-5-10-2012)

7e6ceb3f5190/sist-en-61158-5-10-2012

Table 76 – APMR A Data	141
Table 77 – APMR Ack	141
Table 78 – APMS Error	142
Table 79 – APMS Error ERRCLS/ERRCODE	142
Table 80 – APMR Error	143
Table 81 – APMR Error ERRCLS/ERRCODE	143
Table 82 – APMS_Close	143
Table 83 – APMR_Close	144
Table 84 – Connect	145
Table 85 – Release	146
Table 86 – Read	147
Table 87 – Write	148
Table 88 – Control	149
Table 89 – System capabilities	154
Table 90 – Auto negotiation support and status	155
Table 91 – MDI Power Support	155
Table 92 – Link aggregation status	156
Table 93 – Remote systems data change	159
Table 94 – Allowed values of ReductionRatio	162
Table 95 – Frame IDs for RT_CLASS_3	163
Table 96 – Sync Frame	163
Table 97 – FrameSendOffset	163
Table 98 – Tx Port Entry	164
Table 99 – Port state change	167
Table 100 – Set port state	167
Table 101 – Flush filtering data base	168
Table 102 – IFW IRT Schedule Add	168
Table 103 – IFW IRT Schedule Remove	169
Table 104 – IFW Schedule	169
Table 105 – MAU type change	174
Table 106 – Set MAU type	174
Table 107 – IP Multicast address	177
Table 108 – Set ARP Cache	177
Table 109 – Enterprise number	179
Table 110 – Vendor OUI	180
Table 111 – IRT Schedule Add	181
Table 112 – IRT Schedule Remove	181
Table 113 – Schedule	182
Table 114 – N Data	182
Table 115 – A Data	183
Table 116 – C Data	184
Table 117 – Connectable data types	192
Table 118 – Supported data types according to the Base Object Version	193
Table 119 – Usage of character sets	195
Table 120 – QueryInterface (Unknown interface)	197
Table 121 – AddRef (Unknown interface)	198
Table 122 – Release (Unknown interface)	199
Table 123 – GetTypeInfoCount (Dispatch interface)	200
Table 124 – GetTypeInfo (Dispatch interface)	201

STANDARD PREVIEW

(standards.iteh.ai)

SIST EN 61158-5-10:2012

<https://standards.iteh.ai/catalog/standards/sist/30b236b3-6d3c-4b7f-b8ed-7ccc035190/sist-en-61158-5-10-2012>