
## ETSI EN 301 489-1 V1.8.1 (2008-04)

Harmonized European Standard (Telecommunications series)

Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements



# Reference REN/ERM-EMC-246-1 Keywords EMC, radio, regulation

#### **ETSI**

#### 650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: <a href="http://www.etsi.org">http://www.etsi.org</a>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a></a>

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008. All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup>, **TIPHON**<sup>TM</sup>, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

### Contents

Intell	ectual Property Rights	6
Forev	word	<i>6</i>
1	Scope	9
2	References	10
2.1	Normative references	10
2.2	Informative references	11
3	Definitions and abbreviations	12
3.1	Definitions	12
3.2	Abbreviations	14
4	Test conditions	
4.1	General	
4.2	Arrangements for test signals	14
4.2.1	Arrangements for test signals at the input of transmitters	
4.2.2	Arrangements for test signals at the output of transmitters	
4.2.3	Arrangements for test signals at the input of receivers	15
4.2.4	Arrangements for test signals at the output of receivers	15
4.2.5	Arrangements for testing transmitter and receiver together (as a system)	15
4.3	RF exclusion band of radio communications equipment	16
4.4	Narrow band responses of receivers or receivers which are part of transceivers	16
4.5	Normal test modulation	16
5	Normal test modulation  Performance assessment  General	17
5.1	General dia	17
5.2	Equipment which can provide a continuous communication link	17
5.3	Equipment which does not provide a continuous communication link	18
5.4	Ancillary equipment	18
5.5	Ancillary equipment Equipment Equipment classification	18
6	Performance criteria	19
6.1	Performance criteria for continuous phenomena applied to transmitters and receivers	
6.2	Performance criteria for transient phenomena applied to transmitters and receivers	
6.3	Performance criteria for equipment which does not provide a continuous communication link	
6.4	Performance criteria for ancillary equipment tested on a stand alone basis	
7	Applicability overview tables	20
7.1	EMC emission	
7.2	Immunity	
8	Methods of measurement and limits for EMC emissions	22
8.1	Test configuration.	22
8.2	Enclosure of ancillary equipment measured on a stand alone basis	22
8.2.1	Definition	23
8.2.2	Test method	23
8.2.3	Limits	23
8.3	DC power input/output ports	23
8.3.1	Definition	
8.3.2	Test method	
8.3.3	Limits	
8.4	AC mains power input/output ports	
8.4.1	Definition	
8.4.2	Test method	
8.4.3	Limits	
8.5	Harmonic current emissions (AC mains input port)	
8.6	Voltage fluctuations and flicker (AC mains input port)	
8.7	Telecommunication ports	25

8.7.1 Definition		25
8.7.2 Test method		25
8.7.3 Limits		26
9 Test methods and levels for	or immunity tests	26
9.2 Radio frequency electron	magnetic field (80 MHz to 1 000 MHz and 1 400 MHz to 2 700 MHz)	26
9.2.1 Definition	-	26
9.2.2 Test method		27
9.2.3 Performance criteria		27
9.3 Electrostatic discharge		27
9.3.1 Definition		27
9.3.2 Test method		27
9.3.3 Performance criteria		28
	mode	
	on mode	
	the vehicular environment	
9.6.1 Definition		30
9.6.2 Test method		30
9.6.2.1 Test requirements	for 12 V and 24V DC powered equipment	30
9.6.3 Performance criteria	of for 12 V and 24V DC powered equipment of the state of	30
9.7 Voltage dips and interrup 9.7.1 Definition	DUONS	30
9.7.1 Definition		30
9.7.2 Test method	The state of the s	21
9.8 Surges	CA AND SURVEY OF THE SURVEY OF	31
9.8.1 Definition	11 (Star Cit) all ite	30
9.8.2 Test method	ile ilentile	30
	elecommunication ports directly connected to outdoor cables	
	elecommunication ports connected to indoor cables	
	nains ports	
9.8.3 Performance criteria.	P Jally 5: V	32
	sil <sup>8</sup> litt	
,	he HS Requirements and conformance Test specifications Table	
(I	HS-RTT)	33
Annex B (normative):	echnical requirements for after market equipment (ESAs), which	ch
	re not related to immunity related functions of the vehicle,	.11
	ecessary to demonstrate conformance to the motor vehicle EMC	7
	irective 2004/104/EC	
B.1 General		36
B.2 Technical requirements for	or radio equipment	36
	etic interference (emissions) generated by the ESA	
	gnetic interference (emissions) generated by the ESA	
	is emissions of RF transmitters	
	s emissions of transceivers in stand by mode and receivers	
	s emissions of ancillary equipment	
	transient disturbances conducted along the supply lines	
	(emissions) caused by the ESA	
	· · · · · · · · · · · · · · · · · · ·	
	pplication of harmonized EMC standards to multi-radio and	
co	ombined radio and non-radio equipment	39
C.1 Where all products can op	perate independently of each other	20
C.1 where an products can op	what independently of each other	39 39
C. I. I. E.IIIISSIONS		

C.1.2	Immunity		40
C.2	Where one or more of	the individual products cannot operate independently	40
C.2.1	Products physically:	incorporated within another product	40
C.2.2	1 0	to, but not physically incorporated within, another product	
C.3	Where none of the cor	mponent parts operate independently	41
C.3.1	Emissions		41
C.3.2	Immunity		41
C.4	Application of harmon	nized EMC standards to multi-radio equipment	42
C.4.1		ent capable of independent transmission	
C.4.2	Multi-radio equipme	ent not capable of independent transmission	42
Anne	x D (informative):	Bibliography	43
Anne	x E (informative):	The EN title in the official languages	44
Histor	·V		45

#### Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Foreword**

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [17] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Council Directive on the approximation of the laws of the Member States relating to electromagnetic compatibility ("the EMC Directive") (2004/108/EC [16] as amended) and Directive 1999/5/EC [15] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to the EMC Directive [16] and the R&TTE Directive [15] are given in annex A.

The present document is based upon the Generic Standards EN 61000-6-3 [18] and EN 61000-6-1 [19] and other standards, where appropriate, to meet the essential requirements of Council Directives 2004/108/EC [16], 1999/5/EC [15] and the motor vehicle EMC Directive 2004/104/EC [23] respectively.

The motor vehicle EMC Directive 2004/104/EG [23], is a type approval Directive, and contains in its annexes, all the technical requirements necessary to demonstrate conformance. There are two categories of after market equipment covered by the Directive as follows:

- a) After market (radio) equipment (and ancillary equipment) intended for installation in a motor vehicle, and which **are not related to immunity related functions** (annex I, clause 2.1.12 of the Directive) of the motor vehicle.
- b) After market (radio) equipment (and ancillary equipment) intended for installation in a motor vehicle, and which **are related to immunity related functions** (annex I, clause 2.1.12) of the motor vehicle, are subject to **type approval requirements** of the Directive 2004/104/EC [23].

The present document only deals with equipment of category a) subject to the requirements set out below.

Annex I, clause 3.2.9 of 2004/104/EC [23], sets out the acceptance of conformity according to the procedures of 2004/108/EC [16] or 1999/5/EC [15] for after market equipment (ESAs) not related to immunity related functions of the motor vehicle (annex I, clause 2.1.12), but additionally requires that the ESA fulfils the limits defined in annex I, clauses 6.5, 6.6, 6.8, and 6.9 of the Directive. Requirements applicable to this type of after market equipment (ESAs) are set out in annex B of the present document.

The present document, and the product related parts of it are based on the current EMC standards published by ETSI. It should be noted that the majority of these EMC standards have also been published in the Official Journal of the European Commission.

The present document is part 1 of a multi-part EMC standard for radio equipment which is structured in the following way:

- One EMC standard for all radio equipment made up of several parts.
- All common technical requirements for EMC emission and immunity have been placed in the common part, which is the present document.
- Separate parts have been developed to cover specific product related radio equipment test conditions, test arrangements, performance assessment, performance criteria, etc.
- A clause is included in each of the specific radio parts, entitled "special conditions", which is used as appropriate to cover any deviations or additions to the common requirements set out in the present document.

To demonstrate an adequate level of EMC protection, the present document is to be used together with the appropriate specific radio part of the standard.

The present document is part 1 of a multi-part deliverable covering ElectroMagnetic Compatibility (EMC) standard for radio equipment and services, as identified below:

#### Part 1: "Common technical requirements";

- Part 2: "Specific conditions for radio paging equipment";
- Part 3: "Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 40 GHz";
- Part 4: "Specific conditions for fixed radio links and ancillary equipment and services";
- Part 5: "Specific conditions for Private land Mobile Radio (PMR) and ancillary equipment (speech and non-speech)";
- Part 6: "Specific conditions for Digital Enhanced Cordless Telecommunications (DECT) equipment";
- Part 7: "Specific conditions for mobile and portable radio and ancillary equipment of digital cellular radio telecommunications systems (GSM and DCS)"."
- Part 8: "Specific conditions for GSM base stations";
- Part 9: "Specific conditions for wireless microphones, similar Radio Frequency (RF) audio link equipment, cordless audio and in-ear monitoring devices";
- Part 10: "Specific conditions for First (CT1 and CT1+) and Second Generation Cordless Telephone (CT2) equipment";
- Part 11: "Specific conditions for terrestrial sound broadcasting service transmitters";
- Part 12: "Specific conditions for Very Small Aperture Terminal, Satellite Interactive Earth Stations operated in the frequency ranges between 4 GHz and 30 GHz in the Fixed Satellite Service (FSS)";
- Part 13: "Specific conditions for Citizens' Band (CB) radio and ancillary equipment (speech and non-speech)";
- Part 14: "Specific conditions for analogue and digital terrestrial TV broadcasting service transmitters";
- Part 15: "Specific conditions for commercially available amateur radio equipment";
- Part 16: "Specific conditions for analogue cellular radio communications equipment, mobile and portable";
- Part 17: "Specific conditions for 2,4 GHz wideband transmission systems, 5 GHz high performance RLAN equipment and 5,8 GHz Broadband Data Transmitting Systems";
- Part 18: "Specific conditions for Terrestrial Trunked Radio (TETRA) equipment";
- Part 19: "Specific conditions for Receive Only Mobile Earth Stations (ROMES) operating in the 1,5 GHz band providing data communications";
- Part 20: "Specific conditions for Mobile Earth Stations (MES) used in the Mobile Satellite Services (MSS)";

- Part 22: "Specific conditions for ground based VHF aeronautical mobile and fixed radio equipment";
- Part 23: "Specific conditions for IMT-2000 CDMA Direct Spread (UTRA) Base Station (BS) radio, repeater and ancillary equipment";
- Part 24: "Specific conditions for IMT-2000 CDMA Direct Spread (UTRA) for Mobile and portable (UE) radio and ancillary equipment";
- Part 25: "Specific conditions for CDMA 1x spread spectrum Mobile Stations and ancillary equipment";
- Part 26: "Specific conditions for CDMA 1x spread spectrum Base Stations, repeaters and ancillary equipment";
- Part 27: "Specific conditions for Ultra Low Power Active Medical Implants (ULP-AMI) and related peripheral devices (ULP-AMI-P)";
- Part 28: "Specific conditions for wireless digital video links";
- Part 31: "Specific conditions for equipment in the 9 kHz to 315 kHz band for Ultra Low Power Active Medical Implants (ULP-AMI) and related peripheral devices (ULP-AMI-P)";
- Part 32: "Specific conditions for Ground and Wall Probing Radar applications".

National transposition dates			
Date of adoption of this EN:	4 April 2008		
Date of latest announcement of this EN (doa):	31 July 2008		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2009		
Date of withdrawal of any conflicting National Standard (dow):	31 January 2010		

#### 1 Scope

The present document contains the common requirements for radio communications equipment and associated ancillary equipment, in respect of ElectroMagnetic Compatibility (EMC).

Product dependent arrangements necessary to perform the EMC tests on dedicated types of radio communications equipment, and the assessment of test results, are detailed in the appropriate product related parts of EN 301 489 series [11].

The present document, together with the product related part, specifies the applicable EMC tests, the methods of measurement, the limits and the performance criteria for radio equipment and associated ancillary equipment. In case of differences (for instance concerning special conditions, definitions, abbreviation) between part 1 of the present document and the relevant product related part of EN 301 489 series [11], the product related part takes precedence.

Technical specifications related to the antenna port of radio equipment and radiated emissions from the enclosure port of radio equipment and combinations of radio and associated ancillary equipment are not included in the present document. Such technical specifications are normally found in the relevant product standards for the effective use of the radio spectrum.

The environment classification used in the present document refers to the environment classification used in:

- EN 61000-6-3 [18] and EN 61000-6-1 [19] for the residential, commercial and light industrial environment; or
- TR 101 651 [20] for the telecommunication centre environment; or
- ISO 7637-2 [8] for the vehicular environment.

The EMC requirements have been selected to ensure an adequate level of compatibility for apparatus intended to be used in the environments mentioned above. The levels, however, do not cover extreme cases which may occur in any location but with low probability of occurrence. The applicable environment(s) shall be declared by the manufacturer and shall be in accordance with the equipment documentation.

For radio equipment and associated ancillary equipment intended to be installed in motor vehicles (i.e. ESAs) and not related to immunity related functions of the vehicle, additional technical requirements necessary to demonstrate conformance to the motor vehicle EMC Directive 2004/104/EC [23], are set out in annex B (normative) of the present document.

The present document may not cover those cases where a potential source of interference which is producing individually repeated transient phenomena or a continuous phenomenon is permanently present, e.g. a radar or broadcast site in the near vicinity. In such a case it may be necessary to use special protection applied to either the source of interference or the interfered part or both.

Where none of the existing specific product related radio parts covers the required conditions for a particular radio equipment/service e.g. in case of the initial introduction of a new radio service or a special application, the present document can be used together with specific information for the radio equipment provided by the manufacturer, for the purposes of testing to the EMC requirements set out in the present document.

In all cases where a radio product falls within the scope of a specific product related radio part of the standard, the product related part takes precedence.

Compliance of radio equipment to the requirements of the present document does not signify compliance to any requirements related to spectrum management or to the use of the equipment (licensing requirements).

Compliance to the requirements of the present document does not signify compliance to any safety requirements. However, it is the responsibility of the assessor of the equipment to record in the test report any observations regarding the test sample becoming dangerous or unsafe as a result of the application of the tests called for in the present document.

NOTE: Radio equipment for use in maritime environment is covered by other ETSI EMC standards.

#### 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
  - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
  - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

[1]	CENELEC EN 55022 (2006): "Information technology equipment - Radio disturbance
	characteristics - Limits and methods of measurement"

- [2] CENELEC EN 61000-4-2 (2001): "Electromagnetic compatibility (EMC) Part 4-2: Testing and measurement techniques Electrostatic discharge immunity test".
- [3] CENELEC EN 61000-4-3 (2006): "Electromagnetic compatibility (EMC) Part 4-3: Testing and measurement techniques Radiated, radio-frequency, electromagnetic field immunity test".
- [4] CENELEC EN 61000-4-4 (2004): "Electromagnetic compatibility (EMC) Part 4-4: Testing and measurement techniques Electrical fast transient/burst immunity test".
- [5] CENELEC EN 61000-4-5 (2006): "Electromagnetic compatibility (EMC) Part 4-5: Testing and measurement techniques Surge immunity test".
- [6] CENELEC EN 61000-4-6 (2005): "Electromagnetic compatibility (EMC) Part 4-6: Testing and measurement techniques Immunity to conducted disturbances, induced by radio-frequency fields".
- [7] CENELEC EN 61000-4-11 (2004): "Electromagnetic compatibility (EMC) Part 4-11: Testing and measurement techniques Voltage dips, short interruptions and voltage variations immunity tests".
- [8] ISO 7637-2 (2004): "Road vehicles Electrical disturbances from conduction and coupling Part 2: Electrical transient conduction along supply lines only".
- [9] CENELEC EN 61000-3-3 (1995): "Electromagnetic compatibility (EMC) Part 3-3: Limits Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current  $\leq$  16 A per phase and not subject to conditional connection".

- [10] CISPR 25 (2nd Edition 2002): "Radio disturbance characteristics for the protection of receivers used on board vehicles, boats, and on devices Limits and methods of measurement".
- [11] ETSI EN 301 489 series: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services".
- [12] CENELEC EN 61000-3-12 (2005): "Electromagnetic compatibility (EMC) Part 3-12: Limits Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current > 16 A and  $\le 75$  A per phase".
- [13] CENELEC EN 61000-3-11 (2000): "Electromagnetic compatibility (EMC) Part 3-11: Limits Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems Equipment with rated current ≤ 75 A and subject to conditional connection".
- [14] CENELEC EN 55016-2-3 (2006) "Specification for radio disturbance and immunity measuring apparatus and methods Part 2-3: Methods of measurements of disturbances and immunity Radiated disturbance measurements".

#### 2.2 Informative references

- Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [16] Council Directive 2004/108/EC of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and repealing Directive 89/336/EEC (EMC Directive).
- [17] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [18] CENELEC EN 61000-6-3 (2001): "Electromagnetic compatibility (EMC) Part 6-3: Generic standards Emission standard for residential, commercial and light-industrial environments".
- [19] CENELEC EN 61000-6-1 (2007): "Electromagnetic compatibility (EMC) Part 6-1: Generic standards Immunity for residential, commercial and light-industrial environments".
- [20] ETSI TR 101 651 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Classification of the electromagnetic environment conditions for equipment in telecommunication networks".
- [21] CENELEC EN 61000-3-2/Amendment 1 (2006): "Electromagnetic compatibility (EMC) Part 3-2: Limits Limits for harmonic current emissions (equipment input current up to and including 16 A per phase)".
- [22] IEC 60050-161: "International Electrotechnical Vocabulary. Chapter 161: Electromagnetic compatibility".
- [23] Commission Directive 2004/104/EC of 14 October 2004 adapting to technical progress Council Directive 72/245/EEC relating to the radio interference (electromagnetic compatibility) of vehicles and amending Directive 70/156/EEC on the approximation of the laws of the Member States relating to the type-approval of motor vehicles and their trailers.
- [24] CENELEC EN 55016-1-4 (2004): "Specification for radio disturbance and immunity measuring apparatus and methods Part 1-4: Radio disturbance and immunity measuring apparatus Ancillary equipment Radiated disturbances".
- [25] ITU-R Radio Regulations (2004).
- [26] ETSI EN 301 843-1 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for marine radio equipment and services; Part 1: Common technical requirements".

- [27] IEEE 1284-2000: "IEEE Standard Signaling Method for a Bidirectional Parallel Peripheral Interface for Personal Computers".
- [28] IEEE 1394.1-2004: "IEEE Standard for High Performance Serial Bus Bridges".

#### 3 Definitions and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

ancillary equipment: equipment (apparatus), used in connection with a receiver or transmitter

NOTE: It is considered as an ancillary equipment (apparatus) if:

- the equipment is intended for use in conjunction with a receiver or transmitter to provide additional operational and/or control features to the radio equipment, (e.g. to extend control to another position or location); and
- the equipment cannot be used on a stand alone basis to provide user functions independently of a receiver or transmitter; and
- the receiver or transmitter, to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

**base station equipment:** radio and/or ancillary equipment intended for operation at a fixed location and powered directly or indirectly (e.g. via an AC/DC converter or power supply) by the AC mains network, or an extended local DC mains network

combined equipment: any equipment made of two or more individual products or functions

NOTE: At least one of the individual products or functions falls within the scope of the R&TTE Directive [15] and contains a radio transmitting function. The result of this combination provides additional control and/or functionality to the combined equipment.

**continuous phenomena (continuous disturbance):** electromagnetic disturbance, the effects of which on a particular device or equipment cannot be resolved into a succession of distinct effects

NOTE: See IEC 60050-161 [22].

enclosure port: physical boundary of the apparatus through which electromagnetic fields may radiate or impinge

NOTE: In the case of integral antenna equipment, this port is inseparable from the antenna port.

**Electrical/Electronic Sub-Assembly (ESA):** electrical and/or electronic device or set(s) of devices intended to be part of a vehicle, together with any associated electrical connections and wiring, which performs one or more specialized functions

**host equipment:** any equipment which has a complete user functionality when not connected to a radio communications equipment, and to which this radio equipment provides additional functionality, and to which connection is necessary for this radio equipment to offer additional functionality, and in which the transceiver part of the radio equipment is physically installed

NOTE: This also covers any device that would accept a variety of radio modules, where the original user functionality of the host equipment is not affected.

integral antenna: antenna which may not be removed during the tests, according to the manufacturer's statement

**manufacturer:** manufacturer of the equipment, or his authorized representative, or an equipment supplier to the European market