

# SLOVENSKI STANDARD

## SIST EN 301 908-7 V3.2.1:2007

01-december-2007

9`Y\_Ifca U[ bYfbUnXfi y`1j cgh]b`nUXYj Y`j`nj Yn]`n`fUX]`g\_`ja`gdY\_Ifca`f0FAŁ!`6UnbY  
dcghU`Y`f6GŁzdcBUj`U`b\_]`ffYdYh]hcf`1L]b`i dcfUVb]y`UcdfYa U`fl 9ŁnUWY] bU  
ca fYy`U`fYhY[ YbYfUWY`Y`A H!&\$\$\$`!`+`"XY.`<U`a cb]n]fUb]`9B`nU`A H!&\$\$\$z7 8 A 5  
H8 8`fi HF 5`H8 8Łf6 GŁz\_]`nUYa UV]ghj YbY`nU hYj Y` `YbU` "&X]fY\_hj Y`F/ HH9g

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Base Stations (BS),  
Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks -  
Part 7: Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (BS) covering essential  
requirements of article 3.2 of the R&TTE Directive

[SIST EN 301 908-7 V3.2.1:2007](https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007)

<https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007>

Ta slovenski standard je istoveten z: EN 301 908-7 Version 3.2.1

### ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 301 908-7 V3.2.1:2007

en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 908-7 V3.2.1:2007

<https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007>

# ETSI EN 301 908-7 V3.2.1 (2007-05)

---

*Harmonized European Standard (Telecommunications series)*

**Electromagnetic compatibility  
and Radio spectrum Matters (ERM);  
Base Stations (BS), Repeaters and User Equipment (UE) for  
IMT-2000 Third-Generation cellular networks;  
Part 7: Harmonized EN for IMT-2000,  
CDMA TDD (UTRA TDD) (BS)  
covering essential requirements  
of article 3.2 of the R&TTE Directive**

---

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 908-7 V3.2.1:2007](https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007)

<https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007>



## Reference

REN/ERM-TFES-003-7

## Keywords

3G, 3GPP, cell, digital, IMT-2000, mobile, radio,  
regulation, TD-CDMA, TDD, UMTS**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**SIST EN 301 908-7 V3.2.1:2007<https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b1643/etsi-en-301-908-7-v3-2-1-2007>  
**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2007.  
All rights reserved.

**DECT<sup>TM</sup>**, **PLUGTESTS<sup>TM</sup>** and **UMTS<sup>TM</sup>** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON<sup>TM</sup>** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP<sup>TM</sup>** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Introduction .....	7
1 Scope .....	8
2 References .....	8
3 Definitions, symbols and abbreviations .....	9
3.1 Definitions .....	9
3.2 Symbols.....	10
3.3 Abbreviations .....	10
4 Technical requirements specifications .....	11
4.1 Environmental profile.....	11
4.2 Conformance requirements .....	11
4.2.1 Introduction.....	11
4.2.2 Spectrum emission mask .....	11
4.2.2.1 Definition .....	11
4.2.2.1.1 3,84 Mcps TDD option.....	11
4.2.2.1.2 1,28 Mcps TDD option.....	12
4.2.2.2 Limits .....	12
4.2.2.2.1 3,84 Mcps TDD option.....	12
4.2.2.2.2 1,28 Mcps TDD option.....	13
4.2.2.3 Conformance.....	14
4.2.3 Transmitter adjacent channel leakage power ratio.....	14
4.2.3.1 Definition .....	14
4.2.3.2 Limits .....	14
4.2.3.2.1 General requirements.....	14
4.2.3.2.2 Co-existence with UTRA-FDD.....	15
4.2.3.2.3 Co-existence with unsynchronized UTRA TDD on adjacent channels.....	15
4.2.3.3 Conformance.....	16
4.2.4 Transmitter spurious emissions.....	16
4.2.4.1 Definition .....	16
4.2.4.2 Limits .....	16
4.2.4.2.1 General requirements.....	16
4.2.4.2.2 Co-existence with GSM 900.....	18
4.2.4.2.3 Co-existence with DCS 1800 .....	18
4.2.4.2.4 Co-existence with UTRA FDD .....	19
4.2.4.2.5 Co-existence with unsynchronized TDD .....	19
4.2.4.3 Conformance.....	20
4.2.5 Base station maximum output power.....	20
4.2.5.1 Definition .....	20
4.2.5.2 Limits .....	20
4.2.5.3 Conformance.....	20
4.2.6 Transmit intermodulation .....	20
4.2.6.1 Definition .....	20
4.2.6.2 Limits .....	20
4.2.6.2.1 3,84 Mcps TDD option.....	20
4.2.6.2.2 1,28 Mcps TDD option.....	21
4.2.6.3 Conformance.....	21
4.2.7 Receiver spurious emissions .....	21
4.2.7.1 Definition .....	21
4.2.7.2 Limits .....	21
4.2.7.2.1 3,84 Mcps TDD option.....	21
4.2.7.2.2 1,28 Mcps TDD option.....	22
4.2.7.3 Conformance.....	22

4.2.8	Receiver blocking characteristics .....	22
4.2.8.1	Definition .....	22
4.2.8.2	Limits .....	22
4.2.8.2.1	3,84 Mcps TDD option.....	22
4.2.8.2.2	1,28 Mcps TDD option.....	23
4.2.8.3	Conformance.....	24
4.2.9	Receiver intermodulation characteristics .....	25
4.2.9.1	Definition .....	25
4.2.9.2	Limits .....	25
4.2.9.2.1	3,84 Mcps TDD option.....	25
4.2.9.2.2	1,28 Mcps TDD option.....	25
4.2.9.3	Conformance.....	26
4.2.10	Receiver adjacent channel selectivity .....	26
4.2.10.1	Definition .....	26
4.2.10.2	Limits .....	26
4.2.10.2.1	3,84 Mcps TDD option.....	26
4.2.10.2.2	1,28 Mcps TDD option.....	26
4.2.10.3	Conformance.....	27
5	Testing for compliance with technical requirements.....	27
5.1	Environmental conditions for testing .....	27
5.2	Interpretation of the measurement results .....	27
5.3	Essential radio test suites.....	29
5.3.1	Spectrum emission mask .....	29
5.3.1.1	Method of test .....	29
5.3.1.1.1	Initial conditions.....	29
5.3.1.1.2	Procedure.....	31
5.3.1.2	Test requirements.....	31
5.3.1.2.1	3,84 Mcps TDD option.....	31
5.3.1.2.2	1,28 Mcps TDD option.....	32
5.3.2	Transmitter adjacent channel leakage power ratio.....	32
5.3.2.1	Method of test .....	32
5.3.2.1.1	Initial conditions.....	32
5.3.2.1.2	Procedure.....	34
5.3.2.2	Test requirements.....	35
5.3.2.2.1	3,84 Mcps TDD option.....	35
5.3.2.2.2	1,28 Mcps TDD option.....	35
5.3.3	Transmitter spurious emissions.....	35
5.3.3.1	Method of test .....	35
5.3.3.1.1	Initial conditions.....	35
5.3.3.1.2	Procedure.....	37
5.3.3.2	Test requirements.....	38
5.3.4	Base station maximum output power.....	38
5.3.4.1	Method of test .....	38
5.3.4.1.1	Initial conditions.....	38
5.3.4.1.2	Procedure.....	39
5.3.4.2	Test requirements.....	39
5.3.5	Transmit intermodulation .....	39
5.3.5.1	Method of test .....	39
5.3.5.1.1	Initial conditions.....	39
5.3.5.1.2	Procedure.....	43
5.3.5.2	Test requirements.....	43
5.3.6	Receiver spurious emissions .....	43
5.3.6.1	Method of test .....	43
5.3.6.1.1	Initial conditions.....	43
5.3.6.1.2	Procedure.....	44
5.3.6.2	Test requirements.....	45
5.3.7	Receiver blocking characteristics .....	45
5.3.7.1	Method of test .....	45
5.3.7.1.1	Initial conditions.....	45
5.3.7.1.2	Procedure.....	46
5.3.7.2	Test requirements.....	46

5.3.8	Receiver intermodulation characteristics .....	47
5.3.8.1	Method of test .....	47
5.3.8.1.1	Initial conditions .....	47
5.3.8.1.2	Procedure.....	47
5.3.8.2	Test requirements.....	48
5.3.9	Receiver adjacent channel selectivity .....	48
5.3.9.1	Method of test .....	48
5.3.9.1.1	Initial conditions.....	48
5.3.9.1.2	Procedure.....	49
5.3.9.1.3	Test requirements .....	49
<b>Annex A (normative):</b>	<b>HS Requirements and conformance Test specifications Table (HS-RTT).....</b>	<b>50</b>
<b>Annex B (normative):</b>	<b>BS configurations.....</b>	<b>52</b>
B.1	Receiver Diversity .....	52
B.2	Power Supply options.....	52
B.3	Ancillary RF amplifiers.....	52
B.4	BS using antenna arrays .....	52
B.4.1	Receiver tests.....	53
B.4.2	Transmitter tests .....	53
<b>Annex C (informative):</b>	<b>Environmental profile specification .....</b>	<b>54</b>
<b>Annex D (informative):</b>	<b>The EN title in the official languages .....</b>	<b>55</b>
<b>Annex E (informative):</b>	<b>Bibliography .....</b>	<b>57</b>
History .....		58

SIST EN 301 908-7 V3.2.1:2007

<https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007>

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is part 3 of a multi-part deliverable covering the Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks, as identified below:

- Part 1: "Harmonized EN for IMT-2000, introduction and common requirements, covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 2: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 3: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 4: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 5: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (BS and Repeaters) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 6: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 7: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";**
- Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 10: "Harmonized EN for IMT-2000, FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 11: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD) (Repeaters) covering essential requirements of article 3.2 of the R&TTE Directive";



Part 12: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (Repeater) covering essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates	
Date of adoption of this EN:	27 April 2007
Date of latest announcement of this EN (doa):	31 July 2007
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2008
Date of withdrawal of any conflicting National Standard (dow):	31 January 2009

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 (see bibliography).

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 908-7 V3.2.1:2007](https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007)

<https://standards.iteh.ai/catalog/standards/sist/4ec55045-65ee-473a-ad68-0f7e268b16cc/sist-en-301-908-7-v3-2-1-2007>

# 1 Scope

The present document applies to the following radio equipment type:

- Base stations for IMT-2000 CDMA TDD (UTRA TDD).

This radio equipment type is capable of operating in all or any part of the frequency bands given in table 1.

**Table 1: CDMA TDD Base Station frequency bands**

Operating band	Direction of transmission	CDMA TDD Base Station frequency bands
A	Transmit and Receive	1 900 MHz to 1 920 MHz
	Transmit and Receive	2 010 MHz to 2 025 MHz
D	Transmit and Receive	2 570 MHz to 2 620 MHz

The requirements in the present document apply to both Wide Area Base Stations and Local Area Base Stations unless otherwise stated.

IMT-2000 CDMA TDD (UTRA TDD) supports two options of the TDD mode with the chip rates of 3,84 Mcps and 1,28 Mcps. These two options are called the 3,84 Mcps TDD option and the 1,28 Mcps TDD option respectively. The requirements are listed in different subsections only if the parameters deviate.

The present document covers requirements for 3,84 Mcps TDD option Base Station for Releases 99, 4, 5, 6 and 7 and for 1,28 Mcps TDD option Base Stations for Releases 4, 5, 6 and 7.

For general purpose Base Stations of Releases 99 and 4 only the requirements for Wide Area Base Stations shall apply.

The present document is intended to cover the provisions of Directive 1999/5/EC [1] (R&TTE Directive) article 3.2, which states that "[...] radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [1] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site: <http://www.newapproach.org/>.

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

- [3] ETSI TS 125 105 (V7.4.0): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (TDD) (3GPP TS 25.105 version 7.4.0 Release 7)".
- [4] ETSI TS 125 142 (V7.4.0): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (TDD) (3GPP TS 25.142 version 7.4.0 Release 7)".
- [5] ITU-R Recommendation SM.329-10 (2003): "Unwanted emissions in the spurious domain".
- [6] void.
- [7] ETSI EN 301 908-1 (V3.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 1: Harmonized EN for IMT-2000, introduction and common requirements, covering essential requirements of article 3.2 of the R&TTE Directive".

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and the following apply:

**ancillary RF amplifier:** piece of equipment, which when connected by RF coaxial cables to the BS, has the primary function to provide amplification between the transmit and/or receive antenna connector of a BS and an antenna without requiring any control signal to fulfil its amplifying function

**B:** appropriate frequency in the Bottom of the operating frequency band of the BS: "RF channel"

**Base Station class:** wide area Base Station or local area Base Station, as declared by the manufacturer

**chip rate:** rate of "chips" (modulated symbols after spreading) per second

**DPCHo:** mechanism used to simulate an individual intracell interferer in the cell with one code and a spreading factor of 16

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**Fuw:** frequency offset of the unwanted interfering signal from the assigned channel frequency of the wanted signal

**local area Base Station:** Base Station, characterized by requirements derived from Pico Cell scenarios with a BS to UE coupling loss equals to 45 dB

**M:** appropriate frequency in the Middle of the operating frequency band of the BS: "RF channel"

**maximum output power (Pmax):** mean power level per carrier of the Base Station measured at the antenna connector in a specified reference condition. The period of measurement shall be a transmit timeslot excluding the guard period

**mean power:** when applied to a CDMA modulated signal this is the power (transmitted or received) in a bandwidth of at least  $(1 + \alpha)$  times the chip rate of the radio access mode. The period of measurement shall be a transmit timeslot excluding the guard period unless otherwise stated

**output power:** mean power of one carrier of the Base Station, delivered to a load with resistance equal to the nominal load impedance of the transmitter

**RATed output Power (PRAT):** mean power level per carrier that the manufacturer has declared to be available at the antenna connector

**RRC filtered mean power:** mean power as measured through a root raised cosine filter with roll-off factor  $\alpha$  and a bandwidth equal to the chip rate of the radio access mode

**T:** appropriate frequency in the Top of the operating frequency band of the BS: "RF channel"

**wide area Base Stations:** Base Station, characterized by requirements derived from macrocell and microcell scenarios with BS to UE coupling losses equal to 70 dB and 53 dB

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$\alpha$	roll-off factor, $\alpha = 0,22$
$\frac{DPCH_o - E_c}{I_{or}}$	ratio of the average transmits energy per PN chip for the $DPCH_o$ to the total transmit power
	spectral density in one time slot
F	Frequency (of the assigned channel frequency of the wanted signal)

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

16QAM	16 - Quadrature Amplitude Modulation
3GPP	3 <sup>rd</sup> Generation Partnership Project
ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio
BS	Base Station
BTS	Base Transceiver Station
CDMA	Code Division Multiple Access
CW	Continuous Wave

NOTE: Unmodulated signal.

dB	decibel
dBm	decibel relative to 1 milliwatt
DC	Direct Current
DCS	Digital Cellular System
DL	Down Link (forward link)
DPCH	Dedicated Physical CHannel
EUT	Equipment Under Test
FDD	Frequency Division Duplexing
GSM	Global System for Mobile
HS-PDSCH	High Speed Physical Downlink Shared CHannel
IMT-2000	International Mobile Telecommunications 2000
MS	Mobile Station
P	output Power
Pmax	Maximum output power of the base station
PRAT	RATed output Power of the base station
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
RMS	Root-Mean Square
RRC	Root-Raised Cosine
Rx	Receiver
SCH	Synchronization CHannel
TDD	Time Division Duplexing
TRX	Tansmitter-Receiver
TS	Time Slot
Tx	Transmitter
UARFCM	UTRA Absolute Radio Frequency Channel Number
UE	User Equipment
UL	Up Link (reverse link)
UTRA	Universal Terrestrial Radio Access
WCDMA	Wideband Code Division Multiple Access

## 4 Technical requirements specifications

### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

For guidance on how a supplier can declare the environmental profile see annex C.

### 4.2 Conformance requirements

#### 4.2.1 Introduction

To meet the essential requirement under article 3.2 of the R&TTE Directive [1] for IMT-2000 Base Stations (BS) seven essential parameters in addition to those in EN 301 908-1 [7] have been identified. Table 2 provides a cross reference between these seven essential parameters and the corresponding nine technical requirements for equipment within the scope of the present document.

To fulfil an essential parameter the compliance with all the corresponding technical requirements in table 2 must be verified.

**Table 2: Cross references**

Essential parameter	Corresponding technical requirements
Spectrum emissions mask	4.2.2 Spectrum emission mask
	4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR)
	4.2.4 Transmitter spurious emissions
Conducted spurious emissions from the transmitter antenna connector	4.2.5 Base station maximum output power
Accuracy of maximum output power	4.2.6 Transmit intermodulation
Intermodulation attenuation of the transmitter	4.2.7 Receiver spurious emissions
Conducted spurious emissions from the receiver antenna connector	4.2.8 Receiver blocking characteristics
Impact of interference on receiver performance	4.2.9 Receiver intermodulation characteristics
Receiver adjacent channel selectivity	4.2.10 Receiver Adjacent Channel Selectivity (ACS)

The technical requirements also apply to the BS configurations described in annex B.

#### 4.2.2 Spectrum emission mask

##### 4.2.2.1 Definition

Spectrum emission mask defines an out of band emission requirement for the Base Station transmitter. These out of band emissions are unwanted emissions outside the channel bandwidth resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions.

##### 4.2.2.1.1 3,84 Mcps TDD option

The spectrum emission mask specifies the limit of the transmitter out of band emissions at frequency offsets from the assigned channel frequency of the wanted signal between 2,5 MHz and 12,5 MHz.

#### 4.2.2.1.2 1,28 Mcps TDD option

The spectrum emission mask specifies the limit of the transmitter out of band emissions at frequency offsets from the assigned channel frequency of the wanted signal between 0,8 MHz and 4 MHz.

#### 4.2.2.2 Limits

##### 4.2.2.2.1 3,84 Mcps TDD option

The requirement shall apply to both Wide Area BS and Local Area BS. The requirement shall be met by a Base Station transmitting on a single RF carrier configured in accordance with the manufacturer's specification. Emissions shall not exceed the maximum level specified in tables 3 to 6 in the frequency range of  $f_{\text{offset}}$  from 2 515 MHz to  $f_{\text{offset}}$  from the carrier frequency, where:

- $f_{\text{offset}}$  is the separation between the carrier frequency and the centre frequency of the measuring filter;
- $f_{\text{offset}_{\text{max}}}$  is either 12,5 MHz or the offset to the UMTS Tx band edge (DL transmission in the following bands: 1 900 MHz to 1 920 MHz, 2 010 MHz to 2 025 MHz and 2 570 MHz to 2 620 MHz), whichever is the greater.

The spectrum emissions measured according to clause 5.3.1.1.2 shall not exceed the maximum level specified in tables 3 to 6 for the appropriate BS maximum output power.

**Table 3: Test requirements for spectrum emission mask values, BS maximum output power  $P \geq 43$  dBm (3,84 Mcps TDD option)**

Frequency offset of measurement filter centre frequency, $f_{\text{offset}}$	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	-12,5 dBm	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$-12,5 \text{ dBm} - 15 \left( \frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	-24,5 dBm	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	-11,5 dBm	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	-11,5 dBm	1 MHz

**Table 4: Test requirements for spectrum emission mask values, BS maximum output power  $39 \text{ dBm} \leq P < 43 \text{ dBm}$  (3,84 Mcps TDD option)**

Frequency offset of measurement filter centre frequency, $f_{\text{offset}}$	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	-12,5 dBm	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$-12,5 \text{ dBm} - 15 \left( \frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	-24,5 dBm	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	-11,5 dBm	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	$P - 54,5 \text{ dBm}$	1 MHz

**Table 5: Test requirements for spectrum emission mask values,  
BS maximum output power  $31 \text{ dBm} \leq P < 39 \text{ dBm}$  (3,84 Mcps TDD option)**

Frequency offset of measurement filter centre frequency, $f_{\text{offset}}$	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	$P - 51,5 \text{ dBm}$	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$P - 51,5 \text{ dB} - 15 \left( \frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	$P - 63,5 \text{ dBm}$	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	$P - 50,5 \text{ dBm}$	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	$P - 54,5 \text{ dBm}$	1 MHz

**Table 6: Test requirements for spectrum emission mask values,  
BS rated output power  $\text{PRAT} < 31 \text{ dBm}$  (3,84 Mcps TDD option)**

Frequency offset of measurement filter centre frequency, $f_{\text{offset}}$	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	$-20,5 \text{ dBm}$	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$-20,5 \text{ dBm} - 15 \left( \frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	$-32,5 \text{ dBm}$	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	$-19,5 \text{ dBm}$	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	$-23,5 \text{ dBm}$	1 MHz

iTeh STANDARD PREVIEW

#### 4.2.2.2.2 1,28 Mcps TDD option (standards.iteh.ai)

The requirement shall apply to both Wide Area BS and Local Area BS. The requirement shall be met by a Base Station transmitting on a single RF carrier configured in accordance with the manufacturer's specification. Emissions shall not exceed the maximum level specified in tables 6a to 6c in the frequency range of  $f_{\text{offset}}$  from 0,815 MHz to  $f_{\text{offset}}$  from the carrier frequency, where:

- $f_{\text{offset}}$  is the separation between the carrier frequency and the centre frequency of the measuring filter;
- $f_{\text{offset}_{\text{max}}}$  is either 4,0 MHz or the offset to the UMTS Tx band edge (DL transmission in the following bands: 1 900 MHz to 1 920 MHz, 2 010 MHz to 2 025 MHz and 2 570 MHz to 2 620 MHz), whichever is the greater.

The spectrum emissions measured according to clause 5.3.1.1.2 shall not exceed the maximum level specified in tables 6a to 6c for the appropriate BS maximum output power.

**Table 6a: Test Requirements for spectrum emission mask values,  
BS maximum output power  $P \geq 34 \text{ dBm}$  (1,28 Mcps TDD option)**

Frequency offset of measurement filter centre frequency, $f_{\text{offset}}$	Maximum level	Measurement bandwidth
$0,815 \text{ MHz} \leq f_{\text{offset}} < 1,015 \text{ MHz}$	$-18,5 \text{ dBm}$	30 kHz
$1,015 \text{ MHz} \leq f_{\text{offset}} < 1,815 \text{ MHz}$	$-18,5 \text{ dBm} - 10 \left( \frac{f_{\text{offset}}}{\text{MHz}} - 1,015 \right) \text{ dB}$	30 kHz
$1,815 \text{ MHz} \leq f_{\text{offset}} < 2,3 \text{ MHz}$	$-26,5 \text{ dBm}$	30 kHz
$2,3 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	$-11,5 \text{ dBm}$	1 MHz