



**SLOVENSKI STANDARD**  
**SIST ISO 12240-1:2001**

**01-julij-2001**

---

**Kroglasti drsni zgibi - 1. del: Radialni kroglasti drsni zgibi**

Spherical plain bearings -- Part 1: Radial spherical plain bearings

Rotules lisses -- Partie 1: Rotules lisses radiales

**Ta slovenski standard je istoveten z: ISO 12240-1:1998**

[SIST ISO 12240-1:2001](https://standards.iteh.ai/catalog/standards/sist/7441e108-77a8-436c-a87f-936ccdc3998e/sist-iso-12240-1-2001)

<https://standards.iteh.ai/catalog/standards/sist/7441e108-77a8-436c-a87f-936ccdc3998e/sist-iso-12240-1-2001>

**ICS:**

21.100.10      Drsni ležaji                                      Plain bearings

**SIST ISO 12240-1:2001**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 12240-1:2001](#)

<https://standards.iteh.ai/catalog/standards/sist/7441e108-77a8-436c-a87f-936ccdc3998e/sist-iso-12240-1-2001>

# INTERNATIONAL STANDARD

**ISO**  
**12240-1**

First edition  
1998-08-15

---

---

## **Spherical plain bearings — Part 1: Radial spherical plain bearings**

*Rotules lisses —*

*Partie 1: Rotules lisses radiales*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 12240-1:2001](https://standards.iteh.ai/catalog/standards/sist/7441e108-77a8-436c-a87f-936ccdc3998e/sist-iso-12240-1-2001)

<https://standards.iteh.ai/catalog/standards/sist/7441e108-77a8-436c-a87f-936ccdc3998e/sist-iso-12240-1-2001>



Reference number  
ISO 12240-1:1998(E)

## ISO 12240-1:1998(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standard bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 12240-1 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*, Subcommittee SC 7, *Spherical plain bearings*.

This first edition cancels and replaces ISO 6124-1:1987, ISO 6124-2:1982, ISO 6124-3:1982 and ISO 6125:1982 of which it constitutes a technical revision. (standards.iteh.ai)

ISO 12240 consists of the following parts, under the general title *Spherical plain bearings*:

- Part 1: Radial spherical plain bearings [SIST ISO 12240-1:2001](http://standards.iteh.ai/catalog/standards/sist/7441e108-77a8-436c-a87f-936ccdc3998e/sist-iso-12240-1-2001)
- Part 2: Angular contact radial spherical plain bearings
- Part 3: Thrust spherical plain bearings
- Part 4: Spherical plain bearing rod ends

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland  
Internet iso@iso.ch

Printed in Switzerland

# Spherical plain bearings —

## Part 1: Radial spherical plain bearings

### 1 Scope

This part of ISO 12240 specifies dimension series, tolerances and radial internal clearances for radial spherical plain bearings.

The dimensions and tolerances specified in this part of ISO 12240 have been selected to permit the design of radial spherical plain bearings using a wide choice of sliding material combinations.

The specified tolerance values apply to finished, radial spherical plain bearings before any coating, plating, ring splitting or ring fracturing.

In the case of surface treated radial spherical plain bearings, there may be slight deviations from the specified tolerance values.

Radial spherical plain bearings need not conform to the designs illustrated but compliance is required as regards the dimensions, tolerances and radial internal clearances specified.

NOTE — Spherical plain bearings for airframe applications are not covered by this part of ISO 12240.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 12240. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 12240 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 582:1995, *Rolling bearings – Chamfer dimensions – Maximum values*.

ISO 1132-1:—<sup>1)</sup>, *Rolling bearings – Tolerances – Part 1: Terms and definitions*.

ISO 6811:1998, *Spherical plain bearings – Vocabulary*.

ISO 12240-4:1998, *Spherical plain bearings – Part 4: Spherical plain bearing rod ends*.

1) To be published. (Revision of ISO 1132:1980)

### 3 Definitions and symbols

For the purposes of this part of ISO 12240, the definitions given in ISO 1132-1 and ISO 6811 apply. The symbols (except those for tolerances) shown in the figures and the values given in the tables denote nominal dimensions unless specified otherwise.

$B$	Inner ring width
$C$	Outer ring width
$D$	Outside diameter
$d$	Bore diameter
$d_1$	Outside diameter of inner ring face
$d_k$	Sphere diameter
$r_{s \min}^{2)}$	Smallest single chamfer dimension, inner ring
$r_{1s \min}^{2)}$	Smallest single chamfer dimension, outer ring
$V_{Dmp}$	Variation of mean outside diameter
$V_{dmp}$	Variation of mean bore diameter
$V_{Dp}$	Variation of outside diameter in a single radial plane
$V_{dp}$	Variation of bore diameter in a single radial plane
$\alpha$	Angle of tilt
$\Delta_{Bs}$	Deviation of a single inner ring width
$\Delta_{Cs}$	Deviation of a single outer ring width
$\Delta_{Dmp}$	Deviation of mean outside diameter in a single plane
$\Delta_{dmp}$	Deviation of mean bore diameter in a single plane

### 4 Angles of tilt, $\alpha$

The specified angles of tilt (approximate values) represent the angles by which the axes of the inner ring and of the outer ring may be inclined in relation to each other without reducing the projected theoretical contact area of the two bearing rings when the two ring axes are parallel to each other.

NOTE — Attention is drawn to the fact that after mounting a radial spherical plain bearing on a shaft and into a housing, the angle through which the bearing can tilt may be restricted by the design of the adjacent components.

2) The corresponding maximum chamfer dimensions are given in table 1 of ISO 582:1985.



Table 1 — Radial spherical plain bearings, dimension series E

$d$ mm	$D$ mm	$B$ mm	$C$ mm	$d_1$ $\approx$ mm	$d_k$ 1) mm	$r_s$ min. mm	$r_{1s}$ min. mm	$\alpha$ $\approx$ °
4	12	5	3	6	8	0,3	0,3	16
5	14	6	4	8	10	0,3	0,3	13
6	14	6	4	8	10	0,3	0,3	13
8	16	8	5	10	13	0,3	0,3	15
10	19	9	6	13	16	0,3	0,3	12
12	22	10	7	15	18	0,3	0,3	10
15	26	12	9	18	22	0,3	0,3	8
17	30	14	10	20	25	0,3	0,3	10
20	35	16	12	24	29	0,3	0,3	9
25	42	20	16	29	35	0,6	0,6	7
30	47	22	18	34	40	0,6	0,6	6
35	55	25	20	39	47	0,6	1	6
40	62	28	22	45	53	0,6	1	7
45	68	32	25	50	60	0,6	1	7
50	75	35	28	55	66	0,6	1	6
55	85	40	32	62	74	0,6	1	7
60	90	44	36	66	80	1	1	6
70	105	49	40	77	92	1	1	6
80	120	55	45	88	105	1	1	6
90	130	60	50	98	115	1	1	5
100	150	70	55	109	130	1	1	7
110	160	70	55	120	140	1	1	6
120	180	85	70	130	160	1	1	6
140	210	90	70	150	180	1	1	7
160	230	105	80	170	200	1	1	8
180	260	105	80	192	225	1,1	1,1	6
200	290	130	100	212	250	1,1	1,1	7
220	320	135	100	238	275	1,1	1,1	8
240	340	140	100	265	300	1,1	1,1	8
260	370	150	110	285	325	1,1	1,1	7
280	400	155	120	310	350	1,1	1,1	6
300	430	165	120	330	375	1,1	1,1	7

1) Reference only.

Table 2 — Radial spherical plain bearings, dimension series G

$d$	$D$	$B$	$C$	$d_1$	$d_k$ <sup>1)</sup>	$r_s$	$r_{1s}$	$\alpha$
mm	mm	mm	mm	≈ mm	mm	min. mm	min. mm	≈ °
4	14	7	4	7	10	0,3	0,3	20
5	14	7	4	7	10	0,3	0,3	20
6	16	9	5	9	13	0,3	0,3	21
8	19	11	6	11	16	0,3	0,3	21
10	22	12	7	13	18	0,3	0,3	18
12	26	15	9	16	22	0,3	0,3	18
15	30	16	10	19	25	0,3	0,3	16
17	35	20	12	21	29	0,3	0,3	19
20	42	25	16	24	35	0,3	0,6	17
25	47	28	18	29	40	0,6	0,6	17
30	55	32	20	34	47	0,6	1	17
35	62	35	22	39	53	0,6	1	16
40	68	40	25	44	60	0,6	1	17
45	75	43	28	50	66	0,6	1	15
50	90	56	36	57	80	0,6	1	17
60	105	63	40	67	92	1	1	17
70	120	70	45	77	105	1	1	16
80	130	75	50	87	115	1	1	14
90	150	85	55	98	130	1	1	15
100	160	85	55	110	140	1	1	14
110	180	100	70	122	160	1	1	12
120	210	115	70	132	180	1	1	16
140	230	130	80	151	200	1	1	16
160	260	135	80	176	225	1	1,1	16
180	290	155	100	196	250	1,1	1,1	14
200	320	165	100	220	275	1,1	1,1	15
220	340	175	100	243	300	1,1	1,1	16
240	370	190	110	263	325	1,1	1,1	15
260	400	205	120	283	350	1,1	1,1	15
280	430	210	120	310	375	1,1	1,1	15

1) Reference only.