

---

---

**Information technology — User system  
interfaces and symbols — Icon symbols  
and functions —**

**Part 6:  
Action icons**

iTeh STANDARD PREVIEW

*Technologies de l'information — Interfaces pour système utilisateur et  
symboles — Symboles et fonctions d'icônes —*

*Partie 6: Icônes d'action*

[ISO/IEC 11581-6:1999](https://standards.iso.org/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999)

[https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-  
ca692514ea0e/iso-iec-11581-6-1999](https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999)



**Contents**

1 Scope ..... 1

2 Conformance..... 1

3 Normative references ..... 1

4 Definitions ..... 2

5 Conceptual construction of action icons ..... 2

6 Action icon requirements and recommendations ..... 2

6.1 Requirements ..... 2

6.2 Recommendations..... 2

7 Action icon specifications ..... 3

7.1 General action icons..... 4

7.2 Filing action icons ..... 5

7.3 Print action icons..... 6

7.4 Editing action icons..... 7

7.5 Command reversal action icons ..... 9

7.6 Text action icons..... 9

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

<https://standards.iteh.ai/catalog/standards/sist/02de270a-c57d-4c5b-8b0c-ca692514ea0e/iso-iec-11581-6-1999>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 11581-6 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

ISO/IEC 11581 consists of the following parts, under the general title *Information technology — User system interfaces and symbols — Icon symbols and functions*:

— Part 1: Icons — General

— Part 2: Object icons

— Part 3: Pointer icons

— Part 4: Control icons

— Part 5: Tool icons

— Part 6: Action icons

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 11581-6:1999](https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999)

<https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999>

## Introduction

Action icons permit users to invoke functions that act upon pre-selected or default objects. Functions initiated by action icons may also be available via text commands on menus. Action icons provide more direct access to functions by representing those text commands graphically.

The icon functions and graphics included in this part of ISO/IEC 11581 have been selected on the basis of their common use across contemporary platforms and applications.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 11581-6:1999](https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999)

<https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999>

# Information technology — User system interfaces and symbols — Icon symbols and functions —

## Part 6: Action icons

### 1 Scope

ISO/IEC 11581 applies to icons that are shown on a screen, that users can manipulate and interact with, and that represent data or computer system functions. This part of ISO/IEC 11581 addresses only action icons. Action icons represent actions by association with objects that prompt the user to recall the intended actions. This part of ISO/IEC 11581 describes user interaction with and appearance of action icons on the screen. Other types of icons are covered in other parts of the standard, listed in the Foreword.

### 2 Conformance

A system, application, or set of one or more icons conforms to this part of ISO/IEC 11581 if all action icons available to the user in the system or application conform to ISO/IEC 11581-1, clauses 5 and 6.1 and to subclauses 6.1.1 to 6.1.3 of this part of ISO/IEC 11581.

### 3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 11581. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO/IEC 11581 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 11581-1:—<sup>1)</sup>, *Information technology — User system interfaces and symbols — Icon symbols and functions — Part 1: Icons — General.*

ISO/IEC 11581-2:—<sup>1)</sup>, *Information technology — User system interfaces and symbols — Icon symbols and functions — Part 2: Object icons.*

---

1) To be published.

## 4 Definitions

For the purposes of this part of ISO/IEC 11581, the definitions given in other parts of ISO/IEC 11581 and the following definitions apply.

**4.1 Action icon:** icon which acts upon a selected source and/or target, and provides single step access to functions typically also available via a menu.

NOTE For some action icons, such as «Cut», the source is pre-selected whilst the target is the default. For «Paste» the source is the default whilst the target must be selected by the user.

**4.2 Filing system:** container which provides an organised collection of objects such as documents, folders and filing cabinets.

## 5 Conceptual construction of action icons

The conceptual construction of action icons is similar to that shown for object icons in clause 5 of ISO/IEC 11581-2. The metaphor is that of pushing a button to invoke the associated functionality.

## 6 Action icon requirements and recommendations

### 6.1 Requirements

#### 6.1.1 Graphic and function

If a system or application uses an action icon that has the appearance of the action icon graphic specified in clause 7 of this part of ISO/IEC 11581 within the specific variations given, and within the global variations specified in ISO/IEC 11581-1, it shall serve the primary function specified in clause 7 of this part of ISO/IEC 11581.

#### 6.1.2 Arrangement

Related action icons shall be grouped together. These groups shall be arranged together in rows, columns or boxes.

#### 6.1.3 Selection

Selection of an action icon shall be made by indicating with the pointer and activating the associated input device (e.g. clicking a mouse button).

#### 6.1.4 Visual feedback

There shall be a clear visual discrimination between action icons that represent available and unavailable functions.

There shall be visual feedback when a function has been invoked via an action icon. There shall also be visual feedback that indicates the status of the action.

NOTE Typically, action icons are presented, and have the same behaviour as real, three-dimensional push buttons.

The visual feedback to the user from activated action icons shall be consistent and logical.

### 6.2 Recommendations

#### 6.2.1 Function and graphic

If a system or application uses an action icon that serves the primary function specified in clause 7, it is highly recommended that it have the appearance of the action icon graphic specified in clause 7, within the specific variations given and within the global variations specified in ISO/IEC 11581, 6.3.

### 6.2.2 Metaphor

Action icons should be presented in a cell that uses shadows and highlights to re-enforce the metaphor of real buttons and their corresponding behaviour.

### 6.2.3 Arrangement

If action icons are provided according to clause 7, they should be grouped in the same sets as shown in that clause.

### 6.2.4 Colour

Action icons may be coloured.

### 6.2.5 Appearance

All icons of a similar selection status should be of a similar visual strength.

### 6.2.6 Typeface

An uncomplex typeface should be employed if letters, numbers, punctuation marks and mathematical symbols are used as integrated elements of the action icon.

All text should be concise.

## 7 Action icon specifications

The classifications in this clause are provided to group related action icons. They are classified into the following six sets:

- general action icons (7.1) [ISO/IEC 11581-6:1999](https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999)
- filing action icons (7.2) <https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999>
- print action icons (7.3)
- editing action icons (7.4)
- command reversal action icons (7.5)
- text action icons (7.6)

In the following icon specifications, the illustrations represent the basic graphics for the action icons subject to global variations (see ISO/IEC 11581-1, 6.3) and the specific variations given in this clause, listed for each icon where appropriate.

The graphics for all categories are shown bounded by a rectangular outline cell that represents the edges of the button top only. The size of the cell and the location of the graphic within it are shown for illustration, and are implementation dependent. The three-dimensional button effect, described in 6.2.2, has not been included here.

The grey zone within each cell represents the button top background colour, whilst the white areas within the graphics should be a colour appropriate to the depicted object.

## 7.1 General action icons

### 7.1.1 Help

**Primary function.** To provide access to the Help functions of the system, either to general help or related help to a user-selected object.

**Specific instance.** A question mark.

**Components.**

A question mark as commonly used in Latin languages

**Graphic.**



### 7.1.2 Find

**Primary function.** To locate an object specified by the user within the current system or application. This icon should be enhanced further by additional components to identify the target of this function (see ISO/IEC 11581-1, clause 6).

<https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-14ea0e/iso-iec-11581-6-1999>

**Specific instance.** A hand held torch or flashlight.

**Components.**

- Torch/flashlight. Comprising two diagonal cylinders, joined together and orientated from the upper left to the centre of the button top/cell. The larger cylinder is in the centre of the cell.
- Light beams/rays. A series of lines emanating from the larger cylinder in the general direction of the lower right corner of the cell.

**Graphic.**



**Specific variations.**

- The torch/flashlight may be orientated in any direction.
- The light beam may be illustrated by some other means, e.g. by a highlighted area.



## 7.2 Filing action icons

### 7.2.1 Create new


**Primary function.** To create a new document.

**Specific instance.** An empty document

**Components.**

- Document, see ISO/IEC 11581-2, 7.1.1.

**Graphic.**



**Specific variation.** Gleam/sparkle/star burst. An eight-pointed star located on the unfolded, top corner of the document.

### 7.2.2 Open


**Primary function.** To open an existing document. If no document is pre-selected, this icon will take the user directly into the filing system.

**Specific instance.** An open folder with an arrow moving from it.

**Components.**

- An open folder (based upon ISO/IEC 11581-2, 7.1.2).
- A direction arrow. Located in the top right corner of the cell, above the folder and pointing upwards and to the right, away from the open folder.

**Graphic.**



**Specific variations.**

- An object, representing a document, may be included moving from the folder if space permits this additional level of detail.
- For languages oriented from right to left the graphic may be «mirrored» horizontally.

### 7.2.3 Save

**Primary function.** To save the current document with the same name within the filing system, whilst keeping the document open.

**Specific instance.** An open folder with an arrow moving into it.

**Components.**

- An open folder (based upon ISO/IEC 11581-2, 7.1.2).
- A direction arrow. Located in the top left corner of the cell, pointing downwards and into the open folder.

**Graphic.**



**Specific variations.**

- An object, representing a document, may be included moving into the folder if space permits this additional level of detail.
- For languages oriented from right to left the graphic may be «mirrored» horizontally.

iTech STANDARD PREVIEW  
 (standard.iTech.ai)  
 ISO/IEC 11581-6:1999  
<https://standards.iteh.ai/catalog/standards/sist/02de270a-e37d-4c3b-8b0e-ca692514ea0e/iso-iec-11581-6-1999>

## 7.3 Print action icons

### 7.3.1 Print preview

**Primary function.** To provide a view of the layout and composition of the current document for printing. Typically, several levels of enlargement or reduction are available.

**Specific instance.** A document with a magnifying glass overlaid.

**Components.**

- Document, see ISO/IEC 11581-2, 7.1.1
- Magnifying glass. A circle with an adjoining diagonal line at the lower right to signify the handle. The circular part of the magnifying glass overlays the lower right of the document.

**Graphic.**



### 7.3.2 Print

**Primary function.** To print the current document to the predefined settings within the system or application.

**Specific instance.** An electromechanical printer with a document emerging.

**Components.**

- Printer, see ISO/IEC 11581-2, 7.1.5

**Graphic.**



## 7.4 Editing action icons iTeh STANDARD PREVIEW

### 7.4.1 Cut

(standards.iteh.ai)


**Primary function.** To remove pre-selected text or an object from the current document into a storage buffer.

**Specific instance.** An open pair of scissors.

**Components.**

Two open, crossing blades with handles. The open, cutting part of the scissors pointing upwards.

**Graphic.**



**Specific variation.** The scissors may be rotated in any direction.