

**Broadband Data Transmission Systems operating in the
2 500 MHz to 2 690 MHz frequency band;
Part 1: TDD Base Stations;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/32850b6b-c96d-451b-81c9-e427d9127cfal/etsi-en-302-544-1-v1.1.1-2009-02>



ReferenceDEN/BRAN-0060000-1

Keywordsbroadband, cellular, digital, IMT-2000, mobile,
multipoint, radio, regulation, TDD**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	6
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references	8
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols	9
3.3 Abbreviations	10
4 Essential requirements specification	10
4.1 Environmental profile.....	10
4.2 Conformance requirements	10
4.2.1 Introduction.....	10
4.2.2 Spectrum emission mask	11
4.2.2.1 Definition	11
4.2.2.2 Limits	11
4.2.2.2.1 Spectrum emission mask for 5 MHz bandwidth.....	11
4.2.2.2.2 Spectrum emission mask for 10 MHz bandwidth.....	12
4.2.2.3 Conformance	14
4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR)	14
4.2.3.1 Definition	14
4.2.3.2 Limits	14
4.2.3.2.1 ACLR requirements for 5 MHz Bandwidth	14
4.2.3.2.2 ACLR requirements for 10 MHz bandwidth	14
4.2.3.3 Conformance.....	15
4.2.4 Transmitter spurious emissions.....	15
4.2.4.1 Definition	15
4.2.4.2 Limits	15
4.2.4.3 Conformance.....	16
4.2.5 Maximum output power accuracy	16
4.2.5.1 Definition	16
4.2.5.2 Limits	16
4.2.5.3 Conformance.....	16
4.2.6 Transmit Intermodulation	16
4.2.6.1 Definition	16
4.2.6.2 Limits	16
4.2.6.3 Conformance.....	17
4.2.7 Receiver spurious emissions	17
4.2.7.1 Definition	17
4.2.7.2 Limits	17
4.2.7.3 Conformance.....	17
4.2.8 Receiver Adjacent Channel Selectivity (ACS)	17
4.2.8.1 Definition	17
4.2.8.2 Limits	18
4.2.8.3 Conformance.....	18
4.2.9 Receiver blocking characteristics	18
4.2.9.1 Definition	18
4.2.9.2 Limits	19
4.2.9.3 Conformance.....	19
4.2.10 Receiver intermodulation characteristics	19
4.2.10.1 Definition and applicability.....	19

4.2.10.2	Limits	19
4.2.10.3	Conformance	20
5	Testing for compliance with technical requirements.....	20
5.1	Environmental conditions for testing	20
5.2	Product information.....	20
5.3	Interpretation of the measurement results	21
5.4	Essential radio test suites.....	21
5.4.1	Spectrum emission mask	21
5.4.1.1	Method of test for BS spectral emission mask	21
5.4.1.1.1	Initial conditions	22
5.4.1.1.2	Procedure.....	22
5.4.2	Transmitter Adjacent Channel Leakage power Ratio (ACLR)	23
5.4.2.1	Method of test for BS ACLR	23
5.4.2.1.1	Initial conditions	23
5.4.2.1.2	Procedure.....	23
5.4.3	Transmitter spurious emissions.....	24
5.4.3.1	Method of test	24
5.4.3.1.1	Initial conditions	25
5.4.3.1.2	Procedure.....	25
5.4.4	Maximum output power accuracy	26
5.4.4.1	Method of test	26
5.4.4.1.1	Initial conditions	26
5.4.4.1.2	Procedure.....	26
5.4.5	Transmitter Intermodulation	26
5.4.5.1	Method of test	27
5.4.5.1.1	Initial conditions	27
5.4.5.1.2	Procedure.....	27
5.4.5.1.3	Test requirements	27
5.4.6	Receiver spurious emissions	27
5.4.6.1	Method of test	27
5.4.6.1.1	Initial conditions	28
5.4.6.1.2	Procedure.....	28
5.4.7	Receiver adjacent channel selectivity	28
5.4.7.1	Method of test	28
5.4.7.1.1	Procedure.....	29
5.4.8	Receiver blocking characteristics	30
5.4.8.1	Method of test	30
5.4.8.1.1	Initial conditions	30
5.4.8.1.2	Procedure.....	30
5.4.9	Receiver intermodulation characteristics	32
5.4.9.1	Method of test	32
5.4.9.1.1	Initial conditions	32
5.4.9.1.2	Procedure.....	32
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	34
Annex B (informative):	The EN title in the official languages	36
Annex C (informative):	Bibliography.....	37
History		38

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.5] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [i.1] are given in annex A.

The present document is part 1 of a multi-part deliverable covering the Base Stations (BS) and User Equipment (UE) for Broadband Data Transmission Systems in 2 500 MHz to 2 690 MHz frequency band, as identified below:

- Part 1: "TDD Base Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";**
- Part 2: "TDD User Equipment Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 3: "FDD Base Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 4: "FDD User Equipment Stations; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.2].

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/32850b6b-c96d-451b-81c9-e427d9127cfa/etsi-en-302-544-1-v1.1.1-2009-02>

1 Scope

The present document is applicable to TDD Base Station radio equipment for mobile/nomadic Broadband Data Transmitting Systems operating in the 2 500 MHz to 2 690 MHz frequency band.

TDD radio equipment types operate in the 2 500 MHz to 2 690 MHz frequency band according to national frequency plans designed on the same basic assumption that the assigned blocks are in multiples of 5 MHz (same centre frequency). The present document covers the requirements for 5 MHz and 10 MHz channelized systems.

The document is equally applicable to systems utilizing integral or non integral antennas.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive) Article 3.2, which states that: "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of Article 3 of the R&TTE Directive may apply to equipment within the scope of the present document. The present document does not address those IMT-2000 systems which are considered in EN 301 908 [i.3].

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI EN 300 019 (all parts): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment".
- [2] ETSI TR 100 028 (parts 1 and 2) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

- [3] CEPT/ERC/REC 74-01E (2005): "Unwanted Emissions in the Spurious Domain".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.3] ETSI EN 301 908 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks".
- [i.4] ETSI TR 102 215 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.5] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1] and the following apply:

ACLR Class 1: BS classification that identifies a level of ACLR performance generally appropriate for intra-system operation in contiguous channel assignments

ACLR Class 2: BS classification that identifies a level of ACLR performance appropriate for the boundary between FDD Uplink and TDD and for the boundaries between blocks with unsynchronized TDD usage

ACS Class 1: this class identifies a level of ACS performance appropriate for base stations operating at $P_{nom} \leq 25$ dBm

ACS Class 2: this class identifies a level of intra-system ACS performance for base stations operating at $P_{nom} > 25$ dBm

ACS Class 3: this class identifies a level of inter-system ACS performance for base stations operating at $P_{nom} > 25$ dBm for the boundary between FDD Downlink and TDD and for the boundaries between blocks with unsynchronized TDD usage

burst: period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

environmental profile: declared range of environmental conditions under which equipment within the scope of the present document is required to be compliant

Eval_BW 1: pass band of a rectangular filter with a bandwidth of 4,75 MHz for 5 MHz equipment and 9,5 MHz for 10 MHz equipment

Eval_BW 2: measurement for Eval_BW 2 on the operating channel is performed using a rectangular filter with a 4,75 MHz or 9,5 MHz bandwidth and the measurement on the victim channel is performed using an RRC filter with a 3,84 MHz or 7,68 MHz bandwidth (respectively) both with roll-off factor of 0,22 centred on the 1st or 2nd adjacent victim channel

Eval_BW 3: measurement for Eval_BW 3 on the operating channel is performed using a rectangular filter with a 9,5 MHz bandwidth and the measurement on the victim channel is performed using a RRC filter with a 3,84 MHz bandwidth (with roll-off factor of 0,22) centred on the corresponding adjacent victim channel

integral antenna: antenna which is declared to be part of the radio equipment by the supplier

NOTE: Even when equipment with an integral antenna is concerned, it might still be possible to separate the antenna from the equipment using a special tool. In such cases the assessment of the radio equipment and of the antenna against requirements of this multi-part EN may be done separately.

maximum output power: mean power level per carrier of the base station or mobile station measured at the antenna connector in a specified reference condition

mean power: when applied to a modulated signal, this is the power (transmitted or received) in a bandwidth

NOTE: The term "mean" here is used to exclude the amplitude fluctuation related to those theoretical variations present in signal for example due to amplitude modulation, pulse shaping, pre-equalization etc. Time averaging should be applied to estimate mean power with the affect of the theoretical variations. The duty cycle corresponding to burst activity within a frame should be also incorporated for "mean" power estimation.

nominal maximum output power: maximum nominal mean power level per carrier measured over total allocated channel bandwidth of the base station available at the antenna connector declared by the manufacturer; for equipment implementing dynamic change of modulation format, it is intended as the maximum nominal mean power associated to the modulation format delivering the highest power

operating nominal RF channel width: nominal amount of spectrum used by a single device operating on an identified centre frequency

TDD down-link frame: time interval in which the BS is transmitting and the UE is receiving

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{BS}	Base Station Interface A
A_{MS}	Mobile Station Interface A
A_{UUT}	Unit Under Test Interface A
dB	decibel
dBc	decibel relative to P _{nom} carrier power measured in Eval_BW 1
dBm	decibel relative to 1 milliwatt
f	Frequency (of the assigned channel frequency of the wanted signal)
f_b	FDD/TDD border frequency
NOTE:	A more precise definition is provided below table 15.
f_c	centre frequency of the assigned channel
GHz	GigaHertz
M_{BS}	Base Station Interface M
M_{MS}	Mobile Station Interface M
MHz	MegaHertz
N _{th}	receiver thermal noise of the equipment (in dBm)
P	output Power (in dBm)
P_{nom}	nominal maximum output Power (in dBm)
P_{max}	maximum output Power of the base station (in dBm)
P_{SENS5}	Receiver sensitivity level at BER 10 ⁻⁶ for a 5 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology

P_{SENS10} Receiver sensitivity level at BER 10^{-6} for a 10 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
AWGN	Additive White Gaussian Noise
BER	Bit Error Ratio
BS	Base Station
FDD	Frequency Division Duplexing
PER	Packet Error Ratio
QPSK	Quadrature Phase-Shift Keying
R&TTE	Radio equipment and Telecommunications Terminal Equipment
RF	Radio Frequency
SNR	Signal to Noise Ratio
TDD	Time Division Duplexing
Tx	Transmit, Transmitter
UE	User Equipment
UUT	Unit Under Test

4 Essential requirements specification

With reference to Article 3.2 of Directive 1999/5/EC [1.1] the phenomena in this clause have been identified as relevant to the essential requirements.

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

4.2 Conformance requirements

4.2.1 Introduction

To meet the essential requirement under article 3.2 of the R&TTE Directive [1.1] six essential parameters have been identified. Table 1 provides a cross reference between these six essential parameters and the corresponding nine technical requirements for equipment within the scope of the present document. To fulfil an essential parameter the compliance with all the corresponding technical requirements in table 1 must be verified.

Table 1: Cross references

Essential parameter	Corresponding technical requirements
Spectrum emissions mask	4.2.2 Transmitter Spectrum emissions mask
	4.2.3 Transmitter adjacent channel leakage power ratio
Conducted spurious emissions from the transmitter antenna connector	4.2.4 Transmitter spurious emissions
Output power	4.2.5 Maximum output power tolerance
Intermodulation attenuation of the transmitter	4.2.6 Transmit Intermodulation
Conducted spurious emissions from the receiver antenna connector	4.2.7 Receiver spurious emissions
Impact of interference on receiver performance	4.2.8 Receiver adjacent channel selectivity
	4.2.9 Receiver blocking characteristics
	4.2.10 Receiver intermodulation characteristics

4.2.2 Spectrum emission mask

4.2.2.1 Definition

Spectrum emission mask defines an out of band emission requirement for the transmitter. These out of band emissions are unwanted emissions outside the channel bandwidth resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions.

4.2.2.2 Limits

A base station transmitting on a single RF carrier configured in accordance with the manufacturer's specification shall meet the requirement.

The spectrum emissions measured according to clause 5.4.1 shall not exceed the maximum level specified in tables 2 to 9 for the appropriate BS nominal maximum output power (P_{nom}) and channel widths of 5 MHz and 10 MHz.

4.2.2.2.1 Spectrum emission mask for 5 MHz bandwidth

The spectrum emission mask of the BS applies over the frequency range 0,015 MHz to 10 MHz from the channel edge on both sides of each carrier supported by the BS.

- f_{offset} is the separation between the channel edge and the centre frequency of the measuring filter.

The out-of-channel emission is specified as power level measured over the specified measurement bandwidth. P is the total mean power of the BS carrier set to operate at P_{nom} measured in Eval_BW 1 centred in the 5 MHz channel.

Table 2: Test Requirements for spectrum emission mask values for 5 MHz channels, $P_{nom} \geq 43$ dBm

Frequency offset from channel edge of the measurement filter centre frequency, f_{offset}	Maximum level	Measurement bandwidth
$0,015 \text{ MHz} \leq f_{offset} < 0,215 \text{ MHz}$	-12,5 dBm	30 kHz
$0,215 \text{ MHz} \leq f_{offset} < 1,015 \text{ MHz}$	$-12,5 \text{ dBm} - 15 \left(\frac{f_{offset}}{\text{MHz}} - 0,215 \right) \text{ dB}$	30 kHz
$1,015 \text{ MHz} \leq f_{offset} < 1,5 \text{ MHz}$	-24,5 dBm	30 kHz
$1,5 \text{ MHz} \leq f_{offset} < 5,5 \text{ MHz}$	-11,5 dBm	1 MHz, by aggregation of 30 kHz measurements
$5,5 \text{ MHz} \leq f_{offset} < 10 \text{ MHz}$	-11,5 dBm	1 MHz, by aggregation of 30 kHz measurements