



SLOVENSKI STANDARD
SIST EN 300 422-1 V1.3.2:2008

01-september-2008

9`Y_lfca U[bYfbUnXfi y`1j cgh]b`nUXYj Y`j`nj Yn]`n`fUX]`g_`ja`gdY_lfca`fØFAŁ!
6fYnŷ] b]`a`[_fcZb]`j`Z`Y`_j`Yb`bYa`c`Va`c`1`c`X`&`A`<n`Xc`'`; <n`!`%`r`XY.`HM`b]`bY`
_UfU`h`f]`g`h`_Y`]`b`a`Y`f]`b`Y`a`Y`c`XY

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Wireless
microphones in the 25 MHz to 3 GHz frequency range - Part 1: Technical characteristics
and methods of measurement

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 422-1 V1.3.2:2008](https://standards.iteh.ai/catalog/standards/sist/e924d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008)

<https://standards.iteh.ai/catalog/standards/sist/e924d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008>

Ta slovenski standard je istoveten z: EN 300 422-1 Version 1.3.2

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general
33.160.50	Pribor	Accessories

SIST EN 300 422-1 V1.3.2:2008 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 422-1 V1.3.2:2008

<https://standards.iteh.ai/catalog/standards/sist/e9f24d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008>

ETSI EN 300 422-1 V1.3.2 (2008-03)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Wireless microphones
in the 25 MHz to 3 GHz frequency range;
Part 1: Technical characteristics and
methods of measurement**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 422-1 V1.3.2:2008](https://standards.iteh.ai/catalog/standards/sist/e9f24d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008)

<https://standards.iteh.ai/catalog/standards/sist/e9f24d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008>



Reference

REN/ERM-TG17WG3-008-1

Keywords

audio, radio, radio MIC, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 422-1 V1.3.2:2008

<https://standards.iteh.ai/catalog/standards/sist/e924d68-75ab-4c75-8f7b-6c94a9e71c71/etsi-en-300-422-1-v1-3-2-2008>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	8
2 References	9
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	10
3.1 Definitions	10
3.2 Symbols.....	11
3.3 Abbreviations	11
4 Functional characteristics	12
4.1 Radio microphone descriptions	12
4.2 In ear monitoring.....	12
4.3 Assistive Listening Devices (Aids for the handicapped).....	12
4.4 Tour Guide systems.....	13
5 General	13
5.1 Presentation of equipment for testing purposes	13
5.1.1 Choice of model for testing	14
5.1.2 Definitions of alignment and switching ranges	14
5.1.3 Choice of frequencies	14
5.1.4 Testing of single channel equipment	14
5.1.5 Testing of two channel equipment	14
5.1.6 Testing of multi-channel equipment (more than two channels).....	14
5.1.7 Testing of equipment without a permanent external RF port.....	14
5.1.7.1 Equipment with a permanent internal RF port	15
5.1.7.2 Equipment with a temporary RF port.....	15
5.2 Mechanical and electrical design.....	15
5.2.1 General.....	15
5.2.2 Controls	15
5.2.3 Performance testing with Integral antenna.....	15
5.2.4 Marking (equipment identification)	15
5.3 Interpretation of the measurement results	15
6 Test conditions, power sources and ambient conditions	16
6.1 Normal and extreme test-conditions	16
6.2 Test power source.....	16
6.3 Normal test conditions.....	16
6.3.1 Normal temperature and humidity.....	16
6.3.2 Normal test power source voltage.....	16
6.3.2.1 Mains voltage.....	16
6.3.2.2 Other power sources.....	17
6.4 Extreme test conditions	17
6.4.1 Extreme temperatures	17
6.4.1.1 Procedures for tests at extreme temperatures	17
6.4.2 Extreme test power source voltages.....	17
6.4.2.1 Mains voltage.....	17
6.4.2.2 Other power sources.....	17
7 General conditions.....	17
7.1 Normal test modulation	17
7.1.1 Analogue systems	17
7.1.2 Digital systems.....	18

7.2	Artificial antenna	19
7.3	Test fixture	19
7.4	Test site and general arrangements for radiated measurements.....	19
7.5	Modes of operation of the transmitter	19
7.6	Arrangement for test signals at the input of the transmitter	19
8	Methods of measurement and limits for transmitter parameters	20
8.1	Frequency stability	20
8.1.1	Method of measurement (analogue)	20
8.1.2	Method of measurement (digital).....	20
8.1.3	Limit	20
8.2	Rated output power	20
8.2.1	Method of measurement for equipment without integral antenna	20
8.2.2	Method of measurement for equipment with integral antenna.....	20
8.2.2.1	Method of measurement under normal test conditions	20
8.2.3	Limit	21
8.3	Necessary bandwidth.....	21
8.3.1	Necessary Bandwidth (BN) for Analogue Systems	21
8.3.1.1	Method of Measurement	21
8.3.1.2	Limits	22
8.3.2	Necessary Bandwidth (BN) for Digital Systems	22
8.3.2.1	Method of Measurement	22
8.3.2.2	Limits	24
8.4	Spurious emissions	25
8.4.1	Definition.....	25
8.4.2	Method of measurement	25
8.4.3	Limits.....	26
8.4.4	Measuring receiver	26
9	Receiver.....	26
9.1	Spurious emissions	26
9.1.1	Definitions	26
9.1.2	Method of measuring the power level in a specified load.....	26
9.1.3	Method of measuring the effective radiated power of the enclosure.....	27
9.1.4	Method of measuring the effective radiated power.....	27
9.1.5	Limits.....	27
10	Measurement uncertainty	28
Annex A (normative): Radiated measurement.....		29
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	29
A.1.1	Anechoic Chamber	29
A.1.2	Anechoic Chamber with a conductive ground plane	30
A.1.3	Open Area Test Site (OATS)	31
A.1.4	Test antenna.....	32
A.1.5	Substitution antenna	32
A.1.6	Measuring antenna	33
A.1.7	Stripline arrangement	33
A.1.7.1	General.....	33
A.1.7.2	Description.....	33
A.1.7.3	Calibration	33
A.1.7.4	Mode of use	33
A.2	Guidance on the use of radiation test sites	33
A.2.1	Verification of the test site	33
A.2.2	Preparation of the EUT.....	33
A.2.3	Power supplies to the EUT	34
A.2.4	Volume control setting for analogue speech tests	34
A.2.5	Range length.....	34
A.2.6	Site preparation	35
A.3	Coupling of signals.....	35
A.3.1	General	35

A.3.2	Data Signals.....	35
A.3.3	Speech and analogue signals	35
A.3.3.1	Acoustic coupler description.....	36
A.3.3.2	Calibration	36
A.4	Standard test position	36
A.5	Test fixture	37
A.5.1	Description	37
A.5.2	Calibration.....	37
A.5.3	Mode of use.....	38
Annex B (normative):	Measurement of Necessary Bandwidth (BN) for analogue systems	39
Annex C (informative):	Bibliography.....	40
History		41

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 422-1 V1.3.2:2008

<https://standards.iteh.ai/catalog/standards/sist/e9f24d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been updated in line with the advances in radio microphone technology in the digital field and also with changes generated within CEPT in the former ERMES band for aids for the handicapped.

The present document is part 1 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3 GHz frequency range, as identified below:

- Part 1:** "Technical characteristics and methods of measurement";
Part 2: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates	
Date of adoption of this EN:	14 March 2008
Date of latest announcement of this EN (doa):	30 June 2008
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2008
Date of withdrawal of any conflicting National Standard (dow):	31 December 2008

Introduction

In preparing the present document, much attention has been given to assure a low interference probability, while at the same time allowing maximum flexibility and service to the end-user.

Common technical specifications and harmonized frequency allocations are expected to greatly reduce problems of interference and illegal use.

The present document is a testing standard based on spectrum utilization parameters and does not include performance characteristics that may be required by the user nor requirements for interfacing equipment.

In-ear monitoring systems may be tested to either the present document (< 200 kHz max. occupied bandwidth) or to EN 301 357-1 [4] (< 300 kHz max. occupied bandwidth) with due consideration of power and operating frequency. Consumer radio microphones with 300 kHz occupied bandwidth can also be tested to EN 301 357-1 [4].

Since the initial adoption of I-ETS 300 422 [5] there has been the introduction of further types of equipment into the market - cordless headphones/loudspeakers Low power Band II and consumer in-ear monitoring. These are low power wideband systems that have some characteristics in common with radio microphones but are not compatible with multichannel radio microphones. This equipment is covered by EN 301 357-1 [4].

Additional standards or specifications may be required for equipment intended to interface to the Public Switched Telephone Network (PSTN). This facility may be subjected to regulatory conditions.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 422-1 V1.3.2:2008](https://standards.iteh.ai/catalog/standards/sist/e9f24d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008)

<https://standards.iteh.ai/catalog/standards/sist/e9f24d68-75ab-4c75-8f7b-6c94a9e71c48/sist-en-300-422-1-v1-3-2-2008>

1 Scope

The present document covers the minimum characteristics considered necessary in order to make the best use of the available frequency spectrum for wireless microphones. The present document specifies the minimum performance requirements and the methods of measurement of Assistive Listening Devices, radio microphones and in-ear monitoring systems. It does not necessarily include all the characteristics that may be required by a user, nor does it necessarily represent the optimum performance achievable.

The present document applies to equipment operating on radio frequencies between 25 MHz and 3 GHz (as shown in table 1) using analogue, digital and hybrid (using both analogue and digital) modulation. The present document does not apply to radio microphones or in ear monitoring equipment employing Time Division Multiple Access (TDMA) modulation.

The maximum power recommended for equipment covered by the present document is 250 mW (erp below 1 GHz and eirp above 1 GHz). Equipment above 250 mW should be tested to EN 300 454-1 [6].

The present document also covers radio microphones used in the 863 MHz to 865 MHz band, with a maximum power of 10 mW.

Electromagnetic Compatibility (EMC) requirements are covered by EN 301 489-9 [7].

National regulations on maximum power output will apply or those detailed in the latest version of CEPT/ERC/REC 70-03 [11], annex 10 (see <http://www.erodocdb.dk/>).

Equipment	effective radiated power (erp) or conducted	
	Class 1	Class 2
Radio Microphones	> 250 mW	2 mW
In ear monitoring	> 250 mW	2 mW
Tour guide systems	10 mW	2 mW
Aids for the handicapped	10 mW	2 mW
Radio Microphones 863 MHz to 865 MHz	10 mW	10 mW

The classes of equipment given in the present document are as follows:

- class 1 equipment would normally be considered as a category requiring an operator licence;
- class 2 equipment would be considered in some countries as not requiring an operator licence.

The types of equipment covered by the present document are as follows:

- professional hand held radio microphones;
- professional body worn radio microphones;
- in ear monitoring systems;
- consumer radio microphones;
- tour guide systems; and
- Assistive Listening Devices (Aids for the handicapped).

Table 1: Radiocommunications service frequency bands

	Radiocommunications service frequency bands
Transmit	25 MHz to 3 000 MHz
Receive	25 MHz to 3 000 MHz

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ITU-R Recommendation BS.559-2: "Objective measurement of radio-frequency protection ratios in LF, MF and HF broadcasting".
- [2] IEC 60244-13: "Methods of measurement for radio transmitters; Part 13: Performance characteristics for FM sound broadcasting".
- [3] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM) Uncertainties in the measurement of mobile radio equipment characteristics".

2.2 Informative references

- [4] ETSI EN 301 357-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Cordless audio devices in the range 25 MHz to 2 000 MHz; Part 1: Technical characteristics and test methods".
- [5] ETSI I-ETS 300 422: "Radio Equipment and Systems (RES); Technical characteristics and test methods for wireless microphones in the 25 MHz to 3 GHz frequency range".
- [6] ETSI EN 300 454-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Wide band audio links; Part 1: Technical characteristics and test methods".
- [7] ETSI EN 301 489-9: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 9: Specific conditions for wireless microphones, similar Radio Frequency (RF) audio link equipment, cordless audio and in-ear monitoring devices".
- [8] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).

- [9] ETSI TR 102 273: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [10] ANSI C63.5: "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".
- [11] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

alignment range: See clause 5.1.2.

antenna port: port, where a radio frequency antenna is connected to equipment

audio limiting threshold: audio input or output level at which the transmitter audio limiter action may be said to commence

NOTE: It is specified with any accessible variable gain controls set according to the manufacturer's instructions, with a sinusoidal input signal of 500 Hz.

base station equipment: radio and/or ancillary equipment intended for operation at a fixed location and powered directly or indirectly

EXAMPLE: Via an ac/dc converter or power supply) by the ac mains network, or an extended local dc mains network.

class of emission: set of characteristics of an emission, designated by standard symbols, e.g. type of modulation of the main carrier, modulating signal, type of information to be transmitted, and also, if appropriate, any additional signal characteristics

conducted measurements: measurements that are made using a direct connection to the EUT

confidence level: the probability of the accumulated error of a measurement being within the stated range of uncertainty of measurement

enclosure port: physical boundary of the apparatus through which electromagnetic fields may radiate or impinge

NOTE: In the case of integral antenna equipment, this port is inseparable from the antenna port.

frequency stability: the spontaneous and/or environmentally caused frequency change within a given time interval

integral antenna: antenna, with or without a connector, designed as, and declared as by the manufacturer, an indispensable part of the equipment

integral microphone: microphone, designed as, and declared as by the manufacturer, an indispensable fixed part of the equipment

mean power (of a radio transmitter): average power supplied to the antenna transmission line by a transmitter during an interval of time sufficiently long compared with the lowest frequency encountered in the modulation taken under normal operating conditions

mobile equipment: receiver, transmitter or transmitter/receiver (transceiver) intended for installation and use in a vehicle, and powered by the main battery of the vehicle

modulation schemes:

- analogue modulation: any modulation scheme without discrete constellation points (e.g. FM);
- digital modulation: any modulation scheme with discrete constellation points (e.g. FSK, PSK);
- hybrid systems: will be classified as analogue or digital device depending on the RF- modulation scheme e.g. analogue modulation with digital pre-processing.

necessary bandwidth: for a given class of emission, the width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

out-of-band emission: emission on a frequency or frequencies immediately outside the necessary bandwidth which results from the modulation process, but excluding spurious emissions

port: any connection point on or within the Equipment Under Test (EUT) intended for the connection of cables to or from that equipment

portable equipment: radio and/or ancillary equipment intended for portable (e.g. handheld) operation, powered by its own integral battery

radiated measurements: measurements that involve the absolute measurement of a radiated electromagnetic field

Radio Frequency (RF) port: any connection point on or within the EUT intended for the connection of RF cables

NOTE: RF ports are treated as 50 Ω connection points unless otherwise specified by the manufacturer.

radio receiver: item of electronic equipment designed to receive electromagnetic radio frequency emissions

rated output power: mean power that the transmitter shall deliver at its antenna port under the manufacturer's specified conditions of operation. For the purposes of the present document this shall be quoted as erp below 1 GHz and eirp above 1 GHz.

spurious emissions: emission on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information. Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products but exclude out of band emissions

switching range: See clause 5.1.2.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

λ	wavelength in metres
μF	microFarad
μW	microWatt
Ω	ohm

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ac	alternating current
B	declared channel Bandwidth

NOTE: See table 2.

AF	Audio Frequency
BN	Necessary Bandwidth
dBc	dB relative to the carrier level