

SLOVENSKI STANDARD SIST EN ISO 10211:2008 01-maj-2008

BUXca Yý U. SIST EN ISO 10211-1:1997 SIST EN ISO 10211-1:1997/AC:2002 SIST EN ISO 10211-2:2002

Hcd`chb]'a cghcj]'j 'ghUj VU\ '!'Hcd`chb]'hc_cj]']b'dcj fý]bg_Y'hYa dYfUhi fY'!'DcXfcVb]]nfU i b]`flGC`%\$&%%&\$\$+L

Thermal bridges in building construction - Heat flows and surface temperatures -Detailed calculations (ISO 10211:2007) iTeh STANDARD PREVIEW

Wärmebrücken im Hochbau - Wärmeströme und Oberflächentemperaturen - Detaillierte Berechnungen (ISO 10211:2007)

SIST EN ISO 10211:2008

https://standards.iteh.ai/catalog/standards/sist/64b50ae3-d731-42cd-b80e-Ponts thermiques dans les bâtiments2-dilux.thermiques.et)températures superficielles -Calculs détaillés (ISO 10211:2007)

Ta slovenski standard je istoveten z:

EN ISO 10211:2007

ICS:

91.120.10

SIST EN ISO 10211:2008

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN ISO 10211

December 2007

ICS 91.120.10

Supersedes EN ISO 10211-1:1995, EN ISO 10211-2:2001

English Version

Thermal bridges in building construction - Heat flows and surface temperatures - Detailed calculations (ISO 10211:2007)

Ponts thermiques dans les bâtiments - Flux thermiques et températures superficielles - Calculs détaillés (ISO 10211:2007) Wärmebrücken im Hochbau - Wärmeströme und Oberflächentemperaturen - Detaillierte Berechnungen (ISO 10211:2007)

This European Standard was approved by CEN on 7 December 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovakia, Slovakia, Soweden, Switzerland and United Kingdom.

https://standards.iteh.ai/catalog/standards/sist/64b50ae3-d731-42cd-b80eb7608e2edd2c/sist-en-iso-10211-2008



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

© 2007 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members. Ref. No. EN ISO 10211:2007: E

Contents

Page

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

This document (EN ISO 10211:2007) has been prepared by Technical Committee ISO/TC 163 "Thermal performance and energy use in the built environment" in collaboration with Technical Committee CEN/TC 89 "Thermal performance of buildings and building components", the secretariat of which is held by SIS.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2008, and conflicting national standards shall be withdrawn at the latest by June 2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 10211-1:1995, EN ISO 10211-2:2001.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

iTeh STANDARD PREVIEW

(stan Endorsement-notice)

The text of ISO 10211:2007 has been approved by CEN as a EN ISO 10211:2007 without any modification.

iTeh STANDARD PREVIEW (standards.iteh.ai)

INTERNATIONAL STANDARD

First edition 2007-12-15

Thermal bridges in building construction — Heat flows and surface temperatures — Detailed calculations

Ponts thermiques dans les bâtiments — Flux thermiques et températures superficielles — Calculs détaillés

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 10211:2008 https://standards.iteh.ai/catalog/standards/sist/64b50ae3-d731-42cd-b80eb7608e2edd2c/sist-en-iso-10211-2008



Reference number ISO 10211:2007(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 10211:2008 https://standards.iteh.ai/catalog/standards/sist/64b50ae3-d731-42cd-b80eb7608e2edd2c/sist-en-iso-10211-2008



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forewo	ord	v
Introdu	iction	vi
1	Scope	
2	Normative references	1
3	Terms, definitions, symbols, units and subscripts	
3.1	Terms and definitions	
3.2	Symbols and units	
3.3	Subscripts	
4	•	
5	Modelling of the construction	
5.1 5.2	Dimension systems Rules for modelling	
5.3	Conditions for simplifying the geometrical model	
	Input data	
6 6.1		17
6.2	General	
6.3	Surface resistances (standards.itch.ai) Boundary temperatures	18
6.4	Boundary temperatures	.18
6.5	Thermal conductivity of quasi-homogeneous layers	
6.6 6.7	Equivalent thermal conductivity of air cavities 2008. Determining the temperature in an adjacent unheated room 42cd-b80c-	.18
-	1.7609 and 1.0211 and 1.0211 and 1.0211	
7	Calculation method.	
7.1 7.2	Solution technique Calculation rules	
8	Determination of thermal coupling coefficients and heat flow rate from 3-D calculations	
8.1 8.2	Two boundary temperatures, unpartitioned model Two boundary temperatures, partitioned model	
8.3	More than two boundary temperatures	
9 9.1	Calculations using linear and point thermal transmittances from 3-D calculations Calculation of thermal coupling coefficient	21
9.1	Calculation of linear and point thermal transmittances	
10	Determination of thermal coupling coefficient, heat flow rate and linear thermal	
10		23
10.1	Two boundary temperatures	
10.2	More than two boundary temperatures	
10.3	Determination of the linear thermal transmittance	
10.4 10.5	Determination of the linear thermal transmittance for wall/floor junctions	
	Determination of the external periodic heat transfer coefficient for ground floors	
11	Determination of the temperature at the internal surface	
11.1 11.2	Determination of the temperature at the internal surface from 3-D calculations Determination of the temperature at the internal surface from 2-D calculations	
	•	
12	Input and output data	
12.1 12.2	Input data Output data	
	•	
Annex	A (normative) Validation of calculation methods	30

Annex B (informative) Examples of the determination of the linear and point thermal transmittances	37
Annex C (informative) Determination of values of thermal coupling coefficient and temperature weighting factor for more than two boundary temperatures	40
Bibliography	45

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10211 was prepared by Technical Committee ISO/TC 163, *Thermal performance and energy use in the built environment*, Subcommittee SC 2, *Calculation methods*.

This first edition of ISO 10211 cancels and replaces ISO 10211-11995 and ISO 10211-2:2001, which have been technically revised.

The principal changes are as follows.

- this first edition of ISO 10211 merges the title and general contents of ISO 10211-1:1995 and ISO 10211-2:2001 into a single document tandards/sist/64b50ae3-d731-42cd-b80e-
- Clause 3 indicates that ISO 10211 now uses only temperature factor, and not temperature difference ratio;
- 5.2.2 specifies that cut-off planes are to be located at the larger of 1 m and three times the thickness of the flanking element;
- 5.2.4 contains a revised version of Table 1 to correct error for three-dimensional calculations and to clarify intentions;
- 5.2.7 specifies that acceptable criterion is either on heat flow or on surface temperature; the heat flow criterion has been changed from 2 % to 1 %;
- 6.3 specifies that surface resistance values are to be obtained from ISO 6946 for heat flow calculations and from ISO 13788 for condensation calculations; the contents of Annexes E and G of ISO 10211-1:1995 have been deleted in favour of references to ISO 13788;
- 6.6 specifies that data for air cavities is obtained from ISO 6946, EN 673 or ISO 10077-2; the contents of Annex B of ISO 10211-1:1995 have been deleted in favour of these references;
- 10.4 contains text formerly in ISO 13370, revised to specify that linear thermal transmittance values for wall/floor junctions are the difference between the numerical result and the result from using ISO 13370 (a more consistent definition);
- Annex A contains corrections to results for case 3; the conformity criterion for case 3 has been changed from 2 % of heat flow to 1 %; a new case 4 has been added;
- Annex C contains a corrected procedure;
- all remaining annexes from ISO 10211-1:1995 and ISO 10211-2:2001 have been deleted.

Introduction

Thermal bridges, which in general occur at any junction between building components or where the building structure changes composition, have two consequences compared with those of the unbridged structure:

- a) a change in heat flow rate, and
- b) a change in internal surface temperature.

Although similar calculation procedures are used, the procedures are not identical for the calculation of heat flows and of surface temperatures.

A thermal bridge usually gives rise to three-dimensional or two-dimensional heat flows, which can be precisely determined using detailed numerical calculation methods as described in this International Standard.

In many applications, numerical calculations based on a two-dimensional representation of the heat flows provide results of adequate accuracy, especially when the constructional element is uniform in one direction.

A discussion of other methods for assessing the effect of thermal bridges is provided in ISO 14683.

ISO 10211 was originally published in two parts, dealing with three-dimensional and two-dimensional calculations separately.

(standards.iteh.ai)

Thermal bridges in building construction — Heat flows and surface temperatures — Detailed calculations

1 Scope

This International Standard sets out the specifications for a three-dimensional and a two-dimensional geometrical model of a thermal bridge for the numerical calculation of:

- heat flows, in order to assess the overall heat loss from a building or part of it;

— minimum surface temperatures, in order to assess the risk of surface condensation.

These specifications include the geometrical boundaries and subdivisions of the model, the thermal boundary conditions, and the thermal values and relationships to be used.

This International Standard is based upon the following assumptions:

- all physical properties are independent of temperature; **PREVIEW**
- there are no heat sources within the building element en ai)

This International Standard can also be used for the derivation of linear and point thermal transmittances and of surface temperature factors. https://standards.iteh.ai/catalog/standards/sist/64b50ae3-d731-42cd-b80e-

b7608e2edd2c/sist-en-iso-10211-2008

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6946, Building components and building elements — Thermal resistance and thermal transmittance — Calculation method

ISO 7345, Thermal insulation — Physical quantities and definitions

ISO 13370:2007, Thermal performance of buildings — Heat transfer via the ground — Calculation methods

ISO 13788, Hygrothermal performance of building components and building elements — Internal surface temperature to avoid critical surface humidity and interstitial condensation — Calculation methods

Terms, definitions, symbols, units and subscripts 3

Terms and definitions 3.1

For the purposes of this document, the terms and definitions given in ISO 7345 and the following apply.

3.1.1

thermal bridge

part of the building envelope where the otherwise uniform thermal resistance is significantly changed by full or partial penetration of the building envelope by materials with a different thermal conductivity, and/or a change in thickness of the fabric, and/or a difference between internal and external areas, such as occur at wall/floor/ceiling junctions

3.1.2

linear thermal bridge

thermal bridge with a uniform cross-section along one of the three orthogonal axes

3.1.3

point thermal bridge

localized thermal bridge whose influence can be represented by a point thermal transmittance

3.1.4

three-dimensional geometrical model

3-D geometrical model

geometrical model, deduced from building plans, such that for each of the orthogonal axes the cross-section perpendicular to that axis changes within the boundary of the model REV EW

See Figure 1.

(standards.iteh.ai)

3.1.5

SIST EN ISO 10211:2008

three-dimensional flanking element lards.iteh.ai/catalog/standards/sist/64b50ae3-d731-42cd-b80e-3-D flanking element

part of a 3-D geometrical model which, when considered in isolation, can be represented by a 2-D geometrical model

See Figures 1 and 2.

316

three-dimensional central element

3-D central element

part of a 3-D geometrical model which is not a 3-D flanking element

See Figure 1.

NOTE A central element is represented by a 3-D geometrical model.

3.1.7

two-dimensional geometrical model

2-D geometrical model

geometrical model, deduced from building plans, such that for one of the orthogonal axes the cross-section perpendicular to that axis does not change within the boundaries of the model

See Figure 2.

NOTE A 2-D geometrical model is used for two-dimensional calculations.

3.1.8

two-dimensional flanking element

2-D flanking element

part of a 2-D geometrical model which, when considered in isolation, consists of plane, parallel material layers

3.1.9

two-dimensional central element 2-D central element

part of a 2-D geometrical model which is not a 2-D flanking element

3.1.10

construction planes

planes in the 3-D or 2-D geometrical model which separate different materials, and/or the geometrical model from the remainder of the construction, and/or the flanking elements from the central element

See Figure 3.

3.1.11

cut-off planes

construction planes that are boundaries to the 3-D or 2-D geometrical model by separating the model from the remainder of the construction

See Figure 3.

3.1.12

auxiliary planes

planes which, in addition to the construction planes, divide the geometrical model into a number of cells

3.1.13

guasi-homogeneous layer

layer which consists of two or more materials with different thermal conductivities, but which can be considered as a homogeneous layer with an effective thermal conductivity

See Figure 4.

(standards.iteh.ai)

3.1.14

SIST EN ISO 10211:2008

temperature factor at the internal surface is the standards/sist/64b50ae3-d731-42cd-b80e-

difference between internal surface temperature and external temperature, divided by the difference between internal temperature and external temperature, calculated with a surface resistance R_{si} at the internal surface

3.1.15

temperature weighting factor

weighting factor which states the respective influence of the temperatures of the different thermal environments upon the surface temperature at the point under consideration

3.1.16

external boundary temperature

external air temperature, assuming that the air temperature and the radiant temperature seen by the surface are equal

3.1.17

internal boundary temperature

operative temperature, taken for the purposes of this International Standard as the arithmetic mean value of internal air temperature and mean radiant temperature of all surfaces surrounding the internal environment

3.1.18

thermal coupling coefficient

heat flow rate per temperature difference between two environments which are thermally connected by the construction under consideration