

SLOVENSKI STANDARD SIST ETS 300 232/A1 E1:2003

01-december-2003

DfYbcg']b'a i `h]d`Y_g]fUb'Y'fHAŁE'Cdh] b]'ja Ygb]_]'nUcdfYa c']b'g]ghYa Y'j 'nj Yn]'g g]b\ fcbc'X][]HUbc\]YfUf\]'c fG8 < L

Transmission and Multiplexing (TM); Optical interfaces for equipments and systems relating to the Synchronous Digital Hierarchy (SDH) [ITU-T Recommendation G.957 (1995), modified]

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 232/A1 E1:2003

https://standards.iteh.ai/catalog/standards/sist/laee73d9-a710-4c79-a94f-Ta slovenski standard je istoveten zio/sist-eETS_300a232/41 Edition 1

ICS:

33.040.20 Prenosni sistem Transmission systems
33.180.01 Ùã ¢\{ ã\ /\[1\] [a \] {ā \] a \] a \[1\] a \[2\] E Pibre optic systems in general

SIST ETS 300 232/A1 E1:2003 en

SIST ETS 300 232/A1 E1:2003

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ETS 300 232/A1 E1:2003</u> https://standards.iteh.ai/catalog/standards/sist/1aee73d9-a710-4c79-a94f-8a3f03639319/sist-ets-300-232-a1-e1-2003



AMENDMENT

ETS 300 232

A1

March 1996

Source: ETSI TC-TM Reference: RE/TM-01025

ICS: 33.020

Key words: transmission, optical interfaces, SDH

This amendment A1 modifies the European Telecommunication Standard ETS 300 232 (1993)

iTeh STANDARD PREVIEW
Transmission and Multiplexing (TM);

Optical interfaces for equipments and

systems relating to the Synchronous Digital Hierarchy (SDH)

8a3f03639319/sist-ets-300-232-a1-e1-2003

[ITU-T Recommendation G.957 (1995), modified]

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - Internet: secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

*

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

SIST ETS 300 232/A1 E1:2003

Page 2

ETS 300 232: June 1993/A1: March 1996

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ETS 300 232/A1 E1:2003</u> https://standards.iteh.ai/catalog/standards/sist/1aee73d9-a710-4c79-a94f-8a3f03639319/sist-ets-300-232-a1-e1-2003

Page 3

ETS 300 232: June 1993/A1: March 1996

Foreword

This European Telecommunication Standard (ETS), providing modifications to ITU-T Recommendation G.957 (1995) [1], was prepared by the Transmission and Multiplexing (TM) Technical Committee of the European Telecommunications Standards Institute (ETSI).

The text of ITU-T Recommendation G.957 (1995) [1] has been approved by ETSI as an ETS with the agreed common modifications as given below.

| Transposition dates | | | |
|--|-------------------|--|--|
| Date of adoption of this amendment: | 1 December 1995 | | |
| Date of latest announcement of this amendment (doa): | 30 June 1996 | | |
| Date of latest publication or endorsement of this amendment (dop/e): | 31 September 1996 | | |
| Date of withdrawal of any conflicting National Standard (dow): | 31 September 1996 | | |

Common modifications

1) Insert the following text as the scope for this ETS.

1 Scope

This ETS specifies the optical interfaces for equipment and systems relating to the Synchronous Digital Hierarchy (SDH).

(standards.iteh.ai)

2) Add the following normative references Clause.

SIST ETS 300 232/A1 E1:2003

2 Normative:referencesi/catalog/standards/sist/1aee73d9-a710-4c79-a94f-8a3f03639319/sist-ets-300-232-a1-e1-2003

This ETS incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] ITU-T Recommendation G.957 (1995): "Optical interfaces for equipments and systems relating to the Synchronous Digital Hierarchy".
- 3) Insert the following definitions and abbreviations Clause.

3 Definitions and abbreviations

For the purpose of this ETS the definitions and abbreviations given in ITU-T Recommendation G.957 [1] apply.

4) Add the following "Optical interfaces" Clause.

Page 4

ETS 300 232: June 1993/A1: March 1996

4 Optical interfaces

The optical interfaces are defined in ITU-T Recommendation G.957 [1], together with the following statements and modifications.

As ITU-T Recommendation G.957 [1] was written as a Recommendation, table 1 also gives an indication of the status of each requirement (i.e., normative, informative or not relevant to this ETS).

The normative requirements, as described in table 1, shall only be met when the possibility of transverse compatibility of SDH systems on elementary cable sections is required. In the case of longitudinal compatibility or joint engineering the normative elements, listed in table 1, need not be met.

Table 1: Modifications and statements to ITU-T Recommendation G.957 [1]

| Clause / | Title | Compliance | | |
|-----------|---|-----------------------|--|--|
| subclause | Coome | code N | | |
| 1 | Scope | | | |
| 2 | References | | | |
| 3 | Terms and Definitions | | | |
| 3.1 | Definitions | | | |
| 3.2 | Terms Defined in other Recommendations | | | |
| 4 | Abbreviations | | | |
| 5 | Classification of optical interfaces (including table 1/G.957) | | | |
| 6 | Parameter definitions (including figure 1/G.957) | N | | |
| 6.1 | System operating wavelength range | N | | |
| 6.2.1 | Nominal source type | I | | |
| 6.2.2 | Spectral characteristics | N | | |
| 6.2.3 | Mean launched powerh STANDARD PREVIEW | N | | |
| 6.2.4 | Extinction ratio | N | | |
| 6.2.5 | Eye pattern mask (including figure 2/G:957) | N | | |
| 6.3 | Optical path | N | | |
| 6.3.1 | Attenuation | N | | |
| 6.3.2 | Dispersion SISTEIS 300 232/ATEI:2003 | N | | |
| 6.3.3 | Reflections https://standards.iteh.ai/catalog/standards/sist/laee/3d9-a/10-4c79-a94f- | N | | |
| 6.4 | Receiver 8a3f03639319/sist-ets-300-232-a1-e1-2003 | N | | |
| 6.4.1 | Receiver sensitivity Normative with the exception of the following two sentences (before the final sentence): "Typical margins between a beginning-of-life, nominal temperature receiver and its end-of-life, worst-case counterpart are desired to be in the 2 to 4 dB range. An example of a measurement method for determining ageing effects on receiver sensitivity is given in Appendix II." | N | | |
| 6.4.2 | Receiver overload | N | | |
| 6.4.3 | Receiver reflectance | N | | |
| 6.4.4 | Optical path power penalty | N | | |
| | | | | |
| 7 | Optical parameter values for SDH applications (including tables 2, 3 and 4/G.957) Change in table 4/G.957, columns L-16.1, L-16.2 and L-16.3, the values for transmitter maximum mean launched power from +3 dBm to +2 dBm, and the values for receiver minimum overload from -9 dBm to -8 dBm. Note e) in table 4/G.957 shall be deleted. | N N N N N | | |
| | (continued) | | | |

Page 5

ETS 300 232: June 1993/A1: March 1996

Table 1 (concluded): Modifications and statements to ITU-T Recommendation G.957 [1]

| Clause / | Title | Compliance | |
|--------------|--|---------------|--|
| subclause | | code | |
| 8 | Optical engineering approach | N | |
| 8.1 | Design assumptions | N | |
| 8.2 | Worst-case design approach (including figure 3/G.957) | N | |
| 8.3 | Statistical design approach | | |
| 8.4 | Upgradability considerations | I | |
| Annex A | System operating wavelength considerations: | I | |
| A.1 | Operating wavelength ranges determined by fibre attenuation (including figure A.1/G.957) | I | |
| A.2 | Operating wavelength ranges determined by fibre dispersion (including figures A.2/G.957 and A.3/G.957) Change the third sentence of the paragraph from: "The G.653 fibres can be used also in the 1 310 nm region, for which the maximum dispersion coefficient is comparatively large". to "The G.653 fibres might be used also in the 1 310 nm region, for which the maximum dispersion coefficient is comparatively large". | | |
| Annex B | Measurement of the mask of the eye diagram of the optical transmit signal (including tables B.1/G.957 and B.2/G.957 and figures B.1/G.957 and B.2/G.957) | N | |
| Appendix I | Methods for measuring reflections (including figures I.1/G.957 and I.2/G.957) | I | |
| Appendix II | Possible method for evaluating ageing margin contribution in receiver sensitivity specifications (including figures II.1/G.957, II.2G.957, II.3/G.957 and II.4/G.957) | | |
| Appendix III | Upgradability examples Example 1 Example 2 (including table III.1/G.957 and figure III.1/G.957) | I I N/R | |

iTeh STANDARD PREVIEW

Compliance code to table 1: (standards.iteh.ai)

elements which shall be complied with in order to be able to claim compliance N - Normative:

with this ETS.ETS 300 232/A1 E1:2003

https://standards.iteh.ai/catalog/standards/sist/1aee73d9-a710-4c79-a94f-

I - Informative: sections/subsections present to assist the user in understanding the purpose

and use of this ETS.

N/R - Not Relevant: sections/subsections not being relevant to this ETS. SIST ETS 300 232/A1 E1:2003

Page 6

ETS 300 232: June 1993/A1: March 1996

History

| Document history | | | | | | |
|------------------|---|---------|--------------------------|--|--|--|
| June 1993 | First Edition | | | | | |
| July 1995 | Unified Approval Procedure | UAP 32: | 1995-07-24 to 1995-11-17 | | | |
| March 1996 | Amendment 1 to First Edition of ETS 300 232 | | | | | |
| | | | | | | |
| | | | | | | |

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ETS 300 232/A1 E1:2003</u> https://standards.iteh.ai/catalog/standards/sist/1aee73d9-a710-4c79-a94f-8a3f03639319/sist-ets-300-232-a1-e1-2003

ISBN 2-7437-0495-0 - Amendement 1 Dépôt légal : Mars 1996