

# ETSI ES 282 003 V2.0.0 (2008-05)

---

*ETSI Standard*

## **Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Resource and Admission Control Sub-System (RACS): Functional Architecture**

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/2c03cb00-a3ae-4913-8c31-74a68120733e/etsi-es-282-003-v2.0.0-2008-03>



---

Reference

RES/TISPAN-02036-NGN-R2

---

Keywords

architecture, control, system

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.  
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

# Contents

Intellectual Property Rights .....	9
Foreword.....	9
1 Scope .....	10
2 References .....	10
2.1 Normative references .....	11
2.2 Informative references.....	11
3 Definitions and abbreviations.....	12
3.1 Definitions .....	12
3.2 Abbreviations .....	13
4 General description of RACS.....	15
4.1 High Level functional overview .....	15
4.2 Functional Requirements.....	16
4.2.1 R1 Requirements .....	16
4.2.1.1 Overall.....	16
4.2.1.2 Transport Control Service Requests.....	16
4.2.1.3 Resource Handling .....	17
4.2.1.4 QoS Management.....	18
4.2.1.5 Traffic Handling.....	18
4.2.1.6 Charging and Overload Control .....	18
4.2.2 R2 Requirements .....	18
4.2.2.1 Overall.....	18
4.2.2.2 Resource Handling.....	19
4.2.2.3 QoS Management.....	19
4.2.2.4 e2e QoS Handling .....	19
4.2.2.5 Multicast/Unicast Handling .....	19
4.2.2.6 Topology and Resource Information Retrieval .....	20
4.2.2.7 Network Deployment Scenarios.....	20
4.2.2.8 Charging and Overload Control .....	20
5 RACS functional architecture derivation basis .....	20
5.1 Resource Control for Unicast and Multicast .....	20
5.1.1 Resource control scenarios .....	21
5.1.1.1 Identification of Resources .....	21
5.1.1.2 Multicast Resource Admission Decision Specifics .....	21
5.1.1.3 Resource Admission Decision Prerequisites .....	22
5.1.1.4 Resource Admission Control Approaches .....	22
5.1.1.5 Multicast Resource Admission Control in the Access Network Domain Transport Nodes .....	22
5.2 Charging .....	23
5.3 QoS Management Functions in Fixed Access Networks.....	23
5.4 Resource Control for Service Quality Downgrading.....	25
6 RACS functional architecture definition.....	26
6.1 General .....	26
6.2 Functional elements.....	28
6.2.1 SPDF.....	28
6.2.1.1 SPDF main functions .....	28
6.2.1.2 Summary of SPDF Elementary Functions .....	28
6.2.1.3 Reference points.....	29
6.2.1.4 User profile .....	30
6.2.1.5 Priority .....	30
6.2.1.6 Service request .....	30
6.2.1.7 Coordination function .....	31
6.2.1.8 Charging.....	31
6.2.1.9 Deployment considerations.....	31
6.2.1.10 Overload control .....	32

6.2.1.11	Discovery mechanism .....	32
6.2.2	Generic Resource Admission Control Function .....	32
6.2.2.1	Main functions .....	32
6.2.2.1.1	Specializations of x-RACF .....	33
6.2.2.1.2	Reference points applicable to different specializations of x-RACF .....	33
6.2.2.1.3	Multiple instantiations of x-RACF .....	33
6.2.2.2	Summary of generic Resource Admission Control Function Elementary Functions .....	34
6.2.2.3	A-RACF .....	36
6.2.2.3.1	A-RACF main functions .....	36
6.2.2.3.2	Reference points .....	36
6.2.2.4	C-RACF .....	36
6.2.2.4.1	C-RACF main functions .....	36
6.2.2.5	Admission control process .....	36
6.2.2.5.1	A-RACF .....	36
6.2.2.5.2	C-RACF .....	38
6.2.2.6	Installation of policies .....	38
6.2.2.7	Charging .....	38
6.2.2.8	Abnormal condition handling .....	39
6.2.2.9	Deployment considerations .....	39
6.2.2.10	Overload control .....	39
6.2.2.11	Discovery Mechanism .....	39
6.2.3	BGF .....	39
6.2.3.1	BGF main functions .....	39
6.2.3.2	BGF parameters .....	40
6.2.3.3	Reference points .....	40
6.2.3.4	Addressing latching .....	40
6.2.3.5	Abnormal conditions handling .....	40
6.2.3.6	Overload control .....	40
6.2.4	RCEF .....	40
6.2.4.1	RCEF main functions .....	40
6.2.4.2	Reference points .....	41
6.2.4.3	RCEF parameters .....	41
6.2.5	Application Function (AF) .....	41
6.2.5.1	AF main functions .....	41
6.2.5.2	Reference points .....	42
6.2.5.3	Charging .....	42
6.2.5.4	Abnormal conditions handling .....	42
6.3	RACS reference points .....	42
6.3.1	Rq reference point (SPDF - A-RACF) .....	42
6.3.1.1	Functional requirements .....	42
6.3.1.1.1	Resource management mechanisms .....	43
6.3.1.1.2	Service model .....	43
6.3.1.1.3	Duration semantics .....	44
6.3.1.1.4	Audit and synchronization support .....	44
6.3.1.1.5	Report facilities for unsolicited events .....	44
6.3.1.2	Non-functional requirements .....	44
6.3.1.2.1	Reliability requirements .....	44
6.3.1.2.2	Security requirements .....	44
6.3.1.3	Information exchanged over the Rq Reference Point .....	45
6.3.1.3.1	Resource Reservation Request .....	45
6.3.1.3.2	Resource Modification Request .....	46
6.3.1.3.3	Resource Request/Modification Confirmation .....	47
6.3.1.3.4	Resource Release Request .....	47
6.3.1.3.5	Abort Resource Reservation .....	48
6.3.2	e4 reference point (A-RACF - NASS) .....	48
6.3.3	Ia Reference Point (SPDF - BGF) .....	48
6.3.3.1	Functional Requirements .....	48
6.3.3.1.1	Control of NAT, Hosted NAT traversal and Gating .....	48
6.3.3.1.2	Transport Protocol Type Policing .....	49
6.3.3.1.3	Bandwidth control .....	49
6.3.3.1.4	QoS marking .....	49
6.3.3.1.5	Usage metering and statistics reporting .....	49

6.3.3.1.6	Resource state synchronization .....	49
6.3.3.2	Non-Functional Requirements .....	49
6.3.3.2.1	Reliability requirements .....	49
6.3.3.2.2	Security requirements .....	49
6.3.3.3	Information exchanged over the Ia Reference Point .....	49
6.3.4	Gq' Reference Point (AF - SPDF).....	49
6.3.4.1	Functional Requirements .....	49
6.3.4.2	Non-Functional Requirements .....	50
6.3.4.3	Information exchanged over the Gq' Reference Point.....	50
6.3.5	Ri' Reference Point (SPDF-SPDF inter-domain).....	50
6.3.5.1	Functional Requirements .....	50
6.3.5.1.1	Resource management mechanisms .....	50
6.3.5.1.2	Service model .....	50
6.3.5.1.3	Duration semantics .....	51
6.3.5.1.4	Audit and Synchronization support .....	51
6.3.5.1.5	Report facilities for unsolicited events .....	51
6.3.5.2	Non-Functional Requirements .....	51
6.3.5.2.1	Reliability requirements .....	51
6.3.5.2.2	Security requirements .....	51
6.3.5.3	Information exchanged over the Ri' Reference Point.....	51
6.3.6	Rd' Reference Point (SPDF-SPDF intra-domain).....	51
6.3.7	Re Reference Point (A-RACF - RCEF).....	52
6.3.7.1	Functional Requirements .....	52
6.3.7.1.1	Policy Enforcement Management.....	52
6.3.7.2	Non-functional requirements.....	53
6.3.7.2.1	Reliability requirements .....	53
6.3.7.2.2	Security requirements .....	53
6.3.7.3	Information exchanged over the Re Reference Point.....	53
6.3.8	Rr Reference Point (x-RACF - x-RACF intra-domain).....	53
6.3.8.1	Functional Requirements .....	53
6.3.8.1.1	Overall features .....	53
6.3.8.1.2	Resource management mechanisms .....	54
6.3.8.1.3	Service model.....	54
6.3.8.1.4	Duration semantics .....	55
6.3.8.1.5	Audit and Synchronization support .....	55
6.3.8.1.6	Report facilities for unsolicited events .....	55
6.3.8.2	Non-Functional Requirements .....	55
6.3.8.2.1	Reliability requirements .....	55
6.3.8.2.2	Security requirements .....	55
6.3.8.3	Information exchanged over the Rr Reference Point .....	56
6.3.8.3.1	Resource Reservation Request .....	56
6.3.8.3.2	Resource Modification Request.....	57
6.3.8.3.3	Resource Request/Modification Confirmation .....	58
6.3.8.3.4	Resource Release Request .....	59
6.3.8.3.5	Abort Resource Reservation .....	59
6.3.8.3.6	Resource Allocation Request.....	60
6.3.8.3.7	Resource Allocation Confirmation .....	61
6.4	RACS Flows: Interaction Procedures.....	61
6.4.1	Subscriber Attaches to the Access Network .....	61
6.4.2	Request Resource.....	62
6.4.2.1	Request Resource by using the push mode .....	62
6.4.2.2	Request Resource by using the pull mode.....	63
6.4.2.2.1	Admission control using pull mode when only one x-RACF is involved in managing the same resources.....	63
6.4.2.2.2	Admission control using pull mode when multiple x-RACFs are involved in managing the same resources.....	65
6.4.3	Request Resource Wholesale/Retail Scenario .....	66
6.4.3.1	Request Resource with access to the A-RACF in the retail domain .....	66
6.4.3.2	Request Resource without access to the A-RACF in the retail domain .....	67
6.4.4	Release Resource .....	69
6.4.4.1	Release Resource Request by using the push mode.....	69
6.4.4.2	Release Resource Request by using the pull mode .....	70

6.4.4.2.1	Resource Release using pull mode when only one x-RACF is involved in managing the same resources .....	70
6.4.4.2.2	Resource release using pull mode when multiple x-RACFs are involved in managing the same resources .....	71
6.4.5	Commit Resources procedure .....	72
6.4.6	Resource Modification Request .....	73
6.4.6.1	Resource Modification Request by using the push mode .....	73
6.4.6.2	Resource Modification Request by using the pull mode .....	74
6.4.7	RACS Retrieves Access Profile from NASS .....	75
6.4.8	Subscriber Detaches from the access network .....	75
6.4.9	Abnormal event from the RCEF .....	77
6.4.10	Report of BGF Events .....	77
6.4.11	Indication of a BGF Service Failure (Autonomous Release of BGF) .....	78
<b>Annex A (informative): Binding Information in RACS, NASS and AF .....</b>		<b>80</b>
<b>Annex B (informative): Policy nomenclature for RACS .....</b>		<b>81</b>
B.1	Overview .....	81
B.2	Policy Terminology .....	81
B.2.1	Policy .....	81
B.2.2	Conditions .....	81
B.2.3	Actions .....	81
B.2.4	Events .....	81
B.3	Types of Policy .....	82
B.3.1	Authorization Policy .....	82
B.3.2	Obligation Policy .....	82
B.3.3	Traffic Policy .....	82
B.3.4	Control Policy .....	82
<b>Annex C (informative): Admission control scenarios .....</b>		<b>83</b>
C.1	Example of the handling of Connection Oriented network in the aggregation segment .....	83
<b>Annex D (informative): Network deployment scenarios .....</b>		<b>84</b>
D.1	Resource control scenarios according to distribution of Service-based Policy Decision and Admission Control Functions .....	84
D.1.1	Single NGN operator performs Service-based Policy Decision and Admission Control Functions .....	84
D.1.1.1	Scenario Overview .....	84
D.1.1.2	Business Need .....	84
D.1.1.3	Mapping to TISPAN Architecture: RACS requirements .....	85
D.1.1.4	Technical Analysis .....	85
D.1.1.4.1	Functional Element Analysis .....	85
D.1.1.4.2	Elementary Functions Analysis .....	85
D.1.1.4.3	Reference Point Analysis .....	85
D.1.2	Service-based Policy Decision function handled in two domains .....	85
D.1.2.1	Scenario Overview .....	85
D.1.2.2	Business Need .....	86
D.1.2.3	Mapping to TISPAN Architecture: RACS requirements .....	86
D.1.2.4	Technical Analysis .....	86
D.1.2.4.1	Functional Element Analysis .....	86
D.1.2.4.2	Elementary Functions Analysis .....	86
D.1.2.4.3	Reference Point Analysis .....	86
D.1.3	Service-based Policy Decision and Admission Control functions distributed across two domains .....	87
D.1.3.1	Scenario Overview .....	87
D.1.3.2	Business Need .....	87
D.1.3.3	Mapping to TISPAN Architecture: RACS requirements .....	87
D.1.3.4	Technical Analysis .....	88
D.1.3.4.1	Functional Element Analysis .....	88
D.1.3.4.2	Elementary Functions Analysis .....	88
D.1.3.4.3	Reference Point Analysis .....	88

D.2	Resource control scenarios for Multicast and Unicast .....	88
D.2.1	Independent scenario - Unicast and Multicast admission control are separated.....	88
D.2.1.1	Scenario Overview.....	88
D.2.1.2	Business Need.....	88
D.2.1.3	Mapping to TISPAN Architecture: RACS requirements.....	88
D.2.1.4	Technical Analysis.....	89
D.2.1.4.1	Functional Element Analysis .....	89
D.2.1.4.2	Elementary Functions Analysis.....	89
D.2.1.4.3	Reference Point Analysis .....	89
D.2.2	Synchronized Scenario .....	89
D.2.2.1	Scenario Overview.....	89
D.2.2.2	Business Need.....	89
D.2.2.3	Mapping to TISPAN Architecture: RACS requirements.....	89
D.2.2.4	Technical Analysis.....	89
D.2.2.4.1	Functional Element Analysis .....	89
D.2.2.4.2	Elementary Functions Analysis.....	89
D.2.2.4.3	Reference Point Analysis .....	90
D.2.3	Integrated scenario - Integrated Unicast and Multicast Admission Control.....	90
D.2.3.1	Scenario Overview.....	90
D.2.3.2	Business Need.....	90
D.2.3.3	Mapping to TISPAN Architecture: RACS requirements.....	90
D.2.3.4	Technical Analysis.....	90
D.2.3.4.1	Functional Element Analysis .....	90
D.2.3.4.2	Elementary Functions Analysis.....	90
D.2.3.4.3	Reference Point Analysis .....	90
D.3	Resource control scenario for Metro Network.....	90
D.3.1	Scenario Overview .....	90
D.3.2	Business Need .....	91
D.3.3	Mapping to TISPAN Architecture: RACS requirements .....	91
D.3.4	Technical Analysis .....	91
D.3.4.1	Functional Element Analysis .....	91
D.3.4.2	Elementary Functions Analysis .....	91
D.3.4.3	Reference Point Analysis .....	91
<b>Annex E (informative):</b>	<b>Topology and Resource Management Use Cases and Elementary Functions .....</b>	<b>92</b>
E.1	Topology and Resource Management Use Cases .....	92
E.1.1	Initial RACS Startup .....	92
E.1.2	Network Auto-Discovery .....	92
E.1.3	Managing Network Elements .....	93
E.1.4	Managing Network Topology .....	94
E.1.5	Real-Time Monitoring.....	94
E.1.5.1	Real-time Monitoring (Network Integration) .....	94
E.1.5.2	Real-time Monitoring (OSS Integration) .....	95
E.1.5.3	OSS-based Monitoring .....	95
E.1.6	Just-In-Time Information Pull.....	96
E.2	Topology and Resource Management Elementary Functions.....	97
E.2.1	Provisioning Elementary Function .....	97
E.2.2	Discovery Elementary Function .....	97
E.2.3	Partitioning Elementary Function.....	97
E.2.4	Monitoring Elementary Function .....	97
E.3	Topology and Resource Management Architectural Models.....	97
E.3.1	Centralized Model .....	98
E.3.2	Distributed Model.....	99
<b>Annex F (informative):</b>	<b>Architectural scenarios for supporting unicast and multicast.....</b>	<b>100</b>
F.1	Example of an NGN Access Network Architecture for support of Multicast Resource Admission Control.....	100

F.2	Scenario for supporting multicast in push mode .....	101
F.3	Scenario for supporting multicast with UE requested QoS policy-pull mode .....	102
F.4	Scenario for supporting service authorization control when multicast uses the pull mode.....	102
<b>Annex G (informative): Information flows for supporting unicast and multicast.....</b>		<b>104</b>
G.1	Information flows for supporting unicast .....	104
G.1.1	Unicast stream when a A-RACF is present in the AN .....	104
G.1.2	Unicast stream when a A-RACF is not present in the AN .....	106
G.1.3	Unicast stream when multiple x-RACF instances are present.....	108
G.2	Information flows for enabling and disabling the multicast service .....	110
G.2.1	Control flow for enabling multicast service .....	110
G.2.2	Control flow for disabling multicast service .....	111
G.3	Information flows for supporting multicast in pull mode .....	112
G.3.1	Request Resource in the pull mode .....	112
G.3.2	Multicast stream in pull mode when a A-RACF is present in the AN .....	113
G.3.3	Multicast stream in pull mode when a A-RACF is not present in the AN and the content is in the IP_Edge .....	115
G.3.4	Multicast stream in pull mode when a A-RACF is not present in the AN and the content is in the AN.....	116
G.3.5	Multicast Admission Control for the Access Segment only.....	117
G.3.6	Multicast Admission Control when the maximum bandwidth associated with Multicast service is over-provisioned in the aggregation segment and beyond.....	118
G.4	Information flows for supporting multicast in mixed push and pull mode .....	120
G.4.1	Multicast stream in mixed push and pull mode when a A-RACF is present in the AN .....	120
G.4.2	Multicast stream in mixed push and pull mode when a A-RACF is not present in the AN and the content is in the IP_Edge .....	122
G.4.3	Multicast stream in mixed push and pull mode when a A-RACF is not present in the AN and the content is in the AN .....	124
G.5	Information flows for supporting combined unicast and multicast together with resource handling ..	125
G.5.1	Unicast and multicast services do NOT share resources on the Access Segment .....	125
G.5.2	Unicast and multicast applications share resources on the Access Segment.....	128
G.5.3	Unicast and multicast applications share resources on the Access Segment.....	130
History	.....	135



---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN).

The present document describes the architecture of the Resource and Admission Control Sub-System (RACS) identified in the overall TISPAN NGN architecture.

**ETSI STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/2c03cb00-a3ae-4913-8c31-74a68120733e/etsi-es-282-003-v2.0.0-2008-03>

---

# 1 Scope

The present document describes the functional architecture for the Resource and Admission Control Sub-System (RACS), in TISPAN NGN Release 2, in line with the service requirements described in TS 181 005 [1] and with the QoS Requirements described in TS 181 018 [13]. Moreover, it further indicates high level stage 2 requirements in order to allow the description of its functional operation.

The functional architecture and system description developed in the present document is based on the Release 2 requirements for RACS developed in ES 282 001 [2].

RACS is the TISPAN NGN Sub-System responsible for the implementation of policy-based transport control features, by using procedures and mechanisms that handle resource reservation and admission control for both unicast and multicast traffic in access and core networks.

Besides acting as a Resource Control Framework, RACS also includes support for controlling Network Address Translation (NAT) at the edge of networks and for assisting in remote NAT traversal.

Furthermore, RACS also covers aspects related to the derivation, modification, and installation of traffic policies, end to end quality of service, transport-level charging and overload control.

Hereinafter, the restrictions applicable to some RACS NGN topics for the present document are listed:

- the CPN requirements impact will not be handled;
- only single access and single core domains will be handled;
- the interconnection between domains through the Ri interdomain reference point is limited to scenarios involving only wholesale and roaming between two domains;
- the e2e QoS handling is limited to scenarios involving only wholesale and roaming between two domains;
- other QoS handling aspects, e.g. QoS monitoring and QoS reporting, are covered only in an informative annex;
- the Metro topic aspects are covered in informative annex D; and
- the multicast topic is limited to scenarios involving only a single domain.

---

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
  - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
  - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI TS 181 005: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Services and Capabilities Requirements".
- [2] ETSI ES 282 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture Release 1".
- [3] IETF RFC 3312: "Integration of Resource Management and Session Initiation Protocol (SIP)".
- [4] IETF RFC 2475: "An Architecture for Differentiated Services".
- [5] ETSI ES 282 004: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture; Network Attachment Sub-System (NASS)".
- [6] ETSI TR 180 000: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Terminology".
- [7] ETSI TS 123 107: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Quality of Service (QoS) concept and architecture (3GPP TS 23.107)".
- [8] ITU-T Recommendation Y.1541: "Network performance objectives for IP-based services".
- [9] IETF RFC 3198: "Terminology for Policy-Based Management".
- [10] IETF RFC 2753: "A Framework for Policy-based Admission Control".
- [11] DSL-Forum: "DSL Policy Control Framework (PCF)", Draft Working Text WT-134.
- [12] Damianou, N. et. al.: "The Ponder policy based Management toolkit", August 2002.
- [13] ETSI TS 181 018: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Requirements for QoS in a NGN".
- [14] ETSI TS 187 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN SECURITY (SEC); Requirements".

## 2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [15] ETSI TS 182 027: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IPTV Architecture; IPTV functions supported by the IMS subsystem".

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 180 000 [6] and the following apply:

**access network policies:** policies which are used to make decisions for resource admission control and are designed to derive the traffic policies to be enforced by the A-RACF

NOTE: Access network policies are constructed using Conditions and Actions that are specifically supported by A-RACFs. An example would be a policy which checks the condition that resources are available and the action to reserve the resource.

**Application Function (AF):** functional entity that offers applications the control of IP bearer resources when required

NOTE: The AF is capable of communicating with the RACS to transfer dynamic QoS-related service information.

**application session:** end-to-end user session, which is setup by an AF (using SIP or another protocol) and requires one or more resource reservations to take place

NOTE: An application session may involve one, two or more end users.

**BGF service:** traffic flow function performed by the BGF Functional Entity on media flows and/or the allocation of BGF resources

**DiffServ:** DiffServ networks classify packets into one of a small number of aggregated flows or "classes", based on the DiffServ code point (DSCP) in the packet's IP header

**gate:** operates on a unidirectional flow of packets, i.e. in either the upstream or downstream direction

NOTE: A gate consists of a packet classifier, and a gate status (open/closed). When a gate is open, the packets in the flow are accepted. When a gate is closed, all of the packets in the flow are dropped.

**"Last mile" access network segment:** comprises the functional elements that enable communication between a CPN and an Access Node

**local A-RACF policies:** specific Access network policies that are currently active on an A-RACF (may be a subset of all access network policies)

NOTE: Local A-RACF policies are instances of Access network policies.

**local SPDF policies:** specific Service based policies that are currently active on an SPDF (may be a subset of all service based policies)

NOTE: Local SPDF policies are instances of Service based policies.

**media flow:** uni-directional media stream of a particular type, which is specified by two endpoint identifiers, bandwidth and class of service

**NAT:** generic term for Network Address Translation that includes NAT-PT and NA(P)T

**overbooking admission control:** situation whereby the A-RACF considers that different AF-sessions can reserve the same resources bearing in mind that these resources cannot be committed to more than one AF-session at a time

NOTE: This enables optimal resource management in certain service conditions (e.g. Call Hold, Communication waiting).

**Path-coupled Signaling:** A mode of signaling where the signaling messages follow a path that is tied to the data packets. Signaling messages are routed only through the nodes that are in the data path.

**policy:** set of rules which govern the choices in behaviour of a system and that are comprised of conditions and actions, where conditions are evaluated when triggered by an event

NOTE 1: See annex B for further details.

NOTE 2: The content of policies is outside of the scope of the present document.

**QoS classes:** As defined in ITU-T Recommendation Y.1541 [8] and TS 123 107 [7].

**QoS "Push" model:** model where the RACS "pushes" traffic policies to the transport functions to enforce its policy decisions

NOTE: In this model, the CPN does not itself support native application independent QoS procedures.

**QoS "Pull" model:** model where, upon request from the transport processing functions, the RACS provides traffic policies to the transport processing functions

NOTE: The request from the transport processing functions may itself, for example, be triggered by path-coupled requests coming from user equipment and/or transport network elements.

**resource:** allocatable physical network capability

NOTE 1: A resource can be characterized by a set of parameters, including, but not limited to; memory bandwidth forwarding capacity, scheduling capacity, or other.

NOTE 2: Description and measurement metric of a resource is technology dependent.

**resource identifier:** single key or group of keys used to refer to a resource

NOTE: Resource identifiers can be the same as or derived from Layer-1 keys (e.g. physical port or reference point), Layer-2 keys (e.g. Ethernet VLAN ID), or Layer-3 keys (e.g. IP-address).

**resource reservation session:** set of one or more media flows, which are reserved for a period of time in order to execute an application session

NOTE: A resource reservation session may be uni-directional or bi-directional.

**service based policies:** policies designed to be enforced by an SPDF

NOTE: Service based policies are constructed using Conditions and Actions that are specifically supported by SPDFs. An example would be a policy in which a condition is the type of service required and the action to request the service from either the A-RACF or BGF.

**traffic policies:** policies for which the execution trigger is the arrival of a data packet, and for which the action(s) constitutes some form of processing of this packet before it is forwarded to another device, are known as traffic policies

**xDSL:** type of access network supported by the NGN, based on the different flavours of the xDSL technology, that have their resources controlled by RACS

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACP	Admission Control Process
ACSR	Authorization based on Contents of the Service Request
AF	Application Function
A-RACF	Access-Resource and Admission Control Function
ASP	Application Service Provider
BC	Broadcast Channel
BGF	Border Gateway Function
BGS	Border Gateway Services
BTF	Basic Transport Functions
C-BGF	Core Border Gateway Function
CCI	Charging Correlation Information
CLF	Connectivity session Location and repository Function
CMFE	Coordination of Messages between FEs
CND	Customer Network Device
CoD	Channel on Demand