
Hydrogen fuel — Product specification

Carburant hydrogène — Spécification de produit

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 14687-1:1999](https://standards.iteh.ai/catalog/standards/sist/a3a9c0f5-d97c-4338-910d-10a24ef01771/iso-14687-1-1999)

<https://standards.iteh.ai/catalog/standards/sist/a3a9c0f5-d97c-4338-910d-10a24ef01771/iso-14687-1-1999>



Contents

1 Scope	1
2 Terms and definitions	1
3 Requirements	1
3.1 Classification.....	1
3.2 Applications	2
3.3 Limiting characteristics.....	2
4 Quality verification.....	2
4.1 Quality tests	2
4.2 Production qualification tests	2
4.2.1 General requirements.....	2
4.2.2 Analytical requirements of the production qualification tests.....	2
4.3 Lot acceptance tests	4
4.3.1 Applicability.....	4
4.3.2 Lot definitions	4
4.3.3 Number of samples per lot	4
5 Sampling.....	4
5.1 Sample size.....	4
5.2 Gaseous samples	4
5.3 Liquid samples (vapourized)	5
6 Test methods.....	5
6.1 Parameters of analysis	5
6.2 Hydrogen assay for purity	5
6.3 Hydrogen assay for <i>para</i> -hydrogen	6

iteh STANDARD PREVIEW
(standards.iteh.ai)

ISO 14687-1:1999
<https://standards.iteh.ai/catalog/standards/sist/a5a9c015-d97c-4558-910d-10a24ef01771/iso-14687-1-1999>

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

6.4 Water content 6

6.5 Total hydrocarbon content 6

6.6 Oxygen content..... 6

6.7 Argon, nitrogen, neon and helium contents 7

6.8 Carbon dioxide content..... 7

6.9 Carbon monoxide content 7

6.10 Mercury vapour content 8

6.11 Total sulfur content 8

6.12 Permanent particulates 8

7 Safety and detection..... 8

7.1 Safety 8

7.2 Detection..... 8

Bibliography 9

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 14687-1:1999
<https://standards.iteh.ai/catalog/standards/sist/a3a9c0f5-d97c-4338-910d-10a24ef01771/iso-14687-1-1999>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

This document was prepared by Technical Committee ISO/TC 197, *Hydrogen technologies*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14687-1:1999

<https://standards.iteh.ai/catalog/standards/sist/a3a9c0f5-d97c-4338-910d-10a24ef01771/iso-14687-1-1999>

Hydrogen fuel — Product specification

1 Scope

This International Standard specifies the quality characteristics of hydrogen fuel in order to assure uniformity of the hydrogen product as produced and distributed for utilization in vehicular, appliance or other fuelling applications.

This International Standard applies to all modes of transportation and hydrogen fuelling applications (ground, water, air and space).

2 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

2.1

gaseous hydrogen

GH₂

hydrogen that has been produced to gaseous form, and brought to essentially ambient conditions as an equilibrium mixture of *ortho*-hydrogen and *para*-hydrogen, purified to a minimum mole fraction of 98 %

NOTE The gaseous form is produced typically by any number of methods, including petrochemical, thermochemical, solar, electrolytic or biological processes.

2.2

liquid hydrogen

LH₂

hydrogen that has been liquefied, i.e. brought to a liquid state (*para*)

NOTE Liquefaction may be carried out by either chilling and compression or other means such as the magnetocaloric effect.

2.3

slush hydrogen

SLH₂

hydrogen that is a mixture of solid and LH₂ at the eutectic (triple-point) temperature

3 Requirements

3.1 Classification

Hydrogen fuel shall be classified according to the following types and grade designations:

- | | |
|---------------------------------|------------------|
| a) Type I (grades A, B, and C): | Gaseous hydrogen |
| b) Type II: | Liquid hydrogen |
| c) Type III: | Slush hydrogen |

3.2 Applications

The following information characterizes representative applications of each type and grade of hydrogen fuel. It is noted that suppliers (especially liquid transporters) commonly transport hydrogen of a higher quality than some users may require. The “lower” grades A and B entail less stringent requirements, which may be more suitable for “captive” systems such as vehicle fleets/common fill or on-site hydrogen production/use, such as in industrial complexes.

Type I, grade A	internal combustion engines/fuel cells for transportation; residential/commercial appliances;
Type I, grade B	industrial fuel, for use e.g. in power generation or as a heat energy source;
Type I, grade C	aircraft and space-vehicle ground support systems;
Type II	aircraft and space-vehicle onboard propulsion and electrical energy requirements; land vehicles;
Type III	aircraft and space-vehicle onboard propulsion.

3.3 Limiting characteristics

The Directory of Limiting Characteristics, outlined in Table 1, specifies the requirements applicable to each type and grade of hydrogen fuel. A blank indicates no maximum limiting characteristic. The absence of a maximum limiting characteristic in a listed quality level does not imply that the component is or is not present, but merely indicates that the test need not be performed for compliance with this International Standard.

4 Quality verification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

4.1 Quality tests

The supplier shall assure, by standard practice, the verification of the quality level of hydrogen. The sampling and control procedures described in 4.3.1 and 4.3.2 and in clauses 5 and 6 may be applied. Other control procedures not listed in this International Standard are acceptable if agreed upon between the supplier and the customer.

4.2 Production qualification tests

4.2.1 General requirements

Production qualification tests are a single analysis or a series of analyses that shall be performed on the product to assure the reliability of the production facility to supply hydrogen of the required quality level. This production qualification may be achieved by verifying the analytical records of product from the supplier, or, if required, by performing analyses of representative samples of the product from the facility at appropriate intervals as agreed between the supplier and the customer. Production qualification tests may be performed by the supplier or by a laboratory agreed upon between the supplier and the customer.

4.2.2 Analytical requirements of the production qualification tests

The analytical requirements for the production qualification tests shall include the determination of all limiting characteristics of hydrogen.

Table 1 — Directory of limiting characteristics

Dimensions in micromoles per mole unless otherwise stated

Subclause	Characteristics (assay)	Type I			Type II	Type III
		Grade A	Grade B	Grade C		
6.2	Hydrogen purity (minimum mole fraction, %)	98,0	99,90	99,995	99,995	99,995
6.3	<i>Para</i> -hydrogen (minimum mole fraction, %)	NS	NS	NS	95,0	95,0
	Impurities (maximum content)					
	Total gases			50	50	
6.4	Water (cm ³ /m ³)	NC ^a	NC	b	b	
6.5	Total hydrocarbon	100	NC	b	b	
6.6	Oxygen	a	100	c	c	
6.7	Argon	a		c	c	
6.7	Nitrogen	a	400	b	b	
6.7	Helium			39	39	
6.8	CO ₂			d	d	
6.9	CO	1		d	d	
6.10	Mercury		0,004			
6.11	Sulfur	2,0	10			
6.12	Permanent particulates	f	e	e	e	
	Density					e

NOTE 1 NS: Not specified

NOTE 2 NC: Not to be condensed

^a Combined water, oxygen, nitrogen and argon: max. 1 900 µmol/mol.^b Combined nitrogen, water and hydrocarbon: max. 9 µmol/mol.^c Combined oxygen and argon: max. 1 µmol/mol.^d Total CO₂ and CO: max. 1 µmol/mol.^e To be agreed between supplier and customer.^f The hydrogen shall not contain dust, sand, dirt, gums, oils, or other substances in an amount sufficient to damage the fuelling station equipment or the vehicle (engine) being fuelled.

4.3 Lot acceptance tests

4.3.1 Applicability

Lot acceptance tests are analyses that shall be performed on the hydrogen in the delivery container, or a sample thereof, which is representative of the lot.

4.3.2 Lot definitions

One of the following definitions of the lot shall be used:

- a) no specific quantity, or any quantity of hydrogen agreed upon between the supplier and the customer;
- b) all of the hydrogen supplied, or containers filled, during the contract period;
- c) all of the hydrogen supplied, or containers filled, during a calendar month;
- d) all of the hydrogen supplied, or containers filled, during seven consecutive days;
- e) all of the hydrogen supplied, or containers filled, during a consecutive 24-h period;
- f) all of the hydrogen supplied, or containers filled, during one continuous shift;
- g) all of the hydrogen supplied in one shipment;
- h) all of the hydrogen supplied in one delivery container;
- i) all of the hydrogen in the container(s) filled on one manifold at the same time.

4.3.3 Number of samples per lot

The number of samples per lot shall be in accordance with one of the following:

- a) one sample per lot;
- b) any number of samples agreed upon by the supplier and the customer.

5 Sampling

5.1 Sample size

The quantity of hydrogen in a single sample container shall be sufficient to perform the analyses for the limiting characteristics. If a single sample does not contain a sufficient quantity of hydrogen to perform all of the analyses required to assess the quality level, additional samples from the same lot shall be taken under similar conditions.

5.2 Gaseous samples

Gaseous samples shall be representative of the hydrogen supply. Samples shall be obtained using one of the following procedures.

- a) Fill the sample container and delivery containers at the same time, on the same manifold and in the same manner.
- b) Withdraw a sample from the supply container through a suitable connection into the sample container. No regulator shall be used between the supply and the sample containers (a suitable purge valve may be used).

For safety reasons, the sample container and sampling system shall have a rated service pressure at least equal to the pressure in the supply container.

- c) Connect the container being sampled directly to the analytical equipment using suitable pressure regulation to prevent over-pressurizing this equipment.
- d) Select a representative container from the containers filled in the lot.

5.3 Liquid samples (vaporized)

Vaporized liquid samples shall be representative of the liquid hydrogen supply. Samples shall be obtained using one of the following procedures:

- a) by vaporizing, in the sampling line, liquid hydrogen from the supply container;
- b) by flowing liquid hydrogen from the supply container into or through a suitable container in which a representative sample is collected and then vaporized.

6 Test methods

6.1 Parameters of analysis

The parameters for analytical techniques contained in this clause are:

- a) mole fraction, expressed as a percentage (%);
- b) number of cubic centimetres per cubic metre (cm^3/m^3) [water only];

NOTE 1 Contents in 6.1 a) and b) represent 10^{-6} .

- c) number of micromoles per mole ($\mu\text{mol}/\text{mol}$).

Total hydrocarbon content "as methane" for the purpose of this International Standard is defined as the single carbon atom equivalent. <https://standards.iteh.ai/catalog/standards/sist/a3a9c0f5-d97c-4338-910d-10a24ef01771/iso-14687-1-1999>

Calibration gas standards which contain the applicable gaseous components may be needed to calibrate the analytical instruments used to determine the limiting characteristics of hydrogen.

If required by the customer, the accuracy of the measuring equipment used in preparing these standards shall be traceable to an established institute for standards.

Analytical equipment shall be operated in accordance with the manufacturer's instructions.

Analytical methods not listed in this International Standard are acceptable if agreed upon between supplier and customer.

6.2 Hydrogen assay for purity

The hydrogen concentration shall be determined by one of the following procedures.

- a) Use a thermal conductivity analyser which measures the aggregate impurities which have thermal conductivities different from hydrogen. The analyser shall be calibrated at appropriate intervals using calibration gas standards. The range of the analyser shall be no greater than ten times the difference between the specified minimum hydrogen concentration, in percent, and 100 %. Thus for a 99,5 % minimum hydrogen concentration, the analyser shall have a maximum range of 5 % impurity or from 95 % to 100 % hydrogen.
- b) Use a volumetric or manometric gas analysis apparatus.
- c) Determine the amount of aggregate impurities using the methods in the following subclauses of this International Standard. The hydrogen concentration is the value obtained when this amount, expressed as percent mole fraction, is subtracted from 100 %.
- d) Use any suitable chromatographic system which effectively quantifies specific impurities [see 6.7 a)].