

SLOVENSKI STANDARD SIST EN 301 489-17 V1.3.2:2008

01-september-2008

Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) - Standard elektromagnetne združljivosti (EMC) za radijsko opremo - 17. del: Posebni pogoji za širokopasovne prenosne sisteme na frekvenci 2,4 GHz, visokozmogljivo opremo RLAN na frekvenci 5 GHz in širokopasovne sisteme za prenos podatkov na frekvenci 5,8 GHz

Electromagnetic compatibility and Radio spectrum Matters (ERM) - ElectroMagnetic Compatibility (EMC) standard for radio equipment - Part 17: Specific conditions for 2,4 GHz wideband transmission systems, 5 GHz high performance RLAN equipment and 5,8 GHz Broadband Data Transmitting Systems

SIST EN 301 489-17 V1.3.2:2008 https://standards.iteh.ai/catalog/standards/sist/9c38764e-7a0c-47ae-a702-65813726578c/sist-en-301-489-17-v1-3-2-2008

Ta slovenski standard je istoveten z: EN 301 489-17 Version 1.3.2

ICS:

33.060.01 Radijske komunikacije na Radiocommunications in

splošno general

33.100.01 Elektromagnetna združljivost Electromagnetic compatibility

na splošno in general

SIST EN 301 489-17 V1.3.2:2008 en

SIST EN 301 489-17 V1.3.2:2008

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 489-17 V1.3.2:2008 https://standards.iteh.ai/catalog/standards/sist/9c38764e-7a0c-47ae-a702-65813726578c/sist-en-301-489-17-v1-3-2-2008

ETSI EN 301 489-17 V1.3.2 (2008-04)

Harmonized European Standard (Telecommunications series)

Electromagnetic compatibility
and Radio spectrum Matters (ERM);
ElectroMagnetic Compatibility (EMC)
standard for radio equipment;
Part 17: Specific conditions for 2,4 GHz
wideband transmission systems,
5 GHz high performance RLAN equipment and
5,8 GHz Broadband Data Transmitting Systems

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 489-17 V1.3,2:2008 https://standards.iteh.ai/catalog/standards/sist/9c38764e-7a0c-47ae-a702-65813726578c/sist-en-301-489-17-v1-3-2-2008



2

Reference

REN/ERM-EMC-248-17

Keywords

EMC, HIPERLAN, LAN, radio, regulation

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la

Teh Sous-Préfecture de Grasse (06) N° 7803/88/ IEW

(standards.iteh.ai)

SIST EN 301 489-17 V1.3.2:2008

https://standards.iteh.ai/catalog/standards/sist/9c38764e-7a0c-47ae-a702-

6581372657**Important notice**7-v1-3-2-2008

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP[™] is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intell	ectual Property Rights	5
Forev	vord	5
1	Scope	<i>6</i>
2	References	6
2.1	Normative references	
2.2	Informative references.	
3	Definitions and abbreviations	
3.1	Definitions	
3.2	Abbreviations	8
4	Test conditions	8
4.1	General	8
4.2	Arrangements for test signals	
4.2.1	Arrangements for test signals at the input of transmitters	
4.2.2	Arrangements for test signals at the output of transmitters	
4.2.3	Arrangements for test signals at the input of receivers	
4.2.4	Arrangements for test signals at the output of receivers	
4.2.5	Arrangements for testing transmitter and receiver together (as a system)	و
4.3	Exclusion bands	
4.3.1 4.3.2	2,45 GHz RLAN equipment 5 GHz RLAN equipment 5 ANDARD PREVIEW	٠٠
4.3.3	5,8 GHz Broadband data transmitting systems	 ن
4.4	Narrow band responses on receivers or receivers which are part of transceivers.	
4.5	Normal test modulation	
_		
5	Performance assessment SIST EN 301 489-17 V1.3.2:2008 General https://standards.iteh.a/catalog/standards/sist/9c38764e-7a0c-47ae-a702-	10
5.1	General	I(
5.2 5.2.1	Arrangements for the assessment of host dependant equipment and plug-in cards	
5.2.1	Alternative B: use of a test jig or host	
5.3	Assessment procedures.	
5.4	Ancillary equipment	
5.5	Equipment classification	
	• •	
6	Performance criteria	
6.1 6.2	General performance criteria	
6.3	Performance table Performance criteria for Continuous phenomena applied to Transmitters (CT)	
6.4	Performance criteria for Transient phenomena applied to Transmitters (CT)	
6.5	Performance criteria for Continuous phenomena applied to Receivers (CR)	
6.6	Performance criteria for Transient phenomena applied to Receivers (TR)	
7	Applicability overview	
7.1 7.1.1	EmissionGeneral	
7.1.1	Special conditions	
7.1.2	Immunity	
7.2.1	General	
7.2.2	Special conditions	
	•	
Anne	ex A (informative): Examples of radio equipment in the scope of the present document	14
A.1	Wideband transmission systems operating in the 2,4 GHz ISM band using spread spectrum	
	techniques	14
A.2	Radio Local Area Networks equipment operating in the 5 GHz frequency band	1/
	Tadio 2004 Thou field office equipment operating in the 5 of 2 frequency build	

A.3	Broadband Data Trans	mitting Systems operating in the band 5 725 MHz to 5 875 MHz	14
Anne	x B (informative):	The EN title in the official languages	15
Anne	x C (informative):	Bibliography	17
Histor	rv		18

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 301 489-17 V1.3.2:2008</u> https://standards.iteh.ai/catalog/standards/sist/9c38764e-7a0c-47ae-a702-65813726578c/sist-en-301-489-17-v1-3-2-2008

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [3] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Council Directive 1999/5/EC [2] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is part 17 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

SIST EN 301 489-17 V1.3.2:2008

https://standards.inland.crandsposition.dates/a0c-47ae-a702-					
Date of adoption of this EN:	11 April 2008				
Date of latest announcement of this EN (doa):	31 July 2008				
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2009				
Date of withdrawal of any conflicting National Standard (dow):	31 July 2010				

1 Scope

The present document, together with EN 301 489-1 [1], covers the assessment of the 2,4 GHz wideband transmission systems and 5 GHz high performance RLAN (including HIPERLAN 1 and 2 and other) including Broadband Data Transmitting System equipment, in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of the radio equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment and performance criteria for wideband data communication systems.

Examples of types of wide band data communications systems covered by the present document are given in annex A.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and EN 301 489-1 [1], the provisions of the present document take precedence.

The environmental classification and the emission and immunity requirements used in the present document are as stated in EN 301 489-1 [1], except for any special conditions included in the present document.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply 21. 21)
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:

 https://standards.iteh.ai/catalog/standards/sist/9c38764e-7a0c-47ae-a702-
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at http://docbox.etsi.org/Reference.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

[1] ETSI EN 301 489-1 (V1.7.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
 Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
 ETSI EN 300 328-1: "Electromagnetic compatibility and Radio Spectrum Matters (ERM); Wideband Transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using spread spectrum modulation techniques; Part 1: Technical characteristics and test conditions".
 ETSI EN 301 893: "Broadband Radio Access Networks (BRAN); 5 GHz high performance RLAN; Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".
- [6] ETSI EN 302 502: "Broadband Radio Access Networks (BRAN); 5,8 GHz fixed broadband data transmitting systems; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

3 Definitions and abbreviations REVIEW

3.1 Definitions

SIST EN 301 489-17 VL 3-2-2008 EN 201 400 1 111

(standards.iteh.ai)

For the purposes of the present document, the terms and definitions given in EN 301 489-1 [1], clause 3 and the following apply:

65813726578c/sist-en-301-489-17-v1-3-2-2008

Equipment Under Test (EUT): equipment under test and subject to the performance requirements of the present document

fixed station: equipment intended for use in a fixed location and fitted with one or more antennas

NOTE: The equipment may be fitted with either antenna socket(s) or integral antenna(s) or both.

hand-portable station: equipment normally used on a stand-alone basis and to be carried by a person

NOTE: The equipment may be fitted with one or more antennas. The equipment may be fitted with either antenna socket(s) or integral antenna(s) or both.

host: any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

plug-in radio device: equipment, including slide-in radio cards, intended to be used with or within a variety of host systems, using their control functions and power supply

stand-alone radio equipment: equipment that is intended primarily as communications equipment and that is normally used on a stand-alone basis

8

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK ACKnowledgement

ARQ Automatic Retransmission reQuest

CR Continuous phenomena applied to Receivers
CT Continuous phenomena applied to Transmitters

EMC ElectroMagnetic Compatibility

EUT Equipment Under Test

HIPERLAN HIgh PErformance Radio Local Area Network

MUS Maximum Usable Sensitivity
NACK Not ACKnowledgement

RF Radio Frequency

TR Transient phenomena applied to Receivers
TT Transient phenomena applied to Transmitters

4 Test conditions

4.1 General

For the purposes of the present document, the test conditions of EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for wideband data communications systems are specified in clauses 4.2 to 4.5.

The radio equipment may take forms which may require special software and/or test fixtures. Equipment which requires connection to a host equipment to function shall use the test configuration as defined by the manufacturer. In all cases the EUT shall be exercised in a manner representative of normal intended use.

SIST EN 301 489-17 V1.3.2:2008

4.2 Arrangements of for a test signals 1/9c38764e-7a0c-47ae-a702-

65813726578c/sist-en-301-489-17-v1-3-2-2008

The provisions of EN 301 489-1 [1], clause 4.2 shall apply.

4.2.1 Arrangements for test signals at the input of transmitters

The provisions of EN 301 489-1 [1], clause 4.2.1 shall apply with the following modifications.

The wanted signals and/or controls required to establish a communications link shall be defined by the manufacturer. The transmitter shall be operated at maximum rated power.

4.2.2 Arrangements for test signals at the output of transmitters

The provisions of EN 301 489-1 [1], clause 4.2.2 shall apply with the following modifications.

The manufacturer may provide a suitable companion receiver that can be used to receive messages or to set up a communication link.

4.2.3 Arrangements for test signals at the input of receivers

The provisions of EN 301 489-1 [1], clause 4.2.3 shall apply with the following modifications.

The wanted signals required to establish a communications link shall be defined by the manufacturer.

The level of the wanted signal at the input of the receiver shall be at least 30 dB above the declared Maximum Usable Sensitivity (MUS).

4.2.4 Arrangements for test signals at the output of receivers

The measuring equipment for the output signal from the receiver under test shall be located outside the test environment.

It shall be possible to assess the performance of the equipment by appropriately monitoring the receiver output.

If the receiver has an output connector or port providing the wanted output signal, then this port shall be used via a cable, consistent with the standard cable used in normal operation, connected to the external measuring equipment outside the test environment. The measuring equipment may be supplied by the manufacturer.

Precautions shall be taken to ensure that any effect on the test due to the coupling means is minimized.

The manufacturer may provide a suitable companion transmitter that can be used to transmit messages or to set up a communication link.

4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of EN 301 489-1 [1], clause 4.2.5 shall apply.

The manufacturer may provide a suitable companion transceiver or transmitter and receiver that can be used to send and receive messages or to set up a communication link.

Both the EUT and the companion equipment shall transmit the normal test modulation. Further, the output of the radio equipment under test shall be monitored by the test system.

4.3 Exclusion bands (standards.iteh.ai)

The frequencies on which the transmitter part of the EUT is intended to operate shall be excluded from conducted and radiated emission measurements when performed in transmit mode of operation.

There shall be no frequency exclusion band applied to emission measurements of the receiver part of transceivers or the stand alone receiver under test, and/or associated ancillary equipment.

The emission measurement and immunity test exclusions are referred to as "exclusion bands" and are defined in the clauses 4.3.1, 4.3.2 and 4.3.3 of the present document.

4.3.1 2,45 GHz RLAN equipment

The exclusion band for the transmitter and/or receiver part of the 2,45 GHz RLAN equipment under test shall extend from $2\,280$ MHz to $2\,607,675$ MHz.

4.3.2 5 GHz RLAN equipment

The exclusion band for the transmitter part of the 5 GHz RLAN equipment under test shall extend from 4 892,5 MHz to 6 011,25 MHz.

No exclusion bands applies to receive only products and the receiver part of products covered by the present document.

4.3.3 5,8 GHz Broadband data transmitting systems

The exclusion band for the transmitter part of the 5,8 GHz Broadband data transmitting systems under test shall extend from 5 438,75 MHz to 6 168,75 MHz.

No exclusion bands applies to receive only products and the receiver part of products covered by the present document.