



# SLOVENSKI STANDARD

## SIST ISO 14592-2:2010

01-september-2010

---

**Kakovost vode - Vrednotenje aerobne biorazgradljivosti organskih spojin pri nizkih koncentracijah - 2. del: Pretočni rečni model s pritrjeno biomaso**

Water quality - Evaluation of the aerobic biodegradability of organic compounds at low concentrations - Part 2: Continuous flow river model with attached biomass

### iTeh STANDARD PREVIEW

Qualité de l'eau - Évaluation de la biodégradabilité aérobie des composés organiques présents en faibles concentrations - Partie 2: Modèle de cours d'eau à courant continu avec biomasse associée

[SIST ISO 14592-2:2010](https://standards.iteh.ai/catalog/standards/sist/35a518b-68e3-4195-9610-4b7829fb9e7/sist-iso-14592-2-2010)

[https://standards.iteh.ai/catalog/standards/sist/35a518b-68e3-4195-9610-](https://standards.iteh.ai/catalog/standards/sist/35a518b-68e3-4195-9610-4b7829fb9e7/sist-iso-14592-2-2010)

[4b7829fb9e7/sist-iso-14592-2-2010](https://standards.iteh.ai/catalog/standards/sist/35a518b-68e3-4195-9610-4b7829fb9e7/sist-iso-14592-2-2010)

**Ta slovenski standard je istoveten z: ISO 14592-2:2002**

---

#### **ICS:**

13.060.10	Voda iz naravnih virov	Water of natural resources
13.060.70	Preiskava bioloških lastnosti vode	Examination of biological properties of water

**SIST ISO 14592-2:2010**

**en,fr**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 14592-2:2010

<https://standards.iteh.ai/catalog/standards/sist/3f5a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010>

INTERNATIONAL  
STANDARD

ISO  
14592-2

First edition  
2002-11-15

Corrected version  
2003-08-01

---

---

**Water quality — Evaluation of the aerobic  
biodegradability of organic compounds at  
low concentrations —**

Part 2:

**Continuous flow river model with attached  
biomass**

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

*Qualité de l'eau — Évaluation de la biodégradabilité aérobie des composés  
organiques présents en faibles concentrations —*

*Partie 2: Modèle de cours d'eau à courant continu avec biomasse associée*

<https://standards.iteh.ai/catalog/standards/sist/3f5a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010>



Reference number  
ISO 14592-2:2002(E)

© ISO 2002

**ISO 14592-2:2002(E)****PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 14592-2:2010

<https://standards.iteh.ai/catalog/standards/sist/3f5a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010>

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Printed in Switzerland

## Contents

	Page
Foreword .....	iv
Introduction.....	v
1 Scope.....	1
2 Normative reference.....	1
3 Terms, definitions and symbols .....	2
4 Principle .....	4
5 Reagents and media .....	4
6 Apparatus.....	5
7 Test environment .....	6
8 Procedure.....	7
9 Calculation .....	9
10 Validity of the test .....	12
11 Test report.....	12
Annex A (informative) Example of expression of results.....	13
Bibliography.....	16

[SIST ISO 14592-2:2010](https://standards.iteh.ai/catalog/standards/sist/35a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010)  
<https://standards.iteh.ai/catalog/standards/sist/35a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010>

## ISO 14592-2:2002(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 14592 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14592-2 was prepared by Technical Committee ISO/TC 147, *Water quality*, Subcommittee SC 5, *Biological methods*.

ISO 14592 consists of the following parts, under the general title *Water quality — Evaluation of the aerobic biodegradability of organic compounds at low concentrations*:

- *Part 1: Shake-flask batch test with surface water or surface water/sediment suspensions*
- *Part 2: Continuous flow river model with attached biomass*

This corrected version of ISO 14592-2:2002 incorporates corrections to

- the term numbers 3.1.10 and 3.1.11;
- the reference given in the last line of 5.2;
- the reference given in the second line of 6.1.3;
- the reference given in the second line of 6.1.5;
- the reference given in the first line of 8.1.1;
- the reference given in the second line of 8.1.2;
- the reference given in the second line of the second paragraph of 8.2;
- the reference given in the third line of the second paragraph of 8.3
- the reference given in the fifth line of the first paragraph of 8.4;
- the reference given in the fourth line of the second paragraph of 8.4;
- the reference given in the second line of the first paragraph of 9.1;
- the reference given in the third line of the note under 9.2.

## Introduction

This International Standard consists of two parts. Part 1 describes a die-away batch test for either surface water with or without added sediment in suspension simulating either a pelagic aquatic environment or a water-to-sediment interface. Part 2 describes a continuous flow system simulating a river with biomass attached to stationary surfaces.

The test has been specifically designed to provide information on the biodegradation behaviour and kinetics for test compounds at low concentrations, i.e. sufficiently low to simulate the biodegradation kinetics expected to occur in natural environmental systems.

This method is designed to determine the primary biodegradation in a continuously operating test system simulating a river. Before conducting this test, it is necessary to have information on the biodegradability behaviour of the test compound (e.g. at usual test concentrations in standard biodegradation tests) and, if possible, on abiotic degradability or elimination (e.g. photolysis, adsorption or stripping) under conditions which are comparable to those of the river model and relevant physico-chemical data (e.g. water-solubility, adsorption coefficient  $K_{OC}$ ) so as to properly plan the experiment and interpret the results.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 14592-2:2010](https://standards.iteh.ai/catalog/standards/sist/3f5a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/3f5a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 14592-2:2010

<https://standards.iteh.ai/catalog/standards/sist/3f5a518b-68e3-4195-9610-4b7829fbf9e7/sist-iso-14592-2-2010>



# Water quality — Evaluation of the aerobic biodegradability of organic compounds at low concentrations —

## Part 2: Continuous flow river model with attached biomass

**WARNING AND SAFETY PRECAUTIONS** — Activated sludge, sewage and effluent contain potentially pathogenic organisms. Therefore appropriate precautions should be taken when handling them. Toxic and dangerous test compounds and those whose properties are unknown should be handled with care. Radiolabelled compounds, if used, should be handled respecting existing rules and legislation.

### 1 Scope

This part of ISO 14592 specifies a method for evaluating the biodegradability of organic test compounds by aerobic microorganisms in natural waters by means of a continuous flow river model with attached biomass.

This part of ISO 14592 is applicable to organic test compounds present in lower concentrations than those of natural carbon substrates also present in the system. Under these conditions, the test compounds serve as a secondary substrate and the kinetics for biodegradation would be expected to be first order ("non-growth" kinetics).

This part of ISO 14592 is applicable to organic test compounds, which under the conditions of the test and at the chosen test concentration, are:

- water soluble;
- quantitatively detectable with appropriate analytical methods or available in radiolabelled form;
- non-volatile from aqueous solution (e.g. Henry's law constant  $< 1 \text{ Pa}\cdot\text{m}^3/\text{mole}$ );
- not significantly adsorbed;
- not photolyzed;
- not inhibitory to the microorganisms of the test system.

The test is not recommended for use as proof of ultimate biodegradability (mineralization) which is better assessed using other standardized tests (see ISO/TR 15462).

### 2 Normative reference

The following normative document contains provisions which, through reference in this text, constitute provisions of this part of ISO 14592. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 14592 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/TR 15462, *Water quality — Selection of tests for biodegradability*

## ISO 14592-2:2002(E)

### 3 Terms, definitions and symbols

#### 3.1 Terms and definitions

For the purposes of this part of ISO 14592, the following terms and definitions apply.

##### 3.1.1

##### **ultimate aerobic biodegradation**

breakdown of a chemical compound or organic matter by microorganisms, in the presence of oxygen, to carbon dioxide, water and mineral salts of any other elements present (mineralization) and the production of new biomass

NOTE Total mineralization may be different from ultimate aerobic biodegradation in that total mineralization includes secondary mineralization of biosynthesis products. The kinetics may therefore deviate from first-order kinetics in particular towards the end of the experiment. In this part of ISO 14592, primary aerobic biodegradation is determined when using substance specific analysis and total mineralization when using radiolabelled compounds.

##### 3.1.2

##### **primary biodegradation**

structural change (transformation) of a chemical compound by microorganisms resulting in the loss of a specific property of that compound

##### 3.1.3

##### **biochemical oxygen demand**

##### **BOD**

mass concentration of dissolved oxygen consumed under specified conditions by the aerobic biological oxidation of a chemical compound or organic matter in water

NOTE It is expressed in this case as milligrams of oxygen uptake per milligram or gram of test compound.

##### 3.1.4

##### **dissolved organic carbon**

##### **DOC**

part of the organic carbon in a sample of water which cannot be removed by specified phase separation

NOTE Phase separation may be obtained, for example, by centrifugation of the water sample at 40 000 m/s<sup>2</sup> for 15 min or by membrane-filtration using membranes with pores of 0,45 µm diameter.

##### 3.1.5

##### **lag phase**

$t_{lag}$

(continuous flow-through test system) time from the start of a test until significant biodegradation (about 10 % of the maximum level) can be measured

NOTE Lag phase is expressed in days.

##### 3.1.6

##### **degree of biodegradation**

(continuous flow-through test system) mean biodegraded amount of a test compound, calculated from the measured concentrations in the inlet and the outlet of the system

NOTE The degree of biodegradation is determined when no further degradation can be measured and is expressed as a percentage.

##### 3.1.7

##### **steady state**

(continuous flow-through test system with constant input) state where the concentration of a test compound remains constant at any place and time

**3.1.8****primary substrate**

major carbon and energy source which is essential for growth or maintenance of microorganisms

**3.1.9****secondary substrate**

substrate component present at such low concentrations, that by its degradation, only insignificant amounts of carbon and energy are supplied to the competent microorganisms, as compared to the carbon and energy supplied by their degradation of primary substrates

**3.1.10****degradation rate constant**

$k$   
rate constant for first order or pseudo first order kinetics which indicates the rate at which degradation processes

NOTE 1 The degradation rate constant is expressed as the inverse of days ( $d^{-1}$ ).

NOTE 2 For a batch experiment,  $k$  is estimated from the initial part of the degradation curve obtained after the end of the lag phase. For a continuously operating test system,  $k$  can be estimated from a mass balance for the reactor using data collected under steady-state conditions.

**3.1.11****degradation half-life**

$T_{1/2}$   
characteristic of the rate of a first-order reaction and corresponds to the time interval necessary for the concentration to decrease by a factor of two

NOTE 1 The degradation half-life is expressed in days (d).

NOTE 2 The degradation half-life and the degradation rate constant are related by the following equation:

$$T_{1/2} = \ln 2/k$$

NOTE 3 The degradation half-life  $T_{1/2}$  for first-order reactions should not be confused with the half-life time,  $T_{50}$ , which is often used to describe the environmental behaviour of pesticides and which is simply the time to reach 50 % of total biodegradation. The half-life time  $T_{50}$  may be derived from degradation curves without making assumptions about the kinetics.

**3.2 Symbols**

Symbol	Description	Units
$b$	width of a single tray	metres (m)
$c^1)$	residual molar concentration of the test compound	micromole per litre ( $\mu\text{mol/l}$ )
$c_0$	initial molar concentration of the test compound in the inlet of tray 1	micromole per litre ( $\mu\text{mol/l}$ )
$c_n$	final molar concentration of the test compound in the outlet of tray $n$	micromole per litre ( $\mu\text{mol/l}$ )
$D_s$	degree of biodegradation	percentage

1) In ISO 31-8-13:1992,  $c$  is defined as the symbol for "molar concentration", expressed in moles per litre and in ISO 31-8-11.2:1992,  $\rho$  is defined as the symbol for "mass concentration", expressed in kilograms per litre. Note that in ISO 31, "concentration" of the test compound in solution is expressed in two ways:

- " $\rho$ " refers to the mass of the test compound per unit volume;
- " $c$ " is specifically used to mean the number of moles of the test compound per unit volume.