



# SLOVENSKI STANDARD SIST EN 62386-102:2015

01-junij-2015

Nadomešča:  
SIST EN 62386-102:2009

---

**Digitalni naslovljivi vmesnik za razsvetljavo - 102. del: Splošne zahteve - Krmilje  
(IEC 62386-102:2014)**

Digital addressable lighting interface - Part 102: General requirements - Control gear

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Ta slovenski standard je istoveten z: [SIST EN 62386-102:2015](https://standards.iteh.ai/catalog/standards/sist/en-62386-102-2015) **EN 62386-102:2014**  
[5d41f01b8a0f/sist-en-62386-102-2015](https://standards.iteh.ai/catalog/standards/sist/en-62386-102-2015)

---

**ICS:**

29.140.50	Instalacijski sistemi za razsvetljavo	Lighting installation systems
35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

**SIST EN 62386-102:2015** en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 62386-102:2015](#)

<https://standards.iteh.ai/catalog/standards/sist/6fa6d728-e4e7-4620-aff6-5d41f01b8a0f/sist-en-62386-102-2015>

EUROPEAN STANDARD

**EN 62386-102**

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2014

ICS 29.140; 29.140.50

Supersedes EN 62386-102:2009

English Version

Digital addressable lighting interface -  
Part 102: General requirements - Control gear  
(IEC 62386-102:2014)

Interface d'éclairage adressable numérique -  
Partie 102: Exigences générales - Appareillages de  
commande  
(CEI 62386-102:2014)

Digital adressierbare Schnittstelle für die Beleuchtung -  
Teil 102: Allgemeine Anforderungen - Betriebsgeräte  
(IEC 62386-102:2014)

This European Standard was approved by CENELEC on 2014-12-12. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

SIST EN 62386-102:2015

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

## Foreword

The text of document 34C/1099/FDIS, future edition 2 of IEC 62386-102, prepared by SC 34C "Auxiliaries for lamps" of IEC/TC 34 "Lamps and related equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62386-102:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-09-12
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-12-12

This document supersedes EN 62386-102:2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

## Endorsement notice

The text of the International Standard IEC 62386-102:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60598-1	NOTE	Harmonized as EN 60598-1.
IEC 60669-2-1	NOTE	Harmonized as EN 60669-2-1.
IEC 60921	NOTE	Harmonized as EN 60921.
IEC 60923	NOTE	Harmonized as EN 60923.
IEC 60925 <sup>1)</sup>	NOTE	Harmonized as EN 60925 <sup>1)</sup> .
IEC 61547	NOTE	Harmonized as EN 61547.
IEC 62386-102:2009	NOTE	Harmonized as EN 62386-102:2009.
CISPR 15	NOTE	Harmonized as EN 55015.

---

<sup>1)</sup> Withdrawn publication.

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: [www.cenelec.eu](http://www.cenelec.eu)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61347	Series	Lamp controlgear	EN 61347	Series
IEC 62386-101	2014	Digital addressable lighting interface - Part 101: General requirements - System Components	EN 62386-101	2014
IEC 62386-103	2014	Digital addressable lighting interface - Part 103: General requirements - Control devices	EN 62386-103	2014

**iTech STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 62386-102:2015](https://standards.iteh.ai/catalog/standards/sist/6fa6d728-e4e7-4620-af6e-5d41f01b8a0f/sist-en-62386-102-2015)

<https://standards.iteh.ai/catalog/standards/sist/6fa6d728-e4e7-4620-af6e-5d41f01b8a0f/sist-en-62386-102-2015>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 62386-102:2015](#)

<https://standards.iteh.ai/catalog/standards/sist/6fa6d728-e4e7-4620-aff6-5d41f01b8a0f/sist-en-62386-102-2015>



IEC 62386-102

Edition 2.0 2014-11

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



**Digital addressable lighting interface –  
Part 102: General requirements – Control gear**

**Interface d'éclairage adressable numérique –  
Partie 102: Exigences générales – Appareillages de commande**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

PRICE CODE  
CODE PRIX

**XH**

ICS 29.140, 29.140.50

ISBN 978-2-8322-1906-5

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	12
INTRODUCTION.....	14
1 Scope.....	15
2 Normative references .....	15
3 Terms and definitions .....	15
4 General .....	18
4.1 General.....	18
4.2 Version number .....	18
5 Electrical specification.....	18
6 Interface power supply .....	18
7 Transmission protocol structure.....	19
7.1 General.....	19
7.2 16 bit forward frame encoding.....	19
7.2.1 General .....	19
7.2.2 Address byte .....	19
7.2.3 Opcode byte .....	19
8 Timing .....	19
9 Method of operation.....	20
9.1 General.....	20
9.2 Control gear.....	20
9.3 Dimming curve.....	20
9.4 Calculating “targetLevel”.....	23
9.5 Fading .....	23
9.5.1 General .....	23
9.5.2 Fade time .....	24
9.5.3 Fade rate.....	25
9.5.4 Extended fade time.....	26
9.5.5 Using the fade time.....	28
9.5.6 Using the fade rate .....	28
9.5.7 Behaviour during a fade.....	28
9.5.8 Behaviour during startup.....	28
9.5.9 Stopping a fade .....	28
9.6 Min and max level.....	29
9.7 Commands .....	29
9.7.1 General .....	29
9.7.2 Level instructions without fade.....	30
9.7.3 Level instructions initiating a fade.....	30
9.7.4 Configuration instructions .....	30
9.7.5 Queries .....	30
9.7.6 Special commands .....	31
9.7.7 Application extended commands.....	31
9.8 Command iterations.....	31
9.8.1 General .....	31
9.8.2 Command iteration of “UP” and “DOWN” commands.....	31
9.8.3 DAPC SEQUENCE (deprecated) .....	31

**ITeH STANDARD PREVIEW**  
(standards.iteh.ai)

SIST EN 62386-102:2015

<https://standards.iteh.ai/catalog/standards/sist/6fa6d728-e4e7-4620-a16e-3d41101b8a07/sist-en-62386-102-2015>



9.9	Modes of operation .....	32
9.9.1	General .....	32
9.9.2	Operating mode 0x00: standard mode .....	32
9.9.3	Operating mode 0x01 to 0x7F: reserved .....	32
9.9.4	Operating mode 0x80 to 0xFF: manufacturer specific modes .....	32
9.10	Memory banks .....	33
9.10.1	General .....	33
9.10.2	Memory map.....	33
9.10.3	Selecting a memory bank location .....	34
9.10.4	Memory bank reading .....	34
9.10.5	Memory bank writing.....	34
9.10.6	Memory bank 0.....	35
9.10.7	Memory bank 1.....	37
9.10.8	Manufacturer specific memory banks.....	39
9.10.9	Reserved memory banks .....	39
9.11	Reset.....	39
9.11.1	Reset operation .....	39
9.11.2	Reset memory bank operation .....	39
9.12	System failure.....	39
9.13	Power on .....	40
9.14	Assigning short addresses .....	41
9.14.1	General .....	41
9.14.2	Random address allocation.....	41
9.14.3	Identification of a device.....	42
9.14.4	Direct address allocation.....	43
9.15	Failure state behaviour.....	43
9.16	Status information.....	43
9.16.1	General .....	43
9.16.2	Bit 0: Control gear failure.....	43
9.16.3	Bit 1: Lamp failure .....	44
9.16.4	Bit 2: Lamp on .....	44
9.16.5	Bit 3: Limit error.....	44
9.16.6	Bit 4: Fade running .....	44
9.16.7	Bit 5: Reset state .....	44
9.16.8	Bit 6: Missing short address.....	44
9.16.9	Bit 7: Power cycle seen .....	45
9.17	Non-volatile memory.....	45
9.18	Device types and features.....	45
9.19	Using scenes .....	46
10	Declaration of variables .....	47
11	Definition of commands .....	49
11.1	General.....	49
11.2	Overview Sheets.....	49
11.3	Level instructions.....	55
11.3.1	DAPC ( <i>level</i> ) .....	55
11.3.2	OFF .....	55
11.3.3	UP.....	55
11.3.4	DOWN.....	55
11.3.5	STEP UP.....	55

11.3.6	STEP DOWN .....	56
11.3.7	RECALL MAX LEVEL .....	56
11.3.8	RECALL MIN LEVEL .....	56
11.3.9	STEP DOWN AND OFF .....	57
11.3.10	ON AND STEP UP .....	57
11.3.11	ENABLE DAPC SEQUENCE .....	57
11.3.12	GO TO LAST ACTIVE LEVEL .....	58
11.3.13	GO TO SCENE ( <i>sceneNumber</i> ) .....	58
11.4	Configuration instructions .....	58
11.4.1	General .....	58
11.4.2	RESET .....	58
11.4.3	STORE ACTUAL LEVEL IN DTR0 .....	58
11.4.4	SAVE PERSISTENT VARIABLES .....	58
11.4.5	SET OPERATING MODE ( <i>DTR0</i> ) .....	59
11.4.6	RESET MEMORY BANK ( <i>DTR0</i> ) .....	59
11.4.7	IDENTIFY DEVICE .....	59
11.4.8	SET MAX LEVEL ( <i>DTR0</i> ) .....	60
11.4.9	SET MIN LEVEL ( <i>DTR0</i> ) .....	60
11.4.10	SET SYSTEM FAILURE LEVEL ( <i>DTR0</i> ) .....	60
11.4.11	SET POWER ON LEVEL ( <i>DTR0</i> ) .....	61
11.4.12	SET FADE TIME ( <i>DTR0</i> ) .....	61
11.4.13	SET FADE RATE ( <i>DTR0</i> ) .....	61
11.4.14	SET EXTENDED FADE TIME ( <i>DTR0</i> ) .....	61
11.4.15	SET SCENE ( <i>DTR0</i> , <i>sceneX</i> ) .....	62
11.4.16	REMOVE FROM SCENE ( <i>sceneX</i> ) .....	62
11.4.17	ADD TO GROUP ( <i>group</i> ) .....	62
11.4.18	REMOVE FROM GROUP ( <i>group</i> ) .....	62
11.4.19	SET SHORT ADDRESS ( <i>DTR0</i> ) .....	62
11.4.20	ENABLE WRITE MEMORY .....	63
11.5	Queries .....	63
11.5.1	General .....	63
11.5.2	QUERY STATUS .....	63
11.5.3	QUERY CONTROL GEAR PRESENT .....	63
11.5.4	QUERY CONTROL GEAR FAILURE .....	63
11.5.5	QUERY LAMP FAILURE .....	63
11.5.6	QUERY LAMP POWER ON .....	63
11.5.7	QUERY LIMIT ERROR .....	63
11.5.8	QUERY RESET STATE .....	63
11.5.9	QUERY MISSING SHORT ADDRESS .....	63
11.5.10	QUERY VERSION NUMBER .....	64
11.5.11	QUERY CONTENT DTR0 .....	64
11.5.12	QUERY DEVICE TYPE .....	64
11.5.13	QUERY NEXT DEVICE TYPE .....	64
11.5.14	QUERY PHYSICAL MINIMUM .....	64
11.5.15	QUERY POWER FAILURE .....	64
11.5.16	QUERY CONTENT DTR1 .....	64
11.5.17	QUERY CONTENT DTR2 .....	64
11.5.18	QUERY OPERATING MODE .....	65
11.5.19	QUERY LIGHT SOURCE TYPE .....	65

11.5.20	QUERY ACTUAL LEVEL .....	65
11.5.21	QUERY MAX LEVEL.....	65
11.5.22	QUERY MIN LEVEL.....	66
11.5.23	QUERY POWER ON LEVEL.....	66
11.5.24	QUERY SYSTEM FAILURE LEVEL .....	66
11.5.25	QUERY FADE TIME/FADE RATE .....	66
11.5.26	QUERY EXTENDED FADE TIME .....	66
11.5.27	QUERY MANUFACTURER SPECIFIC MODE .....	66
11.5.28	QUERY SCENE LEVEL ( <i>sceneX</i> ).....	66
11.5.29	QUERY GROUPS 0-7 .....	66
11.5.30	QUERY GROUPS 8-15 .....	66
11.5.31	QUERY RANDOM ADDRESS (H) .....	67
11.5.32	QUERY RANDOM ADDRESS (M).....	67
11.5.33	QUERY RANDOM ADDRESS (L).....	67
11.5.34	READ MEMORY LOCATION ( <i>DTR1</i> , <i>DTR0</i> ).....	67
11.6	Application extended commands.....	67
11.6.1	General .....	67
11.6.2	QUERY EXTENDED VERSION NUMBER .....	67
11.7	Special commands.....	68
11.7.1	General .....	68
11.7.2	TERMINATE.....	68
11.7.3	<i>DTR0</i> ( <i>data</i> ) .....	68
11.7.4	INITIALISE ( <i>device</i> ).....	68
11.7.5	RANDOMISE .....	68
11.7.6	COMPARE .....	69
11.7.7	WITHDRAW.....	69
11.7.8	SEARCHADDRH ( <i>data</i> ) .....	69
11.7.9	SEARCHADDRM ( <i>data</i> ) .....	69
11.7.10	SEARCHADDRL ( <i>data</i> ) .....	69
11.7.11	PROGRAM SHORT ADDRESS ( <i>data</i> ) .....	70
11.7.12	VERIFY SHORT ADDRESS ( <i>data</i> ) .....	70
11.7.13	QUERY SHORT ADDRESS .....	70
11.7.14	ENABLE DEVICE TYPE ( <i>data</i> ).....	70
11.7.15	<i>DTR1</i> ( <i>data</i> ) .....	71
11.7.16	<i>DTR2</i> ( <i>data</i> ) .....	71
11.7.17	WRITE MEMORY LOCATION ( <i>DTR1</i> , <i>DTR0</i> , <i>data</i> ) .....	71
11.7.18	WRITE MEMORY LOCATION – NO REPLY ( <i>DTR1</i> , <i>DTR0</i> , <i>data</i> ) .....	71
11.7.19	PING .....	72
12	Test procedures .....	72
12.1	General notes on test.....	72
12.1.1	Abbreviations.....	72
12.1.2	Test execution.....	72
12.1.3	Data transmission.....	72
12.1.4	Test setup .....	73
12.1.5	Test output .....	73
12.1.6	Fade time measurements based on light output .....	73
12.1.7	Description of test scheme for fast fade times on PWM dimmer .....	74
12.1.8	Test notation .....	75
12.1.9	Test execution limitation .....	75

12.1.10	Test results .....	75
12.1.11	Exception handling .....	75
12.1.12	Unexpected answer .....	75
12.2	Preamble .....	77
12.2.1	Test preamble .....	77
12.3	Physical operational parameters .....	94
12.3.1	Polarity test .....	94
12.3.2	Maximum and minimum system voltage .....	94
12.3.3	Overvoltage protection test .....	95
12.3.4	Current rating test .....	96
12.3.5	Transmitter voltages .....	97
12.3.6	Transmitter rising and falling edges .....	99
12.3.7	Transmitter bit timing .....	101
12.3.8	Transmitter frame timing .....	103
12.3.9	Receiver start-up behavior .....	104
12.3.10	Receiver threshold .....	105
12.3.11	Receiver bit timing .....	106
12.3.12	Extended receiver bit timing .....	110
12.3.13	Receiver forward frame violation .....	112
12.3.14	Receiver settling timing .....	112
12.3.15	Receiver frame timing FF-FF send twice .....	113
12.4	Configuration instructions .....	115
12.4.1	RESET .....	115
12.4.2	RESET: timeout / command in-between .....	119
12.4.3	Send-twice timeout .....	121
12.4.4	Commands in-between .....	129
12.4.5	STORE ACTUAL LEVEL IN DTR0 .....	135
12.4.6	SAVE PERSISTENT VARIABLES .....	136
12.4.7	SET OPERATING MODE .....	136
12.4.8	SET MAX LEVEL .....	137
12.4.9	SET MIN LEVEL .....	137
12.4.10	SET SYSTEM FAILURE LEVEL .....	138
12.4.11	SET POWER ON LEVEL .....	139
12.4.12	SET FADE TIME .....	143
12.4.13	SET FADE RATE .....	143
12.4.14	SET SCENE / REMOVE FROM SCENE .....	144
12.4.15	ADD TO GROUP / REMOVE FROM GROUP .....	145
12.4.16	SET SHORT ADDRESS .....	146
12.4.17	SET EXTENDED FADE TIME .....	147
12.4.18	Reset/Power-on values .....	148
12.4.19	DTR0 / DTR1 / DTR2 .....	154
12.5	Memory banks .....	154
12.5.1	READ MEMORY LOCATION on Memory Bank 0 .....	154
12.5.2	READ MEMORY LOCATION on Memory Bank 1 .....	159
12.5.3	READ MEMORY LOCATION on other Memory Banks .....	161
12.5.4	Memory bank writing .....	163
12.5.5	ENABLE WRITE MEMORY: writeEnableState .....	168
12.5.6	ENABLE WRITE MEMORY: timeout / command in-between .....	171
12.5.7	RESET MEMORY BANK: timeout / command in-between .....	172

12.5.8	RESET MEMORY BANK.....	175
12.6	Level instructions.....	176
12.6.1	Level instructions: Basic behaviour.....	176
12.6.2	FADE TIME: possible values .....	181
12.6.3	FADE TIME: transitions .....	182
12.6.4	FADE TIME: fading to 0.....	184
12.6.5	FADE TIME: small steps fading .....	186
12.6.6	FADE TIME: extended fade time.....	189
12.6.7	FADE RATE: possible values.....	191
12.6.8	FADE RATE: transitions .....	194
12.6.9	FADE RATE: extended fade time.....	195
12.6.10	FADE TIME/FADE RATE: stop fading by setting MIN/MAX levels .....	196
12.6.11	FADE TIME/FADE RATE: stop fading .....	201
12.6.12	FADE TIME/FADE RATE: stop fading when a command is sent, check timing .....	204
12.6.13	FADE TIME/FADE RATE: stop fading during startup.....	210
12.6.14	Level instructions: combined instructions.....	211
12.6.15	Power On Level - System Failure Level combined .....	213
12.6.16	ENABLE DAPC SEQUENCE.....	218
12.6.17	GO TO LAST ACTIVE LEVEL.....	219
12.6.18	GO TO SCENE.....	221
12.6.19	Power on: level control commands.....	222
12.6.20	Logarithmic dimming curve.....	224
12.6.21	Dimming curve: DAPC .....	225
12.6.22	Dimming curve: UP / DOWN.....	226
12.6.23	Dimming curve: STEP UP / STEP DOWN.....	227
12.6.24	FADE TIME/EXTENDED FADE TIME: light output behaviour .....	228
12.6.25	EXTENDED FADE TIME: light output behaviour .....	229
12.6.26	Behaviour during a fade.....	230
12.7	Special commands.....	232
12.7.1	INITIALISE – timer.....	232
12.7.2	TERMINATE .....	234
12.7.3	INITIALISE - device addressing .....	234
12.7.4	RANDOMISE .....	235
12.7.5	COMPARE .....	236
12.7.6	WITHDRAW.....	237
12.7.7	SEARCHADDRH / SEARCHADDRM / SEARCHADDRL .....	238
12.7.8	PROGRAM SHORT ADDRESS.....	239
12.7.9	VERIFY SHORT ADDRESS .....	241
12.7.10	QUERY SHORT ADDRESS .....	242
12.7.11	IDENTIFY DEVICE .....	244
12.7.12	IDENTIFY DEVICE THROUGH RECALL MIN/MAX LEVEL.....	246
12.8	Queries and reserved commands.....	250
12.8.1	QUERY STATUS - lampFailure/lampOn.....	250
12.8.2	QUERY STATUS - lampOn.....	253
12.8.3	QUERY STATUS - limitError/lampOn.....	254
12.8.4	QUERY STATUS - powerCycleSeen.....	258
12.8.5	QUERY CONTROL GEAR PRESENT .....	259
12.8.6	QUERY VERSION NUMBER.....	259

12.8.7	PING .....	260
12.8.8	Broadcast unaddressed .....	260
12.8.9	Reserved commands: standard commands .....	262
12.8.10	Reserved commands: special commands .....	262
12.8.11	Application extended commands .....	263
12.8.12	Not supported device types .....	264
12.8.13	Removed functionality .....	264
12.9	Cross contamination .....	266
12.9.1	DTR0 .....	266
12.9.2	NVM variables .....	266
12.9.3	Random address generation .....	268
12.9.4	Addressing 1 .....	269
12.9.5	Addressing 2 .....	270
12.9.6	Addressing 3 .....	272
12.10	General subsequences .....	273
12.10.1	GetVersionNumber .....	273
12.10.2	GetExtendedVersionNumber .....	273
12.10.3	GetSupportedDeviceTypes .....	274
12.10.4	GetSupportedLightSources .....	274
12.10.5	WaitForPowerOnPhaseToFinish .....	276
12.10.6	WaitForLampOn .....	276
12.10.7	WaitForLampOnAddressed .....	277
12.10.8	WaitForLampLevel .....	277
12.10.9	WaitForFadeToFinish .....	277
12.10.10	SetShortAddress .....	278
12.10.11	GetRandomAddress .....	278
12.10.12	GetLimitedRandomAddress .....	279
12.10.13	SetSearchAddress .....	279
12.10.14	ReadMemBankMultibyteLocation .....	279
12.10.15	FindImplementedMemoryBank .....	280
12.10.16	FindAllImplementedMemoryBanks .....	280
12.10.17	GetNumberOfLogicalUnits .....	280
12.10.18	GetIndexOfLogicalUnit .....	281
12.10.19	ConnectLamps .....	281
12.10.20	DisconnectLamps .....	281
12.10.21	PowerCycle .....	282
12.10.22	PowerCycleAndWaitForBusPower .....	282
12.10.23	PowerCycleAndWaitForDecoder .....	283
Annex A (informative)	Examples of algorithms .....	284
A.1	Random address allocation .....	284
A.2	One single control gear connected to the control device .....	284
A.3	Using application extended commands .....	285
Annex B (normative)	High resolution dimmer .....	286
Bibliography	.....	288
Figure 1	– IEC 62386 graphical overview .....	14
Figure 2	– Control gear directly operating a light source .....	20
Figure 3	– Dimming curve .....	21

Figure 4 – Level over time, fading up and down .....	24
Figure 5 – Timing and response when receiving a command iteration .....	31
Figure 6 – Fading from MIN LEVEL to MAX LEVEL .....	74
Figure 7 – Fading from MAX LEVEL to off .....	74
Figure 8 – Normal fading for a PWM dimmer .....	74
Figure 9 – Fading from MAX LEVEL to off for a PWM dimmer .....	75
Figure 10 – Current rating test .....	97
Figure B.1 – Level behaviour in cases of off-grid starting points .....	287
Table 1 – 16-bit command frame encoding .....	19
Table 2 – Dimming curve tolerance (% , rounded to two decimals) .....	21
Table 3 – Dimming curve .....	22
Table 4 – Fade times .....	25
Table 5 – Fade rates .....	26
Table 6 – Extended fade time - base value .....	27
Table 7 – Extended fade time - multiplier .....	27
Table 8 – Basic memory map of memory banks .....	33
Table 9 – Memory map of memory bank 0 .....	36
Table 10 – Memory map of memory bank 1 .....	38
Table 11 – Power on timing .....	41
Table 12 – Control gear status .....	43
Table 13 – Scenes .....	46
Table 14 – Declaration of variables .....	47
Table 15 – Standard commands .....	49
Table 16 – Special commands .....	53
Table 17 – Light source type encoding .....	65
Table 18 – Device addressing with “INITIALISE” .....	68
Table 19 – Unexpected outcome .....	76
Table 20 – Parameters for test sequence CheckFactoryDefault102 .....	82
Table 21 – Parameters for test sequence CheckFactoryDefault201 .....	86
Table 22 – Parameters for test sequence CheckFactoryDefault202 .....	87
Table 23 – Parameters for test sequence CheckFactoryDefault203 .....	88
Table 24 – Parameters for test sequence CheckFactoryDefault204 .....	88
Table 25 – Parameters for test sequence CheckFactoryDefault205 .....	89
Table 26 – Parameters for test sequence CheckFactoryDefault206 .....	89
Table 27 – Parameters for test sequence CheckFactoryDefault207 .....	90
Table 28 – Parameters for test sequence CheckFactoryDefault208 .....	90
Table 29 – Parameters for test sequence CheckFactoryDefault209 .....	91
Table 30 – Parameters for test sequence Maximum and minimum system voltage .....	95
Table 31 – Parameters for test sequence Transmitter voltages .....	99
Table 32 – Parameters for test sequence Transmitter rising and falling edges .....	100
Table 33 – Parameters for test sequence Transmitter rising and falling edges .....	101
Table 34 – Parameters for test sequence Transmitter bit timing .....	102